

SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter.]

A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY AND MANUFACTURES

Vol. XLIV.—No. 5.
[NEW SERIES.]

NEW YORK, JANUARY 29, 1881.

[\$3.20 per Annum
[POSTAGE PREPAID.]

AN IMPROVED MOUNTAIN RAILWAY SYSTEM.

The construction, maintenance, and operation of mountain railways have long occupied the attention of engineers. Many methods of climbing steep inclines and of rounding curves of small radius have been proposed, and several of these methods have been reduced to actual practice. The systems of Fell and Riggenbach are very well known, and the ancient system of rope tramways is in use in many

places. A distinguished engineer, M. L. Edoux, has conceived a project which is based upon the application of a system of hydraulic elevators to the lifting of cars to any height. This system may be applied to great advantage, when an abundance of water under high pressure is available. These conditions will be frequently met in a mountainous country. Although this project has not yet been realized it seems to possess sufficient merit and novelty to

render it interesting to our readers. The illustrations have been specially arranged for the SCIENTIFIC AMERICAN from the author's plans, elevations, and sectional views.

The particular railway under consideration is intended to establish communication between Caunterets and the baths of La Raillère, France. Caunterets is situated in a narrow valley, at an elevation of more than 900 meters. It is a noted water-

[Continued on page 66.]



IMPROVED SYSTEM FOR MOUNTAIN RAILWAYS.

Scientific American.

ESTABLISHED 1845.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT NO. 37 PARK ROW, NEW YORK.

O. D. MUNN. A. E. BEACH.

TERMS FOR THE SCIENTIFIC AMERICAN.

One copy, one year postage included. \$3 20 One copy, six months postage included 1 60

Clubs.—One extra copy of THE SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.20 each; additional copies at same proportionate rate. Postage prepaid. Remit by postal order. Address MUNN & CO., 37 Park Row, New York.

The Scientific American Supplement

Is a distinct paper from the SCIENTIFIC AMERICAN. THE SUPPLEMENT is issued weekly. Every number contains 16 octavo pages, uniform in size with SCIENTIFIC AMERICAN. Terms of subscription for SUPPLEMENT, \$5.00 a year, postage paid, to subscribers. Single copies, 15 cents. Sold by all news dealers throughout the country.

Combined Rates.—The SCIENTIFIC AMERICAN and SUPPLEMENT will be sent for one year postage free, on receipt of seven dollars. Both papers to one address or different addresses as desired.

The safest way to remit is by draft postal order, or registered letter. Address MUNN & CO., 37 Park Row, N. Y.

Scientific American Export Edition.

The SCIENTIFIC AMERICAN Export Edition is a large and splendid periodical, issued once a month. Each number contains about one hundred large quarto pages, profusely illustrated, embracing: (1.) Most of the plates and pages of the four preceding weekly issues of the SCIENTIFIC AMERICAN, with its splendid engravings and valuable information; (2.) Commercial, trade, and manufacturing announcements of leading houses. Terms for Export Edition, \$5.00 a year, sent prepaid to any part of the world. Single copies 50 cents. Manufacturers and others who desire to secure foreign trade may have large and handsomely displayed announcements published in this edition at a very moderate cost.

The SCIENTIFIC AMERICAN Export Edition has a large guaranteed circulation in all commercial places throughout the world. Address MUNN & CO., 37 Park Row, New York.

NEW YORK, SATURDAY, JANUARY 29, 1881.

Contents.

(Illustrated articles are marked with an asterisk.)

Table listing various articles such as Agriculture, machinery for, Oil, waste, to purify, and others with their respective page numbers.

TABLE OF CONTENTS OF

THE SCIENTIFIC AMERICAN SUPPLEMENT

No. 265.

For the Week ending January 29, 1881.

Price 10 cents. For sale by all newdealers.

Table listing contents of the supplement by section: I. ENGINEERING AND MECHANICS, II. TECHNOLOGY AND CHEMISTRY, III. ELECTRICITY, LIGHT, HEAT, ETC., IV. PHYSIOLOGY, MEDICINE, ETC., V. HORTICULTURE, AGRICULTURE, ETC., VI. ART, ARCHITECTURE, ETC., VII. MISCELLANEOUS.

THE TENDENCY OF RECENT COURT DECISIONS WITH REGARD TO REISSUED PATENTS.

The patent laws provide for the reissue and correction of patents when the original is inoperative or invalid by reason of a defective or insufficient specification, or by reason of the patentee claiming as his invention or discovery more than he had a right to claim as new, provided it is shown that the error arose from inadvertence, accident, or mistake, without any fraudulent or deceptive intention on the part of the patentee.

The matter to be introduced into the amended specification is limited strictly to such as was clearly indicated, described, or suggested in the original specification, drawings, or model, and such as might have been lawfully claimed, but was not, for the reasons mentioned.

The practice of the Patent Office has been less exacting on this point than the rules prescribe, so that in many cases the reissue specifications have contained substantially new matter; sometimes matter which the patentee might lawfully have inserted and claimed originally, but failed to, through ignorance or oversight, and sometimes matter which had been disallowed by the Office or voluntarily disclaimed by the inventor to secure the issue of his patent. By means of such reissues the inventor's afterthoughts and discoveries have been covered, and too frequently the subsequent inventions of others, or processes and machinery which others may have brought into profitable use, knowing them to be not patented. In this way much injustice has been wrought, and occasion given for many if not most of the more serious complaints against the patent system.

At first the courts were inclined to hold that the decision of the Commissioner of Patents in granting the reissue was final and conclusive, and could not be revised. More recently there has been a manifest disposition to go behind the Commissioner's action to inquire whether he may not have exceeded his jurisdiction or improperly performed his duty in granting a reissue for more than was covered by the original patent. Thus in the case of Leggett et al. vs. Avery et al. (U. S. Supreme Court, October, 1879), it was held that no error had arisen through inadvertence, accident, or mistake, but that the Commissioner had committed manifest error in allowing the reissue for more than was included in the extended patent, and for what was expressly disclaimed therein. In this decision Mr. Justice Bradley remarked that the allowance of claims once formally abandoned by the applicant in order to get his patent through is the occasion of immense frauds upon the public, and is to be discountenanced. In the same connection he said:

"It is doubtful whether a reissue patent can be sustained in any case where it contains claims that have once been formally disclaimed by the patentee, or rejected with his acquiescence in order to obtain his patent. In such case the rejection (omission) of the claim can in no just sense be regarded as matter of inadvertence or mistake, and even if it were such the applicant would seem to be estopped from setting it up on application for a reissue."

In the case of the Giant Powder Company vs. the California Vigorite Powder Company et al. (U. S. Circuit Court, District of California, October, 1880, Field, J.), the right of the court to review a decision of the Patent Commissioner was clearly stated. In this case a reissued patent was declared invalid because its specification contained an invention of broader scope than the original. The court said:

"As the power to accept a surrender and issue new letters is vested exclusively in the Commissioner of Patents, his decision in the matter is not open to collateral attack in a suit for the infringement of reissued letters. His action, like that of all officers specially designated to perform a particular duty of a judicial character for the government is presumed to be correct until impeached by regular proceedings to avail or modify it. He must judge, in the first instance, of the sufficiency of the original specification whether the same is defective in any particular, whether such defect was the result of an unintentional error, and if so, to what extent a new or additional specification should be allowed to describe correctly the invention claimed; and it is to be assumed in every case that he has done his duty. The decisions of the Supreme Court to this effect are numerous, and the doctrine is one of the settled rules of patent law. But it does not preclude the examination of the original and reissued patents, to see whether or not they disclose on their face a case in which the Commissioner had authority to act or whether he has exceeded his authority in issuing letters for an invention different from that described in the original patent."

The Commissioner's authority to reissue being limited strictly to those cases in which the original patent is inoperative or invalid from unintentional error, or where the inventor's claim exceeds his invention, the fact that the patent does not cover all that the patentee could have claimed if his specification had come up to his invention, furnishes no sufficient ground for a reissue.

"The statute authorizing a reissue," the court said, "was intended to protect against accidents and mistakes, and it is only when thus restricted that it can be regarded as a beneficial statute. If the patentee does not embrace by his specifications and claim all that he might have done, and there has been no clear mistake, inadvertence, or accident in their preparation, the presumption of law is that he has abandoned to the use of the public everything outside of them, or at least has postponed any additional claim for further consideration."

The same principle was laid down even more specifically

by the United States Supreme Court, in the case of the Swain Turbine and Manufacturing Company, appellant, vs. Ladd. This was another instance of expanded claims in a reissued patent. The original specification was as perfect, so far as it went, as the new one, the pretended corrections having been introduced to widen the scope of the patent to give its owners a large and valuable monopoly of an important class of waterwheels. In the Circuit Court of the United States for the District of Massachusetts, the claims of the reissued letters patent had been restricted to the distinct limitation of the invention in the original patent, and that decision was sustained by the Supreme Court. In the opinion of the court, delivered by Mr. Justice Bradley, it was pointed out that "the mistake of the patentee or his assignees seems to have been in supposing that he was entitled to have inserted in a reissued patent all that he might have applied for and had inserted in his original patent. The appellants produced on the argument exhibits tending to show that the patentee before obtaining his original patent had made and done all those things which are embraced in or covered by the reissued patent. If this were true it would be nothing to the purpose. A reissue can only be granted for the same invention which was originally patented. If it were otherwise a door would be opened to the admission of the greatest frauds. Claims and pretensions shown to be unfounded at the time might, after the lapse of a few years, after a change of officers in the Patent Office, the death of witnesses, and the dispersion of documents, be set up anew, and the reversal of the first decision obtained without an appeal and without any knowledge of the previous investigation on the subject. New light breaking in upon the patentee as the progress of improvement goes on, and as other inventors enter the field, and his monopoly becomes less and less necessary to the public, might easily generate in his mind an idea that his invention was really more broad and comprehensive than had been set forth in the specification of his patent. It is easy to see how such new light would naturally be reflected in a reissue of the patent, and how unjust it might be to third parties who had kept pace with the march of improvement. Hence there is no safe or just rule but that which confines a reissued patent to the same invention which was described or indicated in the original."

If an unswerving adherence to this rule can be secured in the practice of the Patent Office it is obvious that a grave, perhaps the gravest source of objection to the patent system will be stopped. In the meantime the growing disposition of the courts to review the action of the Commissioner in re-issuing patents, in cases of alleged infringement under them, and to construe the reissued patents rigorously, is a matter of much encouragement to manufacturers and the public at large.

OFFICIAL REPORT ON THE STEAMER ANTHRACITE.

We have received from the Bureau of Steam Engineering of the Navy Department, a copy of the full official report of the Board of U. S. Naval Engineers, relating to the tests of the machinery of the little British steamer Anthracite, made at the Navy Yard, Brooklyn, N. Y., August 13 and 14, 1880. The board was composed of three Chief Engineers of the U. S. Navy, namely, Chas. H. Loving, S. L. P. Ayres, and Geo. W. Magee, all gentlemen of ability and experience.

The Anthracite, it will be remembered, is an iron steamer, 86 feet 4 inches long, 16 feet 1 inch wide, 10 feet 2 inches deep, draught loaded, 9 feet. The total weight of engines, boiler, shaft, propeller, and all fittings was 25 tons. Her propeller was worked with three steam cylinders, the first, single acting, 73 1/4 inches diameter; the second, single acting, 15 1/2 inches diameter; the third, double acting, 23 1/2 inches diameter. Stroke of pistons, 15 inches. The most novel feature—the Perkins system—was the high steam pressure intended to be carried, namely, from 300 to 500 pounds to the square inch. The pressure now usually carried on the best sea going vessels rarely exceeds 75 to 80 pounds.

In a previous running trial of the Anthracite in England, by Mr. F. J. Bramwell, C.E., May 22, 1880, with a boiler pressure of 360 pounds, the total horse power per hour was obtained by an expenditure of 16,719-1503 units of heat F. (1.35 pounds combustible used).

In the Brooklyn trial, made with the vessel tied to the wharf and with a boiler pressure of 316 1/2 pounds to the inch, the total horse power per hour was obtained by an expenditure of 20,498-22 units of heat F. (1.92 pounds combustible used).

Mr. Bramwell's results were 18.35 per cent more economical than the Navy Yard results. The reasons for this difference are clearly shown by our engineers to be due to the differences in the conditions of the two trials. Thus, the coal used by Mr. Bramwell was superior; he did not lose heat by throwing open the furnace doors to remove clinker; he carried a lower water level, and consequently superheated the steam more, and had less cylinder condensation; he carried a higher boiler pressure, and so obtained a higher initial pressure in the first cylinder, etc. If the proper calculated deductions for these differences in the conditions were allowed our engineers find that there would be a discrepancy between their results and those of Mr. Bramwell of only 4 per cent; they are further of opinion that the difference of the results was wholly due to the difference in the cylinder condensations; these being greater in the American trials gave poorer economic results. Our engineers speak very highly of the Perkins system, as shown by their trials of the Anthracite. They think that her successful passage of the

Atlantic and the efficient condition of her machinery on arrival here ought to remove all doubt as to the practicability of the system.

THERMOMETERS.

The word thermometer means a heat measure, hence any instrument employed to measure heat should be called a thermometer. When very high temperatures are to be measured, the instruments employed are called pyrometers, or measures of fire. Thermometers do not, of course, measure the quantity of heat in a body, but only tell us the relative temperature. There are several forms of thermometers, all based upon the principle that "heat expands, while cold contracts." Some substances expand unequally for equal increments of temperature, others expand so slightly that they fail to indicate small changes of temperature; both are unfitted for thermometers. It is believed that air expands equally for equal changes of temperature, and as this expansion is quite considerable (1/273d part for each degree centigrade), and as it does not become either liquid or solid under ordinary pressure, at any temperature which we can produce, it is the substance employed for the most accurate measurements of temperature. Any of the difficultly condensable gases, oxygen, hydrogen, marsh gas, might be employed instead of air, but with no advantage and with much inconvenience in their manufacture.

Next to air, the best material we have is mercury, which expands very evenly, does not freeze readily, and boils at a comparatively high temperature. For temperatures below -40° alcohol is generally employed, although it is claimed that glycerine could be used. For temperatures above 300° C. air thermometers alone are admissible; and for very high temperatures, where glass begins to soften, they are made of platinum.

The mercury thermometer, being the one usually employed in the arts, in meteorology, in medicine, and in other sciences, a few words in regard to the manner of making one may be of interest. A glass tube with a very fine bore has a suitable bulb, of any desired form, blown upon one end. At the other end may be a bulb of larger size, blown merely for convenience in filling. Neither bulb can be blown with the mouth, but with a bellows, containing pure, dry air. A small capsule is filled with pure mercury, which is heated to boiling to expel both air and moisture. While still hot the second or temporary bulb is warmed to expel a portion of the air therein; the open end is placed in the mercury, which ascends into the bulb because the air contracts on cooling. When a sufficient quantity of the hot mercury has been introduced into this bulb, the tube and the other bulb are heated to expel a part of the air, and some of the mercury, which must always be kept hot to prevent its chilling and thus breaking the hot glass, enters the real bulb. By repeating the operation the bulb and stem are completely filled with mercury, which is then boiled to expel every trace of air. The tube is now drawn out close beneath the auxiliary bulb to a fine thread and cut off; the thermometer is placed in a bath heated a few degrees higher than the highest temperature which the thermometer is to show; the excess of mercury flows out, and the point is closed with a fine blowpipe flame. As the mercury contracts on cooling it leaves a perfect vacuum above it.

The graduation is effected by putting it into ice or snow, then in the steam from boiling water, marking each of these points, dividing the space between into 100 parts if it is to have a Celsius or centigrade scale, into 80 if a Reaumur, or 180 if a Fahrenheit. This graduation is carried on in each direction to the end of the stem. On the Fahrenheit scale the freezing point is marked 32, on each of the other scales it is marked zero.

Absolute zero is a term applied to a temperature 273° below zero on the centigrade scale, or -460° Fah. If we take 273 cubic inches of air, or any gas, measured at 0° C., it will become 274 at +1° C., or 283 at +10° C., or 373 at +100° C., and at -10° C. it is only 263, at -40° it is only 233, and at this rate it should become only 1 cubic inch at -273°, and at minus 273° it should occupy no space at all, or at least not be a gas any longer. As this temperature is not yet attainable, we cannot positively assert that such would really be the case.

Maximum thermometers are made by placing a little float of steel upon the mercury, and the thermometer placed horizontally or nearly so. As the mercury expands it pushes along the float, which does not, however, follow the mercury when it contracts; hence we are able to ascertain the highest temperature reached during any given interval. To reset the thermometer it is raised to a vertical position and a slight tap given to it, which causes the float to drop down on the mercury again.

A simple and more accurate form of maximum thermometer, employed by Bunsen in measuring the temperature of the Geysers, consisted of an ungraduated thermometer open at the top, such as could easily be made by a person of but little experience. When placed in the spring, of course, a portion of the mercury would flow out and escape. At any subsequent time the thermometer could be placed in an oil bath beside a standard thermometer, and heated until the mercury had entirely filled the tube and was about to flow over; at this moment the standard thermometer is read, and shows the temperature to which the other thermometer had been exposed. The ordinary minimum thermometer contains alcohol instead of mercury, and the float is either of glass or of steel covered with enamel, so that it is drawn back by adhesion, but cannot be pushed forward.

The most reliable form of self-registering thermometer is an upright mercurial thermometer behind which is passed by clockwork a strip of sensitized paper. In front of it is placed a light of sufficient actinic power to blacken the paper above the mercury column. This gives not merely the maxima and minima but all variations of temperature.

Metallic thermometers may be constructed by combining two metals which expand unequally into a spiral, which winds up when heated and unwinds when cooled. One end of the spiral being attached to an index which passes along a graduated arc, the slight motions are magnified so as to be distinctly visible. It is graduated by comparison with a good mercurial thermometer.

For measuring slight changes in temperature a thermoelectric pile, connected with a galvanometer needle, is employed. This is only applicable within very narrow limits and requires great care to obtain satisfactory results.

E. J. H.

HYDRAULIC MORTARS AND CEMENTS.

Certain limestones, which contain upward of 10 per cent silica, possess the property, when burned, of forming a cement or mortar which hardens under water. Such limestone is called hydraulic lime, and the mortar is called hydraulic mortar. This stone, before burning, consists of a mixture of carbonate of lime and silica, or a silicate, chiefly silicate of alumina. The latter is insoluble in hydrochloric acid, hence remains undissolved when the stone is treated with this acid, but in burning this silicate is fluxed by the alkaline carbonates and becomes soluble in acid, the carbonic acid being expelled. When common lime is slaked it swells enormously and develops a great deal of heat; this is not the case in slaking hydraulic lime, which absorbs water without any considerable increase of temperature of volume.

If ordinary lime be mixed with a suitable quantity of silica or sand, an artificial hydraulic mortar is obtained, to which we apply the name of cement. These cements may be either natural or artificial. The former are found in volcanic regions, having been produced by the terrestrial heat. Pozzuolana, found at Pozzuoli, near Naples, is a natural cement of the following composition: Silica, 44.5; alumina, 15.0; lime, 8.8; magnesia, 4.7; oxide of iron, 12.0 (with oxide of titanium); potash and soda, 5.5; water, 9.3; total, 100.8.

The quantity of lime is, however, so small that it requires to be mixed with ordinary lime to form hydraulic mortar. It was employed in combination with an equal quantity of lime in building the Eddystone Lighthouse.

Artificial cement, also called "Roman cement," because it is not made in Rome, has been manufactured in England on the Thames and in the Isles of Wight and Sheppey since 1796. It is made by burning the calcareous nodules which overlie the chalk in that country. A sample analyzed by Michaelis contained: lime, 58.38; magnesia, 5; silica, 28.83; alumina, 6.40; oxide iron, 4.80. When mixed with water it hardens in fifteen or twenty minutes, and possesses great firmness and strength.

Portland cement was patented in England by Joseph Aspdin in 1824. He took the limestone of Leeds, pulverized and burned it, then mixed it with water and an equal weight of clay to a plastic mass. When dry this was broken up and burned again until all the carbonic acid was all expelled. It was then pulverized and was ready for use. Pasley made it from chalk or limestone with Medway River clay, which contains salt. Pettenkofer suggests that cement is improved by soaking the clay in salt water.

Portland cement is now made, says Wagner, by making bricks of an intimate mixture of limestone and clay, drying them in the air and burning them in a tall shaft furnace from 45 to 100 feet, 12 feet in diameter, with a strong grate 4 feet from the bottom. It is charged with alternate layers of coal and cement stone. The properties of the cement are largely dependent on the temperature employed in burning; a white heat is best, but if the temperature is too high it will no longer unite with water, and may even be melted to a glass. If the temperature does not exceed a red heat it unites readily with water and gets hot, like ordinary lime, but possesses very little strength. The color changes with the burning and forms a criterion for judging the quality. In normal condition it forms a gray, sharp powder, with a shade of green, but not glassy.

The manufacture of Portland cement is now carried on in every part of the world where limestone and clay are to be found. In order to obtain a good cement, not only must the proper heat be employed in burning, but the proper proportion of clay, usually 25 per cent, must be used, and the clay must have certain properties, such as a large proportion of silica, must be very finely divided, and must be very intimately mixed with the limestone. Analyses of Portland cement from various sources show the percentage of lime to vary from 55 to 62; silica, 23 to 25; alumina, 5 to 9; oxide of iron, 2 to 6; soda and potash, usually less than 1 per cent.

A calcareous marl found near Kufstein forms a natural Portland cement on burning without any other admixture. The analysis shows that it contains 21.77 per cent of insoluble substance containing 16 per cent of silica. The portion soluble in hydrochloric acid consists of 70.64 carbonate of lime; 1.02 carbonate of magnesia; oxide of iron, 2.58; alumina, 2.86. These figures lead us to expect that a marl containing from 20 to 25 per cent of insoluble matter, with 70 of carbonate of lime, will probably furnish a good cement

when burned. The presence of much magnesia seems to have in all cases an injurious effect; all excellent hydraulic lime contains very little magnesia.

Erdmenger, who has studied the constitution of Portland cement very carefully, concludes that it is not a definite chemical compound. He considers it rather as water glass, in which the alkali is replaced by lime.

A consideration of the use of Portland cement in the manufacture of artificial stone would exceed the limits of our present article.

H.

GENERAL GRANT AS PRESIDENT OF THE WORLD'S FAIR COMMISSION.

General Ulysses S. Grant was chosen permanent President of the World's Fair Commission, at a meeting of the Commissioners held in this city January 13. It was announced that he had consented to serve.

General Grant's ability as an executive officer is known the world over; and probably no other name would have carried so much influence at home and abroad. With a leader so well known, popular, and capable, the Commission should be able to raise promptly all the money needed to secure at Inwood, in 1883, an exhibition worthily representing the progress of the world since 1876.

SOLAR CLOUDS AND SUN SPOTS.

Some recent studies of solar spectra in connection with sun spots and other features of the sun's envelope have led Mr. Charles S. Hastings, of the Johns Hopkins University, to form a somewhat novel theory of the sun's constitution and the conditions producing the more notable phenomena familiar to solar students.

Mr. Hastings finds, contrary to the received opinion, that the spectra of the center and the outer edge of the sun's disk are not precisely alike, though the differences are so minute as to escape all but the most perfect instruments and all methods which do not place them in close juxtaposition. Certain of the Fraunhofer lines, the thickest and darkest in the spectrum, notably those of hydrogen, magnesium, and sodium, which appear with a haze on either side in the spectrum of the center of the solar disk, are sharp and distinct in the spectrum of the limb. Certain very fine lines are stronger at the limb, while other very fine lines are stronger at the center. The ordinarily accepted theory of the solar constitution and the origin of the Fraunhofer lines fails to explain these phenomena. The probable reasons for this failure Mr. Hastings discusses at considerable length in the January issue of the *American Journal of Science*, and then proceeds to frame a theory of the sun's constitution, which, he thinks, will satisfactorily explain all the observed phenomena. The limit of our space forbids more than the briefest summary of his conclusions.

His theory differs from that of Faye chiefly in localizing the phenomena of precipitation instead of regarding it as proper to all portions of the photosphere, and in supposing the precipitation confined to one or two elements. He attributes the granular appearance of the solar surface to ascending currents directed generally from the center of the sun. About these currents are necessarily currents in an opposite direction, which serve to maintain a general equilibrium in the distribution of mass. The ascending currents start from a level where the temperature is probably above the vaporizing temperature of every substance. As they move upward the vapors are cooled, mainly by expansion, until a certain element (probably of the carbon group) is precipitated. This precipitation, restricted from the nature of the action, forms the granules. The precipitated material rapidly cools, on account of its great radiating power, and forms a fog or smoke, which settles through the spaces between the granules till revolvatized below. It is this smoke which produces the general absorption at the sun's limb, and the "rice grain" structure of the photosphere. The reasons for supposing the precipitated element to be of the carbon group (carbon or silicon) is simply that no other substances present the properties indicated by the cloud masses of the photosphere. It is pretty clear that the substance has a boiling point above that of iron, for iron vapor at a lower temperature exists in its immediate neighborhood. The element is not a rare one, and its molecular weight cannot be great, for though precipitated below the upper natural limit of its vapor there are few elements found in abundance above it, and those in general of low vapor density. It is possible that the light coming from the sun is radiated from solid or liquid particles of carbon just at the point of vaporization; but Mr. Hastings is rather inclined to suspect that the photospheric material is silicon. There is also good reason to suppose, he thinks, that carbon is precipitated at a higher level, possibly along with the less common element boron.

The clouds of carbon or other smoke would naturally be drifted into spaces of downward flowing currents, thus forming sun spots, the characteristics of which are readily accounted for by the necessary behavior of smoke clouds sinking into regions of higher temperature. This explanation of sun spots and their allied phenomena is certainly plausible, and we shall look with interest for what older students of the sun shall have to say about it.

THE MATANZAS INTERNATIONAL FAIR.—Mr. Benjamin Giberga, general agent for the United States of the approaching Cuban World's Fair, announces that the opening day has been definitely fixed for February 10, 1881.

AN IMPROVED MOUNTAIN RAILWAY SYSTEM.

(Continued from first page.)

ing place, and during the season is filled with numbers of invalids, who go there in search of health. The hot sulphur springs for which this region is noted, are located at La Raillère, 125 meters higher up the mountain, and more than 915 meters distant.

To travel over this fatiguing route, to go and return, often twice in the same day, in the capricious weather of the mountains and in the crowded omnibuses, is uncomfortable and even dangerous for infirm persons. The waters cannot be conveyed from La Raillère to Caunterets without modifying their temperature and their chemical composition to which their therapeutic properties are due. It is, therefore, necessary to convey the sick to the springs that they may receive the full benefit of the water. This railway has been projected for the purpose of conveying the bathers from Caunterets to La Raillère rapidly and comfortably.

All systems, with the exception of that of M. Edoux, require the consumption of a large amount of fuel, which in this region is very expensive. This inventor utilizes the powerful waterfall at La Raillère, which, in connection with gravity, constitutes the motive power of the railway.

The mode of operating the railway is as follows: The car is raised vertically by means of hydraulic elevators to a greater height than its destination, which, in the present case, is La Raillère, and is then allowed to descend as far as that place by its own gravity upon an inclined railway. To return, the car is transferred by its own gravity to a second railway inclined in the opposite direction. The cars are provided with efficient brakes, by means of which the speed may be effectually controlled.

In practice, the car is not raised the vertical distance of 125 meters at a single lift, but this distance is divided into five parts of 25 meters each. There are five towers at intervals of about 40 meters. In each one is placed a hydraulic elevator, similar to those introduced by M. Edoux into the hotels and houses of Paris. The top of each tower is a little more elevated than the foot of the next one, and is connected with it by an inclined bridge. The car is raised by the hydraulic elevator to the top of the first tower, runs by its own gravity to the base of the following one, is raised to the next level, and so on. Together they form a gigantic staircase with steps 25 meters high. The last landing place is 135 meters above Caunterets.

The return way, which is on the side of the mountain, terminates in the second tower. The cars descend vertically only in the first two towers, which contain two compartments, one for hoisting the car and one for lowering it.

At La Raillère the inclination of the car is reversed, and the car is transferred to the return track by means of a platform supported on wheels and provided with rails. The car on arriving from Caunterets rolls upon the platform. The latter moves by its own gravity on rails slightly inclined in opposite directions (see Fig. 3), so that when the rails of the platform join the return track their inclination will have been reversed, and the car will, of its own gravity, return to the second tower. The movement of the transferring car is controlled by a hydraulic piston. The gradient of the railway to La Raillère is 0.005125 per meter, and of the return road 0.043961 per meter.


The department engineers prefer this plan to all others. The question of construction will be taken up at the next session of the Chambers.

NEW MECHANICAL MOVEMENT.

The engraving represents a novel mechanical movement for converting a continuous rotary motion into an intermittent rotary motion. The driving shaft carries a triple sprocket wheel, which is keyed on or otherwise fastened, and the driven shaft has three sprocket wheels, two of which are secured to it, while the third is movable on the shaft. The endless chain which connects the chain wheels of the two shafts is made of three separate sections—a median section alternating with two outer sections arranged parallel to each other and separated by a space equal to the width of the openings in the narrower section. This chain thus formed, as will be noticed, is double for a portion of its length, while the remainder is single.

When the driving shaft is revolved the chain is carried forward at a regular rate of speed. When the single por-

tion of the chain comes into contact with the loose central sprocket wheel on the driven shaft, only the loose wheel is revolved, the shaft remaining stationary; but when the double portion of the chain engages the outer wheels, which are fixed on the driven shaft, the shaft is revolved until the double portion of the chain has passed over it, when it rests until engaged by another double portion. By means of this ingenious contrivance the driven shaft may be rotated either regularly or irregularly according to the relative proportion of double and single chain. This movement should find a ready application in textile machinery, and in fact in all




MOUNTAIN RAILWAY SYSTEM.—TRANSFERRING THE CAR.

classes of machines where intermittent rotary motion is employed.

This invention was recently patented by Mr. William P. Drew, of Preston, Minn.

IMPROVED WOOD SCREW.

The engraving shows a self-countersinking wood screw, recently patented by Mr. John Eckford, of San Antonio, Texas. It will work in all kinds of wood, and clears itself of the chips made in boring. The screw has on the underside or bevel a series of bits or cutting edges alternating with deep interspaces, which completely fill the under surface of the head. These notches increase in width and




ECKFORD'S IMPROVED WOOD SCREW.

depth from the screw shank to the crown of the head. This form allows the chips to escape readily.

The cutters are formed on the screw head by forcing it while hot into suitable dies. In other respects the manufacture of this screw does not differ from that of the common form. In use, this form of screw saves a great deal of time and insures a good fit between the head and the wood in which it is bedded.

RECENT INVENTIONS.

An adjustable tension, with sufficient power for springs for folding or cabinet bedsteads, is secured by a spring patented by Mr. Herman A. J. Rickett, of New York city.



DREW'S MECHANICAL MOVEMENT.

This is a spiral spring sustained at one end and having a shaft connected with the opposite end and extending through the coil. On the free end of the shaft is a drum on which winds a belt extending to and connected with the hinged bed. Two of these arrangements for each bed are preferably used. The tension of the spring can be adjusted by shortening the belt.

A rotary engine, patented by Mr. Gabriel Jasmagy, of Brooklyn, E. D. N. Y., is a cylinder with interior slotted cylinder half the diameter of the exterior cylinder, mounted on shaft journals in the end pieces of the outer cylinder.

The slotted cylinder has overlapping sliding piston plates provided at the ends with a pin and pivoted curved guide bar fitting in an annular groove on the inside of the end pieces of the outer cylinder, which devices draw the piston plates inward and outward, forming a piston of variable size as the shaft rotates.

An improved machine for packing boned hams and shoulders has been patented by Mr. William Hoefjen, of New York city. The invention consists of a cylindrical receptacle, the upper half of which is pivoted on its longitudinal edge and is provided with a lever lock, by means of which

the lid can be gradually closed, compressing the meat in the cylinder; the meat is then further compressed by closing the front of the cylinder by means of a suitable disk and driving a piston forward, after which the disk at the front of the cylinder is removed, and an envelope of suitable material is drawn over the front of the cylinder; into this envelope the meat is forced by the piston.

A gate that may be opened by an approaching vehicle or by a person on horseback without dismounting, and closed in the same manner, has been patented by Mr. Nathan Scarritt, of Kansas City, Mo. The invention consists of a gate made in

two like sections that are pivoted on horizontal axes, and of novel mechanical devices for operating the gate sections.

A simple and amusing game that can be played by any desired number of persons, and does not require any special skill to understand its operation, has been patented by Mr. Niels C. Larsen, of New York city. The invention consists of a spirally-grooved cone contained within a figure with an aperture in its upper part, which figure rests upon a flat conical base having a spiral groove provided with a series of numbered recesses in its upper surface, so that a small ball that is passed into the aperture of the figure will run through the spiral grooves of the cone and along the spiral grooves of the base, and will finally stop in one of the numbered recesses a greater or less distance from the end of the spiral.

Mr. George O. Keiter, of Spring City, Pa., has patented a meat and vegetable cutter so constructed that the substance to be cut is fed to the cutter automatically. The cutters can be adjusted to cut thicker or thinner slices, and can be used to slice substances smaller than the cavities of the feed boxes.

An improved copybook, which prevents the scholar from copying his own writing as he approaches the bottom of the page, and enables

him to see and study the original copy very distinctly, has been patented by Elmer P. Newman, of Dimondale, Mich.

A sand guard for car axle boxes, patented by Mr. Henry Roth, of New York city, consists in a band fastened upon the inner end of the journal box, and open at the lower side. The opening in the inner end of the box is thus protected from sand.

A fire escape, patented by Messrs. Eduard Kamin and Heinrich Egberts, of Bremen, Germany, seems to be simple, compact, and reliable. It is of the life rope variety. The velocity of descent is regulated by a vibrating balance mechanism.

Mr. Gorham N. Winslow, box 290, Newton, Mass., has patented an improved velocipede or tricycle in which the driving wheel is propelled by hand power, connection being made between the crank shaft and drive-wheel shaft by a shaft and bevel gearing.

An improved glass button and a mould for attaching the eye thereto, has been patented by Mr. August Hamann, of Hoboken, N. J. In this improved button the strain upon the eye is distributed through the cap, which is firmly attached to the glass at all parts of the circumference of the cap.

Mr. Erwin B. Newcomb, of Cumberland Mills, Me., has patented an improved machine for winding paper and similar materials from a loose condition into hard rolls, especially materials of a brittle nature—such as, for

instance, enameled paper, which is usually wound by hand on account of its liability to curl at the edges and become broken.

A device for stretching and smoothing thread, more especially of silk in twists, sewings, embroidery, organzine, and tram, has been patented by Messrs. Lewis E. Leigh and Lewis Leigh, of New Haven, Conn., whereby through special construction of the bobbin stand and cap and correlated appliances, an even tension of any desired degree upon all threads in the different processes of manufacture is secured.

SIMPLE MAGIC LANTERN.

All that is required for this apparatus is an ordinary wooden packing box, A, a kerosene hand lamp, B, with an Argand burner, a small fish globe, and a burning glass or common double or plano-convex lens, C. In one end of the box, A, cut a round hole, D, large enough to admit a portion of the globe, E, suspended within the box, A, with the lamp, B, close to it. The globe is filled with water from which the air has been expelled by boiling.

Now moisten the surface of a piece of common window glass with a strong solution of sulphate of soda, or even common table salt, dissolved in water, and place it vertically in a little stand or clip, as shown at F, so that the light from the lamp, B, will be focused on it by the globe, which in this case answers as the condenser. The image of the glass will then be projected on the wall or screen of white cloth, W, providing the lens, C, is so placed in the path of the rays of light as to focus on the wall or screen. In a few minutes the salt solution on the surface of the glass, F, will begin to crystallize, and as each group of crystals takes beautiful forms, its image will be projected on the wall or screen, W, and as it is watched it will grow, as if by magic, into a beautiful forest of fern-like trees, and will continue to grow as long as there is any solution on the glass to crystallize. Then, by adding a few drops of any of the aniline colors to the water in the globe, the image on the screen will be illumined by shades of colored light.




SIMPLE MAGIC LANTERN.

Powerful Pumping Machinery.

The San Francisco *Bulletin* announces the completion at the Risdon Iron Works of the largest pumping engine ever built. It is to be used in draining the Chollar, Norcross, and Savage shafts of the famous Comstock mines at Virginia City, Nevada. The engine occupies a space 65 feet by 20 feet, and weighs between 200 and 300 tons, which the underground machinery will increase to about 1,000 tons in all. The engine accumulates water at 1,000 pounds pressure to the square inch, in a reservoir at the surface 60 feet high, from which it will be conducted by a pipe 2,400 feet to the bottom of the shaft, there to operate a pump which will raise the seepage water 800 feet to the Sutro Tunnel, into which it will be discharged. The water which does the work returns to the surface by another pipe. The system can be extended to 3,000 feet in depth, or take water from mines half a mile away, simply by extending the pipes. The new system is intended to dispense with the heavy and cumbersome pump rods heretofore used. The engine is compound, with the Davey differential valve motion.

IMPROVED CATTLE FEEDER.

The engraving shows an improved cattle feeder invented by Mr. Wm. Griffiths, of Shrewsbury, England. It consists



GRIFFITHS' CATTLE FEEDER.

of four triangular troughs with racks above, fitted to a square frame having T-section iron uprights supporting a curved corrugated roof, troughed at the eaves for carrying the rain water to the corners. The racks run up from the center of the troughs to each upper angle, forming a triangle. It is fed from either end of the roof, and will hold as much fodder as a man can carry. The whole structure is of iron and mounted on wheels, two of which can be locked at pleasure should it be desired to make it a fixture.

To DEADEN THE NOISE OF HAMMERING IN SHOPS, it has been suggested to place rubber cushions under the legs of the work-benches. We have found wool, felt, or any very thick loosely made woolen texture a much better material for this purpose than rubber. Pieces suitable for these pads can ordinarily be selected from tailors' clippings, and may be had for little or nothing.

An Interesting Railway Relic.

One of the most interesting relics we have seen in some time is a page from a Boston paper of 1825, containing a picture of the "Hetton Railroad," as designed by William Strickland, Esq., civil engineer. The stupendous line was to be seven miles five furlongs in length, and was to extend from the Hetton collieries, in England, to the town of Sunderland, on the River Wier. From the picture and the accompanying description, we find this railroad climbing hill and descending dale, and making no attempt to follow any grade. Several stationary engines are used to transport the coal wagons over these irregularities of the surface, and finally a locomotive, made of thick sheet iron, weighing five tons and possessing twelve horse power, takes them in tow

and pulls them to Sunderland. These locomotives are able to pull ninety-ton trains.

Below the general view of the road is a cut representing a train. The engine is neither a graceful nor a complicated affair, and consists chiefly of boiler, smokestack, and piston. There is no cab for the engineer, who stands on a platform beside the boiler and takes the weather as it comes to him. The tender is equally primitive in its construction, and appears to be about the size of an ordinary box wagon. The coal carts look very much like the bobtail dumps of the present day.

The letter-press on this page contains a description of the Hetton Road; a general article on the value and utility of railroads; an extract from a letter from Hon. De Witt Clinton, comparing railroads with canals to the former's injury, and a series of answers to questions respecting railroads by Thomas Tredgold, an English civil engineer, who was advanced enough in his ideas to believe in railroads. The entire page shows that it appeared at a time when the question of railroads vs. canals was being agitated. The great expense of the former seemed to be the chief difficulty in the minds of the canal advocates, who could not realize the enormous profits which would go to pay those expenses and enrich railroad men to boot. Governor Clinton's arguments are rather amusing in the light of our present railroad facilities.

The relic is weather-stained and exceedingly old-fashioned in appearance. It is the property of Mr. F. H. Munsell, of the Central. And when we look at this picture and think of the great four-track line it seems as if the relic must be a thousand years old. One cannot believe so much had to be learned in the space of fifty-five years.—*Buffalo Courier.*

Apprentice System Reviving.

We are pleased to see that the Ames Manufacturing Company, of Chicopee, Mass., are doing something toward a return to the old apprentice system. The company have been very much troubled to get skilled help, and also by having men leave after they have learned enough to begin to be useful. They have now adopted a plan something like the former system, only the term of service is not more than three or four years instead of seven, and they are overwhelmed with applications. The men sign a contract to stay to the end of the term, and the company will teach them the different branches of the business, so that when they go out they will be masters of the trade instead of knowing how to run but one machine or to do one particular kind of work. The company keep 10 cents a day from their pay until it amounts to \$100, which is given to them at the end of the apprenticeship.

The Yield of Wheat.

To test the bearing qualities of the leading varieties of wheat the Superintendent of the Ohio Agricultural College Farm sold seed wheat to farmers in various parts of Ohio and other States, requesting report of yield from each. The results are shown in the following comparison: Fultz, 24 reports average 25¾ bushels; Clawson, 10 reports average 23¾ bushels; Silver Chaff, 15 reports average 26¼ bushels; Velvet Chaff, 11 reports average 26 bushels; Gold Medal, 12 reports average 21¾ bushels; Sandomicka, 7 reports average 24½ bushels.

Porcelain Manufacture in New Orleans.

A happy coincidence of enterprise and discovery has just occurred in the South. While Mr. Surgi, of New Orleans, was arranging for the setting up of a porcelain factory in that city, expecting at first to import the kaolin to be used, the Assayer of the Mint received from Texas, for analysis, samples of clay which proved to be kaolin of the finest qual-

ity. The deposit had been known for some time, but nothing had been done with regard to its development. The announcement of the proposed porcelain factory called the attention of the owners of the deposit to its possible value, and the two interests have recently been brought together. The kaolin occurs near Bremond, Texas, where a bed of eighty acres or more lies close to the surface. The depth of the deposit is not given.

Water Cresses in Winter.

The *Gardener's Magazine* thinks that many of the writers in the horticultural papers do not know that frost kills water cresses. The delectable *Nasturtium officinale* is properly classed as a hardy plant, for it takes care of itself as a weed, and who, therefore, shall accuse it of tenderness? Where cresses are fast rooted and flourishing in a brook or any other water, it will be found that after a coat of stout ice has been formed the crop is gone entirely. That is to say, all the succulent leafy stems that might have been cut before the frost came have been destroyed by ordinary freezing, if only to the extent of about seven to ten degrees. It follows, therefore, that to preserve cresses for winter use anywhere out of doors shelter of some kind is necessary. There are many ways of doing this. It is not unusual for the market growers to let in a flood of fresh water when a sharp frost is expected. This covers the plants, and the ice is formed so far above them that they escape its effects. Another plan is to lay planks or tree loppings over the bed, and rough contrivances of this kind will carry a crop through a moderate frost, but a continued and severe frost will find its way through such penetrable stuff. Where it happens to be convenient, a frame is the best protection, and those who have to supply the table plentifully in winter would do well to arrange their plans with a view to the use of frames ultimately. That many who should know do not know that frost is destructive in its effects on cresses is not surprising, because hitherto the subject has but rarely obtained any special attention.

Glass Making in Ohio.

Five new glass works were started in Ohio last year, and several more will be added this year. The latest official statistics give 19 firms employed in glass manufacture, with 33 furnaces, having 292 pots and employing 2,032 men. In the production of window glass there are employed 7 furnaces, with 66 pots; flint glass, 19 furnaces with 199 pots; green glass, 4 furnaces with 27 pots. The glass works are in Bellaire, Columbus, Ravenna, Kent, Zanesville, Steubenville, Martin's Ferry, Bridgeport, La Grange, and Newark.

NEW MILKING STOOL.

The combined milking stool and pail holder shown in the engraving is the invention of Mr. G. W. Williams, of Eau Claire, Wis. The seat or stool carries a support for the pail, and is provided with a circular guard rail for retaining the pail in its position. There are two apertures in the seat



IMPROVED MILKING STOOL.

forming a handle by means of which it may be easily carried. The pail support is pivoted and is capable of moving up or down to accommodate itself to inequalities in the ground surface.

Hard Soap by a Cold Process.

Mr. R. F. Fairthorn, Ph.D., has contributed the following recipe to the *Druggists Circular*:

A good hard soap can be easily produced if four pounds of olive or sweet almond oil mixed with two pounds of soda lye, of the strength 36° Baume, are stirred until of the consistency of thick paste, when it should be poured into moulds, covered by several folds of muslin, and kept in a warm room for twenty hours. By this treatment the process of saponification, or union of the acids in the oils with the alkali, is complete. When these materials are first mixed the temperature of the mass rises, and in order to effect the entire union of ingredients so as to form the compound called soap, it is necessary that the heat thus generated should be maintained for some time, hence the necessity for covering the moulds and keeping them in a warm room.

He has found that it is desirable to use oil that is slightly rancid, or, if free from rancidity, to add about ten per cent of oil that has become so. Oil that is perfectly sweet requires two or three days to effect saponification.

Correspondence.

Dangers of Electric Light Wires.

To the Editor of the Scientific American:

Absence at sea prevented me noticing sooner your observations on the death of the fireman on board the *Livadia*, who was killed by an electric light current. If not too long behind the time of the occurrence, I would like to add my experience on the subject, in connection with Siemens machines, which you presume would be equally dangerous under the same conditions.

I have myself received the current capable of giving four lights (each of 400 candle power) through the legs, trunk, left arm, thumb, and one finger, between which I had caught a wire. I do not say I liked the sensation, but could have endured it if necessary; the finger and thumb were rendered incapable of motion, and the wire was so firmly held by them that it took a good tug to drag the wire through by main force. The only resistance the current had to overcome was my shoes and some damp boards.

In another case I know of an operator who inadvertently took a wire in each hand, thus completing across his chest a current of same strength as in my case, but without any harm resulting. The muscles of the hand were strongly contracted, and he was unable to call out for help, although he was perfectly conscious it was close at hand; but by walking back until he could exercise a strain on the wires he dragged them from between his fingers as I did. This, I think, shows that currents such as are generated in Siemens machines are incapable of causing death to a person not affected with heart disease. If, however, passed through the brain or spine it might be more serious, possibly resulting in temporary unconsciousness.

As the *Livadia's* fireman seems undoubtedly to have been killed by the dynamo current, I can only suppose that the machines there used were constructed to give currents of high tension for sake of getting a considerable number of lights on one circuit.

Perfect insulation of the leads throughout the entire circuit should be deemed a necessity, especially in a ship or other structure of iron. This is best done by using covered wire, not omitting to cover any joints that may be made.

Your suggestion about protecting the lamps and terminals is a very good one, even where the insulation of the leads has been attended to, for the reason that a man in renewing the carbons may be up a ladder or in a position from which he might easily fall in case he got even a slight shock, which by startling him might cause him to lose his balance. I think it is better that the exact amount of danger attendant on any system may be known, so that it may be guarded against and so avoided, and also to prevent those who otherwise could inform themselves from forming exaggerated notions of what that amount really is

J. W. L.

S. S. City of Berlin, Pier 37, New York.
January 5, 1881.

The New Comet Pennule.

To the Editor of the Scientific American:

Telegraphic announcement was received by me December 17, 1880, of the discovery of a new comet by Pennule at Copenhagen, Denmark, on the 16th ult. Dense clouds prevented any observations of the object until the evening of December 31, when in a very few minutes I picked up the comet and secured a good observation. It was at discovery in right ascension 18 hours 49 minutes; north declination 10 degrees 35 minutes. When observed by me on the 31st, it was, by estimation, in right ascension, 19 hours 47 minutes; north declination 19 degrees 30 minutes. This brought the comet about midway on a line drawn from Albireo in Cygnus to Epsilon Delphinus—the last star in the tail of the Dolphin. Good observations were also obtained on the two following evenings.

The motion of the comet is northeast something more than one degree daily; so that its position is improving, and being quite a bright telescopic comet, it may be readily seen in moderate telescopes for some time. The present direction of its motion is toward Zeta Cygni.

It is nearly 3 minutes of arc in apparent diameter, has a considerable condensation not quite central, but no tail.

WILLIAM R. BROOKS.

Red House Observatory,
Phelps, N. Y., January 4, 1881.

Cutting Hard Steel with Soft Iron.

To the Editor of the Scientific American:

About forty years ago, having often heard that hard steel could be cut readily with a circular disk of sheet iron when driven at a high motion, I made a disk about ten inches in diameter out of a piece of heavy stove-pipe iron, having a round eye at the center about one and a half inches in diameter. I then put a stick of hard wood in the turning lathe, turned it off true, making a wooden mandrel for holding this iron disk, just as a circular saw is held true on a metallic mandrel. The periphery of the disk, after it was secured to the wooden mandrel swinging in the lathe, was ground and filed until it would run as true as a millstone. The disk was secured to the collar or shoulder of the wooden mandrel by putting four screws through the disk into the wood. While the disk was revolving at a high motion the soft sheet iron would cut off a ten inch cold-steel file in a few seconds. After we were satisfied that soft iron would cut cold and

hard steel (no matter how hard), the disk was put on one of the journals of a circular saw which was driven at a very high motion; and that disk was employed for many years afterward to gum saws of all sizes.

During the past season, having occasion in a new shop to make a goodly number of cutters for the power moulding machine, we made another sheet iron disk, which was fitted to the mandrel of one of the little circular saws, which revolves about two thousand times per minute. After the periphery had been dressed off as true as practicable, that disk of soft iron would (and will) cut off a bar of cold steel four inches broad and one-fourth of an inch thick in one minute, making a kerf as true and smooth as a good saw will cut through a piece of timber. The disk will save an immense amount of filing when making cutters for moulding machines, as we can cut slots into the heel ends of the cutters, and cut and dress off the edge ends faster than twenty men can dress the steel away with chisels and files. One can "gum" an old cross-cut saw, or a mill saw, or drag saw, or large circular saw with such a disk in a few minutes, without any apprehension whatever of cracking or injuring the saw blade. After a large saw has been gummed by an iron disk, if one has a small emery wheel of the proper form he can dress up the teeth almost to a perfect cutting edge without a file, thus saving an enormous expense for files.

I have found in some instances, when gumming cross-cut two-men saws, that the steel of certain kinds of saws would be case-hardened a little on both sides of the kerf made by the disk. That very thin film of case-hardened steel would wear away a new file rapidly. But by employing an emery wheel instead of files until all the case-hardened steel had been removed, the expense for files is always small. Indeed, we use files only to fit up the very points of the teeth.

I may add, for the advantage of beginners, that the true way to fit up the periphery of a disk is to cut it with heavy shears as nearly round as practicable, after which hold a piece of a grindstone or sandstone so that the edge of the disk will strike it when in motion. We always use a stone and file, and then attempt to cut steel a little, thus working off the periphery until it is as smooth and true as it can be made. Then the cold and soft iron when in high motion will literally melt the hard and cold steel and drive the melted metal from the bar in a stream of white-hot sissing and burning steel dust.


S. E. T.

Orange, N. J.

The Meteor.

To the Editor of the Scientific American:

I send you a diagram of a most singular atmospheric phenomenon witnessed here on the 30th ult. The display in the heavens of so peculiar a combination of reflection and



THE METEOR OF DECEMBER 30, 1880, AS SEEN AT SUNK CENTER, MINN.

refraction of the rays of light was of such rare occurrence I doubt if the like was ever before seen. You may the better understand me if I explain from the diagram. It was first observed at five minutes before eleven o'clock, A.M. The mercury registered at the time 5° below zero. The sky was clear, save that the air was full of floating frost crystals that gave a leaden aspect to the heavens around. The sun, as I have tried to represent, was surrounded by a double halo, both very perfect and distinct in outline. To the right and left of the sun and on the rim of the first halo were very bright parhelia or mock suns. Passing through the sun and these mock suns and around the whole dome of the heavens, seemingly, at about 20° from the horizon, was a great circle of light. This had the appearance of the large ring of Saturn—very bright and about 1/4 of a degree in width. Again, about 15° from the rim of the outer or

second halo, and in the path of this circle of light, were other parhelia on either side of the sun; and on the opposite side of it, from the sun, was another or third parhelia. This circle was very brilliant, describing a diameter of about 100°. Intersecting this bright circle, at the points of the two parhelia, passed a somewhat less brilliant ring of light in form of an ellipse, with its longest diameter some 1.0° and the short one 80°. At the northern end of the ellipse were three parhelia, as represented in diagram. These mock suns were all very distinct and beautiful. To complete this phenomenon there was as perfect a rainbow as we ever see in mid-summer, describing an arc of about 35°, with its crown resting on the rim of the second or outer halo, directly over the sun. In fact this rainbow was of such brilliancy that it was too dazzling for the uncovered eye to look at, unlike the soft mellow tints in our summer rainbow phenomena. The duration of this most rare spectacle was an hour and fifteen minutes.

F. M. MORGAN,

Assistant Principal, Sauk Center High School,
Sauk Center, Minn., December 31, 1880.

New Solvents for Nitrocellulose.

To the Editor of the Scientific American:

In the preparation of nitrocellulose compounds, which are known as celluloid, and are also used as varnishes, some new solvents have been patented in Germany by Parkes. Among others he suggests the use of a solution of tetrachloride of carbon and camphor, either alone or with gums, resins, oils, dyestuffs, etc. He also proposes to use the bichloride of carbon and camphor, when the solution takes place under the aid of heat and pressure. Camphor, too, is a good solvent when heated to its melting point; at this temperature and under pressure it dissolves the nitrocellulose as fast as it can be mixed with the melted camphor until it forms a stiff mass. This mass, to which other substances may be added, can be rolled and pressed into moulds. To lower the melting point he adds oil, paraffine, turpentine, alcohol, benzol, ether, etc., whereby thinner solutions are obtained.

Another powerful solvent for nitrocellulose can be made by conducting sulphurous acid gas through granulated camphor, or by dissolving camphor in sulphurous acid.

A solution of camphor in benzole of such quality that no unpleasant odor is left when the compound is done, works very rapidly with the aid of heat and pressure. Oils, gums, resins, and dyes can be added according to taste. Turpentine and camphor also dissolve it with heat and pressure very quickly. Nitrocellulose softens rapidly if sprinkled with alcohol, ether, or other solvents of gun cotton and then pressed into hot moulds.

Sometimes it is better to dye the nitrocellulose before it is dissolved instead of dyeing the compound, as brilliant and delicate colors are obtained in this way of greater beauty than by the usual manner. If the compounds are to be used as lakes, the above-named solvents can be used, but of course larger quantities of the solvent are required than for making solid bodies. The solvents can be used alone or mixed with gums, resins, pigments, and metallic bronzes, to obtain the greatest variety of waterproof paints for surfaces, as well as cement for capping bottles. The solvents of nitrocellulose above given, as well as the bisulphide of carbon mixed with benzole and alcohol, are likewise good solvents for shellac.

D. I. Z.

[The tetrachloride of carbon is a colorless liquid boiling at 170° Fah.; specific gravity, 1.56. It can be made by the action of chlorine gas upon bisulphide of carbon, or on chloroform; also by the action of pentachloride of antimony upon bisulphide of carbon; sells at \$3 per pound.]

The bichloride of carbon is a very mobile liquid; specific gravity, 1.62; boiling at 248° Fah. It is generally made from the tetrachloride. It is quoted at \$17 per pound in Berlin; hence we find a strong objection to its use in the arts at present.—ED. SCI. AM.]

Easy Test for the Purity of Olive Oil.

When it is desired only to ascertain whether the oil is pure or not without precise reference to the nature of the oils used in adulteration, take equal quantities of olive oil known to be pure and the oil to be tested, place the samples in separate test tubes, into which a good thermometer may also be inserted, and heat each separately to a temperature of 482° Fah. The pure oil will become somewhat paler during the heating, while the adulterated oil will turn darker. The pure oil will emit a pleasant smell, while the adulterant oils will give off an offensive odor.

To Prevent Clouding of Mirrors by Moisture.

A writer in the *Manufacturer and Builder* says that by coating over the surface of glass mirrors with glycerine their clouding by the accumulation of condensed water vapor will be prevented for a considerable time. The attraction of the glycerine is so great for the water as to absorb the latter as fast as deposited. This hint may prove of great use to dentists, who are frequently troubled by the clouding of mouth-mirrors, and it may also be of value to those who are compelled to shave themselves in chilly apartments.

SALT WATER FOR STREET USES.—The town of Tyne-mouth, England, has lately completed arrangements for supplying salt water from the mains of all the principal thoroughfares of the place. Salt water is to be used for flushing the sewers, watering the streets, and supplying public baths.

DYNAMO-TELEGRAPHY.

Until within a comparatively recent period all attempts at transmission of telegraphic messages with dynamo-electricity have proven futile.

There seemed to be no probability that the old voltaic battery system, involving multitudinous inconveniences, would ever be supplanted, and there are at the present time only two systems of dynamical telegraphs which are operative from a successful standpoint, both being of very recent origin and as yet comparatively unknown to the public.

For the successful operation of any telegraph line two important elements enter into consideration, viz.:

- 1st. A steady or uniform current.
- 2d. Delicate adjustment of receiving instruments; and any variation of the former necessarily precludes the possibility of the latter, so that they may be operative under all conditions of the line.

It is scarcely necessary to add that electricians have never fully appreciated the difficulties to be overcome in this class of telegraphy, and their attempts heretofore but verify this assertion.

These fluctuations of current are due to several causes, viz.:

- 1st. Any change of velocity in the generator.
- 2d. Any variation of external or internal resistance (the latter being often the result of the former, owing to high normal internal resistance); and either necessarily varying the electromotive force, and hence the current to line.
- 3d. To a total discharge of the magnetism in the field of force magnets on opening the line, and thus completely breaking down the currents until the line shall again be closed.

This might properly be included under the same head as the second, inasmuch as a total discharge of the field of force magnets is, theoretically speaking, simply the result of an infinite resistance offered to the current.

A dynamo machine produces a current of electricity by a series of actions and reactions in its internal mechanism; that is to say, the armature of the machine acts upon the field of force magnets, and these in turn react upon the armature at each revolution, and thus a set of actions and reactions ensue until a maximum effect is attained. This results when the neutral fluids (so to speak) balance each other.

Now, any increase in the external or line resistance acts to discharge the field of force magnets, and a break in the line, which necessarily occurs on opening a key to transmit a signal, increases the resistance to an infinite amount, and hence totally discharges the field of force magnets. Hence, inasmuch as it requires a definite time to charge the line by the above described series of actions and reactions, it is obvious that there would ensue at each break such fluctuations of current as would totally prevent any transmission of signals.

Furthermore, such an increase of external resistance reacts upon the machine and heats it internally, thus offering another objectionable element.

Thus we have a series of changes, which, acting under varying circumstances, produce fluctuations in the line current beyond the limits of accurate adjustment of delicate receiving instruments required on long lines of high resistance.

The problem, then, to be solved is:

- 1st. To prevent the total discharge of the field of force magnets on any variation of external resistance; or, at least, to provide some means for a constant relation between the resistances and the electromotive force of the machine.
- 2d. To prevent undue variations of current caused by an increase or decrease of the velocity of the generator.

Two systems have been devised which involve all of the essential principles required by the problem: one the invention of Mr. Stephen D. Field, Jr., and the other of Dr. Orazio Lugo, of New York city.

To obviate the first difficulty, Mr. Field energizes his field of force magnets by an independent generator, actuated by an independent power, the circuit from the commutators being through the field of force magnets of said generator, thence through the coils of the field of force magnets which develop the line currents. This circuit is entirely independent from the line circuit, and constitutes, as it were, an infinite supply of electricity to energize the field of force magnets, or at any rate an inexhaustible supply dependent on the power and capacity of the generator.

Hence, any change of resistance in the line can have no appreciable effect upon the field of force magnets.

To obviate any change in the current due to a change of velocity of the generator, he connects up a series of line generators whose field of force magnets are energized as above, and connects the commutators and said line generators to common supply points, being necessarily at the opposite poles of the machine. Each generator of line currents is actuated by an independent pulley, so that any change of velocity of any one generator can only affect the sum total of currents by its proportional ratio of gain or loss.

Theoretically, then, an infinite number of generators would be required to produce the best results, bearing in mind, of course, that such a series implies a range of velocities or changes of relative velocities varying from zero to infinity.

It is found in practice that a series of five generators produces satisfactory results. This, of course, is apparent if we consider that a change of velocity in any one from a normal velocity is not liable under ordinary circumstances to be more than ten per cent.

It is apparent that any change of velocity in the generator which energizes the field of force magnets would in-

crease proportionately the electromotive force of the line generators. This is obviated by a governor which regulates the speed of the motive force and keeps it within practical limitations.

The same system of generators might be used to energize the field of force magnets as is required to generate line currents, thus making the system automatic in its operation; but this feature does not appear to have suggested itself to Mr. Field. In this manner any change of speed in any one of the energizing machines would only affect the line field of force magnets a proportional amount, as above suggested.

Thus it will be seen that if any one of the five generators increases or decreases twenty per cent from the normal rate it only has a proportionate effect of one twenty-fifth of the whole line current, which in practice is found to be inappreciable.

The broad idea of energizing the field of force magnets by an independent generator is not new *per se*, as is seen in the Wilde machine; but Mr. Field claims to be the first to energize a series of field of force magnets in this way, and just how much invention is involved in this idea it is not the province of this article to discuss.

Dr. Lugo has recently invented and patented a much simpler method of avoiding these difficulties, dependent upon well known electrical laws.

He uses a single current generator on the line with a shunt wire of low resistance, connecting the opposite poles thereof; so that the total resistance is that due to the lines, the shunt, and the machine.

The resistance of the shunt is less than that of the external lines and greater than that of the machine itself.

There results from this combination, under well known laws, a proportionate division of current between the line and the shunt; a much larger portion, of course, going through the shunt because of its low resistance.

It is obvious, then, that the field of force magnets can never be discharged, for there is always a path of low resistance for the current. Hence the electromotive force is dependent only upon two causes for its variations, viz., a change of velocity of the generator and a change of resistances between the shunt and the line. The former it is proposed to regulate by electrical governors, such as are well known, dependent upon the current sent to line, and the latter is in a measure automatically regulated by the shunt itself, inasmuch as changes of fluctuations which result from changes of resistances in the external line necessarily increase the flow in the shunt itself, and hence vary the resistance of the shunt by heating it. Hence there can be no change of resistance in the internal machine, because normally it is much less than that of the shunt. Of course in practice these adjustments must be made dependent upon varying circumstances of the external lines, but certain ratios may be attained which will produce the best results, and theoretically this will be when these line resistances equal that of the shunt.

When they pass below this limit the system is, of course, inoperative; but there exists a sufficient limit under ordinary circumstances to afford a perfect working system. This limit, it will be understood, is dependent upon the relative sectional area of the external line and that of the shunt, which affords sufficient resistance to prevent the machine from heating; thus in practice the generator never grows warm.

An attendant at the shunt may regulate variable resistances by testing the warmth thereof. Hence as long as a mean temperature exists a uniform current flows to line and no change need be made.

Both of the above described systems are in use, and the best results are attained; it being found that steady currents at all times flow on the line.

It is then entirely probable that within the next decade we shall find our large telegraphic corporations operating their elevators, supplying motive power, heat, and light throughout their buildings, and electricity for their lines from one common source of power.

Thus saving annually thousands of dollars, and being happily rid of numerous annoyances consequent upon such a system of forces as now exists by a concentration thereof at one common center.

C. J. KINTNER,

U. S. Patent Office.

Improvements in Cotton Pressing.

The new Morse Compresses in New Orleans are producing astonishing results by way of largely increased cargoes of cotton from this port.

The ship Mary E. Riggs, of 1,277 tons American register (1,226 British), received a cargo of 5,400 bales of cotton, weighing 2,568,640 pounds; making 2,011 pounds per ton American and 2,095 pounds per ton British measurement.

The first cargo of this ship from this port was 3,740 bales; the last, and largest (previous to the present one), was 4,364 bales, weighing 1,943,498 pounds. Her present cargo of 5,400 bales exceeds her largest previous cargo 1,036 bales, or 625,142 pounds, exceeding her largest previous cargo 1,404 bales of same average weight. With freight at one cent per pound and five per cent primage, the value of this increase, for this medium-sized vessel, is about \$6,600. This cargo was compressed, without the advantage of a "tie puller," in the ordinary course of business by the Factors' Press, one of the seven large Morse Compresses. The only cargoes of single bales taken by sail vessels approximating this one are the following:

The Minnie H. Gerow (1,304 tons American), from the Champion Press, 2,481,790 = 1,903 pounds per ton measurement. The Western Empire (1,399 tons American register), from the Champion Press, 2,022 per ton. The Minnie H. Gerow, from the International Press (Taylor hydraulic, 64-inch cylinders), 2,644,906 = 2,028 pounds per ton. But in all of these cargoes of 1,903, 2,022, and 2,028 per ton measurement, tie pullers were used, for which is claimed an advantage of 20 per cent. If the present cargo of the Mary E. Riggs had had this advantage, her 2,011 pounds per ton American, and 2,095 British, would have been 2,413 and 2,514 per ton—or say 20 per cent larger than any cargo of single bales ever cleared in this country.

Since the above, the British ship Ben Lomond, of 887 tons register, cleared at New Orleans by her agents, Messrs. Forstall, Ross & Clayton, with 4,363 bales cotton under deck, none in cabin or crew spaces, weighing 2,054,848 pounds, making 2,316 pounds to the ton measurement. This is the largest cargo per ton ever taken by a sail vessel from an American port. The larger part of this cargo was "doubled." The cotton was tied by hand (by colored men), and consequently without the 20 per cent advantage claimed for steam "band pullers." It was all compressed at the Southern Press by the 90-inch cylinder Morse Compress. Not more than three years ago the average cargoes of ships from this port did not exceed 1,425 pounds per ton register; and for other modern-built presses the average is now about 1,725. The above cargo of 2,316, without tie pullers, therefore, exceeds recent average compressing by 35 per cent, or 524,773 pounds, in a single cargo of a small ship like the Ben Lomond, and at the rate of freight received makes a gain of £820—say, \$3,936. The proprietors claim that under more favorable circumstances the 90-inch Morse Compress can considerably excel the above.

The Keely Motor Deception.

It is stated that immediately after the annual meeting of the Keely motor stockholders, held two weeks ago, a couple of gentlemen who are heavy on the motor stock called upon Mr. Keely and demanded that he should at once name a day and date for a public exhibition of his wonderful apparatus. They had a very plain talk with him, and announced that they voiced the sentiments of most of the parties interested. Unless the engine was put to work within a short time and sawed wood, sent a locomotive to Jericho on a pint of water, and did a hundred other things claimed for it, they would resist further payments to the discoverer.

Keely was not the least disturbed by their threats, and when they found this they began to persuade and coax him, as a boom in the stock was needed. The man of mysteries declined to accede to their requests, but said: "I see my way as clear as sunlight." Then he eased their minds by stating that he would make no further demands upon the company for funds for his own use, because he had enough to live on. This was very assuring, and made the stockholders happy. If they did not give him the money to complete his invention, he told them that he would keep his secrets to himself. This caused some bitter words, and Mr. Keely was the recipient of some unvarnished opinions. Already they had spent over \$500,000 on the machine, and could see no appreciable results. Keely plainly informed his visitors that he would not give an exhibition for two months at least, because the engine needed some alterations.

Keely has had a new engine built at a cost of \$10,000, and the lower one has been placed on the lower floor of the building on Twentieth street. Keely promised that when the exhibition is given both engines should be placed in operation, so as to show the improvement in the new one over the old. The callers were compelled to depart without being able to convince Keely that a time for a boom was near at hand.

The stock of the Keely Motor Company is now held at about \$7 per share. This time last year it was worth \$18. The highest it ever reached was \$300, when 3,000 shares were disposed of in New York at the figures named. The average price has been about \$150 per share, and the transactions at those rates have been large. Of the present stockholders but few were on the original list, they having all been able to get out at the top price. Keely has been at work some seven years.—*Philadelphia Record.*

Paraffine as a Wood Preserver.

A German chemist, Dr. Schal, has established the useful fact that wood impregnated with paraffine is preserved from rot, especially when employed in alizarine manufactures, where it is exposed to the decaying action of damp, acid, and alkaline lyes. Wooden vessels which become totally rotten in two months last for two years when impregnated with paraffine. The preparation of the wood is effected by drying it in warm air for three weeks, then steeped in melted paraffine to which has been added some petroleum ether or sulphuret of carbon. In preparing this bath great care must, however, be exercised, owing to the inflammability of its ingredients. To prevent the paraffine from escaping from the pores, the wood should be coated with oil varnish or soluble glass, washed after drying with diluted hydrochloric acid. The silicic acid thus formed clogs up the pores from the outside, and protects the paraffine from the action of water. Paraffine, melted with equal parts of linseed or rapeseed oil, is also, according to Dr. Schal, useful for coating iron vessels, which in chemical manufactories are otherwise very liable to rust.

IMPROVED HAND PRESS.

The engraving shows a domestic hand press for fruit, cracklings, hominy, and other articles which require separation from the liquid which they may contain. The invention consists of a perforated bowl or receptacle having a rigid handle extending at right angles to the plane of the bowl, and a perforated presser head conforming to the bowl and connected by a slide with the handle of the bowl. The sliding presser head is connected by a link with a lever handle pivoted to the main handle. By bringing the presser head down on the material contained in the bowl by means of the lever, the liquid is expelled through the perforations. This invention was lately patented by Mr. J. T. Haile, of Whitesborough, Texas.



HAILE'S HAND PRESS.

GOLD IN NEW YORK STATE.—Two hundred and eighty-three notices of discovery of gold and silver were officially entered at Albany, last year. The alleged deposits are chiefly in Hamilton County. The law prescribes that mines of gold or silver found in New York shall be property of the State, but gives to the discoverers or their assigns the right to work them for twenty-one years free of any royalty on condition that they file with the Secretary of State notices describing their discoveries. After the twenty-one years the Legislature may dispose of the mines at its discretion; but the discoverers or their representatives shall be preferred in contracts for working them.

IMPROVED OIL-STOVE WICK TRIMMER.

In ordinary oil burning stoves it is necessary to remove the top of the stove, and any utensils which may be in use in order to trim off the crust which forms on the wicks and prevents the free operation of the stove. It is necessary to put out the fire before the wick can be trimmed. Beside the great inconvenience and delay in trimming the wick with shears in the common way, the wicks are wasted, and with the sharpest shears they will be poorly trimmed on account of their great width, and an uneven burning surface will be left which causes the stove to smoke and throw off a bad odor. Kerosene stoves are often condemned for this reason alone.

By means of the simple invention shown in the engraving these inconveniences are avoided, and the wick is quickly and evenly trimmed. This device is in every way superior to the old method.

A wick should never be cut; it is only necessary to remove the crust, and the stove or lamp burns freely with a flame of the proper form.

This invention is simple in its application and is thoroughly practicable. It consists of a wire rod carrying one or more lateral arms extending over the wick tubes. This wire passes through the front of the stove, and is provided with a ring or handle by which it may be grasped and moved back and forth over the ends of the wicks while they are turned down. By this means the crust is removed and a clean and free burning wick is left, without extinguishing the flame or removing any part of the stove or furniture.

Each wick tube is provided with a guide which is bent up at the ends forming a stop for the trimming attachment. Oil stove manufacturers may, with advantage, adopt this simple but useful and effective invention.

This invention has been patented by Messrs. Walker and Williams, and is owned by Walker, Williams & Co., Sing Sing, N. Y.

A Use for Cotton Seed Hulls.

The Chicago Railway Review reports that the use of cotton seed hulls as a substitute for cotton waste in packing the journal boxes of cars and locomotives has been adopted on several roads, and others are preparing to adopt it. It is claimed that the hulls are actually superior to ordinary cotton waste for packing, and would be preferable at the same cost. But the cheapest cotton waste is worth 7½ cents a pound, and the superior grades range as high as 14 cents. Cotton seed hulls can be delivered in any part of the United States at one cent a pound.

Cements for the Shop.

Iron Cement for Closing the Joints of Iron Pipes.—Take of coarsely powdered iron borings, 5 pounds; powdered sal-ammoniac, 2 ounces; sulphur, 1 ounce; and water sufficient to moisten it. This composition hardens rapidly; but if time can be allowed, it sets more firmly without the sulphur. It must be used as soon as mixed, and rammed tightly into the joint.

2. Take sal-ammoniac, 2 ounces; sublimated sulphur, 1 ounce; cast iron filings or turnings, 1 pound; mix in a mortar and keep the powder dry. When it is to be used, mix it with 20 times its weight of clean iron turnings or filings, and grind the whole in a mortar; then wet it with water until it becomes of convenient consistency, when it is to be applied to the joint. After a time it becomes as hard and strong as any part of the metal.

Cement for Uniting Leather and Metal.—Wash the metal with hot gelatine; steep the leather in an infusion of nut-galls (hot) and bring the two together.

Cement for Leather Belting.—One who has tried everything, says that after an experience of fifteen years he has found nothing to equal the following: Common glue and isinglass, equal parts, soaked for ten hours in just enough water to cover them. Bring gradually to a boiling heat, and add pure tannin until the whole becomes ropy, or appears like the white of an egg. Buff off the surfaces to be jointed, apply this cement warm, and clamp firmly.

Steam Boiler Cement.—Mix two parts of finely powdered litharge with one part of very fine sand, and one part of quicklime which has been allowed to slake spontaneously by exposure to the air. This mixture may be kept for any length of time without injuring. In using it, a portion is mixed into paste with linseed oil; or, still better, in boiled linseed oil. In this state it must be quickly applied, as it soon becomes hard.

Turner Cement.—Melt one pound of rosin in a pan over the fire, and when melted, add one-quarter of a pound of pitch. While these are boiling, add brickdust until by dropping a little on a cold stone, you think it hard enough. In winter it may be necessary to add a little tallow. By means of this cement a piece of wood may be fastened to the chuck, which will hold when cool; and when the work is finished, it may be removed by a smart stroke with the tool. Any traces of the cement may be removed from the work by means of benzine.

Wollaston's White Cement for Large Objects.—Beeswax, 1 ounce; rosin, 4 ounces; powdered plaster of Paris, 5 ounces. Melt together. To use, warm the edges of the specimen, and apply the cement warm.

Gutta Percha Cement.—This highly recommended cement is made by melting together, in an iron pan, two parts of common pitch and one of gutta-percha, stirring them well together until thoroughly incorporated, and then pouring the liquid into cold water. When cold it is black, solid, and elastic; but it softens with heat, and at 100° Fah. is a thin fluid. It may be used as a soft paste, or in a liquid

Fig. 1.





Fig. 2.



IMPROVED OIL-STOVE WICK TRIMMER.

state, and answers an excellent purpose in cementing metal, glass, porcelain, ivory, etc. It may be used instead of putty in glazing windows.


The miner's inch is the amount of water flowing in one second from an orifice 1 inch x 1 inch, under a head of 6 inches, measured from the upper side of the orifice.

SPRING-MAKING TOOL.

A hand tool to be used principally by jewelers for making wire spirals for shirt studs and buttons is shown in the annexed engraving. The mandrel upon which the spirals are formed is secured to an ordinary tool handle, and a carrier is fitted to the lower portion of the mandrel, which is threaded, the pitch corresponding with that of the spiral to be made. The end of the wire is placed in a slot in the end of the mandrel, and while the handle is turned with one hand, the carrier is held in the other hand, and the wire is pressed down upon the mandrel by a small lever pivoted to the carrier and grasped between the thumb and finger.

The crook at the end of the coil is formed by bending the wire back upon the end of the lever.

This invention was recently patented by Mr. A. R. Wilbur, of Baltimore, Md.



TOOL FOR MAKING SPIRAL SPRINGS.

NEW INVENTIONS.

An improvement in that class of devices that are designed for releasing a horse instantly from the vehicle to which he may be attached, has been patented by Mr. Whiteford S. Martin, of Maybinton, S. C. An iron rod is attached to each end of the whiffletree and extends forward a short distance alongside the shafts or thills. The short leather traces are attached to the front ends of these rods by means of keys or eyebolts, which may be withdrawn—for the purpose of releasing the horse from the vehicle—by means of cords or straps that pass through a ring on the crupper or back-strap of the harness, and extend back over the dasher of the vehicle, so as to be easily accessible to the driver.

Mr. John W. Donnel, of Bedford, Iowa, has patented a self-adjusting driver for millstones, by which the stone is balanced on the top of the cock head, and thereby adjusted with a minimum of friction. The invention consists in the combination of a yoke pivoted to the upper end of a mill spindle so as to swing in a vertical plane, and four levers arranged in pairs, one pair being pivoted to each side of the yoke and suspending another yoke, which serves to make all the levers move together. The levers pivoted to the pivotal yoke extend above the point of the mill spindle and are provided with set screws, which bear against the bail at points lying in the same plane and in line with the point of the spindle.

A snow scraper, patented by Geo. F. Bond, of Troy, N. Y., is an improvement in apparatus for clearing ice fields for ice harvesting. Side boards or runners are pivoted or hinged at the front end and provided with apparatus whereby they may be made to assume the V-form, or closed into a parallel position for discharging their load at the will of the operator.

A sugar washing process and apparatus, patented by John V. V. Booraem, of Brooklyn, N. Y., acts to thoroughly wet and wash the crystals of sugar with water or sirup, and deliver the mass in a perfectly homogeneous state to the centrifugal machines. For this end a perforated pipe delivers water in a finely divided state upon the sugar just prior to the passage of the latter through crushing rollers, the pipe and rollers being arranged in relation with each other to secure the object sought. After crushing the sugar is further worked by revolving screws.

An improvement in tile and brick kilns, patented by Mr. Eber Davenport, of Waynesville, Ill., saves time, labor, and fuel. The kiln is circular, has furnaces and fire walls arranged around its peripheral wall, and a central opening in the top. The circulation of the heated air and gases is first upward near the outside wall, then downward, then upward again and out at the central opening, the deflection of the heated currents being effected by the fire walls, crown wall, and vertical passages with bottom flues formed in laying the bricks or tiles when filling the kiln.

A patent on a folding car step, granted to Mr. Josiah W. Radbraugh, of Columbus, Ohio, covers a combination of the folding steps of a car with mechanism whereby the steps on both sides of a car may be simultaneously adjusted by a single movement of a lever.

THE COMMON HORNBILL.

The common hornbill (*Tinotoceros abyssinicus*) is a strong, short-winged bird with a short tail and comparatively long legs. The beak is very large, curved slightly, flattened on the sides, and is provided with a short but quite high protuberance at the root. This protuberance begins on the center line of the beak, projects forward to about one-third of the length of the beak, and may be open or closed in part, and has the general appearance of a helmet. The legs are much more powerful than those of other hornbills and have very strong claws. The sixth feather of the wing is the longest, and the point of the wing projects only a short distance beyond the upper arm feathers. The color of the bird is absolutely black, excepting ten yellowish white feathers of the wings. The eye is dark-brown, the iris lead blue and red, and the beak is black excepting a spot on the upper beak, which is yellow in front and red in the rear. The length of the bird is about four feet. It is found in Central and Southern Africa.

The White Ant's Parasites.

At a late meeting of the Philadelphia Academy of Natural Sciences, Dr. R. S. Kenderdine exhibited specimens of the wonderful parasites found recently by Dr. Leidy in the intestines of the white ant, where they occur in such myriads as to constitute a mass greater in bulk than the food of the insect. When the intestine is ruptured millions of these living occupants escape, reminding one of the pouring out of a multitude of persons from a crowded meeting-house. So numerous are these parasites, and so varied their form, movement, and activity, that their distinctive characters cannot be seen until they become more or less widely diffused and separated.

The termites or white ants are so common, easily obtained and preserved alive, and their parasites are so exceedingly numerous and constant in their occurrence, that once the fact becomes sufficiently known the insects will be favorite subjects to illustrate at once the infinity of life and the wonders that are revealed by the microscope. The forms observed, together with a species of microscopic plant found in the same situation, are fully described and beautifully illustrated by Dr. Leidy in the forthcoming number of the Journal of the Academy.

HUMAN TREES OF INDIA.

BY DANIEL C. BEARD.

All those who feel a sufficient interest in the subject to study or notice the facts must at times be struck with amazement at the wonderful resemblance of certain insects and other animals to vegetable and inanimate objects. So exact is this resemblance in some instances as to deceive the most experienced. Wallace, the great naturalist, was very anxious to secure a specimen of a certain brilliant butterfly, but was unable for some time to capture one on account of the creature's sudden unaccountable and mysterious disappearance. He finally discovered that the outside of this insect's wings was an exact representation of a leaf. When the butterfly alighted upon a shrub and closed its wings it completely deceived even this experienced scientist. Some species of lobsters found at Bermuda so closely resemble submarine stones, even to the coating of sea weeds, that I have passed by an aquarium containing them supposing the tank to be uninhabited. The common katydid, whose constantly-repeated notes, late in summer, warn us of the approaching frosts, has a representative in South America, whose wings not only resemble a green leaf, but, to add to the deception, the tips of the wings are ragged and discolored, having the exact appearance of a leaf that has been disfigured from the attacks of caterpillars. I once had one in my studio, and it was with great difficulty that I could convince visitors that it was not an artificial insect with wings made of real leaves. In the snow-covered regions of

the North the foxes, hares, bears, and birds, with very few exceptions, assume the prevailing white color of the surrounding objects. Man has not been blind to these hints. There are various tribes of savages who successfully imitate stumps and stones by remaining immovable in crouching positions so as to baffle their pursuers.

This mimicry is carried to a wonderful degree of perfection in India. That strange country, as Dr. Latham says,

taining hand. But the most ingenious device to escape capture is that shown by the Bheel robbers in the accompanying illustration. It often happens that a band of these robbers are pursued by mounted Englishmen, and unable to reach the jungle, find themselves about to be overtaken upon one of those open plains which have been cleared by fire, the only shelter in sight being the blackened trunks or leafless branches of small trees that perished in the flames.

For men so skilled in posturing this is shelter enough. Quickly divesting themselves of their scanty clothing, they scatter it with their plunder in small piles over the plain, covering them with their round shields so that they have the appearance of lumps of earth and attract no attention. This accomplished, they snatch up a few sticks, throw their body into a contorted position, and stand or crouch immovable until their unsuspecting enemies have galloped by.

When all is safe they quickly pick up their spoil and proceed upon their way.

The Rev. J. D. Woods gives an interesting account of these marvelous mimics. I quote the following:

"Before the English had become used to these maneuvers, a very ludicrous incident occurred. An officer, with a party of horse, was chasing a small body of Bheel robbers, and was fast overtaking them. Suddenly the robbers ran behind a rock or some such obstacle, which hid them for a moment, and when the soldiers came up the men had mysteriously disappeared. After an unavailing search, the officer ordered his men to dismount beside a clump of scorched and withered trees; and the day being very hot, he took off his helmet and hung it on a branch by which he was standing. The branch in question turned out to be the leg of a Bheel, who burst into a scream of laughter, and flung the astonished officer to the ground. The clump of scorched trees suddenly became metamorphosed into men, and the whole party dispersed in different directions before the Englishmen could recover from their surprise, carrying with them the officer's helmet by way of trophy."

Marine Fauna of the New England Coast.

To the current number of the *American Journal of Science and Arts*, Prof. A. E. Verrill contributes an article on the remarkable marine fauna discovered during the present season off the southern coast of New England by the naturalists connected with the U. S. Fish Commission. The stations at which dredgings were made are all located in the regions designated on the charts as "Block Island Soundings," and nearly all proved to be exceedingly rich in animal life, the vast abundance of individuals of many of the species taken being almost as surprising as the great number and variety of the species themselves. Crustacea, mollusks, annelids, and echinoderms were most numerous. The very large number of specimens obtained on the three trips has, as yet, been only partially examined, but enough has already been done to prove this region to be altogether the richest and most remarkable dredging ground ever discovered on our coast. Of mollusks, about 175 species were taken, 120 of which were not before known to occur on the southern coast of New England; about 65 are additions to the American fauna, and of these about 30 are apparently undescribed species. The star-fishes and ophiurians were exceedingly abundant and beautiful at all the stations, and many species not previously known to our coast were taken, several of these appearing to be undescribed, while others were known only from Northern Europe or from the deep waters off Florida. Many of the species have only recently been obtained from the northern fishing banks off Nova Scotia. One new species of *Archaster* was particularly abundant, several thousands of specimens having been taken. But the two largest and most beautiful species of this genus were *Archaster Agassizii* (new),



THE COMMON HORNBILL.

"of a teeming, ingenious, and industrious but rarely independent population. It is a country of an ancient literature and ancient architecture," and, he might have added, of a modern degradation. A country where such a society as the murderous thugs is possible; a country where robbers are educated from childhood for the profession in which they take great pride, openly boasting of their skill. One of our most skillful and adroit bank robbers would be considered by these India experts but a bungling amateur.

The scientific manner in which these robbers prepare for their raids shows a thorough knowledge of the dangers of



HUMAN TREES OF INDIA.—BHEEL ROBBERS IN HIDING.

their calling, and the best guards against the same, choosing darkness for their forays. When their dusky bodies are least observable they remove their clothes, anoint themselves with oil, and with a single weapon, a keen edged knife suspended from their neck, creep and steal like shadows noiselessly through the darkness. If detected, their greasy and slippery bodies assist them in eluding capture; while their razor-bladed knife dexterously severs the wrist of any de-

and *A. Flors*. Of *Odontaster hispidus* over 100 were taken. One of the most conspicuous star fishes was the remarkable *Pteraster multispus*, Sars, one specimen of which was over six inches in diameter, and very thick and heavy. Its color when living is rich purple above, with the lower side orange streaked with brown, and with large dark purple suckers. A large and handsome orange-colored species of *Luidia* (apparently *L. elegans*), often ten to fifteen inches broad, was very common, but nearly all the specimens dismembered themselves before they reached the surface. Large specimens of two Floridian sea urchins were also taken.

What Machinery has done for Agriculture.

The various agricultural shows held last autumn in different parts of the country cannot fail to impress all who visited them with the extraordinary developments made in recent years in mechanical appliances for agriculture. It is well, therefore, to notice the benefits which this industry has derived from the genius and the labors of the mechanic. We may go back in thought to the time when the spade, the hoe, the sickle, and the flail comprised the farmer's store of machinery, and when the plow was the rudest contrivance hardly worthy to be called a tool. Then every man tilled the soil or engaged in pastoral pursuits because it was all one man could do to provide himself and his dependents with food. Then each man was forced to clothe himself and be his own mechanic for this simple reason. He labored long and with infinite pains, and the ancient sentence that man should earn his bread by the sweat of his brow came home to him with unmitigated force. In course of time improved and effective tools so lightened the labors of the agriculturist, and so increased his products, that the opportunity to make a division of labor arrived, because there was food to spare for the mechanic. This condition of things became more and more firmly established, until it changed the whole social and political aspect of human affairs. And now what do we see? The true "landlord" is not the owner of an English estate, proclaims a writer in *Capital and Labor*, but the farmer who commands an army of farmers, with brigades of plows, reapers, and other machinery upon the plains of Western America. He makes laws for countries thousands of miles away, and his products rule the world's markets. The genius of agriculture to-day is the mechanic; the soul of agriculture is the inventor. One farmer can now, with the help of machinery, feed a hundred men with greater ease than at one time he could feed himself alone. The farmer supports the railroads, for stocks rise and fall with the good and indifferent reports of what the harvest shall be. He supports lines of steamers with his wonderful freights of breadstuffs, provisions, meats, cattle, and sheep. He maintains the millions of artisans who clothe and shelter him, and who provide for every one of his wants outside of the field.

The mechanical power of the age is like a series of concentric and eccentric circles, of which the farmer stands out in the principal center. These all revolve with and about agriculture, and the same force sets all in motion. It is the farmer's duty now to make the most of his opportunities. He should be the foremost man of the age. His influence should be felt everywhere. It is felt everywhere, for the wealthiest merchants and capitalists and the most active politicians all ask themselves how far the farmers can be depended upon before they make a movement in their special pursuits. But the farmer should feel this himself. It is one thing to have power, and another thing to be cognizant of the possession. Let the farmers consider now their position, and, as they take a view of it, let them consider what they owe to the power and influence of machinery. One most conspicuous example of the results pointed out may be noted. A few years ago Minnesota spring wheat was graded very low in the grain markets and brought a low price. Unfortunately for the Western farmers this grade of spring wheat was the only one they could produce. A new process in milling was introduced. Elaborate machinery was invented to perfect the process. The best wheat by this process was the grade known as "Minnesota spring," theretofore despised and rejected—literally "rejected," in fact, in the markets. Afterward this grade became sought by millers, and the value advanced to a point equal to, and sometimes more than that of the previously much-sought winter wheats. If Minnesota farmers produce forty million bushels of wheat annually, this advanced value, due to the new process, puts several millions of dollars yearly into their pockets; and what a vast amount of comfort and happiness may be secured by the right use of so much money! This is but one instance of the vast concatenation of circumstances which points the moral here alluded to.

Supposed Preventive for Carpet Beetles.

A writer in the *Germantown Telegraph* suggests that, as the larvae of the bacon beetle (*Dermestes lardarius*), an insect closely allied to the carpet beetle, will shun their food when tallow is placed near them, their repugnance to that substance being so great that the insects will devour each other rather than approach it, the same peculiarity may be quite possibly met with in the larvae of the carpet beetle; and if so the coating of floors and filling the cracks with tallow (the cracks being their place of concealment) would possibly prove an effective destroyer of these troublesome pests. The experiment could be easily tried. If good mutton tallow be employed there could be no hurtful absorption of the grease, especially when the carpets have linen backs.


The Year.

The Egyptians, it is said, were the first who fixed the length of the year. The Roman year was introduced by Romulus, 753 B.C., and it was corrected by Numa, 713 B.C., and again by Julius Cæsar, 45 B.C., who fixed the solar year as being 365 days and 6 hours. This was denominated the Julian Style, and prevailed generally throughout the Christian world till the time of Pope Gregory XIII. The calendar of Julius Cæsar was defective in this particular, that the solar year consisted of 365 days 5 hours and 49 minutes, and not of 365 days 6 hours. This difference at the time of Gregory XIII. had amounted to 10 entire days. To obviate this error Gregory ordained in 1582 that that year should consist of 365 days only; and in 1751 it was ordered to be so used in England; and the next year 11 days were left out, the 3d of September, 1752, being reckoned as the 14th, so as to make it agree with the Gregory Calendar. The Russians still adhere to the Julian Calendar (called now *Old Style*), which is 12 days behind the reckoning of the Gregorian.

The year 1881 will be a mathematical curiosity. From right to left and left to right it reads the same. Eighteen divided by 2 gives 9 as a quotient; 81 divided by 9 gives 9; if divided by 9 the quotient contains a 9; if multiplied by 9 the product contains two 9s; 1 and 8 are 9; 8 and 1 are 9. If the 18 be placed under the 81 and added the sum is 99. If the figures be added thus, 1, 8, 8, 1, it will give 18. Reading from left to right it is 18, and 18 is two-ninths of 81. By adding, dividing, and multiplying 19 9s are produced, being one 9 for each year required to complete the century.

A CURIOUS GRAVE.

The practice of burning the dead was common among the ancients, and was in vogue during the first two centuries of the Christian era. In Italy, the ashes of the dead were generally buried in the ground or deposited in vaults, while among the Celtic people inhabiting Gaul and Brittany the urn was frequently inclosed in terra cotta globes and then



interred. One of these spherical graves is shown in the engraving; it was discovered near Lincoln, England, by the Rev. John Carters. The globe is roughly made of terra cotta. It has a diameter of several feet, and contains an urn, the shape of which indicates its Roman origin. As at that period Roman legions occupied England, the ashes are probably those of a soldier from the Gallic provinces. The urn is made from white clay.

Treatment of Whooping Cough in Gas Works.

According to the *Lancet*, a series of recommendations on the treatment of whooping cough in gas works has been made to the French *Académie de Médecine*. Some time ago a committee of three was appointed to investigate the subject, and of these M. Roger, the President of the *Académie*, is the sole survivor. He has lately presented a report which is of considerable interest. Before considering the communication, he described the arrangement of the chambers for purifying the gas, and the chemical products which patients would breathe therein. The purifying chamber is a large room with doors and windows freely open. Each contains twenty-four vessels, holding five cubic meters of depurating substance—lime and sulphate of iron, mixed with sawdust—through which the gas has to pass. When the workmen are emptying and refilling these vessels the children with whooping cough are placed around it, and inhale the vapors which escape. They are in an atmosphere containing ammonium sulphide, carbonic acid, and tarry products. As to the efficacy of the treatment, M. Commenge records 120 cases in which the treatment was persevered with. In 20 the treatment failed completely, in 48 improvement followed, and 101 were cured. M. Bertholle merely states that of 341 cases 122 were improved and 219 were cured. Failures or deaths are not mentioned. Besides the 490 cases improved there were, it appears, 671 cases not included, because the treatment was not persevered in, and these perhaps include a large number of failures. The remote situation of most gas works, and the exposure involved in the treatment in winter, must necessarily limit the application of the method. M. Roger thinks that it acts only upon one element of whooping cough—the catarrh—and that it is contra-indicated in febrile attacks of the disease, and would be dangerous in complicated cases. The method, however, is easy of use in some localities in summer, and seems worthy of further trial in suitable cases.

MISCELLANEOUS INVENTIONS.

Mr. Abraham Witmer, of Safe Harbor, Pa., has patented an improved car starter. Coiled springs are engaged by clutches operated by the wheels when the car is stopped, and the springs thus being wound up, the momentum of the car is stored up as a force to assist the subsequent starting. Means for placing this arrangement under the control of the driver or conductor of the car are provided.

Mr. Wallace H. Phelps, of Alliance, Ohio, has invented an improved drill for coal. It is a large auger provided with a peculiar screw feed and means for holding it in adjustment, and the bits or cutters are formed of S-shaped cutting knives formed with cutting edges at both ends. The shape of these knives renders them effective and durable.

A curious combination of water races with gates at different heights, water wheels, tanks, and pumps, has been patented under the title of "water power," by Mr. Robert Thamm, of Oshkosh, Wis., by which means the water can be made to act upon a single motor, or a series of motors, the water acting successively upon the motors in the order of their elevation.

A patent for a spark arrester has been granted to Messrs. Geo. Gunther, of Bath, N. Y., and William Kowalski, of Brooklyn, N. Y. The lower part of the smokestack has a jacket, and the upper part of the stack is attached to the lower part by brackets. In the upper part of the stack is placed a deflecting cone with its apex downward over the opening in the lower part. The blast is turned outwardly and downward, and a portion of it emerges through the opening between the two parts of the stack, while the sparks are retained in a space between the upper and lower parts, the lower part projecting upward into the upper part.

Mr. Jonathan Cornell, of Sandy Hill, N. Y., has patented an improvement in paper pulp washers, which washes the pulp faster than strainers constructed in the ordinary manner, and enables the operator to see into the washers to watch the progress of the work, and to clean the strainers when necessary by water discharged through a hole against the inner surface of the strainers.

Mr. Oley C. Hanson, of Eureka, Cal., has patented an improved shingle machine, in which, by a peculiarly constructed carriage for conveying the block to the saw, a novel sliding crank feed mechanism and a device for changing the lead of the saw, he secures simplicity of construction, speed, and regularity in the operation of the machine.

A rectilinear motion of sulky plows is secured in an invention patented by Mr. Samuel H. Taylor, of Kansas City, Mo. Bars with lateral slots form the connection of the plow to the sulky shaft, which permits the draught pole of the sulky to oscillate laterally without affecting the direction of the plow, which can be raised or lowered at will by the operator.

Messrs. George Biehn and Rudolph Weidauer, of Racine, Wis., have patented an improved band cutter for thrashing machines so constructed as to cut the bands rapidly and surely and deliver the grain in good condition to the feeder. The feeder is protected from being accidentally cut by the knife of the band cutter.

An improved heel for boots and shoes, patented by Jean Leycuras, of Paris, France, provides improved means for mounting the heels upon the shoe, secures increased solidity and greater rapidity in manufacture, and completely masks nails, screws, and threads. The heel is provided with a circumferential groove, and the upper leather is secured at its edge in the groove by nails driven from the outside. An overlapping edge, or strip of leather, is arranged to turn up over and mask the nail heads.

Fires in Coal Mines.

A vein near Coal Castle, Schuylkill County, has been burning for forty-five years. A huge fire was kept in a grate at the mouth of this mine to prevent the water in the gutters from freezing. One night, in 1835, the timbers of the drift caught fire, and when discovered the flames were beyond control, and the mine was abandoned. Many efforts have been made since to work the mine, as the coal was of remarkably good quality; but although it has been flooded many times, the fire continues to rage, and the intense heat makes it impossible for miners to labor even in slopes which were opened some distance from the burning vein. No vegetation grows on the surface above this pit of fire, and it is dangerous to walk across it, as many places have caved in, and there seems to be but a thin shell of earth over it. Near Mauch Chunk there is Summit Hill Mine, which has been burning for about twenty-five years, and vast sums of money have been expended in fruitless efforts to extinguish the flames.

Quillain Toothwash.

BY ALEXANDER E. BENNETT, PH.D.

An excellent toothwash containing glycerin is made as follows: R. Soap bark, ground, 4 ounces; glycerin, 3 ounces; diluted alcohol, sufficient for 2 pints; oil of gaultheria, oil of peppermint, aa 20 drops.

Macerate the soap bark in the mixture of glycerin and diluted alcohol for three or four days, and filter through a little magnesia previously triturated with the volatile oils.

Thus made, a much better preparation is obtained than by macerating the bark in the dilute alcohol, and adding the glycerin afterward.—*American Journal of Pharmacy*.

[New York Tribune.]

Interesting Tests Made by the Government Chemist.

Dr. Edward G. Love, the present Analytical Chemist for the Government of the United States has recently made some interesting experiments as to the comparative value of baking powders. Dr. Love's tests were made to determine what brands are the most economical to use. And as their capacity lies in their leavening power, tests were directed solely to ascertain the available gas of each powder. Dr. Love's report gives the following:

"The prices at which baking powders are sold to consumers I find to be usually 50 cents per pound. I have therefore calculated their relative commercial values according to the volume of gas yielded on a basis of 50 cents cost per pound."

NAME OF THE BAKING POWDERS.	AVAILABLE GAS, CUBIC INCHES PER EACH OUNCE POWDER.	COMPARATIVE WORTH PER POUND.
"Royal" (cream tartar powder).....	127.4	50 cts.
"Patapasco" (alum powder).....	125.2	49 "
"Rumford's" (phosphate) fresh.....	122.5	48 "
" " " " old.....	32.7	13 "
"Hanford's None Such".....	121.6	47 1/2 "
"Redhead's".....	117.0	46 "
"Charm" (alum powder).....	116.9	46 "
"Amazon" (alum powder).....	111.9	44 "
"Cleveland's" (short weight 1/2 oz.).....	110.8	43 "
"Czar".....	106.8	42 "
"Price's Cream".....	102.6	40 "
"Lewis's" condensed.....	98.2	38 1/2 "
"Andrews' Pearl".....	93.2	36 1/2 "
"Hecker's Perfect".....	92.5	36 "
Bulk Powder.....	80.5	30 "
Bulk Aerated Powder.....	75.0	29 "

NOTE.—"I regard all alum powders as very unwholesome. Phosphate and tartaric acid powders liberate their gas too freely in process of baking, or under varying climatic changes suffer deterioration."

[New York Tribune.]

Alum Baking Powders in Court.—Interesting Testimony of Scientific Men.

Within the past two years a bitter controversy has been waged between manufacturers, on account of the use of alum as a cheap substitute for cream of tartar, by many manufacturers of baking powders. The handsome profits yielded by using the substitute have induced dealers as well as manufacturers to push them into the hands of consumers, sometimes under definite brands, frequently by weighing out in bulk without any distinguishing name.

Are such powders wholesome? The Royal Baking Powder Co., who make a cream of tartar baking powder, declared that they are injurious to the public health, while others who make alum powders claim that they are not. The whole matter as to the effects of these alum powders has finally been brought into the courts, and the case was tried in the Superior Court of New York city before Chief Justice Sedgwick, reported substantially as follows in the New York Sun:

CONCLUSION OF A LITTLE TROUBLE BETWEEN A CHEMIST AND AN EDITOR.

The suit of Dr. Henry A. Mott against Jabez Burns, has brought to light the fact that this country produces at least forty-two different kinds of baking powders. Neither Burns nor Mott has been found guilty of making the baking powders, but Burns, who is the editor of a periodical called the *Spice Mill*, has been severely mulcted for libel in his efforts to make his paper spicy. Dr. Mott, it appears, is a chemist, and at one time was employed by the United States Government to analyze different specimens of baking powder which had been recommended for adoption to the Indian Bureau. Dr. Mott reported in favor of the cream of tartar baking powders for the Indians, and against the alum baking powders. The chemist analyzed forty-two kinds of baking powders.

The jury were out about half an hour. Then they came in with a verdict awarding Dr. Mott \$8,000, to which the Court made an additional allowance of \$150.

As the public have a large interest in the wholesomeness of whatever it is called upon to use as food, the following extracts are introduced from the testimony of some of the prominent men as to the injurious effects of alum powders:

DR. MOTT:

Q. Were you employed by the U. S. Government?

A. I was, sir; was employed as chemist, to analyze all the articles of food; to express an opinion as to the analysis of their healthfulness and purity.

Q. Please tell the jury the baking powders that you examined while in the employ of the government.

A. It would be difficult to remember them all; I could refer to my books; I examined twenty-eight powders; was given sixteen at first.

By the Court:

Give your best recollection.

Q. And one of the powders included was "Dooley's Baking Powder?"

A. Yes, sir.

Q. And the "Charm?"

A. Yes, sir; the "Charm" and "Patapasco."

Q. Please state in which powders you found alum.

A. I found alum in Dooley's "Patapasco," "Charm," "Queen," "Vienna," "Orient," "Amazon," "Lake Side," "Twin Sisters," "Superlative," "King," "White Lily," "Monarch," "One Spoon," "Regal," "Imperial," "Honest," "Economical," "Excelsior," "Chartres," "Grant's," "Giant."

Q. Recurring to the question that has been asked you upon this suit—the result of these examinations which you have made—is it your opinion that alum in these various compounds, in baking powders such as you have examined, is injurious?

A. It is my opinion, based upon actual experiments on living animals.

CHARLES F. CHANDLER, called on behalf of the plaintiff, being duly sworn, testified as follows:

Q. Dr. Chandler, you reside in the City of New York?

A. I do.

Q. Your business is that of a chemist?

A. It is.

Q. You are and have been Professor of Chemistry in several colleges?

A. I have.

Q. Please state how long that employment of yourself has been, and with what colleges you are now connected.

A. I am at present Professor of Chemistry in the Academic Department of Columbia College; the School of Mines, Columbia College; the New York College of Physicians and Surgeons, and the New York College of Pharmacy.

Q. You are President, also, of the Board of Health, are you not?

A. I am.

Q. In your various employments, have you had frequent occasion to examine the question of the wholesomeness of food, and the beneficial or injurious effects of its ingredients?

A. I have.

Q. I will ask you in regard to the use of alum with soda, in a baking powder, whether or not it is neutralized—is there any injurious constituent of alum left?

A. There is an injurious constituent left after the mixture of alum and bicarbonate of soda.

Q. Without using any nicety of chemical terms, what is your opinion about the use of alum in a baking powder, in combination with bicarbonate soda and other ingredients, for raising bread—whether injurious or not?

A. I think it is dangerous to the digestive organs, and liable to produce serious disturbance of the liver of the individual making use of such powders.

HENRY MORTON, President of "Stevens Institute," called in behalf of the plaintiff, being duly sworn, testified as follows:

Q. You are President of Stevens Institute?

A. I am.

Q. And have for many years been a chemist?

A. I have.

Q. Have you had occasion to examine the substances which are used in the composition of baking powders?

A. I have.

Q. Did you, some time ago, examine a sample of Dooley's Baking Powder?

A. I did.

Q. Is that it, sir? [handing can].

A. Yes, sir; that is it.

Q. Well, what kind of alum did it contain?

A. It contained potash alum.

Q. Did you make any extract of that alum, to show the kind?

A. I did; I extracted a large quantity of it as potash alum, and it is in that bottle which I have now here [showing bottle]; that is potash alum which came out of the alum baking powder that was in that can.

Plaintiff's Counsel offers said can of Dooley's Baking Powder in evidence.

Q. Now, sir, have you made any experiment in the bread made from baking powder, to see whether there was any soluble alumina in the bread itself?

A. I have; I took a portion of this powder and mixed it with flour in the directed proportions, and baked a small loaf with it; then I soaked this loaf—the interior part of it—in cold water, and made an extract, in which I readily detected, by the usual tests, alum—that is, alumina in a soluble condition.

Q. Does any baking powder in which any alumina salts enter, contain alumina, in your opinion, which can be absorbed in the process of digestion—are not such objectionable?

A. Very decidedly objectionable, in my opinion.

Q. Why do you say—from what system of reasoning do you make it out—that because alum is injurious, alumina is injurious?

A. Because the injurious effects of alumina, when it gets into the stomach and reacts on the organs, are the same; this hydrate of alumina meets in the stomach the gastric juices, and reacts with them the same as alum would; it forms, in fact, a kind of alum in the stomach with those acids, and whatever alum would do, it would do.

DR. SAMUEL W. JOHNSON, Professor of Chemistry in the Scientific School, Yale College, being duly sworn, testified as follows:

Q. You have had much to do in the examination of substances that enter into food, and the adulteration of food?

A. More or less; yes, sir.

Q. After the use of alum with soda, in a baking powder, in your opinion, is there any injurious substance left?

A. In my opinion, there is an injurious substance left.

Q. What, sir, two years ago, was the prevailing opinion among scientific men, as to the effect of the use of alum in baking powders?

A. As far as my acquaintance with scientific men is concerned, my personal opinion is derived from my investigation and from reading; I should think the opinion was that alum, or any compound of alumina, would be decidedly injurious.

Q. Do I understand you to say that any baking powder in which there are aluminous salts, or any resultant from alum which could be absorbed in digestion, is objectionable and injurious?

A. Extremely so.

Prof. JOSEPH H. RAYMOND called, sworn and testified as follows:

Q. Would you be good enough to state your profession?

A. I am a physician, sir, and a professor of physiology.

Q. You also were, and have been for some time, Sanitary Superintendent in Brooklyn—is not that so?

A. I have, sir.

Q. Now, sir, I will ask you your opinion, from this experience, whether the use of alum with soda, in a baking powder, is injurious or not, in its physiological effects?

A. I consider it to be dangerous.

Q. You examined this question for the Board of Health in Brooklyn, some years ago, did you not?

A. Two years ago, sir, in December.

By the Court:

Q. What was the result of your investigation as to the use of alum in baking powder?

A. The result of my investigation at that time was this: that the changes which took place between the time that alum baking powder was put in the bread, and the time the bread was eaten, the chemical changes were so little understood by chemists, that as a physician and physiologist, I considered it a dangerous experiment.

Dr. Mott, the Government chemist, in his review on the subject in the SCIENTIFIC AMERICAN, makes special mention of having analyzed the Royal Baking Powder, and found it composed of pure and wholesome materials. He also advises the public to avoid purchasing baking powders as sold loose or in bulk, as he found by analyses of many samples that the worst adulterations are practiced in this form. The label and trade mark of a well known and responsible manufacturer, he adds, is the best protection the public can have.

DECISIONS RELATING TO PATENTS.

United States Circuit Court.—Northern District of New York.

UNITED STATES STAMPING COMPANY vs. JEWETT et al.
Blatchford, J.:

1. Patent to E. A. Heath, No. 119,705, granted October 10, 1871, not anticipated by invention of Weber, the proofs failing to show beyond a reasonable doubt that Weber was prior to Heath.

2. Where the decree in a former suit against one licensee of a patentee was for a simple dismissal of the bill a claim that the plaintiff is estopped from suing another licensee will not be entertained.

3. Where a patent has been allowed and ordered to issue, and an assignment has then been made authorizing the Commissioner to issue patent to assignee, and patent issue to inventor, the assignment not having been recorded until after the issue of the patent, Held that the legal right to the patent became vested in the assignee on the recording of the assignment.

Our Trade with China.

Recent official reports show an encouraging increase in American trade with China, whose vast and undeveloped markets offer enormous opportunities for our manufacturers and farmers.

A few years ago wheaten bread was all but unknown in China. The multitudes of returning Chinamen carry home with them not only a knowledge of wheat but a preference for it. One steamship from San Francisco carried to China, last year, 1,400 tons of flour; and the entire shipment for 1879 was 234,789 barrels. The vast wheat fields of the Pacific coast are likely soon to find an ample market for their products among the millions of the Celestial Empire.

During the same year California found in China a market for half her quicksilver product, or 36,696 flasks. Of other products the total shipment from the country was not large, but the variety indicates great possibilities of future development. The exports to China for the year, the last for which official reports have been published, included clocks, to the value of \$50,397; cottons, colored, \$270,000; cottons, uncolored, \$1,302,000; drugs and chemicals, \$13,700; glassware, \$14,000; silver bullion, \$1,831,000; machinery, \$9,000; other iron manufactures, \$9,000; firearms, \$17,000; lamps, \$22,000; kerosene, \$690,000; ordinance stores, \$9,000; provisions, such as bacon and other meats, butter and cheese, etc., \$42,000; refined sugar, \$7,000; tobacco, \$52,000; clothing, \$10,000.

TO RENDER IVORY FLEXIBLE.—Ivory is readily rendered quite flexible by immersion in a solution of pure phosphoric acid (specific gravity 1.13) until it loses, or partially loses, its opacity, when it is washed in clean cold water and dried. In this state it is as flexible as leather, but gradually hardens by exposure to dry air. Immersion in hot water, however, restores its softness and pliancy. The following method may also be employed: Put the ivory to soak in three ounces nitric acid mixed with fifteen ounces water. In three or four days the ivory will be soft.

Business and Personal.

The Charge for Insertion under this head is One Dollar a line for each insertion; about eight words to a line. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

Ladies who board or live in hotels, will do well to secure one of Frothingham & Emory's Patent Portable Safety Jewel Cases. Attachable to bureau drawers, etc., keeping secure jewelry and ornaments from dishonest domestics. Manufactured at 39 Vesey St., New York city. See advertisement on last page.

For Sale—A 10 H. P. Wood and Mann Portable Engine and Boiler, in good condition. The E. Ingraham & Co., Bristol, Conn.

Books for Engineers and Mechanics Catalogues free. E. & F. N. Spon, 48 Broome St., New York.

Repairs to Corliss Engines a Specialty. L. B. Flanders Machine Works, Philadelphia, Pa.

Driving Clocks for Equatorial Telescopes. Address Th. Fischlein, 158 Varonia Ave., Jersey City, N. J.

Inventors. Attention—Apparatus wanted to discharge coal barges by steam shovel instead of hand shoveling. R. C. Hebenner, 24 Exchange Place, Boston, Mass.

The greatest attraction at the last Am. Inst. Fair was the Cider Press of Messrs. Hooper & Baschett, where it was to daily operation. New York Office, 15 Park Row.

For Sale—A Valuable Patent Invoice File and Holder, including dies and formers necessary for the manufacture of same. Sample file, 30 cts. Terms and circulars free. Moore, Patterson & Co., Saltburg, Pa.

Wanted—State and County Agents to introduce a New and Valuable Patent. Address, with references, Box 43, Lake Forest, Ill.

Send to John D. Leveridge, 3 Cortlandt St., New York, for illustrated catalogue, mailed free, of all kinds of Scroll Saws and Supplies, Electric Lighters, Tyson's Steam Engines, Telephones, Novelties, etc.

Wanted—Second-hand Iron Planer, 6 foot bed, plane 16 to 24 in. wide. Must be in best order. Give maker's name, weight, and price. Mosley & Co., Elgin, Ill.

Wanted—An experienced Mechanical Engineer as Superintendent. One well known to the trade and competent to estimate. Give reference, and address Atlantic Steam Engine Works, Brooklyn, N. Y.

Wanted—Second-hand Root Blower. S. Moulson, Rochester, N. Y.

American Inventions Wanted to Sell Abroad. Address J. R. Fox, 50 St. Aubyn St., Davenport, England.

Why risk boiler explosion from mud? It can be avoided, at nominal cost, by Hetchkiss' Mechanical Boiler Cleaner, 54 John St., N. Y. Engineers make ten per cent selling other parties than employers. Send for circular.

Saunders' Pipe Cutting and Threading Machines. See adv., p. 45.

Abbe Bolt Forging Machines and Palmer Power Hammer a specialty. Forsyth & Co., Manchester, N. H.

List 25—Descriptive of over 2,000 new and second-hand machines, now ready for distribution. Send stamp for same. Forsyth & Co., Manchester, N. H.

Pure Oak Lea Bolting. C. W. Army & Son, Manufacturers, Philadelphia. Correspondence solicited.

Two Patents for sale. R. Munroe, Fitchburg, Mass.

Within the last ten years greater improvements have been made in mowing machines than any other agricultural implement. It is universally acknowledged that the Eureka Mower Co., of Towanda, Pa., are making the best mower now in use, and every farmer should write to the manufacturers for catalogue, with prices.

Eureka Vegetable Boiler Scale Eradicator, strictly vegetable, and perfectly harmless to iron. Warranted to remove scale of any thickness, and to prevent scaling from either fresh or salt water use. Circulars and particulars of G. E. Brinkerhoff, 105 Liberty St., N. Y.

For Machinists' Tools, see Whitcomb's adv., page 28 Jenkins' Patent Valves and Packing "The Standard." Jenkins Bros., Proprietors, 11 Dey St., New York.

Presses & Dies. Ferracute Mach. Co., Bridgeton, N. J. Superior Malleable Castings at moderate rates of Richard P. Tim, Wilmington, Del.

Wood Working Machinery of Improved Design and Workmanship. Cordesman, Egan & Co., Cincinnati, O.

The "1890" Lace Cutter by mail for 50 cts.; discount to the trade. Sterling Elliott, 32 Dover St., Boston, Mass.

The Tools, Fixtures, and Patterns of the Taunton Foundry and Machine Company for sale, by the George Place Machinery Agency, 121 Chambers St., New York.

Experts in Patent Causes and Mechanical Counsel. Park Benjamin & Bro., 50 Astor House, New York.

Corrugated Wrought Iron for Tires on Tractor Engines, etc. Sole mfrs., H. Lloyd, Son & Co., Pittsburg, Pa.

Malleable and Gray Iron Castings, all descriptions, by Erie Malleable Iron Company, limited, Erie, Pa.

Power, Foot, and Hand Presses for Metal Workers. Lowest prices. Peerless Punch & Shear Co., 51 Dey St., N. Y.

Recipes and information on all Industrial Processes. Park Benjamin's Expert Office, 50 Astor House, N. Y.

For the best Stave, Barrel, Keg, and Hoghead Machinery, address H. A. Crossley, Cleveland, Ohio.

National Steel Tube Cleaner for boiler tubes. Adjustable, durable. Chalmers-Spence Co., 40 John St., N. Y.

The Brown Automatic Cut-off Engine; unequalled for workmanship, economy, and durability. Write for information. C. H. Brown & Co., Fitchburg, Mass.

Best Oak Tanned Leather Belting Wm F. Forspaugh, Jr. & Bros., 35 Jefferson St., Philadelphia, Pa.

Stave, Barrel, Keg, and Hoghead Machinery a specialty, by E. & B. Holmes, Buffalo, N. Y.

Downer's Cleaning and Polishing Oil for bright metals, is the oldest and best in the market. Highly recommended by the New York, Boston, and other Fire Departments throughout the country. For quickness of cleaning and luster produced it has no equal. Sample five gallon can sent C. O. D. for \$5. A. H. Downer, 17 Peck Slip, New York.

Wright's Patent Steam Engine, with automatic cut off. The best engine made. For prices, address William Wright, Manufacturer, Newburgh, N. Y.

Split Pulleys at low prices, and of same strength and appearance as Whole Pulleys. Yocom & Son's Shafting Works, Drinker St., Philadelphia, Pa.

Presses, Dies, and Tools for working sheet metal, etc. Fruit & other can tools. Bliss & Williams, B'klyn, N. Y.

Lightning Screw Plates and Labor-saving Tools, p. 60. 4 to 40 H. P. Steam Engines. See adv. p. 45.

National Institute of Steam and Mechanical Engineering, Bridgeport, Conn. Blast Furnace Construction and Management. The metallurgy of iron and steel. Practical instruction in Steam Engineering, and a good situation when competent. Send for pamphlet.

Eclipse Portable Engine. See Illustrated adv., p. 30.

Nickel Plating.—Sole manufacturers cast nickel anodes, pure nickel salts, Importers Vienna lime, crocus, etc. Condit, Hanson & Van Winkle, Newark, N. J., and 92 and 94 Liberty St., New York.

Clark Rubber Wheels adv. See page 29.

Reed's Sectional Covering for steam surfaces; any one can apply it; can be removed and replaced without injury. J. A. Locke & Son, 32 Cortlandt St., N. Y.

Silent Injector, Blower, and Exhauster. See adv. p. 60.

The American Electric Co., Proprietors and Manufacturers of the Thomas Houston System of Electric Lighting of the Arc Style. See illus. adv., page 61.

Rollstone Mac. Co.'s Wood Working Mach'y ad. p. 29.

Fire Brick, Tile, and Clay Retorts, all shapes. Borgner & O'Brien, M'Frs, 234 St., above Race, Phila., Pa.

See Bentel, Margendat & Co.'s adv., page 60.

Tyson Vase Engine, small motor, 1-33 H. P.; efficient and non-explosive; price \$50. See illus. adv., page 60.

Use Vacuum Oil Co.'s Lubricating Oil, Rochester, N. Y.

Steam Hammers, Improved Hydraulic Jacks, and Tube Expanders. R. Dudgeon, 24 Columbia St., New York.

Diamond Planers. J. Dickinson, 64 Nassau St., N. Y.

50,000 Sawyers wanted. Your full address for Emerson's Hand Book of Saws (free). Over 100 illustrations and pages of valuable information. How to straighten saws, etc. Emerson, Smith & Co., Beaver Falls, Pa.

Frank's Wood Working Mach'y. See illus. adv., p. 60.

Peerless Colors—For coloring mortar. French, Richards & Co., 410 Callowhill St., Philadelphia, Pa.

Peck's Patent Drop Press. See adv., page 45.

For Pat. Safety Elevators, Hoisting Engines, Friction Clutch Pulleys, Cut-off Coupling, see Frisbie's ad. p. 60.

For Separators, Farm & Vertical Engines, see adv. p. 61.

Tight and Slack Barrel machinery a specialty. John Greenwood & Co., Rochester, N. Y. See illus. adv. p. 61.

Elevators, Freight and Passenger, Shafting, Pulleys and Hangers. J. S. Graves & Son, Rochester, N. Y.

For Patent Shapers and Planers, see illus. adv. p. 60.

For Heavy Punches, etc., see illustrated advertisement of Hillies & Jones, on page 61.

Comb'd Punch & Shears; Universal Lath Chucks. Lambertville Iron Works, Lambertville, N. J. See ad. p. 60.

Blake "Lion and Eagle" Imp'd Crusher. See p. 45.

Mineral Lands Prospected, Artesian Wells Bored, by Pa. Diamond Drill Co. Box 423, Pottsville, Pa. See p. 60.

Wren's Patent Grate Bar. See adv. page 45.

For best low price Planer and Matcher, and latest improved Sash, Door, and Blin Machinery, send for catalogue to Rowley & Hermance, Williamsport, Pa.

The only economical and practical Gas Engine in the market is the new "Otto" Silent, built by Schleicher, Schumm & Co., Philadelphia, Pa. Send for circular.

Penfield (Pulley) Blocks, Lockport, N. Y. See ad. p. 61.

Notes & Queries

HINTS TO CORRESPONDENTS.

No attention will be paid to communications unless accompanied with the full name and address of the writer.

Names and addresses of correspondents will not be given to inquirers.

We renew our request that correspondents, in referring to former answers or articles, will be kind enough to name the date of the paper and the page, or the number of the question.

Correspondents whose inquiries do not appear after a reasonable time should repeat them. If not then published, they may conclude that, for good reasons, the Editor declines them.

Persons desiring special information which is purely of a personal character, and not of general interest, should remit from \$1 to \$5, according to the subject, as we cannot be expected to spend time and labor to obtain such information without remuneration.

Any numbers of the SCIENTIFIC AMERICAN SUPPLEMENT referred to in these columns may be had at this office. Price 10 cents each.


(1) W. C. L. asks: Will a combination of coal gas and air confined in a chamber explode if exposed to heat? A. We have not heard of any instance of such an explosion having taken place without contact with a flame.

(2) W. W. G. asks: What is the scientific reason for the fact that the moons of Jupiter may be seen by reflecting his image in a common looking glass or mirror held horizontally, that is, the moons may be seen reflected in the glass? A. What are imagined to be the moons visible under such circumstances are not so in reality, but only a reduplicating of the body of the planet itself. The following are the optical principles involved in the formation of these false satellites. When the light from a luminous body falls upon a mirror held as described, two primary reflections reach the eye of the spectator, one from the first surface of the glass, the other from the back or silvered surface, which is much brighter than that from the outer surface. But this is not all. When the rays from the silvered side were being transmitted to the eye, part of them, when encountering the upper surface of the glass, were stopped, reflected back to the mirrored surface, to be again sent forward to the eye from a point different from those at which the two previous, or primary, reflections were made. The thicker the plate of glass the greater will be the separation of those images. This phenomenon may very easily be seen and studied by holding a plain piece of glass up on a level with the face, watching in it the reflected image of the flame from the gas or a lamp. When, if the glass is properly held, from four to eight or ten of these supplementary reflected images will readily

be seen. This is usually designated "multiple reflection."

(3) C. H. B. inquires: What acid or other liquid will destroy or decompose any kind of wood with the greatest rapidity? A. Wood is chemically composed of two parts, lignin and cellulose. The walls of the vegetable cells are formed of the former; the filling matter of such cells by the latter. Lignin may be separated from wood in a pure state by boiling sawdust successively in alcohol, water, weak potash solution, dilute muriatic acid, and, finally, water. Lignin is not soluble in water, alcohol, ether, or oils; it is, however, soluble in strong nitric acid, which, on the other hand, has no action on the other constituent of wood, the cellulose, which is readily soluble in sulphuric acid, and by which it is converted into a substance similar to dextrine. From this the inference will at once be drawn that a solvent of wood must be composed of both acids. Whether these had better be employed in succession or mixed together in the form of nitrosulphuric acid, one or two experiments will determine, such experiments to be made on sawdust of any special kind of wood that our correspondent may have in his mind when putting the query.

(4) R. G. and others ask how to construct a simple and inexpensive sand blast apparatus for engraving glass and hard metals. A. Well dried sand, contained in the cylindrical vessel, A, is allowed to flow in a continuous manner through the tube, C, whose length and inclination can be altered at will, so as to regulate the fall of the sand. The tube conveying the current of air or steam terminates just above this spout, in a nozzle containing a series of fine holes. The sand, urged on by the jet, is thrown violently against the



glass plate, E, or other body placed within its range, and thus exerts an abrading action. By varying the quantity of the sand, the volume and the velocity of the current, as well as the diameter of the jet, more or less rapid effects are produced. Holes may be drilled in glass and in substances much harder than glass by means of this apparatus. In engraving on glass very little pressure is needed, the current from the bellows of an engraver's lamp being quite sufficient. In this way the divisions on graduated tubes, the labels on bottles, etc., can easily be engraved in laboratories with but little trouble. The portions of the glass which are to remain clear are covered with paper, or with an elastic varnish, these substances being sufficient protection against the abrading action of the sand.

(5) J. F. asks how to remove the hard burnt oil of the cylinder head of a steam engine. A. Try a small quantity of a strong solution of caustic potash in alcohol.

(6) W. H. W. asks if the oil that is caught by the cups under the hangers or journals can be used again. A. It should not be used again without purification. According to Simm's process the waste oil is dissolved out from the impurities by bisulphide of carbon filtered, and the bisulphide distilled off in a retort jacketed with hot water or steam, condensed and collected so that it may be used again for a similar purpose.

(7) H. C. G. asks how to color violins a dark cherry similar to the Cremonas, and how to prepare the stain and shellac. A. Stain—Dragon's blood 2 ounces, spirits of wine 1 quart. Digest with occasional agitation until dissolved. Varnish—Coarsely powdered gum copal and glass, each 4 oz.; alcohol, 1 pint; camphor, ½ oz.; heat the mixture with frequent stirring in a water bath so that the bubbles may be counted as they rise, until solution is complete, and when cold decant the clear portion.

(8) T. P. writes: In glazing sash, when the glass is crooked or convex, which is the proper side to place next to the wood, the convex or concave side? A. The concave side, for the simple reason that the convex side gives the window a better appearance when placed outward.

(9) P. M. H. writes: I have a cast iron kettle that is cracked: how can I repair the damage? A. Sulphur, 2 parts; blacklead (plumbago), 1 part; melt the sulphur in an old iron pot over the fire, then add the blacklead, stir well together, and pour out on an iron plate or smooth stone. Apply with a hot iron after the manner of tinsmith's soldering.

(10) F. D. M. asks: Will water expand or contract in freezing? Will a water pipe burst when it freezes or when it begins to thaw out? A. Water contracts on cooling, but in congealing it expands. The rupture of water pipes is caused by the change of the water from the liquid to the solid state—not by the thawing, though it is only then that the damage to the pipe becomes apparent. Consult Tyndal's "Heat as a Mode of Motion."

(11) A. F. T. asks how to make jet black writing ink. A. Blue galls, 4½ oz.; braised cloves, 1 drachm; cold water, 40 oz.; pure sulphate of iron, 1½ oz.; pure sulphuric acid, 35 minims; sulphate of indigo in the form of a thin paste, and which should be neutral or nearly so, ¼ oz.; pure water, about 1 quart. Boil the galls gently in 1½ pint of water for an hour, adding water for what is lost by evaporation. Strain and squeeze the galls (in a press). Cool, filter, and add the iron salt dissolved in water and filtered; add the acid, agitate briskly, then add the indigo, shake, and filter. Improves by age.

(12) C. H. S. asks: What are the ingredients of the lightning stove polish sold by men on the streets? It is rubbed on with a cloth, requires no brushing, and gives a bright luster. A. Pure graphite, or plumbago, reduced to an impalpable powder by grinding and boiling.

(13) G. H. C. asks: What preparation (weighing much less than paint) will effectually waterproof a canvas canoe? A. Try paraffine mixed with 1 its weight of boiled oil. Melt by heat or dissolve in benzole.

(14) A. J. S. asks: Is there any air in pure water? If so, in what proportion; or how much to the gallon? A. All natural waters hold air in solution. The quantity is usually small and very variable.

(15) J. D. S. asks: 1. Can you inform me if there is to be had a mineral (or other) powder which will answer the following requirements, namely: Color a bright full yellow; insolubility in hot or cold water or sugar solution; an impalpably fine state of division as is seen in the best German ultramarine; not poisonous unless taken in quantities over ten grains? A. Reduce the deepest yellow glass, pure crown, free from lead, the color of which is due to silver, to impalpable powder by milling. Then pass it through a silk sieve. 2. Is there any way of preparing a cement of rubber or other gum which I could use to firmly attach two pieces of leather without impairing its pliability? It must be entirely waterproof and strong. A. See p. 2510, No. 158, SCIENTIFIC AMERICAN SUPPLEMENT.

(16) J. L. S. asks (1) for a receipt for a varnish or paste, or solution, by which to cover or saturate woolen felting to make it waterproof (against warm water) and at the same time remain pliable. A. a. Dissolve 1 part of pure gum rubber (caoutchouc) cut in shreds in about 20 parts of bisulphide of carbon free from dissolved sulphur. Pass the felting, first thoroughly dried, through this, then expose to the air until the smell of the solvent has disappeared. Do not use the solvent too strong—dilute with bisulphide. b. Paraffine, 10 parts; boiled oil, 2 parts; benzole (pure), 46 parts. Apply as above. 2. Also a receipt for a cement for cementing felting together. A. See marine glue—p. 2510, No. 158, SCIENTIFIC AMERICAN SUPPLEMENT.

(17) W. T. asks (1) how to prepare the silver solution in electro-silver-plating. A. Pure nitrate, 2½ ounces; cyanide of potassium (pure), 4¼ ounces; water, 1 gallon. Dissolve the cyanide in a portion of the water and the silver nitrate in another, mix well together until clear. 2. Is one cell of gravity battery sufficient for silver-plating small articles, such as spoons, forks, etc.? A. Hardly. The exposed surface of zinc should about equal the surface of the work in the bath.

(18) J. H. V. & Co. ask: Can you inform us of any solder with which we can mend small cast iron (20 cts.) castings with a heat that will melt hard solder? We find, by using common solder, the muriatic acid in a short time rusts under and lets the solder loose. A. Silver solder will answer your purpose, providing the fracture is clean and fresh. Paint the adjoining surfaces sparingly with borax ground to a fine cream on a slate or slab. Clamp or wire the joint firmly, and apply the silver solder in small pieces around the casting on the joint, sticking them with the borax cream. Heat in a charcoal fire or blow-pipe flame until the solder flows. If soft solder has been previously applied to the casting it cannot be soldered with silver solder. See soldering in SUPPLEMENT, No. 20.

(19) F. P. C. asks: 1. What is the best preparation to use on a stove pipe, to keep it from rusting? Something not very expensive, although durable, yet will not cause the pipe to burn out. A. Apply pure graphite (plumbago) ground to a very fine powder and mixed with a little water, then rub over with some of the same, dry. 2. Which is the best foot and power lathe, and where made—all things considered—for range of work, light running, moderate cost, durability, accuracy in the work without d ad centers, something suitable for ordinary workshop or amateur varied work; screw cutting included? A. See our advertising columns, also "Hints to Correspondents." 3. Will pure virgin India-rubber, dissolved in about 8 or 10 times its own weight in benzole, do to mend boots? If serviceable, how should it be used? Should it be applied as varnish over the worn or damaged parts, or put under pressure with a suitable size to cover the defect or damaged part? And if pasted or cemented on under pressure, will it be serviceable? A. Yes; patch and put under moderate pressure until dry. 4. How are uppers on leather boots and shoes mended without using thread, etc.? Can a piece of leather, of suitable size, be pasted or cemented over the defective parts on the body of the boot or shoe, making a neat mend and also serviceable? A. See marine glue (second receipt), p. 2510, SCIENTIFIC AMERICAN SUPPLEMENT, No. 158; also rubber cement, same page.

(20) E. E. S. asks how to plate small articles of steel and brass with gold, silver, and nickel, without a battery. A. Gilding by dipping: Distilled water, 17 pints; pyrophosphate of potassa or soda, 25 ounces; solution of hydrocyanic acid (½ pure acid), ½ ounce; terchloride of gold, 1 ounce. Put 16 pints of the water in a porcelain or porcelain-lined iron vessel, and gradually stir in the pyrophosphate, heat, filter, and let it cool down. Add the gold chloride dissolved in water, and then the hydrocyanic acid. Heat the bath nearly to the boiling point for use. Hydrocyanic acid, it must be remembered, is very poisonous, and it must be handled accordingly. When heated the liquid becomes colorless. If a red or violet is developed, add a few drops more hydrocyanic acid. Clean the articles thor-

oughly; dip them in a strong aqueous solution of mercurous nitrate, then, for a few seconds, in the hot gold bath, rinse in clear water, dry in warm sawdust, and burnish if desired. Silvering by dipping: To a saturated aqueous solution of bisulphite of soda in pure water add solution of nitrate of silver, with constant stirring, until the precipitate at first formed ceases to redissolve. Use the bath cold in a porcelain enameled iron vessel. Clean and dip as in the gold bath. We know of no satisfactory method of coating with nickel without a battery.

(21) R. M. asks for a receipt for making a gold and silver wash suitable for small brass articles. A. See answer to E. E. S., above.

(22) L. A. B. wants to know the cheapest and best deodorizer or deodorizing process for kerosene or petroleum. A. Hydrocarbon derivatives of petroleum—such as kerosene—possess a characteristic odor which cannot be totally removed without altering the identity of the substance. The unpleasant odor imparted to it by impurities which it commonly contains may be removed by the following treatment: Agitate it briskly with three per cent of oil of vitriol, wash out the acid with water; digest, with frequent agitation, for several hours with 5 per cent of clean, fresh chloride of lime, settle and wash out with water. Remove moisture by agitating with powdered chloride of calcium. Settle and decant.

(23) L. D. M. asks whether there is any law against turning out or filing off one side of United States gold and silver coins to make bangles of them, or against melting coins for the sake of the gold or silver. A. Section 549 Revised Statutes, reads: "Every person who fraudulently, by any art, way, or means, defaces, mutilates, impairs, diminishes, falsifies, scales, or lightens the gold or silver coins which have been or which may hereafter be coined at the mints of the United States, or any foreign gold or silver coins which are by law made current or are in actual use and circulation as money within the United States, shall be imprisoned not more than two years and fined not more than two thousand dollars." We think this law prohibits the defacement of coins as in making bangles. We do not know of any provision that prohibits the melting of coins for the sake of the gold or silver.

MINERALS, ETC.—Specimens have been received from the following correspondents, and examined, with the results stated:

Dr. G. H. P.—It is quartz rock.—J. T. C. and O. L.—A fair quality of fire clay. See column of Business and Personal for the addresses of dealers.—J. T. S.—A poor quality of peat.—O. A. P. T.—The ore consists chiefly of carbonate and sulphide of copper—it carries a small quantity of silver.—F. G. D.—A semi-decomposed feldspathic rock, with a little quartz and talc.—D. Mc. G.—Coal shale—of no commercial value.—P. M. C.—Limestone—of no value to lithographers.—J. G.—Hematite—an iron ore.—W. St. J.—The rock is a common mica and talcose schist—not the "tin bloom" of miners. It would hardly pay to dig deeper.—C. H. G.—The crystals are smoky quartz—of very little economic value.—H. S.—Chiefly carbonate of lime—not valuable.—G. J. G.—Quartz pebbles.—J. F. S.—Ferromanganese—iron and manganese oxides.—H. T. C.—It is a fair quality of carbon black. If properly packed might command a market here.

NEW BOOKS AND PUBLICATIONS.

CHICAGO FIELD, 155 and 157 Dearborn street, Chicago, Ill. Dr. N. Rowe editor. An illustrated weekly devoted to field sports. Price \$4 per year.

This journal, under the editorship of Dr. Rowe, has taken a foremost position among papers devoted to sport and sporting. It is well edited, and each week contains articles of much valuable information for lovers of dogs and horses. It is the only illustrated paper published in this country devoted to sports of the field, and is well worth its subscription price to those who are fond of out-door sports.

WAR SHIPS AND NAVIES OF THE WORLD. By Chief Engineer J. W. King. Boston: A. Williams & Co. 1880. 8vo, cloth, pp. 623. Sixty-six pages of engravings.

Mr. King has had exceptional facilities for making a thorough study of the naval progress of Europe during recent years, and has brought to the task a degree of practical experience and insight quite as exceptional. He entered the United States Navy when the steam marine was in its infancy, and served in the first paddle wheel frigate, the first screw war ship, indeed in all the pioneer naval steamers with the single exception of the Fulton. He has been Government Inspector of ocean mail steamers, and Chief Engineer of the New York Navy Yard. He was Chief Engineer of the North Atlantic fleet in the early part of the civil war, and subsequently was superintendent of the construction of all the armor clads built west of the Alleghenies. More recently he has been chief of the Bureau of Engineering. Most of the information embodied in the present work was gathered during several tours of observation abroad under orders from the government of the United States, made for the purpose of studying recent progress in naval architecture and the mechanical appliances for use in naval warfare. The result is a comprehensive treatise containing a vast range of fresh information touching the construction, motive power, and armament of modern warships, naval artillery, marine engines, torpedoes, and torpedo boats, etc. The navies of all the naval powers are separately described, dwelling especially upon the changes in types of war ships, and in armor and armament made during the past decade. Much information is also given with regard to naval dock yards, methods of contracting for ships and machinery, naval administration, the personnel of navies, naval expenditures, and related matters. Extremely valuable also are the chapters on recent progress and improvements in artillery construction, the different systems of great guns, gun trials; armor plates and war ship materials and tests of them; the different systems of marine engines and boilers; steam and hydraulic steering gear; torpedo explosives;

torpedo warfare, and the like. The author's wide experience as an engineer has admirably fitted him for this part of his task. Though treating of difficult subjects he has successfully endeavored to set down the information given in a manner so clear that the non-technical reader will be easily able to follow him. The volume is particularly timely at this juncture, when the great problems of restoring our commercial and naval marine, and of providing for the defense of our coasts, are attracting the attention of our legislators and citizens.

CHRISTMAS BOOKS. By Charles Dickens. New York: I. K. Funk & Co. 2 vols. 8vo, paper. Each 25 cents.

A Christmas Carol, The Chimes, The Cricket on the Hearth, The Battle of Life, and the Haunted Man, with sixteen full page illustrations, printed on clear type, are here given for fifty cents. The books comprise Nos. 48 and 49 of the standard series, the excellent quality and extreme cheapness of which we have several times taken occasion to speak.

JOSH BILLINGS' COOK BOOK. New York: G. W. Carleton & Co.

A cent's worth of proverbial philosophy badly spelled, some poor engravings, and a few burlesque recipes as destitute of wit as they are of resemblance to English speech.

INDEX OF INVENTIONS FOR WHICH Letters Patent of the United States were Granted in the Week Ending December 28, 1880, AND EACH BEARING THAT DATE.

[Those marked (r) are reissued patents.]

A printed copy of the specification and drawing of any patent in the annexed list, also of any patent issued since 1866, will be furnished from this office for one dollar. In ordering please state the number and date of the patent desired and remit to Munn & Co., 37 Park Row, New York city. We also furnish copies of patents granted prior to 1866; but at increased cost, as the specifications not being printed, must be copied by hand.

Addressing machine, F. A. Darling..... 236,001
Amalgamator, W. D. Smith..... 236,100
Angle shears, W. & C. Sellers..... 235,928
Assay furnace, W. E. Judson..... 236,037
Axle boxes, oil guard for car, J. G. Tiller..... 235,917
Axle, car, J. M. Sigmourney..... 236,007
Axles, machine for machining, F. D. Bliss..... 235,929
Bale tie, T. A. Weber..... 236,128
Bale tie, J. White..... 235,973
Bandage, W. E. Hull..... 236,033
Barrel, metal lined wooden, J. L. Barlow..... 235,980
Bat, game, C. Kreutzer..... 236,045
Beehive, J. W. Read..... 235,996
Belt lifter, F. Stapelmann..... 235,970
Billiard table chuck, V. Estephe..... 235,861
Billiard time register, automatic, H. Von Leesen..... 236,123
Boiler, etc., covering, I. N. Peirce..... 236,077
Boneblock, kiln for drying and revivifying, W. R. Elmenhorst..... 235,942
Book, copy, E. P. Newman..... 236,070
Boot and shoe heel, F. Richardson..... 236,086, 236,087
Boot and shoe stiffeners, machinery for moulding, S. Prior..... 235,962
Bottle filler, E. Kiebler..... 236,043
Bottle stopper, J. Morschhauser (r)..... 9,521
Bougies, stomach pumps, and other surgical instruments from celluloid, etc., manufacture of, G. Otto..... 235,958
Box trimming machine, T. Vanier..... 236,120
Bracket stand, A. B. Denison (r)..... 9,517
Brick, pottery, etc., kiln for burning, Schlimp & Honzik..... 235,907
Buckle, G. Pratt..... 235,895
Buckle, J. F. Molloy..... 236,061
Buildings, construction of, W. H. Older..... 236,072
Burnishing machine, W. O. Way..... 235,921
Butter cooler and water holder, comb'd, P. Dorlon..... 235,857
Button hole cutting machine, S. D. Tripp..... 235,918
Button or stud, Cooke & Spencer, Jr..... 235,853
Cans, sealing fruit, G. T. Hunsaker..... 235,879
Cant dog, T. F. Cassidy..... 235,992
Car brake, S. S. Leach..... 236,048
Car brake, G. Smith..... 235,912
Car brake, automatic, S. P. Tallman..... 236,016
Car coupling, McDougall & Shaw..... 236,064
Car, dumping, M. Van Wormer..... 236,121
Car heater, M. C. Root..... 235,899
Carpet cleaners, stretcher for, Bixby & Brooks..... 235,848
Carpet exhibitor, A. Peterson (r)..... 9,522
Carriage dash frame, H. Davies..... 235,905
Carriage seat, W. S. Durie..... 236,008
Carriage shifting seat, C. K. Mellinger (r)..... 9,520
Carriage spring gear, A. Warnock..... 235,920
Carriage top, J. Deline..... 236,022
Carriage top, F. A. Norcross..... 235,892
Carriage top, child's, J. N. Hazellip..... 236,027
Carriage belt, A. Mills..... 236,050
Catacomb sack, J. Korff..... 235,884
Catarrh remedy, J. D. Olcott..... 236,071
Celluloid tubes, necking, W. B. Carpenter..... 235,932
Check row cords, coupling hook or button for, G. D. Haworth..... 236,025
Cheese cutter, L. J. Smith..... 236,102
Chuck, nipple, A. Saunders..... 235,902
Cigar box, J. M. Roberts..... 236,099
Cigarette machine, L. J. Hejottas..... 235,993
Clay press, Wilcox & Pearson..... 236,132
Clay to obtain porous and slagged bodies, preparing, G. Praetorius..... 235,901
Clock, J. H. Gerry..... 236,016
Clock winding attachment, J. H. Gerry..... 236,017
Clothes line fastening, E. A. Rice..... 235,964
Coffin pedestal, F. R. Taylor..... 236,100
Collars and cuffs, method of and apparatus for turning, L. P. Turner..... 236,118
Collars, sweat pad for horse, E. R. Jones (r)..... 9,519
Cooling, disinfecting, perfuming, etc., apparatus for, G. Praetorius..... 235,907
Copying press, J. S. Sammons..... 235,936
Cornice, window, J. Hermann..... 236,028
Corpses preserver, J. H. Forshay..... 235,923
Corset, T. C. Bates..... 235,928
Corset, L. S. Bortree..... 235,899
Corset, I. Newman..... 236,069
Cot, folding, R. E. Avery..... 235,977
Crank, apparatus for overcoming dead points in, P. E. Jay..... 235,876

Cultivator, S. R. Bell..... 235,966
Curtain fixture, W. L. Washburn..... 236,136
Decoy duck, J. Appleton..... 235,845
Dental engine, portable, B. J. Quattlebaum..... 236,090
Dolls, coloring the eyebrows, etc., of celluloid, W. B. Carpenter..... 235,933
Door hanger, S. A. Drake..... 236,006
Draught equalizer for side reaping machines, A. Dress pipe, burning, J. Murtagh..... 236,066
Drum protector, M. M. Graham..... 236,019
Egg boiler, L. M. Couchoud..... 235,998
Electric lighting device, G. D. Bancroft..... 235,978
Electric vapor bath, Hoffman & Palmer..... 236,030
Electrical apparatus, adjustable armature for, T. Cochran..... 235,997
Electricity, lighting cities by, H. C. Spalding..... 235,913
Electricity, lighting towns by, H. C. Spalding..... 235,914
Engine stopping device, G. H. Dougherty..... 236,004
Explosive compound, W. Heick..... 235,871
Eyeglass, H. Borsch..... 235,900
Eyeglass holder, F. A. Clark..... 235,995
Fare box, S. R. Ruckel..... 235,900
Fence holster, etc., T. B. Jones..... 235,877
Filter and cooler, water, Chapman & Miles..... 235,934
Filter, water, E. Over..... 235,893
Fire escape ladder, E. J. Krause..... 236,044
Fire extinguisher for railway cars, J. Berg..... 235,847
Fire kindling stick, C. Rieger..... 236,088
Fleam, Reinhold & Schreiber..... 236,064
Fore end stocks, fastening for, C. A. King..... 235,881
Fruit drier, J. M. Rusk..... 236,093
Fruit drier, domestic, H. M. Daks..... 236,000
Furnace, F. Schaffer..... 235,904
Game apparatus, A. Christie..... 235,930
Game apparatus, N. C. Larsen..... 236,047
Game board, P. Lawrence..... 235,951
Gateway and life raft, combined, J. E. Barstow..... 235,987
Gas burners by automatic means, apparatus for lighting and extinguishing, W. Effer..... 236,010
Gas lighting apparatus, electric, G. D. Bancroft..... 235,979
Gas, process of and apparatus for manufacturing, M. W. Kidder..... 236,039
Gate, N. Scarritt..... 236,094
Gate, S. Small..... 236,099
Glass button and mould for manufacturing the same, A. Hamann..... 236,022
Governor, steam engine, F. Heyer..... 236,029
Grain separator, A. A. Russell..... 235,965
Grinding mill, J. Stevens..... 236,104
Guard finger and sickle bar, P. Deevy..... 235,855
Harness, O. E. Hollister..... 235,874
Harness loops, machine for forming, Perkins & Allen..... 236,078
Harvester, corn, G. A. Harvey..... 235,869
Headlight, locomotive, L. A. Williams..... 235,924
Hinge, awning blind, F. B. Brown..... 235,927
Hinge, strap, B. D. Washburn..... 236,124
Hinge, wire, Dudley & Mansfield..... 235,859
Hitching strap, J. D. Stotlemeyer..... 236,107
Horseshoe calks, securing, O. Lampe..... 236,046
Hose connections, clamp for, J. Broughton..... 235,931
Hot air furnace, L. Gould..... 235,945
Hydrocarbon furnace, B. Sloper..... 236,098
Ice cream freezer, N. Kidney..... 236,040
Ice machine, O. Kropff..... 235,950
Ivory, horn, etc., factitious material to imitate, Hyatt, Lockwood, & Stevens..... 236,034
Journal bearings, composition from mineral wool for, G. F. Senter..... 235,909
Knitting machine, I. N. Moore..... 236,002
Knitting machine ribbing attachment, F. Kittell..... 235,882
Lamp, D. Arndt..... 235,926
Lamp, F. A. Taber..... 236,108
Lamp holder, J. S. Goldsmith..... 235,877
Lantern candle, J. Churchill..... 235,994
Life preserving mattress, A. A. Young..... 236,135
Life raft, T. B. Griffith..... 235,946
Lock, A. B. Prouty..... 235,963
Lock and latch, combined, C. F. Batt..... 235,983
Loom, S. O'Neill..... 236,073
Loom, S. T. Thomas..... 236,110
Loom, H. Wyman..... 235,975
Loom for weaving cartridge belt fabric, A. Mills..... 236,058
Looms for weaving seamless corsets, etc., feeding mechanism for, X. Stiegler..... 235,915
Lubricating crank pins, device for, W. H. Merriek..... 236,056
Measurements upon fabrics, machine for registering, T. Shaw..... 235,968
Meat and vegetable cutter, G. O. Kelter..... 236,028
Meat cutter, E. Bourne..... 235,850
Mechanical movement, G. T. Beck..... 235,884
Metal vessels, machine for making rims for tops of, W. W. Jones..... 235,878
Metallic line or cord and fastening for suspending pictures, etc., G. Hookham..... 236,031
Middlings purifier, G. T. Smith..... 236,101
Millstone dressing machine, G. F. Letellier..... 236,069
Millstone driver, J. W. Donnel..... 236,003
Motor, B. P. Kimball..... 235,890
Nut lock, J. S. Rosensteel..... 236,092
Nut warmer and preserver, F. A. Bowdoin..... 235,900
Oiler, car axle box, J. D. Merritt..... 236,057
Ore feeder, J. Hendy..... 235,852
Ore flume and rifle box, comb'd, W. B. Farwell..... 235,944
Ore separator, E. B. Hastings..... 236,023
Ore separator, dry, W. O. Bourne..... 235,851
Overalls, G. P. Evans..... 236,012
Packer, oil well, L. Stewart..... 235,952
Packing, metallic, T. Tripp..... 236,116
Packing, piston, F. B. Stevens..... 235,971
Packing, sectional steam, G. C. Phillips..... 235,894
Padlock, permutation, F. G. Farnham..... 235,892
Pantaloons and overalls, J. Mandel..... 235,888
Paper, machine for winding dry enameled, E. B. Newcomb..... 236,008
Paper pulp engine, J. R. Abbe..... 236,844
Pencil case, C. H. Downes..... 236,003
Pencil sharpening machine, H. Van Houser..... 236,119
Pessaries from celluloid, etc., manufacture of, G. Otto..... 235,950
Petroleum burner and apparatus for burning, E. Schultz..... 236,095
Planter and fertilizer distributor, seed, C. E. Gardner..... 236,015
Planters, reel for check lines for corn, G. D. Haworth..... 236,024
Plow, gang, C. Myers..... 235,890
Plumbago from its ores, separating, H. J. Dreher..... 235,858
Pocket, W. Vogel..... 236,019
Pocket register, F. Horn..... 236,032
Postmarking and canceling machine, T. Leavitt..... 235,952
Power press, J. L. Lewis..... 235,895
Pressure brake, fluid, G. Westinghouse, Jr..... 236,022
Pulley, suspension clothes line, D. H. & J. H. Payne..... 236,076
Pulp strainer, L. Zeyen..... 235,978
Pump attachment, S. Donaldson..... 235,938
Pump reel, sand, W. R. Keelen..... 236,039
Pump, steam, M. Schultz..... 235,935
Punching machine, W. & C. Sellers..... 236,096
Railway crossing, C. H. White..... 236,130
Railway frog, F. C. Weir..... 236,129

Railway spike, H. Greer..... 236,090
Railway switch, automatic, J. S. Clements..... 236,136
Reaping machine, A. C. Scarr..... 235,903
Refrigerating rooms, apparatus for, E. A. Hayt..... 235,870
Refrigerating rooms, construction of, J. Tiffany..... 236,111
Refrigerator, G. E. Seiple..... 235,906
Refrigerator, E. T. Timanus..... 236,112
Relay, W. L. Voelker..... 236,122
River channels of sediment and forming levees, relieving, N. Sewell..... 235,967
Rock drill, electrical, Holcombe & Cheever..... 235,947
Rolling machine, metal, S. F. Reynolds..... 236,085
Rotary engine, G. W. Dudley..... 236,077
Saddle, harness, H. W. Jones..... 235,949
Sails, reefing, J. Gondie..... 235,868
Sawing irregular curves, gauge for, Parks & Streeter..... 236,075
Scale, pendulum, C. P. Batt..... 235,982
Scissors, O. C. Hayward..... 236,026
Screw polishing machine, C. Steinfels..... 236,106
Seeder and cultivator, Nauman & Stoddard..... 236,067
Sewage, method of and apparatus for removing, I. Shone..... 235,910
Sewer trap, E. B. Ward..... 236,125
Shade and refractor combined, J. S. Goldsmith..... 235,896
Sheet metal can, W. W. Flint..... 236,018
Shirt, A. N. Horner..... 235,975
Shoe button fastener, A. G. Wilkins..... 235,974
Shot, drop, H. J. & W. T. Witherlich..... 236,134
Sinking tubes and running tunnels and drifts by pneumatic pressure, H. R. Leonard..... 235,955
Skate, roller, J. Mackay..... 235,897
Skate, roller, S. M. Tinkham..... 236,113
Slate, manufacture of artificial, H. Reinhold..... 236,093
Soldering iron, V. Storch..... 236,106
Sower and cultivator, combined seed, E. Emmert (r)..... 9,518
Spinning frames, etc., mechanism for compressing drawing rolls of, P. C. Dawson..... 235,906
Spoons and forks from celluloid and analogous material, manufacture of, M. C. Lefferts..... 235,954
Stamp, branding, A. M. Darrell (r)..... 9,516
Stamp cancelling device, E. Osgood..... 236,074
Steam boiler, J. H. Edward..... 236,081
Steam engine, portable, T. McGregor..... 236,056
Steam generator for cooking and laundry purposes, J. E. Smith..... 235,989
Steam pipe covering, E. H. Ashcroft..... 235,846
Stove, cooking, C. H. Danton..... 235,859
Stove grate and bearings, J. Jewett..... 236,136
Stove grate, bottom, A. S. Newby..... 235,891
Surgical bandage, J. Jacques..... 236,035
Swing, portable, W. J. Watson..... 236,127
Syringes from celluloid and other plastic material, manufacture of, M. C. Lefferts..... 235,953
Tanning, composition for use in, H. Trenk..... 236,115
Tanning extract, H. L. Wilcox..... 235,923
Telegraph line, underground, E. A. Kitamiller..... 235,883
Telegraph, telephonic, C. A. Randall..... 235,891
Telephone, C. T. Dickson..... 235,856
Telephone, F. A. Gower..... 236,021
Telephone lines, electric signal for, L. S. White..... 236,131
Telephone support and switch, S. Bergmann..... 235,988
Tenoning machine, H. Moiby..... 236,060
Tether, J. Rodger..... 236,091
Textile fabrics, drying, A. Delharpe..... 235,907
Thill coupling, G. W. Fried..... 236,014
Thrashing machine, F. W. Robinson..... 235,897
Tickets, apparatus for issuing and registering, J. N. Maskelyne..... 236,053
Tin can lining, F. W. Bartlett..... 235,881
Tobacco, manufacture of coherent compressed, I. Lindsley..... 235,886
Tobacco smoking tube, compressed, I. Lindsley..... 235,885
Tongs, pipe, J. O. Morse..... 235,957
Tool handle, F. A. Stohlmann..... 236,105
Traction engine, P. T. Kistner..... 236,041
Truck, railway car, W. T. Browne..... 235,852
Tug hook and clevis, L. W. Burrell..... 235,991
Tug, shaft, O. W. Morley..... 236,063
Turning flat-sided objects, machine for, C. Preuss..... 236,079
Umbrella and sun shade, F. M. C. Fardesche..... 235,943
Valve for oscillating engines, M. I. Garrison..... 235,864
Valve gear, steam engine, E. A. Marsh..... 236,032
Valve, safety, J. W. Melling..... 235,889
Vehicle spring, L. Rodenhausen..... 236,090
Veloipede, G. N. Winslow..... 235,925
Vinegar generator, S. J. Clark..... 235,996
Wagon bodies, crate cover for, E. J. Malone..... 236,050
Wagon bow socket, R. P. Williams..... 236,133
Wagon brake, J. Real..... 236,082
Wagon bound brace holder, L. J. M. Mortenson..... 236,064
Washing machine, E. Bourne..... 235,849
Watch regulator, L. Eaton..... 235,940
Watch, stem winding and setting, H. J. Elsen..... 235,941
Water elevator, W. D. Mayfield..... 236,056
Weaner, calf, Dupe & Housam..... 235,880
Welt trimmer, Deacon & Miller..... 235,854
Wick trimmer and burner and chimney cleaner, combined lamp, J. Coyle, Jr..... 235,899
Windwheel, J. Glisstrap..... 236,013
Wood, preserved, H. H. Muller..... 236,035
Wool washing machine, F. G. Sargent..... 235,804
Wrench, J. M. Totten..... 236,114
Writing on manifold paper, stylus for, L. H. Rogers..... 235,898
Yoke tip, neck, C. Shuman..... 236,111
Zinc, manufacture of chloride of, E. J. Mallett, Jr..... 236,051

DESIGNS.


Button, C. F. Waldron..... 12,081
Carriage step pad, H. M. Beecher..... 12,079
Glassware, King & Swift..... 12,080
Key bow, G. S. Barkentin..... 12,077
Stove, Bascom & Heister..... 12,078

TRADE MARKS.

Cigars, L. Andrae..... 8,183
Cigars, Boston Cooperative Association..... 8,135
Medicine, H. C. Collins..... 8,137
Medicine, certain proprietary, Chamberlain & Co..... 8,138
Oil, wool, W. H. Place..... 8,138
Tobacco, plug chewing, C. W. Allen..... 8,134

English Patents Issued to Americans.

From December 24 to December 28, 1880, inclusive.
Barrel machinery, E. & B. Holmes, Buffalo, N. Y.
Carriage belt fabric, A. Mills, Washington, D. C.
Castrating horses, G. L. Matthews, New York city.
Coal elevator, G. W. Wood, Fairbault, Minn.
Condenser surface, I. B. Blumenberg, Washington, D. C.
Dynamo-elec. tel., O. Lugo, New York city.
Gold, extraction of, O. Bailey, White Cloud, Kan.
Linch pins, W. Gardner, Hartford, Conn.
Mining apparatus, O. S. Hershford, Port Henry, N. Y.
Saccharine matter, extraction of, B. Odio et al., N. Y. city.
Safety valve, G. W. Copeland, Boston, Mass.
Submarine vessels and guns, J. Ericsson, New York city.
Tobacco, manufacture of, J. Lindsley, Pawtucket, R. I.
Wood turning machinery (3), F. Hanson, Hollis, Me.



While the bird sings, it moves its mouth (or bill) and tail in exact imitation of a live bird. By mail, \$1.00.

THE AMERICAN SONGSTER.

The Greatest Novelty and Wonder of the Day.

Made of metal, nickel-plated. The Songsters are painted in a variety of bright colors in almost perfect imitation of life. They sing as clear and liquid as the best living song birds. Are substantially and handsomely made and finished, and not liable to get out of order. It is highly appreciated by ladies, who use it to teach birds to sing. It surpasses the bird-organ, and when used near a bird it will induce it to start up its best notes immediately. Each bird is life-size. 1881 Catalogue, 50 Illustrations, by mail, five cents. PECK & SNYDER, 124 Nassau Street, New York.

Advertisements.

Inside Page, each insertion - - - 75 cents a line. Back Page, each insertion - - - \$1.00 a line. (About eight words to a line.)

Engravings may be had at the same rate per line, by measurement, as the letter press. Advertisements must be received at publication office as early as Thursday morning to appear in next issue.

MOULDING MACHINES FOR Foundry Use. 25 per cent. saved in labor. Manufactured by REYNOLDS & CO., P. O. BOX 1169, NEW HAVEN, CONN.

LADIES' AND GENTS' FLEXIBLE RUBBER MITTENS. As elegant in appearance as black kid mittens, which they closely resemble. Just the thing for ladies to wear to hang out clothes. Just the thing for clergymen, doctors, carriage drivers and everybody. Pile-lined, warm as toast, and cheapest thing of the kind in the world. Sample pair by mail, 50 cents; 3 pair for \$1. Circulars free. Large discount to agents. AMERICAN MANUFACTURING CO., City Mills, Massachusetts.

MACHINISTS' TOOLS. Lathes, Planers, Drills, Gear Cutters, Shaping Machines, AND SPECIAL MACHINERY. GOULD & EBERHARDT, NEWARK, N. J.

BRASS PADLOCKS, ASK YOUR HARDWARE MAN for the six tumbler fast keyed Padlock, made by D. K. MILLER Lock Company, of Philadelphia. They contract to supply them in large quantities to the trade, Rail Roads, and U. S. Government.

AMERICAN INVENTIONS WANTED TO SELL abroad. Address, T. B. FOX, 50 St. Aubyn St., Devonport, England.

DRUNKENNESS OPIUM HABIT CURED By LESLIE R. KEELEY, M.D., Surgeon, C. & A. R. Wright, Ill. Books Free.

Livingston's Perfection TOMATO. Bred by the originator of and is superior to the Arme and Paragon Tomatoes. Blood-red, smooth, solid and productive. Original Packet, 25 cents; 5 for \$1.00. Brewer's Garden Calendar for 1881 mailed free. Valuable to the market gardener, amateur and farmer. HENRY A. DREER, Seedsman, 714 Chestnut St., Philadelphia.

SOME THOUGHTS ON THE TREATMENT OF DISEASE. By James G. Clark, M.D. A valuable paper by an old and experienced practitioner predicting that radical improvements must ere long take place in the treatment of disease, and that maladies heretofore regarded as incurable will be brought under the control of remedial measures, showing the importance of the skin as a depurating and eliminating element of the organism; and pointing out the value of certain modes of treatment in various diseases. The Vacuum Treatment, The Absorption Plan, The Inhalation Plan, Cures by Electricity. Importance of Keeping the Skin in Good Condition. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 216. Price 10 cents. To be had at this office and from all newsdealers. The same number contains a valuable "Catarrh Cure," by Hans M. Wilder.

DM FERRY & CO'S SEED ANNUAL FOR 1881. Will be mailed free to all applicants, and to customers without ordering it. It contains 500 colored plates, 600 engravings, about 500 pages, and full descriptions, prices and directions for planting 100 varieties of Vegetable and Flower Seeds, Plants, Trees, etc. Invaluable to all. Send for it. Address, D. M. FERRY & CO., Detroit, Mich.

ENGINE CASTINGS, COMPLETE SET FOR TWO horse power engine, \$15.00. Circulars free. Address, W. M. BOYD, Box 798, Pittsburg, Pa.

CENTENNIAL AND PARIS MEDALS. Mason's Friction Clutches and Elevators. New and Improved Patterns. VOLNEY W. MASON & CO., Providence, R. I., U. S. A.

CARY & MOEN STEEL WIRE OF EVERY DESCRIPTION. 224 W. 23 ST. EVERY & STEEL SPRINGS, NEW YORK CITY.

EKOWE POCKET HELIOGRAPH. Major Macgregor's. Description and diagrams of an exceedingly cheap, portable, easily constructed heliograph, which is not liable to get out of order, and which has been found peculiarly effective for the purposes of the solar rays. Illustrated with two figures. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 258. Price 10 cents. To be had at this office and from all newsdealers.

FOR SALE. (PARIS FURNACE CO.)

A fine manufacturing property, located at Clayville, Oneida Co., N. Y., eleven miles south of Utica. Two distinct water powers and one steam engine, shafting, hangers, pulleys, etc. Works built for manufacturing scythes, Forks, Hoos, etc. For terms, description, etc., address B. F. AVERY & SONS, Louisville, Ky.

SHEPARD'S CELEBRATED 60 Screw Cutting Foot Lathe. Foot and Power Lathes, Drill Presses, Scrolls, Circular and Band Saws, Saw Attachments, Chucks, Mandrels, Twist Drills, Dogs, Callipers, etc. Send for catalogue of outfits for amateurs or artisans. H. I. SHEPARD & CO., 321, 323, 325, & 327 West Front Street, Cincinnati, Ohio.

500 VIRGINIA FARMS AND MILLS for sale or exchange. Write for free catalogue. R. B. CHAFFIN & CO., Richmond, Va.

EXPERIMENTS FOR BEGINNERS - A valuable set of experiments for beginners in the art of dyeing, the performing of which understandingly will serve to make clear many of the otherwise obscure and puzzling passages which the learner finds in the text books relating to his art. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 252. Price 10 cents. To be had at this office and from all newsdealers.

PATENT COLD ROLLED SHAFTING.

The fact that this shafting has 5 per cent. greater strength, a finer finish, and is truer to gauge, than any other in use renders it undoubtedly the most economical. We are also the sole manufacturers of the CELEBRATED COLLINS PAT. COUPLING, and furnish Pulleys, Hangers, etc., of the most approved styles. Price list mailed on application to JONES & LAUGHLIN, Try Street, 31 and 33 Avenues, Pittsburg, Pa. 100 S. Canal Street, Chicago, Ill. 27 Stocks of this shafting in store and for sale by FULLER, DANA & FITZ, Boston, Mass. Geo. Place Machinery Agency, 121 Chambers St., N. Y.

Do Your Own Printing \$3 FRESH prints (Self-inked \$4) Larger sizes for larger work. For 10 or young. Great money saver. A paying business anywhere for all or spare time. Send two stamps for a catalogue of all sizes Presses, Type, Cards, Paper, Ac., to the Manufacturers KELSEY & CO., Berlin, Conn.

Shafts, Pulleys, Hangers, Etc. Full assortment in store for immediate delivery. WM. SELLERS & CO., 79 Liberty Street, New York.

ECONOMIC PUMP. F. B. DAVIS, MAKER, HARTFORD, CONN. I. B. DAVIS PATENT MAY, 1879. Philadelphia Warehouse, 23 North 4th St. New York Warehouse, 57 Liberty.

\$55.66 Agents' profit per week. Will prove it or forfeit \$500.00. Outfit and Samples worth \$50.00 free. Address E. G. RIDEOUT & CO., 10 Barclay Street, New York.

"The 1876 Injector." Simple, Durable, and Reliable. Requires no special valves. Send for illustrated circular. WM. SELLERS & CO., Phila.

COE BRASS MFG. CO. BRASS WOLCOTTVILLE CONN. WIRE AND COPPER MATERIALS FOR METALLIC. IN SHEETS. AMMUNITION A SPECIALTY. BLANKS

THE BLAKE TRANSMITTER - AN explanation of the more obscure parts of the microphone, and of the method of showing its faults, when such exist in it, and also of the method of locating the faulty spot. Description of microphone. How to put up new microphones. How to discover faults and how to remedy them. How to adjust. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 256. Price 10 cents. To be had at this office and from all newsdealers.

50 New styles, Perfumed Motto, Moss-Rose, Violet, Japanese Cards, name on, 10c. Card Mills, Northford, Ct.

ELEVATORS. Steam and Hand Power. Automatic Hatch Doors, etc. CLEM & MORSE, 411 and 413 Cherry St., Philadelphia, Pa.

PORTER MANUF'G CO. The New Economizer, the only Agricultural Engine with Reversible Fly Wheel in use. Send for circular to PORTER Mfg. Co., Limited, Syracuse N. Y. G. G. YOUNG, Gen. Agt., 41 Cortland St., New York.

Steel Castings. From 4 to 1500 lb. weight, true to pattern, of unequalled strength, toughness, and durability. 1500 Crank Shafts and 1000 Gear Wheels of this steel now running prove its superiority over other Steel Castings. Send for circular and price list. CHESTER STEEL CASTINGS CO., 47 Liberty St., Phila. Pa.

Mechanical Hose Pipe. Gives Gentlest Flame or Hottest Blast. Is simple, durable, weighs 13 lb., is 24 inches high, 1 in use by Jewelers, Dentists, Chemists, Machinists, Locksmiths, Metal Workers. Price \$10.

AN EXPERIENCED LEAD BURNER wanted for erecting and maintaining sulphuric acid chambers, MATTHEWS & HEGELER ZINC CO., La Salle, Ill.

50 Lithographed Chromo Cards, no 2 alike, 10c. Name in fancy type. CONN. CARD CO., Northford, Ct.

JAS MURDOCK JR. - CINCINNATI. BRASS COPPER SILVER. WIRE, ROD SHEET & TUB IN THE THREE METALS. LIST FOR

Perfectly Smooth Thoroughly Seasoned CUT THIN LUMBER!! Manufactured by our Patent Board Cutting Machines and Seasoning Presses. Pronounced the only Perfect Cut Lumber!! MAHOGANY, Rosewood, Satinwood, Walnut, Ash, Red Cedar, Cherry, Oak, Poplar, Maple, Holly, French Walnut, etc., etc., in Logs, Planks, Boards, and Veneers. Send for catalogue and price lists. GEO. W. READ & CO., 186 to 200 Lewis St., foot 5th and 6th Sts., New York.

The "SWEETLAND CHUCK." Universal, Independent, and Eccentric. Unexcelled for Accuracy, Strength, Durability, and Simplicity of construction. SWEETLAND & CO., 128 Union St., New Haven, Conn.

ICE-BOATS - THEIR CONSTRUCTION and management. With working drawings, details and directions in full. Four engravings, showing mode of construction. Views of the two fastest ice-sailing boats used on the Hudson river in winter. By H. A. Horsfall, M.E. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, 1. The same number also contains the rules and regulations for the formation of ice-boat clubs, the sailing and management of ice-boats. Price 10 cents.

MACHINE KNIVES FOR PAPERMILLS, BOOK-BINDERS, WOOD WORKING AND AGRICULTURAL MACHY. ALSO PARALLEL VISES FOR MACHINISTS, PIPE FITTERS, BLACKSMITHS, WHEELWRIGHTS, PATENT MARKERS, ETC. MANUFACTURED BY TAYLOR, STILES & CO., REIGELSVILLE WARREN CO. N. J.

WOOD WORKING Machinery. Celebrated "Scheneck" Planers and Matchers. 20,000 ft. flooring, 45,000 ft. surfacing per day. Resawers, Moulders, Tenoners, Scroll Saws, etc. H. B. Scheneck, Successor to Jno. B. Scheneck's Sons, Mattawan, N. Y.

50 CHROMOS, name in new type, 10c. by mail. 40 Agts. Samples, 10c. U. S. CARD CO., Northford, Ct.

NO MORE USE FOR OIL ON MACHINERY. Oils Lubricating Compound, manufactured by HOLLAND & THOMPSON, Troy, N. Y. Avoids hot Journals, dripping and waste. Send for catalogue of Grease and Cups for all kinds of machinery.

GREAT IMPROVEMENTS Recently made in CRUSHING AND GRINDING GOLD and SILVER ORES, BONES, PHOSPHATE, Etc., and CHEMICALS. We complete QUARTZ to grind of ALL SIZES. Address, for new circular, BAUGH & SONS, Philadelphia, Pa.

DO YOUR OWN PRINTING Presses and outfits from \$3 to \$500 Over 2,000 styles of type. Catalogue and reduced price list free. H. HOOVER, Phila., Pa.

VELOCITY OF ICE BOATS. A COLLECTION of interesting letters to the editor of the SCIENTIFIC AMERICAN on the question of the speed of ice boats, demonstrating how and why it is that these craft sail faster than the wind which propels them. Illustrated with 10 explanatory diagrams. Contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 214. Price 10 cents. To be had at this office and from all newsdealers.

Leffel Water Wheels, With recent improvements. Prices Greatly Reduced. 8000 in successful operation. FINE NEW PAMPHLET FOR 1879. Sent free to those interested. James Leffel & Co., Springfield, O. 110 Liberty St., N. Y. City.

THE PERFECTED STYLOGRAPH. The most convenient and economical outfit for writing. Pen, Pencil, and Inkstand in one. Can be ordered by illustrated circular. READERS' AND WRITERS' ECONOMY CO., 25-33 Franklin Street, Boston; 4 Bond Street, New York; 38 Madison Street, Chicago.

GET THE BEST AND CHEAPEST. TRADE MARK. Silver Finish. J. A. FAY & CO. (Cincinnati, Ohio, U. S. A.) Exclusive Agents and Importers for the United States, of the CELEBRATED PERIN BAND SAW BLADES, Warranted superior to all others in quality, finish, uniformity of temper, and general durability. One Perin Saw outwards three ordinary saws.

UNIVERSAL GRINDER. These Grinders consist of a series of disks with beveled edges locked together on a shaft. They revolve toward each other at different rates of speed. They combine strength and durability. No friction; hence no heat. They will grind all kinds of Grain, also Quartz Rocks, Ores, Gypsum, Brimstone, Shavings, Shells, Brick Clay, Cork, Rubber, Bone, Oil Cake, Flax Seed, Cotton Seed, and any number of articles in use by manufacturers and farmers. These Grinders are disposed of on reasonable terms. Send for Illustrated Catalogue with terms. THE NEWELL UNIVERSAL MILL CO., Office, 3, 5 and 7 Courtland St., Room 11.

CATALOGUES FREE TO ANY ADDRESS. GEARS AND PARTS OF MODELS. GOODNOW & WIGHTMAN BOSTON

Gold, Silver, and Nickel Plating. A trade easily learned. Costs little to start. The Electro Plater's Guide, a 75 pp. book, and Gold and Silver, and How to Make It, a 96 pp. book, will be sent free for 3 three cent postage stamps. Every opportunity will be given to persons desiring to start in this business. Complete outfit from \$1. F. LOWEY, 90 Eleventh St., Brooklyn, N. Y.

SPECIALTIES. WOODWORKING MACHINERY, Of Superior Quality, for CABINET AND PIANO MAN'FRS. SHAFTING, PULLEYS & HANGERS. P. Prybil, 461 to 467 W. 40th St., New York.

PATENTS. CAVEATS, COPYRIGHTS, LABEL REGISTRATION, ETC.

Messrs. Munn & Co., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine Improvements and to act as Solicitors of Patents for Inventors. In this line of business they have had over THIRTY YEARS' EXPERIENCE, and now have unequalled facilities for the Preparation of Patent Drawings, Specifications, and the Prosecution of Applications for Patents in the United States, Canada, and Foreign Countries. Messrs. Munn & Co. also attend to the preparation of Caveats, Registration of Labels, Copyrights for Books, Labels, Reissues, Assignments, and Reports on Infringements of Patents. All business intrusted to them is done with special care and promptness, on very moderate terms.

We send, free of charge, on application, a pamphlet containing further information about Patents, and how to procure them; directions concerning Labels, Copyrights, Designs, Patents, Appeals, Reissues, Infringements, Assignments, Rejected Cases, Hints on the Sale of Patents, etc.

Foreign Patents. - We also send, free of charge, a Synopsis of Foreign Patent Laws, showing the cost and method of securing patents in all the principal countries of the world. American inventors should bear in mind that, as a general rule, any invention that is valuable to the patentee, in this country is worth equally as much in England and some other foreign countries. Five patents - embracing Canadian, English, German, French, and Belgian - will secure to an inventor the exclusive monopoly to his discovery among about one HUNDRED AND FIFTY MILLIONS of the most intelligent people in the world. The facilities of business and steam communication are such that patents can be obtained abroad by our citizens almost as easily as at home. The expense to apply for an English patent is \$75; German, \$100; French, \$100; Belgian, \$100; Canadian, \$50.

Copies of Patents. - Persons desiring any patent issued from 1836 to November 30, 1866, can be supplied with official copies at reasonable cost, the price depending upon the extent of drawings and length of specifications.

Any patent issued since November 30, 1866, at which time the Patent Office commenced printing the drawings and specifications, may be had by remitting to this office \$1.

A copy of the claims of any patent issued since 1836 will be furnished for \$1.

When ordering copies, please to remit for the same as above, and state name of patentee, title of invention, and date of patent.

A pamphlet containing full directions for obtaining United States patents, sent free. A handsomely bound Reference Book, gilt edges, contains 140 pages and many engravings and tables important to every patentee and mechanic, and is a useful handbook of reference for everybody. Price 25 cents, mailed free. Address MUNN & CO., Publishers SCIENTIFIC AMERICAN, 37 Park Row, New York.

BRANCH OFFICE - Corner of 4 and 7th Streets, Washington, D. C.

ROSE'S MACHINIST.

FIFTH EDITION.

THE COMPLETE PRACTICAL MACHINIST: Embracing Lathe Work, Vise Work, Drills and Drilling, Taps and Dies, Hardening and Tempering, the Making and Use of Tools, etc., etc. By Joshua Rose. Illustrated by 125 engravings. In one Volume, 12mo, 375 pages. Price \$2.50.

CONTENTS.

CHAPTER I. LATHE AND MACHINE TOOLS.—Round-Nosed Tools; Square-Nosed Tools; Holding Tools; Side Tools for Iron; Front Tool for Brass Work; Side Tool for Brass Work. II. CUTTING SPEED AND FEED.—Tables of Cutting Speeds and Feeds; Table for Steel; Table for Wrought Iron; Table for Cast Iron; Table for Brass; Table for Copper. III. BORING TOOLS.—Tools for BORING.—Boring Tool for Brass; Boring Tool for Lathe Work.—Boring Tool for Brass; Boring Tool for Lathe Work. IV. SCREW-CUTTING TOOLS.—Hand Chasing; To make a Chaser; To Calculate the Gear Wheels necessary to cut a Thread in a Lathe. V. GENERAL OBSERVATIONS ON LATHE WORK.—Lathe Dogs and Drivers; Emery Grinders; Centering Machine; Lathe Work; Emery Cloth and Paper. VI. TURNING EVEN THROATS.—Turning Cranks; To Chuck a Crank; Turning Pistons and Rods; Piston Rings; Ball Turning; Cone Plate for Boring in the Lathe; To turn a Pulley; Turning and Fitting Tapers; Bolts; Oiling and Greasing of Belts; Directions for Calculating the Width of Belts required for Transmitting Different Numbers of Horse Power; Directions for Calculating the Number of Horse Power which a belt will Transmit, its Velocity and the Number of Square Inches in Contact with the Smallest Pulley being Known. VII. HAND TURNING.—Houghing Out; The Graver; The Heel Tool; Brass Work; Scrapers; Lathe Chucks. VIII. DRILLING IN THE LATHE.—Half-Round Bits; Cutters; Reamers; Shell Reamers. IX. BORING BARS.—Small Boring Bars. X. LAPS.—Allowance for Shrinkage; Crank Pins; Chucking Brasses; Slotting Machine Tools. XI. TWIST DRILLS.—Feeding Drills; Drills and Drilling—Flat Drills; Drilling Hard Metals; Slitting or Keyway Drills; Pin Drills; Countersink Drills. XII. TOOL STEEL.—Forging Tools; Tool Hardening and Tempering; Hardening; To Harden Springs; Case Hardening Wrought Iron; To Case Harden Cast Iron; To Harden Malleable Iron; The Crystallization of Wrought Iron; The Wear of Metal Surfaces; Annealing or Softening; Mixtures of Metals. XIII. TAPS AND DIES.—Adjustable Dies for Use in Hand Stocks. XIV. VISE WORK.—Tools.—Callipers; The Square; The Scribing Block; Chipping; Filing; Emery Paper; Tools for Scraping Surfaces; Vise Clamps; Pening; Fitting Brasses to their Boxes; Fitting Link Motions; Fitting Cylinders; Scraped Surfaces; To Make a Surface Plate; To Cut and Saw Blades; To Bore Leaky Pumps to their Case; Setting Work by Weights; To estimate the Weight of a Casting from the Weight of the Pattern; Grades and Speeds for Emery Wheels; Threads of Gas or Steam Pipes; Steam and Water Joints; To Make Spiral Springs; Hardening; Tempering. XV. FITTING CONNECTING RODS.—Drifts; Reverse Keys. XVI. MILLING MACHINES AND MILLING TOOLS. XVII. TO CALCULATE THE SPEED OF WHEELS, PULLEYS, ETC. XVIII. THE SLIDE VALVE.—Movements of Piston and CRANK; Steam Supply; To Measure the Throw of an Eccentric. XIX. HOW TO SET A SLIDE VALVE. XX. PUMPS.—Suction Pumps; Force Pumps; Piston Pumps.—INDEX.

BY THE SAME AUTHOR.

The Slide Valve Practically Explained. Embracing simple and complete Practical Demonstrations of the operation of each element in a Slide Valve Movement, and illustrating the effects of Variations in their Proportions by examples carefully selected from the most recent and successful practice. By Joshua Rose, M.E., author of "The Complete Practical Machinist," "The Pattern Maker's Assistant," etc. Illustrated by 35 engravings. \$1.00

The above or any of our books sent by mail, free of postage, at the publication prices. Our various catalogues of Practical and Scientific Books sent free to any one who will furnish his address.

HENRY CAREY BAIRD & CO., Industrial Publishers, Booksellers, and Importers, 310 WALNUT STREET, PHILADELPHIA.

THE HOLLY SYSTEM OF STEAM HEATING. LOCKPORT N.Y.

ERICSSON'S NEW MOTOR. ERICSSON'S New Caloric Pumping Engine FOR DWELLINGS AND COUNTRY SEATS. Simplest, cheapest, and most economical pumping engine for domestic purposes. Any servant girl can operate. Absolutely safe. Send for circulars and price lists.

DELAMATER IRON WORKS C. H. DELAMATER & CO., Proprietors, No. 10 Cortlandt Street, New York, N. Y.

RUBBER STAMP Outfits and instructions for making. S. A. BROWN, Buffalo, N. Y.

PLANING AND MATCHING MACHINE. C. H. HODGINS & CO., No. 100 Liberty St., N. Y.



Special Machines for Car Work, and the latest improved Wood Working Machinery of all kinds.

JOHN R. WHITLEY & CO. European Representatives of American Houses, with First-class Agents in the principal industrial and agricultural centers and cities in Europe. London, 7 Poultry, E.C. Paris, 8 Place Vendôme. Terms on application. J. R. W. & Co. purchase Paris goods on commission at shippers' discounts.

\$72 A WEEK. \$12 a day at home easily made. Costly outfit free. Address TRUE & Co., Augusta, Me.

MACHINISTS' TOOLS. NEW AND IMPROVED PATTERNS. Send for new illustrated catalogue. Lathes, Planers, Drills, &c. NEW HAVEN MANUFACTURING CO., New Haven, Conn.

ORGANS \$30 to \$1,000; 2 to 32 Stops. Pianos \$125 up. Paper free. Address Daniel F. Beatty, Washington, N. J.

SAFETY HOISTING MACHINERY. OTIS BROS. & CO., No. 348 Broadway, New York.

\$66 a week in your own town. Terms and \$5 outfit free. Address H. HALLET & Co., Portland, Me.

HUB MACHINERY.—HUBTURNING HUB MORTISING, and Hub Boring Machines. Send for price list and circulars. DAVID JENKINS, Shelbygan, Wis.

SCIENTIFIC AMERICAN SUPPLEMENT. Any desired back number of the SCIENTIFIC AMERICAN SUPPLEMENT can be had at this office for 10 cents. Also to be had of newsdealers in all parts of the country.

Permanent Cure of Catarrh! Thirteen Years Ago

CATARRH was considered an incurable disease. I had then suffered for eighteen years. I was first attacked by a slight cold, followed with deafness and ringing in the ears, soreness of the throat, disgusting nasal discharges, weak, inflamed eyes, hawking, rising of vile matter, black and sometimes bloody mucus, coughing, with great soreness of the lungs. The liver and stomach were polluted with the diseased matter running from the head. Compelled to resign my pastorate, I compounded my CATARRH SPECIFIC, and cured myself. Now at the age of sixty-seven, I can speak for hours with no difficulty, and never have had in the whole thirteen years the slightest return of the disease.

To Catarrh Sufferers: 60,000

Catarrhal cases have applied to me for relief. Many thousands have received my Specific and are cured. We deem it only fair that every one who wishes should have the opportunity to ascertain whether we are able to accomplish all that we claim, and for this purpose we add a few of the many hundreds of addresses of those who have been successfully treated, almost any of whom will doubtless respond to any inquiry by letter, if accompanied by a stamp to pay postage. We have thousands of these certificates from all classes—physicians, clergymen, judges, merchants, bankers, and business men.

DEAR MR. CHILDS: I have used your Catarrh treatment now three months, and almost all this time in hopelessness, as it seemed hopeless. By and by it began to take effect, and I began to have hope; I improved rapidly, soon could sit up, passages of the head began to open, throat and bronchial tubes grew better, cough ceased, and I now can see to write. I now expect to get well and go about my business again. I owe you a great debt of gratitude. Indeed I owe my life to your treatment. THOMAS J. DAILY, Homer, Champaign Co., Ill.

JUDOK J. COLLETT, of Lima, O., writes: "You will remember how terribly Catarrh had taken hold upon me. Now I am cured: head free, air passages all open, and breathing natural. I express to you again what I said in a recent letter, 'A thousand thanks to you for so sure a remedy and so very cheap.'"

DR. CHILDS.—Dear Brother: My son, now in Madison University, New York, was so badly afflicted with Catarrh I feared for a time that he was incurable, and when I applied to you for medicine, my hope was faint. It acted speedily and efficiently, and I believe saved him from an early grave. He is now perfectly cured. My wife, who had become very much reduced by a residence in farther India as a missionary, has derived great benefit from your Inhalant Balm. I can most heartily commend these medicines to the afflicted, believing they are all they profess to be. THOMAS ALLEN, Dayton, O.

REV. T. P. CHILDS.—Dear Sir: I think you have the true theory and practice for cure of Nasal Catarrh, and also for the treatment of the respiratory organs. My throat is now so well restored that I can lecture daily without any difficulty, and find no difficulty whatever in preaching. You are at full liberty to use my name for the benefit of others. Yours very truly, E. R. FAIRFIELD, D. D., L. L. D., Chancellor of the University of Nebraska, Lincoln, Neb.

THOS. J. DAILY, Homer, Champaign Co., Ill.; JUDGE J. COLLETT, Lima, O.; W. S. SAUND, Willis, Texas; Rev. THOMAS ALLEN, Dayton, O.; E. B. FAIRFIELD, D. D., L. L. D., Lincoln, Neb.; Rev. E. S. MARTIN, Fort Carbon, Pa.; A. M. STEWART, 179 Cambridge St., East Cambridge, Mass.; W. H. STEPHENS, Shawneetown, Pa.; J. P. ROBERTS, 78 Michigan Ave., Chicago, Ill.; Mrs. E. P. HOOKER, DeLafayette, O.; Rev. G. W. DALBY, Shelbyville, Tenn.; T. B. HAND, 130 E. Fayette St., Baltimore, Md.; J. W. RILEY, U. S. Express Agent, Troy, O.; E. MARBLE, Concord, Jackson Co., Mich.; Rev. E. L. HARRIS, Darien, Wis.; C. A. HURBERT, 210-216 S. Illinois St., Indianapolis, Ind.; Rev. W. E. LEO, Auburn, Ill.; SAMUEL BURCHE, Parkersburg, W. Va.; CHAS. B. DAY, Peoria, Ill.; J. H. BULLARD, Springfield, Mass.; W. D. BROWN, 76 Market St., Lynn, Mass.; T. B. ROSE, Mattoon, Coles Co., Ill.; Rev. A. J. GAINES, Waterford, Miss.; ISAAC HILL, Kirkville, Wagon Co., Ia.; M. ALSHULER, Mattoon, Coles Co., Ill.; J. K. SIGFRIED, Pottsville, Pa.; Miss F. J. DEMENT, Dyer Sta., Gibson Co., Tenn.; Rev. Henry Stout, Hartian, N. J.

What the Editors Say:

"The publishers and editors of the Journal and Messenger have known Rev. T. P. Childs for many years, and feel every confidence in any statements he may make. Our subscribers can feel every confidence in giving their cases into his hands for treatment."—Journal and Messenger, Cincinnati.

"While not supposing that all cases of Catarrh will be cured by the prescription advertised, the publishers of the Illustrated Weekly, after diligent inquiry, have reasons to believe that it has in many cases proved effectual. We do not ordinarily insert medical advertisements."—Illustrated Christian Weekly.

"The publishers of the Congregationalist, with multitudes of other people, are somewhat suspicious of patent medicines as a rule, and when we received the advertisement of Mr. Childs, we at first declined its insertion; but, on making inquiry, we received such satisfactory replies, and one especially from a well-known Congregational pastor not far from Rev. Mr. Childs, the proprietor of the medicine, that we withdrew the objections."—Congregationalist, Boston.

CHILDS' CATARRH SPECIFIC will effectually and permanently cure any case of Catarrh, no matter how desperate. It can only be obtained at Troy, Ohio. The treatment is local as well as constitutional, and can not be obtained at the drug-stores. A full statement of method of home treatment and cost, with scores of testimonials from those who have been cured will be sent on application. Address Name this paper. REV. T. P. CHILDS, Troy, Ohio.

ROCK BREAKERS & ORE CRUSHERS.

We manufacture and supply at short notice and lowest rates, Stone and Ore Crushers containing the invention described in Letters Patent, issued to Eli W. Blake, June 15th, 1858, together with NEW AND VALUABLE IMPROVEMENTS, for which Letters Patent were granted May 11th and July 30th, 1880, to Mr. E. L. Marsden. All Crushers supplied by us are constructed under the superintendence of Mr. Marsden, who, for the past fifteen years has been connected with the manufacture of Blake Crushers in this country and England. FARREL FOUNDRY AND MACHINE CO., Manufacturers, Ansonia, Conn.

RUBBER BACK SQUARE PACKING. BEST IN THE WORLD.

For Packing the Piston Rods and Valve Stems of Steam Engines and Pumps. B represents that part of the packing which, when in use, is in contact with the Piston Rod. A the elastic back, which keeps the part B against the rod with sufficient pressure to be steam-tight, and yet creates but little friction. This Packing is made in lengths of about 20 feet, and of all sizes from 1/4 to 2 inches square. JOHN H. CHEEVER, Trens, NEW YORK BELTING & PACKING CO., 37 & 38 Park Row, New York.

THE STEARNS MANUFACTURING CO., ERIE, PENNSYLVANIA, make a specialty of improved SAW MILL MACHINERY.

Designed in its construction for producing lumber economically and rapidly. Plans and estimates for Mills of any capacity furnished on request. Also build ENGINES, BOILERS, AND MACHINERY IN GENERAL.

\$5 to \$20 per day at home. Samples worth \$5 free. Address STUBBS & Co., Portland, Me.

SURFACE FILE HOLDERS. By their use a crooked file may be utilized as well as a straight one, and both are made to do better execution in filing broad surfaces than has hitherto been possible. No. 4 holds files 12 to 14 in. long. Price 75c. each. No. 5 " " 14 to 16 in. " " Price \$1.00 each. For sale by the trade generally. Manufactured only by the NICHOLSON FILE CO., Providence, R. I.

Langdon Mitre Box Co., MILLERS FALLS, MASS., Langdon and New Langdon Mitre Box. Send for circular.

TELEPHONE Works 1 mile. Price \$1. Pat'd. Circulars free. HOLLAND & Co., Mallet Creek, Ohio.

Pond's Tools, Engine Lathes, Planers, Drills, &c. DAVID W. POND, Worcester, Mass.

"RELIABLE" Engines a complete success. Prices still 25 per cent. below those of other makers. Unequaled for efficiency, simplicity and durability. Prices from \$50 for 10 H.P. to \$400 for 30 H.P. All complete, with Governor, Pump, and Heater. Address, for circular, HEALD, SISCO & CO., Baldwinville, N. Y.

CARNEGIE BROS & CO UNION IRON MILLS PITTSBURGH PA WROUGHT IRON BEAMS CHANNELS TEES & ANGLES STRUCTURAL IRON. The attention of Architects, Engineers, and Builders is called to the great decline in prices of wrought STRUCTURAL IRON. It is believed that, were owners fully aware of the small difference in cost which now exists between iron and wood the former, in many cases, would be adopted, thereby saving expense and avoiding all risk of interference in business in consequence of fire. Book of detailed information furnished to Architects, Engineers, and Builders, on application.

ROOTS' NEW IRON BLOWER.



POSITIVE BLAST. IRON REVOLVERS, PERFECTLY BALANCED IS SIMPLER, AND HAS FEWER PARTS THAN ANY OTHER BLOWER.

P. H. & F. M. ROOTS, Manuf'rs, CONNERSVILLE, IND.

S. S. TOWNSEND, Gen. Agt., 6 Cortlandt St., 8 Dey Street, NEW YORK. WM. COOKE, Selling Agt., 6 Cortlandt Street, JAS. BEGGS & CO., Selling Agts., 8 Dey Street, NEW YORK.

SEND FOR PRICED CATALOGUE.



WITHERBY, HUGG & RICHARDSON Manufacturers of Patent Wood Working Machinery of every description. Facilities unsurpassed. Shop formerly occupied by R. Ball & Co., Worcester, Mass. Send for Catalogue.

Just issued, TRAUTWINE'S CIVIL ENGINEER'S POCKET BOOK, illustrated with 60 engravings from original designs. Fourteenth Thousand. Revised and Corrected. 16mo, 674 pages. Thick, gilt edge. Price \$5. Mailed on receipt of price. E. Caxton & Co., Phila.

MACHINISTS AND STEAM FITTERS.

We manufacture a Double-Acting Steam Jet Pump. Elevates water 15 feet with 45 lb. steam. It is the best and most economical in use. Suitable for Locomotives, Mills, etc. We want agents in all parts of the country. Write for circular to J. B. SHERRIFF, SON & CO., Pittsburgh, Pa., owners of "Coll" Patents.



ROOFING.

For steep or flat roofs. Applied by ordinary workmen at one-third the cost of tin. Circulars and samples free. Agents Wanted. T. NEW, 32 John Street, New York.



OF THE Scientific American FOR 1881.

The Most Popular Scientific Paper in the World. VOLUME XLIV. NEW SERIES. COMMENCES JAN. 1st.

Only \$3.20 a Year, including postage. Weekly. 52 Numbers a Year.

This widely circulated and splendidly illustrated paper is published weekly. Every number contains sixteen pages of useful information, and a large number of original engravings of new inventions and discoveries, representing Engineering Works, Steam Machinery, New Inventions, Novelties in Mechanics, Manufactures, Chemistry, Electricity, Telegraphy, Photography, Architecture, Agriculture, Horticulture, Natural History, etc.

All Classes of Readers find in THE SCIENTIFIC AMERICAN a popular resume of the best scientific information of the day; and it is the aim of the publishers to present it in an attractive form, avoiding as much as possible abstruse terms. To every intelligent mind, this journal affords a constant supply of instructive reading. It is promotive of knowledge and progress in every community where it circulates.

Terms of Subscription.—One copy of THE SCIENTIFIC AMERICAN will be sent for one year—52 numbers—postage prepaid, to any subscriber in the United States or Canada, on receipt of three dollars and twenty cents by the publishers; six months, \$1.00; three months, \$1.00.

Clubs.—One extra copy of THE SCIENTIFIC AMERICAN will be supplied gratis for every club of five subscribers at \$3.00 each; additional copies at same proportionate rate.

One copy of THE SCIENTIFIC AMERICAN and one copy of THE SCIENTIFIC AMERICAN SUPPLEMENT will be sent for one year, postage prepaid, to any subscriber in the United States or Canada, on receipt of seven dollars by the publishers.

The safest way to remit is by Postal Order, Draft, or Express. Money carefully placed inside of envelopes, securely sealed, and correctly addressed, seldom goes astray, but is at the sender's risk. Address all letters and make all orders, drafts, etc., payable to

MUNN & CO., 37 Park Row, New York.

To Foreign Subscribers.—Under the facilities of the Postal Union, THE SCIENTIFIC AMERICAN is now sent by post direct from New York, with regularity, to subscribers in Great Britain, India, Australia, and all other British colonies; to France, Austria, Belgium, Germany, Russia, and all other European States; Japan, Brazil, Mexico, and all States of Central and South America. Terms, when sent to foreign countries, Canada excepted, \$1.00 gold, for SCIENTIFIC AMERICAN, 1 year; \$1.00 gold, for both SCIENTIFIC AMERICAN and SUPPLEMENT for 1 year. This includes postage, which we pay. Remit by postal order or draft to order of Munn & Co., 37 Park Row, New York.



PURE EMERY.

Emery, as a rule, is bought of Dealers who have no practical knowledge of the goods they sell. The various Companies who sell Emery of their own make in the American market all profess to have special arrangements for a supply of Emery Rock or Ore, nearly every one claiming to control that supply, and praising their own goods by declaring them equal to those of one well known Company which has made its name the synonym for excellence. THE TANITE COMPANY OF STROUDSBURG, MONROE COUNTY, PA., do not profess to control any mine, nor to manufacture any Emery; but they do profess to UNDERSTAND, PRACTICALLY, ALL POINTS CONNECTED WITH EMERY, being well informed as to the quality of the crude ore, the various peculiarities of different makers, and as to all the applications of Grain and Flour Emery. Being among the largest users of Emery in this country, and having to exercise constant vigilance in order to keep up the standard of their own well known brand of Solid Emery Wheels, they are always obliged to KNOW what GOOD EMERY is, and they offer to the public the benefit of this knowledge, and are able to supply Emery which they KNOW to be first-class (regardless of all questions as to established reputation), AT PRICES LOWER THAN ANY OTHER FIRST-CLASS EMERY HAS BEEN OFFERED FOR. Sold under THE TANITE CO.'S labels, in kegs of about 275 lb. each.

THE
New York Ice Machine Company,
21 Courtland St., New York, Rooms 54, 55.

LOW PRESSURE BINARY ABSORPTION SYSTEM
Machines Making

ICE AND COLD AIR.

Low Pressure when running. No pressure at rest. Machines guaranteed by C. H. Delamater & Co.



Our new Stylographic Pen (just patented), having the duplex interchangeable point section, is the very latest improvement. THE STYLOGRAPHIC PEN CO., Room 18, 109 Broadway, New York. Send for circular.


BOGARDUS' PATENT UNIVERSAL ECCENTRIC MILLS—For grinding Bones, Ores, Sand, Old Crucibles, Fire Clay, Guano, Oil Cake, Food, Corn, Corn and Cob, Tobacco, Snuff, Sugar, Salts, Roots, Spices, Coffee, Cocoa, Flaxseed, Asbestos, Mica, etc., and whatever cannot be ground by other mills. Also for Paints, Printers' Inks, Paste Blacking, etc. JOHN W. THOMPSON, SUCCESSOR TO JAMES BOGARDUS, corner of White and Elm Sts., New York.

BRICK-TILE-METALS.

The initial number of the BRICK, TILE, AND METAL REVIEW will be issued at an early date. Parties desiring to avail themselves of this valuable medium for advertising Brick and Tile Machinery, Building Materials, New Inventions, etc., should communicate with us at once. Specimen copies will be mailed FREE to thousands of firms in all sections of the Union. TERMS LIBERAL! Wide circulation guaranteed! Address GEO. E. WILLIAMS & CO., Pittsburgh, Pa.

THE BELMONT OIL

Prevents Rust, Tarnish, etc., on Firearms, Machinery, Tools, Cutlery, Saws, Skates, Stoves, Hardware, etc., without injury to the polish. In use over 10 years. Highest Testimonials. Samples 50 cents, three for \$1.50, sent free of expressage. Send for circular. BELMONT OIL CO., 150 Front Street, New York.



WATCHMAN'S Improved Time Defector, with Safety Lock Attachment, Patented 1876-77. Beware of Infringements. This instrument is supplied with 12 keys for 12 different stations. Invaluable for all concerns employing night watchmen. Send for circulars to E. IMHAUSEN, P. O. Box 2755, 212 Broadway, New York.

Mill Stones and Corn Mills.

We make Burr Millstones, Portable Mills, Smut Machines, Packers, Mill Picks, Water Wheels, Pulleys, and Gearing specially adapted to Flour Mills. Send for catalogue. J. T. NOYE & SONS, Buffalo, N. Y.

Pyrometers. For showing heat of Ovens, Hot Blast Pipes, Boiler Flues, Superheated Steam, Oil Mills, etc. HENRY W. BULKLEY, Sole Manufacturer, 142 Broadway, N. Y.

UPRIGHT DRILLS SEND FOR CIRCULAR
H. BICKFORD Cincinnati

NEW YORK BELTING AND PACKING COMPANY
LOOK FOR OUR STAMP on the goods whenever you buy BELTING, HOSE, or PACKING.
37 & 38 PARK ROW, NEW YORK.

SPECTACLES Thermometers, Opera Glasses, Microscopes, Barometers, Telescopes, and Compasses. H. & J. BECK, Manufacturing Opticians, Philadelphia, Pa. Send for Illustrated Priced Catalogue.

Established 1844.
JOSEPH C. TODD,
SUCCESSOR TO TODD & RAFFERTY,
PATERSON, N. J.,
Engineer and Machinist.
Flax Hemp, Jute, Rope, Oakum, and Bagging Machinery, Steam Engines, Boilers, etc. Sole Agent for Taylor's New Patent Acme Steam Engine and Form Pump combined. Also owner and exclusive manufacturer of

THE NEW Barter Patent Portable Steam Engine.

These engines are admirably adapted to all kinds of light power for driving printing presses, pumping water, sawing wood, grinding coffee, spinning cotton, and all kinds of agricultural and mechanical purposes, and are furnished at the following low prices:
1 Horse Power, \$150 1 1/2 Horse Power, \$190
2 Horse Power, 215 2 1/2 Horse Power, 275
3 Horse Power, 290 4 Horse Power, 350
Send for descriptive circular. Address
J. C. TODD,
PATERSON, N. J.
Or No. 10 Barclay St., New York.


THE "Scientific American" is printed with CHAS. KESSEY JOHNSON & CO.'S INK. Tenth and Lombard Sts., Philadelphia, and 50 Gold St. New York.

SCROLL SAWYER.

This Three-Shell Bracket Design, size 18x21, and over 300 miniature designs for Scroll Sawing, sent post-paid on receipt of 10 cts., and the names and addresses in full of two active scroll sawyers. Price of pattern alone, 15 cents. Or send two stamps for illus. Catalogue of scroll saw goods. I offer inducements to purchasers made by no other house. Liberal discounts to the trade. State where you saw advertisement. A. H. POMEROY, Hartford, Conn.

HARTFORD
STEAM BOILER
Inspection & Insurance
COMPANY.
W. B. FRANKLIN, V. Pres't. J. M. ALLEN, Pres't.
J. B. PIERCE, Sec'y.

THE BAKER BLOWER.
Centennial Judges Report.
"Good Design and Material. Very efficient in action. With the special advantages that they can be connected for motion directly with engine without the use of gearing or belting."
SEND FOR CATALOGUE.
WILBRAHAM BROS.
No. 2318 Frankford Avenue,
PHILA DELPHIA, PA.



DIES FOR EVERY PURPOSE.
STILES & PARKER PRESS CO., Middletown, Conn.

ARNOUX-HOCHHAUSEN ELECTRIC CO.,

[ELECTRIC LIGHT.] Electrotipers and Electroplaters

Offer their machines for single and series lights, warranting their successful operation. Refer to
Iron Pier, Coney Island, . . . 9 Machines.
Paul Bauer, . . . 5 " "
Messrs. E. Ridley & Sons, . . . 5 " "
Rogers, Peet & Co., . . . 5 " "
N. Y. Herald, Stern Bros., M. H. Moses, Huyler's, Booth's Theater, Macy & Co., where their machines can be seen in constant use.

OFFICE AND SALESROOMS, 227 EAST 20th STREET, NEW YORK.

COLUMBIA BICYCLE.
The Bicycle has proved itself to be a permanent, practical road vehicle, and the number in daily use is rapidly increasing. Professional and business men, seekers after health or pleasure, all join in bearing witness to its merits. Send 3 cent stamp for catalogue with price list and full information.
THE POPE MFG CO.,
607 Washington Street, Boston, Mass.

BOILER COVERINGS.

Plastic Cement and Hair Felt, with or without the Patent "AIR SPACE" Method.
ASBESTOS MATERIALS.
Made from pure Italian Asbestos, in fiber, mill board, and round packing. THE CHALMERS-SPENCE CO., 40 John Street, and Foot of E. 9th Street, New York.

FRIEDMANN'S PATENT EJECTORS

Are the cheapest and most effective machines in the market for Elevating Water and Conveying Liquids

from Mines, Quarries, Ponds, Rivers, Wells, Wheel Pits; for use in H. H. Water Stations, Factories, etc. They are splendidly adapted for conveying liquids in Breweries, Distilleries, sugar Refineries, Paper Mills, Tanneries, Chemical Works, etc. Send for illus. catalogue to

NATHAN & DREYFUS,
Sole Manufacturers, NEW YORK.

The George Place Machinery Agency
Machinery of Every Description,
121 Chambers and 79 1/2 Beado Streets, New York.

BRICK-TILE-METALS.

Brick and Tile Makers—Manufacturers of Brick and Tile Machinery—Drain, Sewer, Steam, Water, and Gas Pipe Manufacturers, Stone and Marble Works—Manufacturers of Lighting, Heating, and Ventilating Apparatus—Architects—Builders—Gas and Steam Fitters—Inclosing stamp for postage, will receive a sample copy FREE of a new publication, soon to be issued, specially devoted to the Brick, Tile, and Building Trades. Incline business card and address GEO. E. WILLIAMS & CO., Pittsburgh, Pa.

GENERAL AGENT FOR STATE OF OHIO WANTED, preferably at Cincinnati, by a prominent firm of Emery Wheel Makers. Also a General Agent for the North-West, preferably at Detroit. A liberal stock will be assigned. None need apply except those who have the means and disposition to push the business energetically. Address EMERY WHEEL, Box 778, New York.

Telegraphy.

The "Morse" Learner's Instrument and outfit complete, including Battery, Chemicals, Wire and Book of Instruction, &c. The very best. Complete, \$1.50. J. H. BUNNELL & CO., Telegraph Supplies, 112 Liberty Street, New York.

TELEPHONE and Electrical Supplies. Send for Catalogue.
C. E. JONES & BRO., CINCINNATI, O.

H.W. JOHNS' ASBESTOS

LIQUID PAINTS, ROOFING, Steam Pipe & Boiler Coverings, Steam Packing, Mill Board, Sheathing, Fire Proof Coatings, &c. See our Descriptive Price List.
H. W. JOHNS MFG CO. 87 MAIDEN LANE, N. Y.

The Asbestos Packing Co.,

Miners and Manufacturers of Asbestos, BOSTON, MASS., OFFER FOR SALE: PATENTED ASBESTOS ROPE PACKING, " " LOOSE " " " JOURNAL " " " WICK " " " MILL BOARD, " " SHEATHING PAPER, " " FLOORING FELT, " " CLOTH.

NON-CONDUCTOR COVERINGS, FOR STEAM BOILERS AND PIPES. THE RAYMOND MFG CO., 642 West 52d St., 108 Liberty St., New York.




At Low Prices. Large Assorted Stock. A. & F. BROWN, 57-61 Lewis St., New York.

WM. A. HARRIS.

PROVIDENCE, R. I. (PARK STREET), Six minutes walk West from station. Original and Only builder of the HARRIS-CORLISS ENGINE With Harris' Patented Improvements, from 10 to 1,000 H. P. Contemplating the purchase of new Dynamo Machines, should examine the working of our machines at Messrs. Harper & Bros., Appletons, Methodist Book Concern, Am. Tract Society, Craske's, John Mathews, Raisbecks, Smith & Wesson, Greene, Tweed & Co., Ransom, Littlefield & Rathburn Stove Works, Scoville Mfg. Co., Jno. Russell Cutlery Works, and Five Hundred others whose addresses will be given to those in interest.

THE HOWARD MANUFACTURING CO. Manufacture and Introduce Patented Novelties AND YANKEE NOTIONS. THE LATEST NOVELTY.



Mirror, Pin Cushion and Tape Measure. PRICE 25 CENTS. Sample by mail on receipt of price. A liberal discount to the trade. HOWARD MANUFACTURING CO., Box 2295, New York.

Pictet Artificial Ice Co., Limited, P. O. Box 368, 142 Greenwich St., New York. Guaranteed to be the most efficient and economical of all existing Ice and Cold Air Machines.

CATALOGUED.

THE FOLLOWING MANUFACTURERS ARE PROMINENT IN THEIR RESPECTIVE LINES, IN SHORT, ARE HEADQUARTERS.

WIRE ROPE

THE HAZARD MANUF'G. CO., C. M. THOMPSON, Agt., 87 Liberty St., N. Y.

PLUMBING & SANITARY GOODS

OF ALL KINDS. THE J. L. MOTT IRON WORKS, Nos. 88 and 90 Beekman St., New York.

HOISTING ENGINES. COPELAND & BACON, NEW YORK.

THE DEANE STEAM PUMP. DEANE STEAM PUMP COMPANY, NEW YORK. Holyoke, Mass. Boston.

MECHANICAL BOOKS.

Send 10 cents for 96-page Catalogue of Books for Machinists and Engineers. D. VAN NOSTRAND, 23 Murray St., New York.

VERTICAL STEAM ENGINES. NEW YORK SAFETY STEAM POWER CO., 30 Courtland St., New York.

Korting's Improved Steam Blowers, For increasing capacity of Steam Boilers by creating perfect combustion and consuming cheap fuel advantageously. A. ALLER, 109 Liberty St., New York.

BRADLEY'S CUSHIONED HAMMER

Approaches the nearest to the action of the Smith's arm of any Hammer in the World. BRADLEY & COMPANY, Syracuse, N. Y.

SHAFTS, PULLEYS, HANGERS, &c. P. FRYBIL, 461 West 40th Street, New York.

CELEBRATED "RED STRIP" BELTING, RUBBER BELTING, PACKING, AND HOSE. THE GUTTA PERCHA AND RUBBER MFG CO., 23 Park Place, New York.

MACHINISTS' TOOLS AND SUPPLIES. H. PRENTISS & COMPANY, 14 Dey St. (P. O. Box 3362), New York.

PATENT SAFETY JEWEL CASES Having Double Lock. Can be made fast to dressing case or trunk. Lined with silk, satin, velvet. Beautifully finished. 4 sizes, \$5, \$8, \$10, \$12. Sent C. O. D. Frothingham & Emery, 20 Vesey St., N. Y.

Mason & Hamlin's Cabinet Organs. THE BEST IN THE WORLD. Boston. New York. Chicago.

FAIRBANKS' STANDARD SCALES, Manufactured for every department of trade. THE CHEAPEST SCALE manufactured, quality considered. THE LARGEST SCALE FACTORY IN THE WORLD.

AIR ENGINES AND ELEVATORS. SHERRILL ROPER AIR ENGINE CO., 91 & 93 Washington St., New York.

THE PERFECTED TYPE WRITER. Faster and better than the most expert penman. E. REMINGTON & SONS, 231 & 233 Broadway, New York.

Rock Drills and Air Compressors. INGERSOLL ROCK DRILL CO., 1 1/2 Park Place, New York.

Emery Wheels and Grinding Machinery. 1 LEHIGH VALLEY EMERY WHEEL CO., WEISSPORT, Carbon Co., Pa.

FILES, DRILLS, CHUCKS, VISES, TAPS, REAMERS, STUB TOOLS, &c., &c. GOODNOW & WIGHTMAN, Boston, Mass.

Metaline and Star Roller Bush Tackle Blocks, &c. BAGNALL & LOUD, Boston, Mass., and 33 South Street, New York.

DOUBLE SCREW, PARALLEL, LEG VISES. Made and WARRANTED stronger than any other Vise by FISHER & NORRIS only, Trenton, N. J.

BOLT CUTTERS and SCREW CUTTING MACHINES. HOWARD IRON WORKS, BUFFALO, N. Y.

Since 1868 BARBER'S BIT BRACE has been the leading one in market, and at present is the only good brace left. Buy it with the Ratchet Attachment. MILLERS FALLS CO., No. 74 Chambers Street, New York.

Brass Cocks, Valves, and Fittings. McNAB & HARLAN MAN'G CO., 56 John Street, New York.

EXETER MACHINE WORKS, Manufacturers of Steam Engines, Blowers, and Steam Heating Apparatus. 50 Federal St., Boston, Mass.

DABDOW & BEABLE'S MINER'S PAT. SQUIBS for BLASTING. Mfd. by Miner's Supply Co., St. Clair, Sch'l Co., Pa.

Steam Engines & Mining Machinery. BECKETT & McDOWELL, 17 Courtland Street, New York.

The Greatest Rock Breaker on Earth. Capacity, a ton a minute. All kinds of Mining Machinery. Send for circulars. GATES & SCOVILLE IRON WORKS, Chicago, Ill.

Plans and estimates furnished for any capacity of SAW MILL MACHINERY. Also Builders of Engines, Boilers, and General Machinery. THE STEARNS MFG. CO., Erie, Pa.

PRINTING INKS. The leading Periodicals, including the SCIENTIFIC AMERICAN, are printed with our inks. G. MATHER'S SONS, 60 John St., New York.