A WEEKLY JOURNAL OF PRACTICAL INFORMATION, ART, SCIENCE, MECHANICS, CHEMISTRY, AND MANUFACTURES.

Vol. XXXV.-No. 11.

NEW YORK, SEPTEMBER 9, 1876.

IMPROVED DITCHING MACHINE.

The improved apparatus illustrated in the annexed en graving can be constructed of any size, and hence may be used for ditching, dredging, or for railroad embankment making and leveling. It can be operated either by animal or by steam power, and is so designed as to perform the triple motion of a ditching hand. The earth is cut do vn and loosened by the cutters and scrapers, then taken up by the buckets, and is received therefrom by the vibrating pan.

The frame of the machine is supported on wheels, which are pivoted to lower ends of rack bars, A, which slide in guides and are secured by pins passing through their notches, so that the apparatus can be readily lowered as the depth of the ditch increases. The slice of soil to be raised is separated by the plow, B, the standard of which is notched or perforated, and works in guides, so that it may be secured to adjust the plow to work deeper or shallower in the ground. In order to loosen the soil above the plow, colters, of zinc scrap per month and per horse power is the proper respectful distance. The sun's rays, which had hitherto

C, are provided, attached to an oscillating block, the latter also having hinged to it scrapers, D, which are curved forward and backward, so as to scrape off the soil from the forward end and sides of the ditch and throw it back so that it will be taken up by the buckets of the ditching wheel, E. The scrapers are supported to their work by a spring attached to the oscillating block. Said block is moved by the joint levers, F, which by suitable cranks commu nicate with the drum, G, which is turned by a rope unwound from it by the team pulley in the direction in which the machine moves. It will also be observed that, by a simple assembinge of jointed levers and pawls, the bucket wheel, E, is rotated so as to scoop up the earth and (by the tilting spoon, H, which is in each bucket) to deliver it to the pan, I. Said pan causes the spoons to be thrown out by being swung in so as to arrest the edge of each successive spoon in passing. The spoon in turn throws its load in-

the drum, moves out and back during two movements of the bucket wheel, so that a bucket is presented to the pan each time it moves back.

At J is a shovel, which is so arranged as to be drawn forward at each movement of the ditching wheel to scrape up any soil that may be dropped or missed by the buckets. As the earth accumulates on the shovel, the bucket wheel, in its revolution, scrapes it off. The machine is ingeniously constructed, and embodies many useful devices. It was patented through the Scientific American Patent Agency, April 4, 1876. For further information, address the inventor, Mr. Hyacinth Gonellaz, Vermilionville, Lafayette Parish, La.

Zine as an Anti-Incrustant.

We have already noted numerous reported cases wherein pieces of zinc, inserted in steam boilers, seem to have prevented incrustation or scale. Some further and more extended investigations into the subject have recently been carried on by Messrs. Bruckmann & Son, manufacturers at Heilbronn, Germany, and the results given point strongly to the efficacy of the metal introduced.

In the first experiment, 66 lbs. of zinc, in the shape of shavings and small fragments, were inserted in a boiler of 307 square feet of heating surface, having, besides, two new superheaters. At the end of six weeks there was formed in the boiler a muddy, white-gray mass, easily withdrawn by a sheet iron shovel; and water forced in by a hand pump sufficed to render the interior of boiler and heaters completely clean. The iron of the latter retained its black color, and in ported articles

the boiler not a trace of former incrustations was visible The zinc had entirely disappeared, with the exception of a little débris in a state of disaggregation, and this remained in the locality where the mass had previously been deposi-


A second experiment was then made on a larger boiler, with but 37 lbs. of zinc, and at the end of four weeks the deposit was easily washed out. The third experiment was made on the boiler first mentioned, using well water, which was very hard and rich in calcareous matter; 57 lbs. of zinc were used. Formerly this water produced the hardest kind of scale, which almost defied hammer and chisel. After four weeks' running the boiler was opened and merely a few easily detachable bits of lime were found. A part of the zinc was still in its normal state, and seemed fully capable of protecting the boiler for from two to four weeks longer. An average of several experiments shows that about 2.2 lbs.

Walking in the Fiery Furnace.

In London, on August 8 last, experiments were made in the grounds of the Alexandra Palace with an extraordinary invention, by which results somewhat analagous to those recorded as miraculous in Jewish history were achieved. Mr. Oersberg, a Swedish mechanician, claims to have invented, and Captain Ahlstrom, a compatriot, to have matured and fitted for practical use, a dress which will enable the wearer to dash with impunity into the fiercest fire for the purpose of saving life and property. At the east end of the Palace, be tween the circus and the banqueting hall, huge piles of old dried wood were heaped up, intersected by narrow avenues, and the wood was drenched with petroleum. The conse quence was that, the moment a light was applied to the pyre, the whole blazed up with a flame so fierce, and sending forth a heat so intense, that the thousands who had gathered around to witness the scene were forced to retire to a more

> been inconveniently felt from above, were quite forgotten in the glow which now flamed up from below, and it really seemed as if there was malice in the tongues of fire that spat out on every current of passing air. Standing 40 yards to the windward of this fierce fire, the heat was all but intolerable; and even the firemen of the Palace brigade, under the command of Captain Archer, the chief officer, were fain to give a wide berth to the burning center. Then it was that Captain Ahlstrom, clad in a dress not at all unlike that worn by Captain Boyton when he paddled himself across the Straits of Dover, made his appearance on the scene. His costume consisted, so far as it was possible to ascertain, of an overcoat of fustian, covering an inner garment of wool and felt. Between the two skins, so to say, is a network of veins, through which are pumped continuous supplies of air and water, the main air tube, before it reaches the body, being enclosed in

the larger water tube, to the pan, which, by a series of levers, also connecting with | proportion. This, however, must be increased or diminished | and by such means kept perfectly cool. The escape for the cool air is through orifices in front of the face, and the current so made forces back the flames, and leaves perfect breathing space. Assurance was given that the clothing itself is in no way chemically prepared, and is simply protected against the action of the flames by the torrents of water that pour over the man from head to foot. With the greatest possible nonchalance Captain Ahlstrom walked into and through the fiery furnace, not only free from discomfort, but apparently with enjoyment. After spending about ten minutes in about the warmest climate it is possible to imagine enveloped at times so as to be hidden by flames, he carried out a chair which was on fire, sat coolly down upon it, and, to the amusement and astonishment of a crowd of spectators, smoked a cigar.



GONELLAZ'S DITCHING MACHINE

with reference to the known composition of the feed water.

Wages in England,

Complaints regarding the inflated state of wages in England are becoming both bitter and frequent. At a recent meeting of the Manchester, Sheffield, and Lincolnshire Railway Company, the chairman said that at the present day the cost of mining coal in Great Britain is 15 per cent higher, as a matter of wages, than it was eight or nine years ago. He pointed out that the English fected, and that it is now impossible for it to compete in American or other markets of the world. He further stated, however, that the diminution of wages paid in England was already nearly \$10,000,000 weekly, and expressed the hope that, after another year of such discipline in the way of financial stress, England, by reducing the inflation of wages and doing more work, would outbid all other producers in the world in the cheapness of her products.

Novel Folding Scissors.

Many travelers who return from abroad bring home to their friends, as a novelty, a pair of folding seissors. travelers can no longer astonish their friends with this novelty, for Marx Brothers, of 430 Broadway, New York city, are manufacturing, under patent issued May 28, 1872, a superior quality of folding scissors, which are five inches long when in use, but fold into a length of two and a half inches for the pocket, highly finished and neatly put up in leather cases, which they offer in competition with the im-

New Artesian Well, Charleston, S. C.

A new artesian well is in progress and has now reached a depth of nearly three hundred feet. The drills are still digging their way through the eocene marl of the Ashley River beds, and at a depth of two hundred and sixty feet a stratum of silicious rock, about three feet in thickness, was struck and passed through without much difficulty. In this stratum are found millions of little microscopic shells, which are almost invisible to the naked eye, but upon being viewed through a magnifying glass are clearly seen as beautifu! nautilus-shaped shells, perfect in formation and color. The work is creating much interest, and numbers of scientific gentlemen visit the well every day for the purpose of inspecting the fossils.

Scientific American.

ESTABLISHED 1846.

MUNN & CO., Editors and Proprietors.

PUBLISHED WEEKLY AT NO. 87 PARK ROW, NEW YORK.

	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW
TERMS FOR THE SCIENTIFIC	O AMERICAN.
One copy, one year, postage included	
One copy, stx months, postage included	
Club Rates.	
Ten copies, one year, each \$2 70, postage included	827 00
Over ten copies, same rate each, postage included	
IF The postage is payable in advance by the	

Norg.—Persons subscribing will please to give their full names, and Post Office and State address, plainly written. In case of changing residence state former address, as well as give the new one. No changes can be made unless the former address is given.

Scientific American Supplement.

A distinct paper from the Scientific American, but of the same size, and published simultaneously with the regular edition.

TERMS. The safest way to remit is by draft, postal order, or registered letter.

Address MUNN & Co., Il Park Row, N. Y.

LE Subscriptions received and single copies of either paper sold by all the news agents.

VOLUME XXXV., No. 11. [New Series.] Thirty-first Year

NEW YORK, SATURDAY, SEPTEMBER 9, 1876.

(Illustrated articles are marked with an asterisk.)		
American Science Association Answers to correspondents Asphyristion, the cause of Battery, brehromate (23) Blattery, brehromate (23) Blattery, brehromate (23) Blattery, brehromate (23) Blattary, brehromate (23) Business and personal Catorimetes, hew Cement for leabels (19) Cheese factories in England Chemicals at the Centennial Brehromate (25) Copper boilers, cleaning (19) Contes line fastener Coths, faded (23) Copper boilers, cleaning (19) Coremation, American Beath rate and occupations Death rate and occupations Deposit in heaters (2) Diching machine Do oss from the and lead (7) Electrical amsignm (9) England (26) England (27) England (27) England (28) Firer formate, walking in the Firer arms, breech-loading Gas for stage use (23) Gas in coal mines (22)	Meteoric from in steeples 150 Moon's longitude, etc., the. 164 Moon, the green fields of the 164 Moon, the green fields of the 150 Occupations and death rates 150 Patents, American and foreign 150 Patents, Official list of 172 Patern making—The founders' 165 Phosphoras, Keeping (18) 171 Pipes, cutting and threading' 162 Plant ansishesia 162 Pointo beetles, notes on 164 Pounding of piston (18) 171 Practical mechanism—No. 10* 165 Propeller shaffs (4) 171 Hadlata, the. 167 Hadlometer, Professor Crookes 164 Hailways, South African 166 Hailways, South African 168 Hailways, South African 168 Hailways, South African 169 Hand her dangerous 18, 166 Railways, South African 168 Hauber shoe making 168 Hust on holter plates (24) 171 Sand and gravel separator' 163 Scissors novel folding 159 Simian sagacity 166 Soldering fluid (11) 171 Stainsfrom shirts [10) 171 Telegraph, the voice sent by 163 Test colors Thunderer explosion, the 161 Trout in warm water 164 Tree, a useful 164 Trout in warm water 164 Varnish, black (21) 171	
Doss from the and lead (7) [1] Electrical amalgam (9) [2] En ince and bollers (5) [1] En ince and bollers (5) [1] En ince and bollers (5) [1] Fiery furnace, walking in the [5] Fire arms, breech-loading [6] French working men's visit [6] Gas for stage use (2) [7] Gas in coal mines (22) [7] German silver; to analyze [7] Learning, no royal road to [7] Life on the earth [7] Life the earth [7] Melted from, etc., handling (7) [7]	Soldering fluid (11) 171	

THE SCIENTIFIC AMERICAN SUPPLEMENT. Vol. II., No. 37.

For the Week ending September 9, 1876.

With S3 Figures and Engravings.

TABLE OF CONTENTS.

THE INTERNATIONAL EXHIBITION OF 1876. With 37 Blustrations. THE INTERNATIONAL EXHIBITION OF 1876. With 37 Illustrations.—
The Life-Saving Service Apparatus, 3 engravings.—Life Signals.—Life
and Surf Beats.—Life Boat Station Houses.—The Ball Puzzle, 5 figures.
—A Tour through the Boller Houses.—The Galloway Boller.—Green's
Fuel Economizer.—Pearn's Pump.—Corliss Bollers.—Exeter Boller.—
Kelly's Sectional Boller.—Low's Tobular Boller.—Smith's Boller Furnace.—Howard Sectional Boller.—Bobook &
Wilson Tubular Boller.—Harrison Boller.—Andrews' Boller.—Rogers &
Black Boller.—Bobook &
Boller.—Rogers &
Boller.—Rogers &
Boller.—Rogers &
Boller.—Rogers &
Boller.—Boller.—Boller.—Boller.—Rogers &
Boller.—Boll and Lime Catcher.—Exhibit of Carriages, 19 figures.—Exhibit of Woodworking Machines, 9 figures.—Bert's Shingle Machine, Hoult's Molding Machine,—Machine for Dressing Heads.—Carving and Molding Machine, 1 engraving.—Door and Blind Machine.—Walker's Scroll Saw.

- ENGINEERING AND MECHANICS. With 5 engravings.—Drilling Machines, 2 engravings.—Combined Self-Acting Silde Lathes, 1 engraving.—Railway Locomotives in China, 2 engravings.—The Radiometer. What Makes it Turn
- III. TECHNOLOGY. With 28 Bustrations,-How to Build Cheap Boats Raises for the Management of San Boats — Architecture in Terra Collabor Edward Sanar, 5 cogravings.—Platt Church, near Manchester.—
 Manufacture and Working of Steel, by D. Cherksorr, 11 figures.—
 Proper Structure of Steel for Successful Forging.—Microscopic Appearances of Steel Crystals.—Steel Crystalized by Over-Heating.—How Immigrants from England .- New Iron Process .- Flour Mills of the
- IV. LESSONS IN MECHANICAL DRAWING, by Professor MacCond, 1
- MISCELLANEOUS.—The A. B. C. Process for Sewage.—Free Silics taken up by Plauts, I engraving.—Best Nursery Fruit Trees. Names.— New Chalk Fossils, I engraving.

The Scientific American Supplement

RIBERS WHO WISH TO TAKE THE SUPPLE

MUNN & CO., PUBLISHERS,
77 Park Row, New York. All the numbers of the Supplement from its commencement, January 1, 1876, can be supplied; subscriptions date with No. 1 unless otherwise or-

gs single copies of any desired number of the SUPPLEMENT sent to any idross on receipt of 10 cents,

THE GREEN FIELDS OF THE MOON.

When the moon is at the full, the unassisted eye readily listinguishes on her face certain dark gray spots more or the telescope these spots appear as broad level spaces, re-sembling terrestrial seas. Indeed the earlier observers mistook them for seas, and by that name (Latin, mars) they are known to this day, They are not seas, however, but ancient sea beds, now probably nearly, if not quite, destitute of water: vast arid basins like the Sahara, or the great interior Utah basin of our own continent,

Examined more closely, these dried-up sea beds-to which Neison applies the irregular but convenient plural maresare seen to have a rolling surface like some of our western prairies, or to be traversed by numerous long ridges, resem bling the wave-like sand hills which give so marked and pe culiar an appearance to the deserts of Western Australia, the leveler portions being dotted with low mounds inter spersed with small crater pits. In many places formations of an apparently alluvial character abound, while the ancient coast lines show distinct traces of water action. Two of these lunar plains-Mare Humorum and Mare Chrisiumare walled in completely by lofty mountains, presenting stupendous precipices to the vanished sea. The larger mares are more like ocean beds. They run together as terrestrial oceans do, and sometimes merge into the brighter continental regions, without a distinct line of demarkation. In other places they show a rugged coast line, rising into cliffs and peaks, and pierced at times by valleys and ra-

One of the most conspicuous of these lunar ocean beds, also one of the deepest, is known as the Mare Serenitatis. Its area is nearly 125,000 square miles. Within its dark gray border, from thirty to eighty miles wide, is an extensive inner plain which at times presents a fine clear light green tint with a central streak of pure white, the green area lying lower apparently than the gray exterior. The green tint is difficult to catch, except under favorable conditions, and is much weakened by the effect of numerous small white round spots and gray ridges.

Another of the moon's green plains was discovered by Madler in the Mare Humorum, already mentioned. This is one of the smallest as well as most distinctly bordered of the dark gray plains. Its area is 50,000 square miles. The greater portion of its interior is distinctly tinged a dusky green, sometimes very marked, affording a strong contrast with the pure gray of the borders and high enclosing ridges. On the west the green area extends nearly to the edge of the mare, but elsewhere, as in the Mare Serenitatis, it is separated from the border by a narrow darker gray fringe, except on the northwest, where the gray and green areas merge insensibly into each other.

Still another area of green is observed in the Mare Chrisium, one of the most conspicuous of the moon's dark plains. It is completely enclosed and is, perhaps, the deepest of the lunar mares. Its area is 78,000 square miles. Its general tint is a gray mixed with an unmistakable tinge of green, especially under high illumination. This verdant hue is seen to best advantage for several days before and after the States and of England have drawn upon our columns. moon is full.

These and other color changes on the face of the moonas, for instance, the darkening of the great ring plain of Plato with increasing light, and like changes in certain long winding lunar valleys-led Beer and Mädler to suggest that they would indicate vegetation, were vegetation possible on the surface of the moon. But having accepted Bessel's conclusion that there could be neither air nor water on the lu nar surface, and consequently no life, those much respected selenographers could not entertain the hypothesis of lunar vegetation, however strong the evidence might seem,

But Bessel's opinion, as our readers already know, is inconsistent not only with the conditions on which he based his calculations, but also with the results of more recent studies of the state of the moon's surface. So far from being an airless, waterless, unalterable desert, a changeless mass of dead matter, like so much volcanic scoria, the moon is now known to have an atmosphere of considerable volume and density, to present abundant evidence of physical activity and change, and to have in all probability water enough to make life easily possible on its surface.

The moon is dying, but very far from dead. Being so much smaller than the earth, it has run its course more rapidly, but is still a good way off from that goal of ultimate Neison says, of the popular view, and "its truth would be admitted by no astronomer who had devoted sufficient attention to selenography to enable him to thoroughly realize the probable present condition of the moon.

Such being the case, the hypothesis that the moon's green plains derive their color from vegetation ceases to be impossible or absurd. The evidence is not of a character to justify a positive assertion that the mythical man in the moon may have abundant pasturage for his cattle; but his case ceases to be absolutely hopeless when a thorough-going selenographer can say, as Neison does, that the moon may possess an atmosphere that must be regarded as fully capable of sustaining various forms of vegetation of even an advanced type; that it does not appear how it can justly be questioned that the lunar surface in favorable positions may yet retain a sufficiency of moisture to support vegetation of many kinds; and that in a very considerable portion of the entire surface of the moon, the temperature would not vary sufficiently to materially affect the existence of vegetable life

Who can tell but that the aforementioned man in the moon

may not follow the plan of the African tribe which Living stone tells of, and keep himself and his cattle in extensive lunar caverns, where the temperature is uniform and water less sharply separated from the brighter portions. Through abundant; driving them forth upon these great green fields for a fortnightly feed when the sun is up for its long days and the grass in good condition? Jules Verne ought not to neglect so inviting a field of exploration.

WORKMEN AND THEIR TEACHERS.

For examples of the lack of definite knowledge upon simple practical subjects, by those who act as judges of workmanship, we need not look far. For instance, if we find in a mechanical newspaper a discussion on the proper manner of putting wheels upon axles, we shall perhaps read as follows 'Make them parallel and bore the hole parallel." "We have tried that, and we had more wheels come loose than we do now when we put them in taper," says another. The truth is that "make them parallel" is correct for good workmanship, and "make them taper" is suitable for inferior workmanship, Who ever heard of a properly designed and constructed parallel axle becoming loose in its wheel, unless from a fracture of the one or the other? If the boring and turning were either out of parallel or out of round, if the tool marks were left too deep, or if the sizes had not allowed the proper amount for shrinkage or the hydraulic pressure, as the case may be, the parallel shaft will come loose; but these defects have no business to exist, and can only exist from a lack of either surveillance or practical knowledge on the part of those in charge of the work.

Another cause for the common ignorance of certain and accurate methods is the unwillingness of a great many of our expert mechanics to impart their knowledge to others. This undoubtedly exists to a deplorable extent, and we have heard it defended upon the plea that business men are not in the habit of bruiting to the world any advantages they may happen to possess in their business facilities; and why should mechanics do so in their business? This is indeed a difficult question to answer upon a business basis, and brings us to the main question, which is how to utilize the knowledge possessed by our most expert artisans, and, by imparting it to our apprentices for their guidance, make superiority and rapid workmanship the rule and not the exception. Much effort has been expended in this direction by various publications, but we regret to say that we very rarely find a book in a machine shop; and need we look far for the reason, which lies not in the backwardness of the press in utilizing the materials at hand, but in the quality of the materials themselves, which do not as a rule commend themselves to those they are intended to benefit? The reasons for this are that, as we have before remarked in these pages, we must look for the science of practice to those who are known from their practical skill; and this course we have endeavored to take in the SCIENTIFIC AMERICAN and the SCIENTIFIC AMERICAN SUPPLEMENT, which have drafted into their service the best known talent in each branch of practical education upon which they have treated. That our efforts have been appreciated is attested by the freedom with which the scientific newspapers of both the United

Of the importance of imparting to others the results of the experience of the skilled workman, we will cite the following: Some four years ago there was introduced, from England, a special tool steel, possessing the peculiarity that it did not require any hardening. It was however difficult to forge, since it would crumble to pieces if heated to more than a bright red, and also if hammered at a very low red heat. The writer was one of the first men in this country to try it, and found no noteworthy advantage possessed by it for light lathe or other work. It had no advantages, in fact, as a finishing tool, and but very few for such roughing purposes as the shop in which it was tried afforded Its cost, too, being sometimes as great as that of ordinary tool steel, its use was not considered advisable. A year afterwards it became known that a certain printing press manufactory had adopted this steel, and had speeded up its machinery faster in consequence of the superiority of the new steel. A visit to the establishment failed to elicit from its manager any data or opinion; but first the speed and feed of some of the tools, communicated to the writer by workmen, disclosed that there was "nothing in it," as mechanics say, and a tool made of that steel and at the manufactory in question, lent by one of the artisans to the writer, showed upon experiment that its superiority was confined to deadness to which so many astronomers have theoretically heavy cuts on hard metal, circumstances sufficiently unusual assigned it. There is not the slightest adequate evidence, to show that the steel was suitable for special purposes only: and hence it was no surprise to learn that its general at that factory been discontinued at a subsequent date. However, it was tried, at the suggestion of the writer, upon pulleys, by Messrs. Laffan and Edgar, of New York, who, finding it served excellently well, applied it to turning shafting, and they were so well pleased with its adaptabillity to their purposes as to adopt it and recommend it to others. On another occasion, the writer was requested to visit one of the United States navy yards to see the excellent results obtained from a certain brand of American tool steel, for which universal merits were claimed; but on inspection, he found the cutting speed on small work to be only about 25 feet per minute, and that on larger work to range between 9 and 12 feet per minute; so that in neither case was the duty obtained from the tools sufficient to form any criterion of their cutting value.

If we turn to written instructions, we shall find tha for no kind of iron work is a speed of more than 25 feet per minute recommended, while in most cases 23 feet per minute is not exceeded. On small work, however, 35 feet per minute is easily attainable, and is by far the most economical. Two out of every three "authorities" give the cutting speed for east iron as being less than that for wrought iron, whereas the exact contrary is the fact. Now wherein does the fallacy lie? We have been asked that question by expert workmen, many times over, and we could find no reasonable answer, except that they did not properly forge or temper their tools No doubt that, in many cases, defects in the shape of the tools may have had something to do with it; but be the cause what it may, one thing is painfully apparent, that the author likewise account for the spread of the affliction attributable of the information was ignorant of his subject : as ignorant as the mechanical correspondent who visited Sheffield in England, and came back and exposed his mechanical ignorance a few weeks ago by writing a long article upon the want of progressive ideas among Sheffield manufacturers, adducing as proof that they forged the blades of fine cutlery instead of rolling them, all unconscious of the fact that to the forging belonged a superiority of quality that can under no circumstances be attained by rolling processes.

IS RARE BEEF DANGEROUS!

For several years past hygeists and pathologists have been closely studying the progressive invasion of the twniodea or tape worms in the human species, in order to discover all the causes which lead to the presence of these terrible parasites and the means of preventing them. While many vital points relating to the subject are still in controversy, it has been demonstated that we are attacked by the armed tænia (tænia solium) and by the non-armed tænia (tania medio canellata or inermis), that the germs of these two entozoa are introduced into the intestinal canal through flesh food, and that the germs of the first usually come from pork and those of the second from beef and mutton. It has furthermore been pointed out, by M. Régnault, that, while the number of attacks of the armed tenia has not notably augmented, those of the non-armed worm are becoming more and more frequent.

The cause attributed to this increase is first the therapeutic use of raw beef, and second, the habit of eating that meat, as well as mutton (the latter, however, in a less degree than the former), in a very rare state. Both beef and mutton contain morbific germs, which might well escape the scrutiny of a much more rigid inspection of market food than direct contact with steam, its under surface being in contact obtains here: and these, lodged in some organ of the body, speedily develope into the mature worm. Cooking the meat through thoroughly is a sure safeguard; but on the other flange, therefore, tended to prevent the expansion of the hand, there are many who have no relish for well done beef or mutton, and, among the Germans especially, the meat is had an increased radial expansion inwards. Now taking inprepared in various ways without being cooked at all. We have frequently seen raw beef steak served and eaten with ture of the steam, and the coefficient of expansion of brass, the simple accompaniments of pepper, salt, and vinegar. Butchers in New York city chop finely the good meat which is trimmed from joints or bones, and sell it in its hashed were thus obviously fitted too nicely, and through the unstate, at a low price, to the poorer classes, who likewise eat it raw, and thus save the fuel required for cooking. As indicated above, physicians often prescribe raw meat to the weak and debilitated, and it is no very uncommon thing to see infants sucking tender pieces of raw steak. Of course all this is dangerous, and the fact, we have reason to believe, is not entirely unknown to those who favor the practice; but on the other hand, there is a general idea that if meat be cooked ever so little, merely warmed through, all peril is obviated. That this is a subtle error will be clear from a brief consideration of the cooking process

The rationale of broiling is the subjection of a large surface of meat to a sudden high temperature. Coagulation of the exterior albumen succeeds, and the juices are prevented from escaping, so that they are cooked with the fibrous part of the meat, enclosed as it were between two shells. Roasting, or rather baking, as it is practised in this country, is virtually the same process, the hot oven being substituted for the coals. Frying accomplishes the same end by the action of highly heated fat. Boiling is just the reverse, as the heat in that case is applied gradually, so that structure, to the water leaders, etc., down which the lightning the albumen can be coagulated uniformly through the mass. Now albumen coagulates at 142° Fah., and further heat reduces it to a firm transparent body, so that a piece of beef which is left "unbasted," that is, unmoistened, during the cooking process, and its exterior temperatures not thus kept down, or a steak allowed to cook slowly over a slow instead of a brisk fire, is likely to become encased in a close crust, not inaptly termed "leathery," which tends to prevent the lives of inmates are in jeopardy. On the other hand, all experiences that thus, although the meat has been subjected to cooking a year 1752, when rods were first invented by Franklin, to the proper length of time, and although its exterior may appear present time, has shown that conductors are an essential overdone, a part of its interior may be practically raw, and means of safety in thunderstorms, that they preserve human may never have reached the temperature of 140°, beyond life, and prevent the destruction of property whenever prowhich it has been proved such portion of the meat thus prepared, the germs are none

It does not follow, however, from this that we are to interdict that most noble of all dishes, the rare cut of sirloin, care in its preparation. And in this respect we have a very safe and simple guide in the two temperatures noted above, or rather in their close approximation. Everybody knows the difference in color and general appearance between meat nearly raw and meat cooked, and is capable of observing the glairy, flabby condition of the former as compared with ing above the points of the electrical conductors; and such coagulated, in the other it has. But in the latter instance and before it can reach the conductor. we know that a temperature of 142° has been attained, and that that is two degrees higher than the germ death point; nected with the ground. They are simply stuck down for hence we are thus rendered certain that the danger is obviated, on simple inspection of the condition of the meat, which still is rare enough to satisfy any healthy taste,

It is not difficult to perceive that the ravages of that other fearful parasite, of the hog, the trichina spiralis, have been the cause of greater care in the preparation of pork; and as the same thorough cooking which destroys the trichina likewise destroys the tenia germ, both evils are obviated at once. Hence we find another cause for the diminution in cases of armed tsenia noted by Régnault, while the prevalent neglect of precautions regarding beef and mutton may to those meats.

It is a curious fact in this connection that a prominent French medical journal (the Abeille Médicale) strongly re commends horse flesh to be used raw therapeutically, and asserts that it is much more nourishing than either beef, mutton, or pork. We doubt whether this last assertion will meet with general acquiescence; but if it appears, as our contemporary states, that the horse is not subject to the parasitic affections common to the cattle now used as food, there can be no question but that, from a sanitary point of view, the food value of our superannuated chargers is greatly enhanced. At all events, for some reason the consumption of horsefiesh in France is rapidly increasing, as recent statistics show that nearly 30 per cent more of the animals have been slaughtered, for the markets in Paris, during 1876 than were killed last year.

THE "THUNDERER" EXPLOSION.

It will be remembered that, in our recent account of the disastrous boiler explosion on board the new English war vessel Thunderer, we stated, on the authority of the London Times, that the casualty was owing to the gross carelessness of not removing the wedges which had held down the safety valves during a previous hydraulic test. Such negligence seemed almost inconceivable, and therefore we are glad to welcome the flat contradiction given by Engineering to the Times report. The valves were not wedged down, and the similar valves in the unexploded boiler were all in working order when tested cold. Our contemporary points out that the valves of the burst generator, when cold, were 1 inch free in their seats. Around the latter, except at the steam connection, there is a broad flange not heated by with the air of the fire room, and its upper surface forming the inside of the bottom of the valve weight box. This cool cast iron chamber. So that the brass valve seat must have to consideration the dimensions of the parts, the temperait is found that the valve, after the seat had expanded inwards, would be 0 005 inch larger than its seat. The valves equal expansion they set fast. In addition to this the stop valves were shut, and it is known that the steam gage was badly out of order, and these three causes are, in Engineering's opinion, amply sufficient to account for the explosion.

LIGHTNING RODS.

"Professor Wise, the balloonist, who has had rare oppor-tunities for studying and observing storms as well as caims, has repeatedly expressed his convictions that lightning rods has repeatedly expressed his convictions that lightning rods are useless in electrical storms, but that metal roofs are an absolute protection. He says that during a recent storm several flagstaffs were shivered down to the point of contact with the metal roofs, when the damage ceased, the fluid dispersing over the expanse of metal. This corresponds to hundreds of other cases that he has examined; and he declares his conviction that 'the lightning rod, as a protection in itself, is of no more value than a bodkin would be to ward off the ball fired from a Columbiad.'"—American Architect and Ruilding News and Building News.

A metallic roof may, in some cases, avert damage to an unrodded building, by facilitating the passage of the electricity to the best wetted portions of the exterior of the may pass to the earth; a well wetted wooden roof may assist to the same result. Hundreds of unrodded houses, with and without metal roofs, have been struck, and not seriously damaged. But it is nonsense to assume that a good lightning rod, properly connected with the roof and with the ground, has no value. Although unrodded buildings may by chance escape, they are always in danger, and the

On the other hand, all experience, the world over, from the

but it does follow that we should exercise some greater broad expanse of the sea for their rod terminals, they would earth." be as universally exempt from injury by lightning.

We except, however buildings and vessels containing petroleum, or other substances from which inflammable form an explosive atmosphere of large extent, often reach-

In nearly all cases, our house rods are defectively confive or six feet into dry earth; whereas they should be soldered to a water or gas pipe, or be connected with some large extent of conducting material placed underground. restrial life began,

The following valuable and practical hints, as to the proper arrangement of lightning rods, are given by Mr. John T. Sprague, in his excellent treatise upon "Electricity; Its Theory, Sources, and Applications:

3 It must be remembered that lightning is not a mere thread of flame, or confined to the visible line; a large space all round the line takes part in the discharge, and gives up the force previously accumulated in it as tension.

"These principles settle conclusively all questions as to the construction of lightning conductors. Their object should be to connect to earth every portion of a building; and as this is actually possible only with metal buildings, they should connect every salient point and as much of the surface as possible, so as to extend around the building the area of low tension, or artificial "earth" surface opposed to the cloud. Chimneys require especial attention, because they are tubes lined with conducting material, containing warmer air: and if with fires, then extending a comparatively good conducting column of warm air towards the cloud and so inviting a discharge; hence it is that lightning almost always enters a house by the chimneys. All doors and windows causing currents of air should be closed during a thunderstorm.

'The prime essential is a good connection to water; water and gas mains provide the best if the conductor is well se cured to them; next to them is the metal shaft of a good pump, in a well constantly supplied by springs; then ponds or ditches. What is required is a large metal surface terminating the conductor, and in contact with a stratum of moist earth, so that a hole sunk into wet gravel, into which the conductor is led, and surrounded with a quantity of coke to increase its surface of contact, will answer, but dry clay, or rock, is not safe. This connection should, if possible, surround the building by means of rods from its various corners, either led to different earths or else continued by a rod round the house to one earth connection. Every piece of metal work above the building should be utilized, such as ridge caps, guttering, and water pipes. They cannot be trusted as conductors because of the joints in them, which offer great resistance, and therefore prevent reduction of tension, but they will help to form a protecting network around the building, especially if strips of copper are soldered across each joint. For the same reason a connection should be led from the bottom of the down pipes from the gutters to the nearest suitable earth, though a very good but variable earth connection is set up from these by the water itself during heavy rain. The lower parts of the bell wires may also be advantageously connected to an earth, such as the nearest gas or water pipes, as several accidents have occurred from their having either received a direct charge through the walls, or having a violent current induced in them.

"The terminals should be attached to all high or salient points, most particularly chimney stacks; if these are wide, and contain several chimneys, it is safer to have two points, though usually one is sufficient; but the kitchen chimney, or any one commonly used, and therefore lined with soot, and containing warm air, should be specially attended to. The points may be made of rods of 1-inch iron drawn out to a point, rising 2 or 3 feet above the building; they are better also for galvanizing. There is no advantage in any of the fancy points, patented or otherwise. The conductor depends upon the size and hight of the building. A factory chimney or church steeple should have a copper conductor of at least inch section, either as a rod or as a wire rope, well protected against injury; for smaller buildings, iron rod may be used instead of copper. In ordinary cases galvanized iron wire of about 1-inch diameter (such as is used for telegraphic purposes) will answer perfectly, if led separately from various salient points, and carried down the different sides of the house and connected as above described, to the guttering, etc., but for a single conductor at least \(\frac{1}{2}\) inch rod should be used. Solid rod is best, as it exposes least surface to rust, for it is the mass or weight of metal which conducts, not its surface, as some suppose; but every joint must be carefully made and soldered, to secure metallic continuity and low resistance.

"It will be seen that conductors should never be insulated from the building, but, on the contrary, as much of the surface as possible should be connected to the conductor. Electrometers, etc., are often surrounded with a cage of wire connected to the earth or to the negative pole of the active source of electricity, in order to prevent them from being affected by external electric disturbances. That is exactly what we require to do with our buildings; an iron house well connected to earth would not only be perfectly safe, Formerly, when ships sailed without rods, the loss of produced on the nervous system by "thundery" weather, the worse for their warming, and enter the body in an active life and property at sea was appalling. Nearly all vessels except so far as these are due to heat. The object aimed at now carry rods, and such an occurrence as serious damage in a lightning conductor should be to approach that condito a rodded vessel by lightning is almost unknown. If, tion as nearly as possible; to obtain an enclosed area within like ships, our dwellings and buildings could have the a conducting envelope provided with points and connected to

Life on the Earth.

Professor P. G. Tait, of the University of Edinburgh, in gases exude. The latter mix with the surrounding air and his lectures on recent advances in physical science, lately published, considers the question how long life has been possible on the earth. He concludes that ten millions of the firmness of the latter. In one case the albumen has not mixtures will be set on fire by the electricity on its way to years is "the utmost that can be allowed from the physical point of view for all the changes that have taken place on the earth's surface since vegetable life of the lowest known form was capable of existing there." Opposed to this is the view of the most eminent modern geologists, that at least three hundred millions of years have passed away since ter-

BREECH-LOADING FIREARMS.

We publish the third and last series of illustrations of breech-loading fire arms, which we select from the pages of single motion puts it in order for firing. The cartridges E. H. Knight's "American Mechanical Dictionary." It shows are placed in the magazine by pressing them through the three American and one Swiss inventions, the latter being a

U U' are two positions of the Remington gun; the left hand figure shows the gun when fired, the right hand ready to load. The breech block, b, swings upon a strong pin within a mortise of the stock. c is a tumbler which braces the breech piece against recoil at the time of firing, and forms a part of the hammer which strikes a firing pin which passes through the tumbler and is driven against the cap or part of the cartridge case containing the fulminate.

The breech piece, b, and tumbler, c, are so formed that when the former is closed the rounded upper portion of the tumbler works in a concavity in the back of the breech

piece works in a concavity in the front of the tumbler, asshown in Fig. U'. This mode of matching the breech piece and tumbler prevents the possibility of the hammer falling until the breech piece is perfectly closed, and so obviates the possibility of premature explosion of the charge. The extractor, by which the discharged cartridge shells are drawn out from the chamber of the barrel, works between the receiver and the breech piece, and is operated by the opening movement of the latter. The breech piece is opened by a thumb piece. A guard lever, d, prevents the trigger being drawn when the breech piece is

W W' are two views of the Dodge breech loader, shown as a double barreled breech-loading fowling piece. W is a perspective view, and W' a sectional view. The barrels are hinged to the front end of the stock, so as to tilt upwardly at the rear and nearly balance upon the hinging point, the motions being made by means of the pivoted lever d, which laps over the trigger guard and locks the barrels in firing position by engagement of a hook,c, with a pin passing through the lug,g. The front end of the lever extends beyond the pin on which it turns, and works in a slot in the center of lug, g, beneath the barrels, which it serves to elevate and depress. As the barrels are elevated, the front end of the lever strikes against a projection on the stem of the extractor, and retracts the spent cartridge capsule. The frame, e, is made of a single piece of metal extending from the front, where the barrels are hinged, to the grip in the rear of the breech; and the locks are fitted in recesses therein, dispensing with separate lock plates. The locks are rebounding, that is, they go forward and fire the cap and return to half cock. The hammers draw back the firing pin when fully cocked. The barrels are adjusted on the frame, and wear is compensated by means of the block, b. In use, the left hand need not be moved from where it is in firing; the breech is brought un-der the right arm, the lever thrown down, a fresh cartridge inserted, the lever returned, the hammer cocked, and the piece is ready to fire.

The gun adopted by the Swiss Federal Government has the magazine and cartridge carrier of the Winchester, with the needle exploder and bolt breech. The large figure is a longitudinal central section; z is a perspective view of the bolt, firing pin, and lever detached;

x1 is a view of a piece of the breech cylinder; x2 is a view rier block into the chamber, drops the carrier block to re- | double work performed. of the cartridge carrier detached.

The motions are as follows: the lever, a, is raised, rothe arm in readiness to be fired. tating on the firing pin, b, andcocking the latter by the sure of a cam upon the transverse trigger bar, c the bolt is then drawn back, carrying the firing pin and the hook, which retracts the spent cartridge; the motion eventually rocks the bell crank lever, d, and raises the carrier e, which brings another cartridge in line with the barrel. The bolt, h, is then pushed back, pressing down the carrier, e, catching of studs, f, on the bolt behind lugs,g, on the breech cylinder. The firing pin has remained on the cock since the first motion of the semi-rotation of the bolt, and is now pulled off by the trigger. The combination is known as

Y' is the Henry magazine rifle, now known as the Winchester repeating gun. It may be used as a single loader or a repeater. As a repeater the motion of the lever, a, withdraws the spent shell of the previous charge, raises the hammer, recharges the gun, and relocks the breech mechanism. The magazine contains seventeen cartridges,

*Published in numbers by Messis, Hurd & Houghton, New York city,

loading, the cartridge is placed in the carrier block, and a trap, b, on the right hand side of the gun, the magazine being easily filled while the gun swings at the side. They are fed from the magazine into the carrier block by a spiral

Y is a section of the gun immediately after discharge; c is an empty shell; d, one in the carrier block; e, one in the magazine; by the forward motion of the lever, a, the links take the position shown in Y', the piston, g, is withdrawn, raising the hammer to the full cock, and extracting the empty shell, c, which is thrown upward at the same time the carrier block, A, with the carriage which it contains is raised by the lever, i, placing the cartridge opposite the chamber. This position is seen at Y'. The returning mopiece, as shown in Fig. U; and when the hammer is drawn tion of the lever drives the piston forward, leaves the hamback to half cock or full cock, the rounded back of the breech | mer at full cock, forces the cartridge contained in the car- ity to do printing in different characters, leaves the Ameri-

> Dodoe's Double-barreled Shot-ma Winchester's Repeating Gun

BREECH-LOADING FIREARMS.

ceive the following cartridge from the magazine, and places

Plant Anæsthesia.

The curious discovery has recently been made that an esthesia may take place not only in animals but in plants, and, in brief, in all forms of life. It has been demonstrated that etherisation acts finally on all the tissues of animals and on the central nervous system. Hence, if plants and driving the cartridge into the barrel; a partial rotation have tissues, the ansesthetic should equally act on them. of the bolt, by means of the lever, a, locks it firmly by the This substantially appears to be the case; and every vital act, whether occurring in animal or vegetable, may be an esthetised. In plants, M. Claude Bernard, to whom is due the credit of the discovery, has found that germination ceases under the influence of ether. He introduced water cresses, which germinate from day to day, into two precisely similar tubes. In one tube he placed a little ether. The plant therein on the following day was found not to have germinated, as the other had; but after being removed from the anæsthetic, the first went on and germinated in a natural manner. The plant had literally been put to sleep.

The same is true of ferments; for beer yeast, after con- for acquiring the knowledge they seek.

which can be discharged in as many seconds. With single tact with ether for twenty-four hours, completely loses its activity, and yet regains it as soon as the etherization is stopped.

EXHIBITION NOTES.

PAPER MAKING.—The papermaking machinery is among the most attractive features of the hall, and, to most visitors, also among the most novel. It is exceedingly interesting to them to see the rags come out of the great iron drums, where they are churned and ground, in the form of a milky fluid; to watch the deposit of the snowy pulp, and to see the pulp carried forward on broad belts and between successive rollers, until, growing always thinner and drier, it finally is rolled on a drum as firm, white printing paper. The machinery is said to be the best for the purpose made.

NOVEL TYPE WRITER.-A Russian inventor, M. Alissoff, of St. Petersburg, shows a type writer which, for excellence of mechanical structure, cleanness of impression, and abil-

> can type writer far behind. It cannot be made to work nearly as fast, however, as its American rival; and as speed is what most people seek in such a machine, it is doubtful if it will ever come into extensive use. M. Alissoff says that he first turned his attention to making a machine for speed, but finding by observation that few men can think faster than they can write with pen or pencil, he concluded that such an invention was not what was needed, but something that would make as accurate and legible copy as a printed page. In this undertaking he has fully succeeded. His machine writes in the Russian and English characters, makes capitals, small capitals, figures, signs, punctuation points, and all the French accents. As the types are movable, it can be arranged to print Greek, Hebrew, or any other written language. The manner of working it is to move a lever on a dial to the letter desired, and make the impression with the foot upon a pedal. The speed is about that of ordinary writing. M. Alissoff also exhibits an invention for photolithographing music. The staves notes, and signs. printed on thin paper, are kept in small boxes, from which they are taken and pasted upon a large plate of glass, regularity being secured by lines on cardboard at the back of the pane. Thus the composition is built up much more rapidly than could be done with types. A negative is then taken of any size desired -the light passing through the glass -and when transferred to stone the printing is done by the usual pro

CURIOUS SEWING MACHINE CONTRI-VANCES .- A French machine has a universal feed, which enables the operator to give the cloth any direction desired, without touching it-a very useful device for embroidering on stamped patterns.

Still more ingenious is an American invention for embroidering set figures automatically. By a curious arrangement under the table, the feed is set so that the machine goes on of itself, reproducing the pattern. About a dozen different simple patterns can be embroidered by changing the apparatus.

Another noticeable invention is a machine which sews with either one or two needles, as may be desired. It is especially useful for embroidery, as threads of two colors can be used and

Three kinds of machines are shown that sew from the spools, and thus dispense with the troublesome shuttle and bobbin.

The Visit of the French Working Men.

About fifty French mechanics, who have been selected by the Government of France to visit the Centennial, recently arrived in this city. They are to make a critical examination of the Exposition, each man devoting himself to the display presented in his particular branch of art or industry, and, on their return to France, are to prepare reports of the progress exhibited in each separate branch of manufac ture. Nearly every class of French industry has its representative in this commission, and the members themselves appear to be intelligent and wide-awake mechanics. There is nothing political in their mission; and in this respect they differ from a body of reputed French artisans who lately visited us, but who deservedly received no special attention, owing to their affiliations with that unfortunate class of men who are always at the head of labor agitations and communistic disturbances. We trust our American working men will give their French brethren a cordial welcome, and spare no pains in affording them every facility

IMPROVED PIPE CUTTING AND THREADING MACHINE.

Messrs. Joseph B. Eaton and Charles Latham, of Shamokin, Pa., have patented (July 4, 1876), through the Scientific American Patent Agency, an improved pipe cutting and threading machine, that may be worked effectively in a very narrow space, so as to produce a saving in time and labor in grade of sand. the digging and the working of the machine. Fig. 1 is a top view of the cutter and threader, and Fig. 2 a sectional which keeps large pieces from passing into the machine. end view of the same.

The shell or casing, A, is made of two hinged sections, which are applied around the pipe to be worked upon, and locked firmly together by a suitable device. The threading dies, B, and the cutters, C, are guided in interior recesses of the shell, and adjusted or fed forward to the required depth of cutting by means of set screws worked from the outside of the shell. The shell is cast at the ends with raised ratchet teeth, D1, along which an operating handle, D, is guided at both ends by an outer arc-shaped part, b, and an inner concentric piece, d, that slides in a recess of the shell below the ratchet. The outer guide pieces of the handle, D, lock, by spring pawls, D*, into the ratchets, to take hold of the shell, and turn it in one direction, while releasing it when turned back in opposite direction. A drawing pipe, with threaded end, fits into the threaded end of the shell, and is attached by clamp screws tightly to the pipe to be threaded, drawing by the screw the threading machine forward for cutting the thread on the pipe.

When the pipe is threaded, the machine is returned for clearing the thread by a semicircular handle with hook end, that is inserted into the small socket holes, ϵ , of the shell.

It is claimed that thus a deep or shallow thread may be cut on water and gas pipes of different sizes with ease and rapidity while the cutting is done in perfect manner without leaving a shoulder at the end of the pipe.

South African Railways.

A line of railway 120 miles in length was recently opened between Cape Town and Worcester, South Africa. The road is an extension of the Cape Town and Wellington Railway, purchased by the government some years ago, and is part broad and part narrow gage. It is intended eventu ally to make the whole line of the latter description. Railway work in other parts of the colony is being vi gorously prosecuted; 65 miles of road are nearly complete on the eastern line from Port Elizabeth, 60 miles on

end of the year, and a similar distance on the Midland line will shortly be finished. The estimated cost of the new works was about \$30,000 per mile, but this has been exceeded by as much as \$3,500 per mile in some cases, the increase being accounted for chiefly by the deficient supply of labor, enhanced rate of wages, and high cost of provisions.

Meteoric Iron in our Church Steeples.


On August 10, the earth passed through the great belt of meteors; and on about November 13, it will again plunge into the midst of these vagrant bodies. People who are curious about meteoric iron, or who desire to investigate that substance, will probably therefore find the present a good time to look for it. M. Tissandier has lately shown that the metal is constantly found in the cosmical dust, which often may be collected from rain, and which exists in the at-mosphere of elevated regions. Most of the meteors which strike our atmosphere are at once dissipated by the heat of intense friction, and the iron, melting, falls like shot, in the r or nearly globular form in which M. Tissandier ha found it, and which, he thinks, is one convincing proof of its celestial origin. M. Yung recently told the French Academy of Sciences that the best places in which to look for meteoric dust is an old church steeple. Collect all the dust which has become deposited in out-of-the-way corners, where the wind has not been able to reach it, and examine it under the microscope. Apart from learning how many curious things are floating about invisible in our atmosphere, the student may be able to get together sufficient of the iron to examine it by chemical means.

IMPROVED SAND AND GRAVEL SEPARATOR.

Builders, masons, roadmakers, contractors, and others will doubtless be interested in the invention herewith illustrated, | board which can be raised or lowered to regulate the flow of which is adapted for acreening sand and separating gravel, sand to the machine. L is a shelf for carrying off coarse overcoming the slow and tedious process now in use. It is gravel. A single screen is made of four meshes to the inch claimed to screen sand, no matter how wet, when it cannot or any other size required, to be used for screening sand


coarse gravel for walks, etc., in separate places from the sand, thus saving the necessity of a second screening when roofing gravel is in demand. It can be worked to screen thirty yards a day, by one man throwing the sand and a boy to turn the crank. It works rapidly, and will supply any

A is a coarse screen on which the sand is thrown and The sand passes down to the feeder, B, which carries it



EATON & LATHAM'S PIPE CUTTING AND THREADING MACHINE.

of pins, and revolves with velocity, spreading and separating the adjoining building where one of the telephones was the sand and gravel and throwing it against the screens, G G. These screens are placed one over the other. The roofing gravel and sand pass through the upper screen (which is made of half inch mesh or any other size needed) to the lower, which is six meshes to the inch, or any size required. The roofing gravel passes down between the legs, which are inclosed, and the sand through the fine screen. The coarse gravel passes down in front of the machine. H is a wrapper or beater, which strikes eight times with every revolution of the crank, against the under part of the screens, and loosens any sand that may stick to the screen. K is a feed



entirely from the sand, and deposits the roofing gravel and I to pass down in front of the machine.

The manufacturers also make a large-sized machine to be run by horse or steam power, having one elevator to raise sand and another to carry the sand into bins, cars, or other places of deposit.

For further information address the manufacturers Messrs. Chambers & Quinlan, Decatur, Ill.

The Human Voice Transmitted by Telegraph.

Several weeks ago we gave a sketch and description of

the thread telegraph, consisting of two small tin or wooden cylinders, each having a membrane stretched over one end, the two membranes connected by a stout thread. Two persons may readily communicate the sounds of the voice by means of these instruments over a thread fifty or a hundred feet in length. The person sending speaks within one of the cylinders, which causes the membrane to vibrate; the vibration passes along the stretched thread to the membrane of the other cylinder; which being held to the ear of the ear of the person receiving the message, the vibration is duly heard, or, in other words, the voice of the sender is made audible.

Professor Graham Bell, by a device somewhat analogous, has succeeded in transmitting the tones of the human voice by telegraph. Instead of the thread he connects the membranes of the two cylinders or drums with the armatures of the electro-magnets, one drum being placed at each end of the telegraph wire. In fact, he not long ago demonstrated the possibility of conveying vocal sounds by means of the ord nary telegraph wires and special appliances for transmitting and receiving the sounds. The apparatus used by Professor Bell is thus described: Two single-pole electro-magnets, each having a resistance 10 ohms, were arranged in circuit with a battery of five carbon elements-the total resistance being about 25 ohms. A drumhead of goldbeater's skin, about 2‡ inches in diameter, was placed in front of each electro-magnet, and a circular piece of clock spring was glued to the middle of the membrane of each drumhead. One of these telephones was placed in the experimental room, and the other in the basement of an adjoining house. Upon singing into the telephone the sounds of the voice were reproduced by the instrument in the distant room; and if two persons sang simultaneously, the two notes were audible at the other telephone.

At the time of the lecture, an experiment was made to show the

the border line, from East London, will be ready by the down to the cylinder, E. The latter is made with four rows transmission of articulate speech, an assistant going into placed. Several familiar questions were, it is said, understood after a few repetitions. The vowel sounds alone are those faithfully reproduced; dipthongal sounds and rotund vowels are readily distinguished, but consonants are generally unrecognizable. Now and then, however, a sentence comes out with almost startling distinctness, the conscnants as well as the vowels being clearly audible. Professor Bell stated that telephonic effects can be produced with three varieties of currents-the intermittent, the pulsatory, and the undulatory. The first are characterized by the alternate presence and absence of electricity in the circuit; the pulsatory current by sudden changes in intensity, while undulatory currents are obtained by gradual changes analogous to the changes of density of air produced by vibrations of a pendulum.

The most recent trial of Professor Bell's instrument was at his residence, Brantford, Canada, August 11. The Toronto Globe states that instruments were placed, one in the grounds, and communication between these made by ten miles of wire. Musical notes, the human voice, and songs spoken and sung before one instrument were plainly audible by placing the instrument to the ear at the other. By this invention, too, any number of messages can be conveyed over one wire in either direction, provided they have a different pitch; the tones of the voice can pass over the electric wire, enabling the hearer at any distance to hear distinctly what is said, and to distinguish the voice of the speaker. On August 10 the professor had communication made with his instrument on the common telegraph wire between Brantford and Mount Pleasant (five miles), and was spoken with, while in Mount Pleasant, by Professor D. C. Bell and Mr. Griffin from the Dominion office in Brantford. On the evening of August 12, the professor tried a new experiment, having had an instrument made so that three persons could sing different tunes or different parts of be screened by any other process. It separates the gravel when roofing gravel is not wanted, allowing all the gravel the same tune into the instrument at the same time. The trial was perfectly successful, the different voices coming

distinctly over the wire at the same time, so that they could be separately distinguished by the listener. The practical exemplification of the lately discovered system of telephony made by the professor afforded much pleasure and information to those present.

Correspondence.

The Moon's Longitude and Solar Retrograde Motion.

To the Editor of the Scientific American

In the Scientific American Supplement (page 492, volume I), you state that a paper by Professor Newcomb, on "Inequality of the Moon's Longitude," was read at the June meeting of the Royal Astronomical Society, and that several of the more notable members of that scientific body expressed themselves as being at present quite unable to tell the cause of the phenomenon. Allow me to advance the following, which, I think, points to the cause.

The sun, his planets, and their several satellites are all distinct members or wheels of the great, grand celestial machine called the solar system; and unless we look upon the whole as a machine, and trace the effects which the retrograde motion of the largest one has upon the smaller ones, and these upon the smallest ones, we shall never be able to tell the cause of the phenomenon now under consideration, nor the cause of kindred phenomena in other moons; for they all move more or less ahead of their times while in one side of their respective orbits, and lag behind while on the other side, just as the earth herself and every other planet does, and must do, although practical astronomy has not yet discovered the facts.

To explain. We take the sun, or main wheel, first: His orbit is to be considered the rim of the wheel; the center of his orbit, the center of the wheel; and he (the sun) fixed, as it were, on or in the rim. That wheel turns on its axis retrogressively; and the rim, and the sun, of course, retrograde at the rate of nearly 504" annually. Now, by virtue of the earth being carried retrogressively by the sun, she, too, retrogrades annually, as it were in her own orbit, nearly 501". Could we stand at the center of the sun's orbit, and view clearly the longitude of the earth at the moment she reaches 180°, we would find that she had fallen behind her sidereal place in the heavens, that is, the point at which she was when she came to 180° the previous time, say 501"; and when she came to 0°, she would be 501" retrogressively in advance of where she was at the moment she came to the same point in her orbit one exact year before. In other words, she would be behind time on one side of her orbit, and in advance of time on the other side

And it is exactly so with the moon. In one exact terrestrial year the moon retrogrades in space to the same exact amount; or, in other words, her orbit, as a whole, is carried retrogressively in space nearly 504", annually, or about 4" for every revolution she makes. It seems easy to see, then, that, in consequence of her retrogression in space, caused by the retrograde motion of the sun, she must be behind time, while on that side of her orbit which is outside of the sun's orbit, and vice versa.

I submit the above to the consideration and amendment of the wise and learned.

Gloucester City, N. J. JOHN HEPBURN.

Professor Crookes' Radiometer.

To the Editor of the Scientific American: On page 116 of your current volume, Mr. Joseph Delsaux, of Louvain, Belgium, presents some interesting experiments upon the radiometer. As I have not a radiometer at hand, I assume that the described tests were correctly made; and feel that there is good cause to suspect a coaction of forces to move the electrometer vanes. Could it not be settled beyond a doubt by charging the radiometer globe from an elec trical machine, to the same tension and with the same kind of electricity as the globe contained after being submitted to the radiation of the sun or any source of light, and then as-

certain if the action of the radiometer were the same? Some other phenomena could be investigated in this connection. For instance, it is well known that selenium varies in electrical resistance from 15 to 100 per cent, inversely as the intensity of light to which it is subjected. It is also an established fact that on telegraphic circuits the speed of signaling is decreased during the middle portion of the day, and improved at night. Mr. R. S. Culley, the well known English electrician, called attention, in 1872, to this re dation, and said that the cause was not clear, but attributed it to "the ordinary diurnal variation of earth currents and to the increased resistance of the wires from increased temperature." As Mr. Culley has drawn no line between warm and cold weather, it would be well for Mr. Delsaux and other skillful experimenters to take the matter up, and apply the electrometer to things in the light and in the dark. We may perhaps thus be informed of what we are seeking to know. Chicago, Ill. F. W. JONES.

Test Colors.

To the Editor of the Scientific American :

In No. 7 of your current volume, I notice a report of a discovery of new test colors from the iris and violet. I have found the blue convolulus major, or morning glory, of considerable practical value as a test for acids and alkalies, the first place, the flower itself is very sensitive, indicating the trace of nitric acid in rain water after a thunderstorm. The flowers show red spots wherever the rain water has platform scales, and all connections to the tanks are made by anglers

wetted the surface after a shower during the night. A few by means of rubber pipes, which only change their direcof the flowers rubbed in a glass of water will give a bright tion slightly during an experiment, and consequently do not blue liquid, which will instantly redden if a drop of nitric or sensibly affect the weights. The large tank has a circula other acid be put in; and the blue will be restored by neutralization. But if the alkali is much in excess, it will turn green and return to blue on neutralizing again. Water colored by the red convolulus will turn blue on the addition of an alkaline salt, but is not so sensitive as the blue.

M. W. VENABLE. Milledgeville, Ky.

Some Notes on Potato Beetles.

To the Editor of the Scientific American:

It is not often that you are caught napping, and you are more apt to be so caught when lounging in the field of natural history than in any other. In your issue for July 29, you copy an article from the SCIENTIFIC FARMER, entitled 'Facts about Potato Beetles," in which, among the prominent statements offered as "facts," we are told that the potato beetle (by which of course is meant the well known immigrant from Colorado, and not any of the other beetles that affect that plant) does not fly till night and does not eat. Both these statements are incorrect. The doryphora 10lineata, like most of the species of its family, flies readily in the daytime, but not at night; and it feeds freely upon the various plants of the nightshade family besides the potato, and sometimes does considerable damage in spring long before the larvæ appear; though it is not as voracious as these and seldom abounds on a plant to the same extent. Reasoning from his "facts," the writer of the article goes on to say that "any mode of destroying the beetle, practised by the farmer here and there, is only lost time * * * therefore let the beetle alone "-an erroneous deduction naturally following from the erroneous premise, and very unsound advice. It is in fact all important, from the practical view, to destroy the first beetles and thus prevent the laying of eggs and the subsequent injury; for while it is true that they may continue to fly in from neighboring fields, the fact nevertheless remains that the more you kill the less you have. Many experienced farmers in this part of the country justly consider the destruction of the early beetles important enough to warrant the laying of traps before the potatoes begin to put out of the ground; and they do this by dipping slices of the tuber in Paris green and laying them about a field where no domestic animal can get at them.

There are other errors in the article in question, but of minor importance. For instance, every one who has had much experience knows that the third or last brood of beetles is fully developed and flies around for weeks or even months before seeking winter quarters, and that they hybernate in the perfect state, ready to awaken in the spring and fly about again for a few weeks before procreating. The species is, also, northern, not southern, in habitat, and while spreading east along certain parallels, has not extended south. The talk, therefore, about the insects remaining dormant through the winter merely "because the temperature is too low to perfect the insects," and about the probability that, if they reached a tropical climate, their "transmigration (transformation) will be uninterrupted "-is 'misty," to say the least. The hybernating state is induced not alone by cold, and many insects prepare for it and cease multiplying months before winter sets in; and doryphora is one of them.

St. Louis, Mo. C. V. RILEY.

THE CALORIMETER OF THE MASSACHUSETTS INSTITUTE OF TECHNOLOGY.

Among the drawings displayed by this institution at the Centennial is one of the calorimeter used in the mechanical aboratory of the school, and a description of it by the professor of engineering may be found on one of the tables. A courteous attendant is usually on duty also, who takes pleasure in answering the questions of visitors. Profiting by these sources of information, the writer has prepared a description of the apparatus, which will doubtless be of interest to engineers.

The general use of the calorimeter is to measure the quantity of steam condensed in it in a given time, and the amount of heat imparted to the condensing water by the steam. In this connection it is valuable for determining the quality as well as the quantity of steam evaporated by a boiler, the steam required per horse power per hour by an engine, the condensation in the cylinder, the total and latent heat of steam at different pressures, the transmission of heat by different conductors, and numerous other problems of a similar character. Its great value in teaching the students tion, and claims that it simply suffocates by filling the lungs ight methods of investigation will be obvious, and at the same time practical questions of importance to steam users can be examined. The calorimeter to be described was used by Mr. Dixwell in his experiments on condensation in steam cylinders, a notice of which will be found in the SCIENTIFIC AMERICAN for March 11, 1876.

The essential features of the instrument are a tank containing a condensing coil, a tank for the condensed steam. scales for determining the weights, and thermometers for ascertaining the temperatures. Steam enters the condenser, which is arranged so as to drain thoroughly, and after being condensed is discharged into a small tank where the weight and temperature are noted. The large tank is filled with water, the weight and temperature of which are noted at

ting pump which is worked at intervals during an experiment, so as to make the temperature of the condensing water uniform in all parts of the tank. To illustrate the use of the apparatus, suppose the exhaust pipe of a steam engine to be connected with the condenser, and that the consumption of steam per indicated horse power is to be de. termined. The large tank is filled with water, until the cover in the expansion tank floats, and the weight and temperature of the water are noted. The engine is then started, and at regular intervals indicator diagrams are taken, and the weights and temperatures of condensing and condensed water are noted, the temperature of the water in the large tank being equalized by the aid of the circulating pump before it is recorded. The result of a series of operations shows that a certain weight of steam of a known pressure imparts a definite amount of heat to the condensing water, and from these data the quality of the steam can be calculated.

The reader is doubtless familiar with other calorimeters, as they are frequently used by engineers. A large one was employed for two years at the fair of the American Institute in tests of steam boilers, the weight and temperature of the condensed water being noted, and a somewhat similar apparatus was used on a later occasion for testing the amounts of steam required for several rotary engines. The difference between these calorimeters and the one described above seems worthy of notice. In the one case the calculations are made by observing the successive changes in temperature of a definite weight of water which is used throughout the experiment, and in the other the condensing water flows away continually, so that the temperature of the discharge does not vary much during a test. It will be seen that, where a definite volume of water is heated by condensing steam, the amount of heat thus measured is not all that has been given up by the steam, since some of the heat is absorbed by the apparatus; while in the other form of calorimeter, if a definite temperature is reached before commencing an experiment, and is afterwards maintained, no more heat will necessarily be absorbed by the apparatus. Of course, in the form of apparatus used at the Massachu setts Institute of Technology, the amount of heat absorbed under various conditions might be determined, and the ne cessary corrections applied. Perhaps this has already been done, but it does not appear in the account given by the professor of mechanical engineering, who is quite minute in describing the tests of gages and thermometers. It may be, however, that the correction would generally be unim-

As appears from the descriptions of the use of this apparatus, the students are well drilled in some special tests of testing apparatus. This is one of the most important points in the engineer's practice, and it seems to be duly appreciated at the school. Experience shows that physical apparatus cannot be made free from defects, but that, if the amount of error is determined, corrections can be applied which R. H. B. will give accurate results.

Philadelphia, Pa.

A Useful Tree.

Mr. Morgan, an English consul resident in Brazil, cites, in a recent report to his government, the carnouba tree, a species of palm (copernicia cerifera) as one of the most valuable vegetable productions of the country. It flourishes without culture at Bahia, Rio Grande do Norte, and other well known localities, resists drought, and always appears green and luxuriant. Its roots possess properties similar to those of the sarsaparilla. The trunk furnishes a superior fiber. When the tree is young, it yields wine, vinegar, a saccharine matter, and a species of gum closely resembling sago. Its wood is excellently suited for the manufacture of musical instruments, as well as for tubes and conduits for water. The pulp of the fruit is very palatable, and the oily nut roasted and pulverized is a good substitute for coffee. The trunk also yields a flour similar to maizens. With the straw, hats, brooms, and baskets are made, and over half a million dollars worth of it are exported to Eng land yearly. Lastly, a wax, used in the manufacture of candles, is extracted from the leaves

The Cause of Asphyxiation.

Dr. Blandet, in the French Gazette Medicale, denies that carbonic acid gas has any toxic effect in cases of asphyxiaby carbonic acid gas can usually be restored by inhalations of oxygen. The true cause of bad air poisoning, Dr. Blandet thinks, is carbonic oxide, which is disengaged prior to carbonic acid. This does not diffuse itself in the blood like the latter, but remains and destroys the hemoglobine and the hematine.

The best remedies are not only inhalations of oxygen, but friction of the skin with oxygenated water and decomposible oxides, such as those of manganese and of cadmiun. It is also suggested that sulphydrate of ammonia, administered hypodermically, might decompose the carbonic oxide.

A CANADIAN sportsman declares that the speckled trout regular intervals. The small tank is closed at the top by a in Ontario have been killed by warm water. The woods floating cover, secured to the edges by a rubber diaphragm. have been cut down, and the sun, shining upon the water The large tank is also closed at the top, but provision is from morning till night, heats the streams. He asks the made for expansion by an expansion tank placed above, and farmers to plant willow limbs along the water's edge to having a floating cover. Each tank rests upon a pair of shade the brooks and give the trout a chance—to be caught

PRACTICAL MECHANISM.


BY JOSHUA ROSE.

SECOND SERIES-Number X

PATTERN MAKING-THE FOUNDERY


It has been already remarked that the operations of the molder are, to a large extent, predetermined by the pattern maker; hence it becomes necessary that the latter shall have a knowledge of foundery work, otherwise he is likely to make the patterns very expensive and awkward to mold In learning the trade, an apprentice is usually put to work and distinctly instructed as to the required form of his work without knowing anything of the reasons therefor. In this way he attains a practical knowledge of how different classes of patterns should be, or are, usually made; but it takes him years to become an expert mechanic, for the reason that, having learned by rote, he is incapable of meeting new con ditions to the best advantage, until his experience has included both observations in the foundery and, in some cases consultations with founderymen. Before entering, there fore, into the method of putting together different kinds of pattern work, it will be well to take a glance at the founde ry, and examine the contrivances and the operations of the workmen, so that our operations in pattern work may be intelligently made from the beginning.

The floor of the foundery first demands our attention. It is composed of a layer of molding sand of sufficient depth to imbed patterns of the size usually cast in that foundery. For exceptionally large work, there is usually a place where the natural earth has been excavated to a greater depth; the cavity is filled with molding sand. This place is usually within easy reach of the cr ne (which commands almost every part of the floor) and the threshold of the melting furnace or cupola. We next observe the capacious oven for baking cores and drying molds for such special work as may require these operations; but the particular contrivance with which the patternmaker has now to concern himself is represented in Fig. 67. It is called a flask, and is composed of two or more parts (two only being shown in the engra-




ving). The lower part is called the nowel, and the upper the cope. Each part is simply a strong rectangular frame of wood or iron. The sides, being continued past the rectangles, are roughly shaped for use as handles. The cope is provided with several crossbars, which embrace the pattern as it were, being roughly shaped like it in contour and approaching it in size, being about half an inch larger all round. These bars, by their adhesion, support the body of the sand in the cope, and in this they are frequently assisted by nails driven in nearly half way into them. When an intermediate part is used with the two parts shown in Fig. 67, the contrivance is called a three-part flask; with two in termediates it is called a four-part flask, and so on. As the cope is provided with crossbars, so also the intermediates, having to lift a ring of sand, are provided with wings; that is to say, as much crossbar as will extend from the sides to within about half an inch of the pattern. The parts are guided, in their position one to the other, by taper pins on one part fitting into eyes fixed to the other part, as shown in Fig. 67, in which the cope is shown with the side having the two pins exposed to view, while the opposite side ping cannot be scrutinized, and it may therefore produce an of the nowel, having one eye, is visible. In many cases foundery floor is used in its stead, in which case the cope is guided to, and retained in, its place by stakes driven into the floor sand, as shown in Fig. 68, so that, when lifted to admit of the pattern being drawn from the mold, the cope may be returned again to its exact proper and former position. In Fig. 68, A represents the pattern whose impression in the floor sand, at M, forms part of the mold. B represents the cope; for the word cope is usually applied to the upper part of the mold as well as to that portion of the flask which contains it. The top print, C, of the pattern, has formed its impression in the cope at P. R is a round taper peg, which leaves a hole in the cope at r, through which hole the molten metal is poured. It also leaves an indentation at r'; and from this latter a gutter is made by the molder to communicate with the mold, M, as shown. from crossgrain of the wood or from some other cause. This The stakes referred to above are marked S. The dots, shown around the impression of the top pattern print, C, in the dom resorted to; and it may be generally disregarded in the cope, are small holes made in the sand (after the molding is calculations of the pattern maker. The cope, then, being, task by his handicraft.

the metal is poured in.




It will be seen that, when a mold is made in the flask we have described, it can perform no further duty until the casting has been made; for every mold, therefore, we require a flask, and hence the pile of these appliances we always see in a foundery. For light work, however, a comparatively modern and greatly improved device has come into general use. It is termed a snap flask, each part having a hinge at one corner and a latch at the diagonally opposite one; so that, after the mold is made, it can be detached from the perfected mold and can be used to make another. For the details of its construction and use, the reader is referred to page 111, Vol. XXVIII., since it is not our purpose to here discuss the merits of such contrivances. Sometimes, though rarely, it happens that a casting is required of such form that the patterns cannot be constructed so as to be molded with a flask of the ordinary kind. The flask requires to come to pieces and the mold to be parted sideways; this adds greatly to the labor of the molder, and the patternmaker should so construct the pattern as to avoid this whenever he can devise any means of so doing. Even when the pattern is molded in the floor, the mold is sometimes of necessity made to part on one or more of its sides, and these partings are termed drawbacks. An example of this class of work will be given hereafter.

By matching the operations of a molder, we shall observe that, in the case of a solid pattern, that is to say, a pattern not made in halves, he always endeavors to have as little of the pattern in the cope as possible, and in this respect the patternmaker should supplement his efforts. The reason is obvious: the cope has to be lifted while as yet there has been no opportunity to loosen the pattern in the mold. has to be mended, it is doubtful if the correct form, such as




the pattern would have given it, will be left. Furthermore it is all work in the dark; for the effect or extent of the rap undue distortion in one direction, while in another it may not have been effectual. Perhaps the bar may have descend-



ed at a place in the pattern where it is comparatively weak measure is, therefore, on account of these difficulties, sel-

finished) by a piece of fine wire, and are for the purpose of as we may say, a dead lift, and with nothing to guide the giving vent to the air and gases which must escape when operator in moving it, either horizontally or vertically, any part of the mold contained in it is much more liable to break down than is the other part of the mold. In extracting the pattern from the lower part of the mold, the eye lends to the molder great assistance. The pattern can be loosened in the sand before extraction, and is furthermore less cumbersome to handle than is the cope: all of which circumstances tend to preserve the lower part of the mold from damage during the extraction of the pattern. Rapping a pattern tends to alter the form of the mold from that calculated upon. A circle becomes slightly oval, a square becomes an oblong, and so on : and this cannot in most cases be avoid ed, because it is necessary to rap the pattern so as to enable the molder to extract the pattern without drawing out the sand with it; all that can be done in this direction is to rap the pattern as little as possible, and equally in all directions.

When a flask nowel is used, the labor involved in making a parting of the mold is facilitated. Fig. 67 shows a board cope and nowel for an ordinary straight parting; but it is evident that the parts of the flask may be made to show a crooked, a curved, or irregular line at the joint, if it is required, in which case the bed board must be made of similar conformation. The process of molding with a flask independently of using the floor, instead of a flask nowel, is illustrated in Figs. 70 and 71. If it be required to mold the pattern illustrated in Fig. 69, which is made in halves, the joint being denoted by the line, A A, one of the halves is taken and laid with its flat face upon the molding board, B, shown in Fig. 70. The nowel, N, is then placed upon the board, so that the half of the pattern will be in about the middle of the flask nowel. Sand is then rammed tightly in the nowel; and when the latter is filled with the sand, it is turned upside down, showing the flat face of the half pattern, the rest of the half pattern being imbedded in the sand. The other half of the pattern is then placed upon the one in the sand, its proper position being determined and regulated by pegs fitting into holes, provided in the first part, to re-ceive them. The next operation is to put on the cope, as shown in Fig. 71, the taper pins being fast to the cope lugs shown on the sides, fitting into holes provided in the nowel lugs, similarly shown, serving to hold the cope in position and prevent it from moving. The cope is then filled with



sand, lightly rammed, the taper pin, R, Fig. 68, being insert It is true that, in some cases, a bar is passed through the ed to leave in the mold the hole, R, Fig. 71, through which cope and driven into the pattern, and by rapping it the to pour the melted metal. The cope is now lifted verticalloosening is accomplished; but it is not well to have recourse ly; and as the pattern is made in halves, the top half lifts to such an expedient, because, wherever the bar passes, the with the sand in the cope. In some cases a screw is fixed cope is damaged, and must be mended; and when a mold into the top half of the pattern, the head of the screw projecting into the cope: the object being to insure that the top half of the pattern shall lift with the cope. The next procedure is to extract the two halves of the patterns from the molds, and perform any trimming or repairing that the mold may require, after which the cope is again placed upon the nowel, and the mold is complete, ready to have the metal poured in.

Simian Sagacity.

The sagacious monkey, who, according to the time-honored story, used the reluctant paw of a cat to withdraw hot chesnuts from the fire, is outdone by the performance of another member of his tribe, which is recounted by a French resident of South Africa, in a letter to Les Mondes. The writer is the possessor of a large coffee plantation, and his crops have suffered severely from the ravages of a large species of baboon, which greedily devours the fruit of a small tree which grows among the bushes. The best safeguards against the depredations are the wasps which make their nests in the lower part of these trees, for, of the fierce atack and painful stings of these insects, the baboons have a wholesome fear. One morning, a hideous chorus of yells and howls was heard from a portion of the plantation where the wasps had most thickly congregated, and where the fruit trees consequently were heavily laden. On searching for the cause, the writer saw from afar a venerable and ancient baboon busily engaged in throwing infant monkeys at the trees. These living projectiles thus knocked down the nests and of course were objects of the keen attentions of the infuriate occupants. Meanwhile the baboon quietty made his way to the upper branches, gorged himself, and then added insult to injury to the badly stung monkeys by pelting them with the rinds and pits of his repast.

THERE is no royal road to learning; its acquisition without study is like the acquisition of wealth without labor. It is as necessary for the mechanic to study out his problem, when it comes to him to be studied, as it is for him to finish his

IMPROVED CLOTHES LINE FASTENER.

We have had washing machines innumerable, sadirons, ironing tables, etc., in endless variety, until we had almost reached the conclusion that there was nothing connected with the laundry but that some ingenious inventor had, of late years, improved upon its construction, and that the end of improvements in this line was near at hand. The present device shows us, however, that, in one respect at least, the laundress's work has not been perfected, namely, in the operation of hanging out the clothes to dry.

The invention illustrated herewith offers a way of doing

this easier than any previous plan that has come to our knowledge, and we recommend it to the favorable consideration of our housekeeping readers.

With the tenement houses of large cities, where building space is economized to the utmost, there is very little or no yard in which clothes can be dried. Consequently the roof is utilized, and where its accommodations fall short, as usually is the case, since professional washerwomen, as a rule, dwell in such localities, the expedient adopted is to reeve lines leading from the various windows to through pulleys on adjacent buildings, and to fasten the clothes on these. It is obvious, however, that only one part of the endless rope can be utilized; and that as soon as that is full, the nearest garment enters the further pulley, and so chokes it. Hence just half the double line is empty. The present invention supplies a means by which both parts of the rope can be utilized, by simply substituting, for the block which may constitute the distant pulley of the endless rope, a roller se constructed that the clothes, while attached to the line, can easily pass around it. The shape of this roller is shown at A, Fig. 2, where it is represented as attached to a post by simple devices which allow of its angle being adjusted so as to tauten the rope

tions afforded, and may, for this reason, prove a really valuable invention in the localities we have noted.

The lower engraving, Fig. 1, represents more clearly how the device is arranged both to economize room as well as to save labor. The line, instead of being attached rigidly to several posts, passes over the pulleys of the shape shown, on their summits. The arrangement of two pulleys on one post

lows that the laundress can stand still and fasten on one piece at a time, pull the rope along for a short distance, fasten on another, and so on until the line is full, when the first garment, after traveling around all the pulleys, will have returned to its starting point. This saves carrying a basket of heavy clothes, for the circuit of a yard during hot or very cold weather. To render the endless rope easily moved, its bight passes over a horizontal roller at B, which is turned by a belt from the drum, C. This part of the device may, if desired, start from the kitchen window or just inside the same, so that the operator need not go outdoors at all, but, standing in the house, may fill the line without risking injury to health caused by passing suddenly from a warm laundry to the cool outer air. There are various minor details for adjusting the pulleys and tautening the line, which are plainly shown in the engraving, and need no further description.

Patented through the Scientific American Agency, July 18, 1876. For further particulars address the inventor, Mr. George Almont, 604 Grand street, Jersey City, N. J., where the device may be seen in operation.

IMPROVED METAL-PUNCHING MACHINE,


The invention herewith illustrated, besides being of novel mechanical construction, includes a simple and efficient arrangement for putting in and removing interchangeable dies and punches of different sizes. It is sufficiently powerful, we are informed, to punch readily a five-eighth inch hole in plow steel, and it has been practically tested with excellent success during the year which has elapsed since it was

The operation is as follows: At A are the housings, near the top of which a cam lever, B, which forces down the punches, is pivoted. C is the die block, which slides freely in between the housings and is locked by a suitable spring pin. D are guide plates for the punch over the die. A head block, E, serves to connect the punches to the cam lever, the attachment being effected by lugs which engage the lever by its

into a channel above the slotted plate through which the shank hangs, the lower end being in the guide plates, D.

It will be observed that the mechanical power is very advantageously applied, that the punch and die, although easily removable, are tightly held, and that the general construction of the device is strong and durable. Two sizes of the machine are made, weighing respectively 175 and 275 lbs. They are excellently adapted for use in ironing wagons and blacksmiths' ordinary jobbing work.

Patented July 13, 1875, by Mr. Daniel W. Baer. For fur. water, and dry. When the oxide of copper thus obtained




ALMONT'S CLOTHES LINE FASTENER

This thus doubles the capacity of the drying accommoda- | ther particulars address Clayton Bush, Sextonville, Richland | fore, each time; gather the precipitate on to the filter, wash county, Wis.

To Analyze German Silver.

the alloy, and dissolve in a limited quantity of aqua regia | stand at a gentle temperature for several hours. By these (one part nitric and three parts of hydrochloric acid) at a temperature of about 70° Fah. When complete solution is is shown on the right. The line again forms an endless cord; effected, add sulphureted hydrogen water until, after stand-



BAER'S METAL-PUNCHING MACHINE.

grooves. The punch is secured in place by sliding the head filter, and wash the precipitate on the filter with distilled water containing a little sulphureted hydrogen several times, and dry. When dry, remove it as completely from the filter paper as possible, and boil until completely dis-solved in strong nitric acid. Then dilute the acid with water, filter from the yellow sulphur that has separated in the operation, add solution of pure soda or potassa (in water, until no further precipitate forms, boil the suspended precipitate with constant stirring until it is of a brownish. black color, then filter it, wash several times with distilled

> is perfectly dry, remove it completely from the filter paper, place it carefully in a previously weighed porcelain crucible, and beat to reduce gradually over a spirit or gas lamp. Then suspend it in the crucible over strong sulphuric acid in a tight glass vessel until cold, when it is ready for weighing. The weight thus obtained, multiplied by 0.79849, will give you the weight of the pure copper contained in the given weight of the alloy. The zinc and nickel, which were contained in the alloy, are to be found in the first filtrate from the first sulphureted hydrogen precipitate. To separate them from each other, add to the solution some pure ammonia until the solution is quite alkaline, and then sulphide of ammonium; heat gently for a short time, filter, wash the precipitate with water containing a little sulphide of ammonium ; dry, separate from filter, and heat for some time with aqua regia. When the solution is effected, dilute considerably with water, and add drop by drop a strong solution of pure carbonate of soda, with constant stirring, until evolution of gas ceases (be sure you add sufficient); then boil for a few minutes and allow to subside. When this has taken place, decant the supernatant liquor (through a filter, so as to avoid loss), and wash the precipitate several times with water, decanting, as be-

with hot water, and dry perfectly at a temperature of about 212° Fah. When dry, dissolve the precipitate (in an excess of pure acetic acid) by the aid of heat, and to the solution Take a weighed quantity of the clippings or trimmings of add some strong sulphureted hydrogen water, and allow to means the zinc will all be precipitated, and the nickel will remain behind in the solution. To separate the nickel, evaporate the filtrate, from the last zinc precipitation, nearly to and as the clothes easily pass around all the pulleys, it folding for half an hour, the liquid smells distinctly of it; then dryness in a porcelain vessel, add some nitro-hydrochloric

acid (aqua regia), and heat gently until a clear solution is obtained; then mix the solution with pure potassa or soda in excess; heat for some time nearly to boiling, decant three or four times, boiling up at each time; wash the precipitate thoroughly with hot water, and dry perfectly. Then place the precipitate in a porce lain crucible, heat to redness, place the crucible with its contents in a desiceator to cool, and finally weigh. The weight obtained, minus the weight of the crucible, multiplied by 0.78667. equals the amount of nickel contained in the given weight of the alloy. The weight of the copper, plus the weight of the nickel deducted from the given weight of the alloy, equals the amount of zinc it contains.

Mocking Birds at the Centennial.

Two hundred and fifty mocking birds from Texas lately arrived at Agricultural Hall, Phladelphia. These birds were raised by Miss Antoinette Christi, of Denison, Texas, and made the journey in about two weeks. After a ride of five hundred miles to Galveston, they were transferred to a steamer and brought two thousand miles by water, without accident, until the ship encountered a gale off New York, when, s the cages were on deck, over fifty of the birds died from the effects of the sudden change of temperature caused by the storm. All the rest, however, reached here in safety, and evidently in perfect health. Though most of them are young and can be taught any tune desired, there are among the number many trained birds which whistle all the popular airs of the day.

Rubber Shoe Making.

Among the interesting processes shown in the Centennial is the making of india rubber shoes. The operation consists in stretching the flat patterns upon lasts, joining them together at the heels, and pasting on the soles. The shoes are left on the lasts until they take shape. Machinery for purifying the rubber, by passing it between toothed rollers under water, and for rolling it into sheets, is shown in operation

THE RADIATA

The zoological class termed the radiata was comparatively unknown until within the past century, and its species were considered to be connecting links between the animal and vegetable kingdoms, being known as zoophytes; and Linnæus defines them as "composite animals which appear to rank between animals and vegetables; though they are true animals, and possess sensation and voluntary motion.'

The radiata are entirely aquatic, and are mostly marine. They are divided into three classes. These are: 1. Polyps -sea anemones, nearly all the corals, etc. 2. Acalephsjelly fishes, medusæ, Portuguese men-of-war, etc. 3. Echinoderms-sea cucumbers, star fishes, crinoids, etc.

that a single illustration will answer for all, although they differ greatly in size, shape, and minute particulars. Let us suppose an orange with a small portion of the stem end removed, and a hole descending to a little past the center from this end. Now the skinny partitions which, like longitudinal planes, extend through the fruit will divide it into chambers. We must suppose a similar wall surrounding the cavity which runs down from the end of the fruit, but communicating freely with all the inner portions of the orange, through the lower end of this opening. Polyps have but this one orifice, which is the mouth. Into this all the food is taken, and from this all rejected matter is thrown out. The digested food passes from an opening in the lower portion of this cavity or sack into all the chambers of the polyp, and finally into the delicate, hollow tentacles with which the upper part of the body is fringed. This is the general form of life of all the polyps, some of which, like the corals, are stationary, while others are nomadic, and still

radiata. The polyps vary quite materially in shape, some being almost saucer-like, others pyramidal, cone-shaped,

In the lower polyps the eggs are formed on all the inner edges of the vertical partitions, and when these are ready for exclusion they drop to the bottom of the digestive sack, whence they pass outward through the mouth. In the higher order of polyps not all of these partitions are fruitful, the limitation increasing as the species rise in organic superiority. Some of the polyps also increase by buds similar to fruit buds, others by subdivision. Polyps may be cut into several pieces, and the majority of these will each become a perfect animal. They vary in size from a foot in diameter to mere microscopic mites.

fellowship of bees, ants, etc., as hardworking creatures, pens that the jelly fishes which are possessed of these sting- passing craft.—Home and School.

with some knowledge or method of architecture. They produce coral no more ingeniously or laboriously than a fish produces bones, and cannot help it if they would. Coral is only what is left after the death of a whole community-a village of individuals whose bones, not their houses, are fashioned by cunning artisans into such beautiful adornments for our fashionable belles.

The acalephs are perhaps more interesting to the student and naturalist than the polyps. In these we find exemplifications of the curious law of alternate generations. The egg of a butterfly produces a caterpillar, which in turn becomes a chrysalis, and from this the perfect fly is in due time hatched. In some of the jelly fishes different but no less wonderful changes take place, while in others the method of reproduction is similar to that of the budding polyps. In some cases two generations intervene between the parent and a progeny resembles it in form or mode

comparison with other radiates, some of the polyps living many years, while star fishes and sea urchins are sometimes ten or a dozen years in attaining their maturity. The acaleph's cycle of existence is only about twelve months. The eggs, laid in the fall, become hydroids in the winter, jelly fish in the spring, and, having made the necessary arrangements for a continuance of the species, die during the autumn. Great numbers of jelly fishes are annually killed by the severe storms of that season, and are washed upon the beach, where they almost literally melt into jelly, and leave no trace behind, there being none but the most perishable elements in their physical construction, nearly the entire animal being water. Mention is made of one specimen, which when alive weighed thirty-four pounds, being left to dry for some days, and then weighed five and one half ounces. The radiate partitions of the polyps are changed into tubes

in the jelly fishes, but the general law of radiation is strictly followed. Excepting a few species they are all jelly-like in their construction; the discophora have a trifle more solid structure, but all are exceedingly soft and frail.


Very many of the more delicate species are so transparent that the casual observer often fails to see every portion of a specimen, even in the still water of the aquarium, until a movement of the animal presents its parts in a different

A great variety exists in the shape of these animals, and they vary no less in size, some being so small as to be entirely overlooked by the casual observer, while Agassiz mentions one, a cyanea arctica, a sea blubber, whose umbrella-The structural plan of all the polyps is so nearly similar shaped disk measured seven feet across, while the tentacles to a distance of thirty feet from the main body of the ani-



THE DISK-BEARING JELLY FISH

others are parasites, living in the mouth folds of still larger | which streamed behind him measured roughly about one | there is a marked resemblance to a beautiful white flower. hundred and twelve feet. The parent of this monster is one of many from a single egg, transformed first into a stalk not unlike a cabbage stump in shape, but which subsequently changes into a tolerable representation of a pile of saucers, open side up. Each saucer, when cast off, turns over and is then a perfect cyanea. Yet the stalk which produces all these, when fully grown, is but an inch or so in hight. Were it not for their delicate structure these creatures would be as dangerous as sharks, for each of these long tentacles is capable of producing a severe smarting sensation by mere contact, while their nearly perfect transparency renders their noiseless approach almost imperceptible. Bathers along the coast of the Atlantic often encounter these unawares, and lose no time in extricating themselves from the dilem-From what has been said of the growth of these polyps it ma, while large, red swellings, not unlike those produced by will be seen that coral insects have too long enjoyed the nettles, attest the truth of the contact. It sometimes hap-



THE PORTUGUESE MAN-OF-WAR AND THE SEA BLUBBER.

The jelly fishes, with few exceptions, are short-lived in ing threads-for many of the species are without themfind themselves entangled with a too formidable antagonist. In such an event they drop or shed the tentacles, and escape with all possible haste; but notwithstanding their separation from the body of the jelly fish, contact with the dead tentacles is equally painful as when living.

The stinging property is used by the jelly fish not only for defence but also for the purpose of paralyzing and retaining jelly fish, or polyps. Captured individuals often show the remnants of a meal, their transparency affording the most perfect study of their internal organisms. These tentacles are covered by minute cells, lasso cells as they are called, each one of which contains a whip finer than the finest thread, coiled in a spiral within it. These are thrown out at the will of the animal, and their movements are so instantaneous that their irritating power is very great.

The Portuguese man of war is also an acaleph, belonging to a prominent genus. This individual, physalia arethusa, is one of the most remarkable of the group. The pearshaped sack, ornamented with a sort of shirt ruffle fringe or crest, and filled with air, gracefully floats upon the surface of a calm sea, while beneath it trail numerous appendages of various functions. These may be compared to the members of a military or communist organization. Each pendant has its own peculiar duty. Some are the providers, commissaries; others are the locomotive organs, while still others are charged with the duty of growing new medusæ buds for the perpetuation of the race. Those tentacles which belong to the transportation department often extend

mal, which is usually but five or six inches in length. This hydroid is properly an inhabitant of the tropical seas, but occasionally, having drifted into the Gulf Stream, it is borne along the shores of the Atlantic far away from its native home.

The hydroids are not all free to move about at will. Agassiz and Vogt have thrown the two together, this simple difference not warranting distinctive groups in which earlier naturalists had placed them. Many of the hydroids bear a close resemblance to some species of vegetation growing on the bottom, where at low tide they are taken by the casual observer for marine plants. Some of these are exceedingly minute; and the little bell; or buds, in which the diminutive embryo creatures are imprisoned, are, to all casual observers, flower buds or seed vessels. This is also true of the polyps, which, in structure and colors, resemble nearly every form of vegetable life.

The colors of the jelly fishes are as varied as are their forms and dimensions. In the bolina, for instance,

The cyanca is a dark, brownish red with a milk-white margin, and tentacles of purple, yellow, and pink. Idyia is mostly of a bright pink, while red, yellow, orange, green, and purple chase each other rapidly along its undulating fringes. Other varieties appear in no less beautiful and different shades of beauty; while at night, if the sky be overcast or the moon is not a disturbing witness, the slightest movement, of the depths where these delicate beauties are, brings out the most resplendent flashes of green and gold and liquid phosphorescent flames that seem almost to kindle the entire waters. Myriads of the lesser varieties, scarcely noticeable in the bright light of day, thus disturbed, become globes of brilliant gold, and the oars of the boat, as they rise from the water, drip with liquid flame given out by these and other minute inhabitants of the deep, while the glistening particles extend far in the diverging wake of the

Cheese Factories in England.

British farmers are notoriously slow to accept innovations, and this may be said without fear of hurting their feelings, as they are well aware of it, and in fact rather pride themselves on their conservatism. But they are now moving in a direction which possesses some interest to Canadian farmers. The United States and Canada may be said to have absolute possession of the British cheese market except for certain fine brands with which we do not compete. Our factory system has already made its way into Britain, and is as success ful there as it is here. And now they are going to adopt another of our institutions, the Dairymen's Association. Certain leading spirits think it a shame that English cheese makers can be beaten in their own mar kets, and they are going to leave no stone unturned in the attempt to regain possession. Dear land and high

as distance will against us. The fu-, ture will show whether the new British Dairymen's Association, which was formally instituted at Birmingham recently, will enable the farmers over the water to drive us out of their markets. We opine, says the Canadian Farmer, that it will not. Nevertheless, it is never well to have only one string to one's bow. The move of our English brethren should teach us to be on the alert for new markets. And if it should also direct our energies more to the manufacture its prey, which consists of small crustacea, fish, and other of butter by the factory system, it will benefit us as much as it will them.

> AMERICAN CREMATION .- A citizen of Washington, Penn., has built a large stone house on a hill for the reception of dead bodies, and a furnace scientifically constructed, in which they are to be burned. He has given strict injunctions to his executors that his own body be burned in the

CHEMICALS AT THE CENTENNIAL.

It is generally admitted that the German section at the Centennial Exposition is far inferior to what it ought to be, and does not adequately represent the present state of manufacture and industry in that empire. Be this true or not, it certainly does not apply to the chemicals, for in this department Germany is facile princeps. She supasses France, is far beyond England, and finds a worthy competitor only on this side of the ocean. In quantity, Philadelphia chemists far excel; but in rare chemicals, new compounds, and interesting preparations, Germany leads. Entering by the cross nave, we have on our right the magnificent display of Powers & Weightman, Rosengarten, and Pease; on our left the smaller black show cases of the German exhibitors, Brohme, Trommsdroff, and others.

THE GERMAN EXHIBIT.

This department has an advantage over all others in having a complete and instructive catalogue, which enables the visitor to examine with greater ease and understand more readily what is to be seen here. An intelligent attendant is also ready at all times to explain more fully whatever is of interest The chemicals in this department may, for our convenience, be arranged under three heads, namely, chemicals largely employed in the arts, rare and curious chemicals chiefly of theoretical interest at present, and coal tar products, including the aniline colors. This division is, of course, very imperfect, because new substances are so rapidly passing from the second to the first class, while the third class belongs to both the others.

The most interesting of the commercial exhibits, because the newest, are the samples of carbonate and bicarbonate of soda made by Moritz Honigmann at Aix la Chapelle, by the ammonia soda process of Solvay (see SCIENTIFIC AMER-ICAN, June 24, 1876). This establishment employs 35 men and 3 steam engines of 25 horse power in the aggregate, producing 6,600 lbs. of soda ash per diem. The operations are performed in large wrought iron vessels at a pressure of to 4 atmosphere. Chloride of sodium obtained from the saltpeter works (Scientific American, January 22, 1876) is decomposed, at a temperature of 95° Fah., by carbonic acid and ammonia, into bicarbonate of soda and chloride of ammonium. The ammonia is recovered from the latter by means of unslaked lime, at a temperature of 212° Fah.; the lime is obtained by burning mountain limestone with coke, and the carbonic acid utilized for converting the salt into a bicarbonate of soda in the presence of ammonia, as above stated. No use has yet been found for the waste chloride of calcium. The calcined soda ash contains 98 to 99 per cent of the carbonate; and, being free from iron, sulphur, and sulphuric acid, is largely employed in dye works and glass houses. This process will attract our notice again in the chemical sections of France and Belgium.

Vorster and Grueneberg, of Kalk, exhibit potash and saltpeter made from the Stassfurt salts.

There are several exhibitors of glue, gelatin, and phosphates from animal refuse.

Xanthate and sulpho-carbonate of potassium, the new in-sect destroyer, is exhibited by J. F. Hayl & Co., the well known manufacturers of oisulphide of carbon. This establishment, which covers over 7 acres and employs 12 men, is chiefly occupied in the extraction of fatty oils by means of bisulphide of carbon. They exhibit oil cake and oils. They claim for the oil cake that it contains 6 to 15 per cent less oil than those which have been pressed, but are better as fodder because the nitrogenous principles remain in the residues.

Paraffin and paraffin candles made from peat are exhibited by two stock companies, one at Rehmsdroff, the other at Halle.

The Nuremberg Ultramarine Works have a pyramid over ten feet high, around and on which their products are arranged. Green, blue, and violet ultramarines are exhibited. Several smaller exhibits of ultramarine, both blue and green, were also noticed.

The exhibition of mineral colors, although varied and pleasing to look at, requires but little to be said about them Zinc and cadmium yellows, umbers, ochers, siennas, lampblacks, etc., filled the list.

Brohme & Co., Bergen, exhibit soda and potash water glass in solid and liquid form, composition for artificial stone, water glass whetstones, etc.

Oxalic acid and oxalate of potash are exhibited by R the rarer substances, tungstate of soda, naphthaline yellow, | L) There are several exhibitors of these goods, the large and phthalic acid.

The largest exhibit of alkaloids is by Fried. Jobst, Stuttgart, and includes also opium grown in Würtemberg and Silesia. Here we notice a dozen different salts of quinine, including the anetholate, and several salts of other cinchona alkaloids. The new preparations made since the Vien na Exposition of 1873, and never before exhibited, are the muriate, sulphate, and salicylate of phenyl-quinine, sulphate of phenyl-cinchonidine, oxalates of cinchonicine and of quinicine, santoninic acid, cotoine, echicerine, chinamine, echitine, and echi eine.

The exhibit of alcoholic preparations, by C. A. F. Kahlbaum, Berlin, is deserving of special notice, showing as it rare and curious chemicals to commercial articles. These works, which are under the direction of Drs. G. Krämer and Bannow, were the first to manufacture artificial mustard oil (from allyle alcohol) on a large scale, and now it is capable, by excellence and cheapness, of competing with the na-

ic acid, and acetates The most interesting portion of this exhibit is, however, a series of scientific preparations, made organized and executed this difficult work. in the laboratory connected with these works, and in many cases from waste products. A list of these curious and new compounds would exceed our present limits, and we may only mention a few, such as metaldehyd, a white solid crystaline substance having the same percentage composition as common aldehyde, and convertible into it by heat at 112° to 115° in a closed tube. Paraldehyd, a liquid isomer of aldehyd, which boils at 124° and crystalizes below 10°, is also exhibited. Resorcin, phenylacetic acid, phloron, main entrance on Elm Avenue, and passing up the center phthalic acid, azobenzol, methyl and ethyl iodides, zinc methyl and ethyl, sulpho butylates, methylates, propylates, and vinates are among the things seldom, if ever, seen before in America.

In the case adjoining Kahlbaum's exhibit is the far smaller but equally interesting one of Dr. Wilhelm Haarmann, Holzminden on the Weser. Here is exhibited the new artificial vanillin, discovered by Drs. Haarmann and Tiemann; also a glass of coniferine, a glucoside contained in the cambium of coniferous woods, and from this the vanillin is made. The latter is identical in composition, melting point, flavor, and all other properties with vanillic acid from the vanilla bean. Vanillinic acid (a by-product), vanillinic sugar, vanillinic alcohol, and vanillinic glycerin are also exhibited. These works were established in 1875, and employ in the summer months about 46 workmen.

Next to this is the exhibit of the Berlin Stock Company, formerly E. Schering. The exhibit is large and handsome including salycilic acid in large quantities, salicylates of ammonium, quinine, sodium, and zinc, also chloral hydrate, both in cake and crystals. Just around the corner is the curious little exhibit of Dr. F. Wilhelm, Reudnitz-Leipsic. He exhibits the artificial bitter almond oil (not, he says, nitrobenzol), of which he claims to be the inventor and only manufacturer. He also exhibits benzoic acid, Niobe essence (?), benzyl chloride, and some manganese salts.

The well known house of H. Trommsdorff, Erfürt, makes a very large and interesting show. It includes 50 different alkaloids, glucocides, and bitter principles, 30 organic acids, various physiological preparations, such as glycocoll, allantoine, cholestrine, taurine, etc. Among the rare metals and metallic salts, we noticed selenous, tellurous, and vanadic acids, sulphate of beryllium, casium, and rubidium alums, sulphates of cerium, lanthanum, and didymium, bichromate of rubidium, bivanadate of ammonium, and metallic tellurium, thallium, titanium, tungsten, molybdenum, etc.

Another fine display, in close competition with Tromms dorff and Kahlbaum, is that of Dr. Theodor Schuchart, Görlitz. There are 110 preparations of purely scientific interest, and 20 for technical purposes. Among the former are included nearly all the rare metals and their salts. One of the most beautiful things here is the double cyanide of yttrium and platinum, which consists of dichroitic (red and green) crystals. We also noticed some handsome crystals of boron, also specimens of nitrate of roseo-cobalt, chloride of purpureo-cobalt, sulphate of xantho-cobalt, crystals of nitrate of uranium, metallic chromium, nickel salts, sesquichloride of titanium, chloride of niobium (columbium), and blue oxide of tungsten. A few organic preparations, thymol, anthracene, alizarin, etc., completed the list.

Salicylic acid and its derivatives are exhibited in large quantities by Dr. F. von Heyden, Dresden, who manufactures, under Professor Kolbe's patent, from the best English carbolic acid. The collection contains wintergreen oil, pure and crude salicylic acid, crude and pure salicylicate of sods, and sodium phenylate.

Dr. L. C. Marquart, Bonn, has a very good display, including salicylic acid, cæsium, and rubidium alums, ethyl sulphate of lithium, ethyl benzol, bibrom-benzol, and dichlorhydrine, the curious chlorine derivative of glycerin.

Chloral hydrate is the specialty of Saame & Co., Ludwigshafen. The works cover 17 acres, and originally were devoted to the production of chloral hydrate only; but since he fall in price of that article, they have begun the manufacture of the mineral acids, of which they produce 13,200,060 bs, annually. They also manufacture and exhibit chloroform, made from chloral and absolutely free from other chlorine compounds, chloral alcoholate, chloride of sulphur, bisulphite of soda, used in making the new reducing agent hydrosulphurous acid, chlorate of potash, etc.

The third class of chemicals, coal tar products, form the most beautiful and interesting part of the chemical section. Koepp & Co. and Kunkeim & Co. The latter also exhibit (See Scientific American Supplement, page 496, volume and best being those of Fried, Bayer & Co., at Barmen and Elberfeld, and the Action Gesellschaft für Anilin-Fabrika tion at Berlin. The former is especially interesting, as showing all the steps of the process, and all the intermediate products from the coal to the finished dye, all numbered and labeled, the formulas being given, too, in most cases. Among the rarer substances, we noticed the new and beautiful cosine and silks dyed with it, also fluorescin. resorcin, phthalic acid, benzyl chloride, cumol, xylol, rosolic acid, iodide of ethyl and methyl, coralline, and a full series that this metal is quite as reliable as iron, all cases of disof anthracene derivatives, bibrom-anthracene, anthraquinone, sulphanthroquinonic acid and its barium and sodium and sodium salts, alizarates of sodium, potassium, barium, does how soon chemical compounds pass from the class of and aluminum, alizarine itself, and samples of dyeing. The Action-Gesellschaft present even a better show of the aniline dyes and dyed specimens, many of the dyes being in much larger quantity, and the whole well mounted and catalogued. The Frankfurt Anilin Color Works exhibit 25 specimens, including cosine, phosphine, indigotine, phenyl-

and amyl alcohols, iodoform, acetone, aldehyde, ether, acet- Taken as a whole, the exhibit of German chemicals does credit to the manufacturers and to the committee who

[For the Scientific American.]

BOILER NOTES.

We have just received the last annual report of the Hartford Steam Boiler and Insurance Company, and, in ac. cordance with our usual custom, proceed to present a synopsis of it to our readers.

The present report is one of unusual interest, as the President, in honor of the completion of the first decade of the company's existence, gives a review of the work done since the organization. The task undertaken by the company, as most of our readers doubtless know, is to institute such a system of inspection of the boilers under their charge as to render them reasonably secure against explosion, agreeing to pay the owners the amounts of insurance stated in the policies, in case explosions do occur. The company's record for two years shows a list of 848 boiler explosions in the United States, by which 1,768 persons were killed, and 1,904 injured. Of these boilers that exploded, 18 were insured by the company, and a careful examination of the causes shows them to have generally been such as no inspection could have prevented. Thus, in one instance, a boiler being under repairs, the workman drove a plug into the steam pipe, and neglected to remove it when the work was completed. As might naturally be expected, in getting up steam in the boiler, it exploded. Several other cases of explosion occurred with long boilers, supported only at three points of their length, and fired by the waste gases from iron furnaces. The President states that it cost the company \$10,000 to learn that such boilers should have supports not more than 10 feet apart-though, if we mistake not, considerable attention has been paid to this subject in England in former years, resulting in the adoption of a method of supporting long boilers which seems to give good results. During the period covered by this last report, from August 31, 1874, to December 31, 1875, the company have made 44,-763 inspections, discovering 24,040 defects, of which 5,149 were classed as dangerous, requiring immediate attention. Some of these defects may be briefly recounted and discussed. Their nature is clearly illustrated in the report, by a series of well executed engravings.

Furnaces become distorted, and plates are fractured, chiefly by bad management, such as suddenly introducing cold water into an overheated boiler. These distortions and fractures are frequently hastened by the method of construction, the plates being overstrained by using drift pins to bring the rivet holes in line. A sheet may be nearly fractured by this mal-construction, and yet appear to be uninjured, when viewed from the outside.

Plates become burned from forcing the fire too fiercely, or on account of the deposition of scale or sediment. Com paratively few manufacturers seem to realize the danger of using a boiler that is too small for the work, and forcing it to the utmost extent. When a blister forms on a plate, it is generally due to the uneven character of the iron, and the whole plate should be renewed, the application of a patch being only a temporary expedient. Sheets may be corroded on the outside by leaks at the seams, in places which are not readily accessible for examination. Such defects can only be discovered by careful inspection. The use of impure water frequently causes the rapid destruction of a boiler by internal corrosion; and unless this is discovered by internal inspection, a so-called mysterious explosion may be the result.

Careless engineers allow water gages to become clogged, blow valves to leak, and safety valves to stick fast. following simple rules should be observed by every one in charge of a boiler.

Blow through the water gage at least once a day, and several times, if the water is dirty

Before starting the fire in the morning, always try the water in the boiler, and do not raise steam until assured that it is at the proper level.

Raise the safety valve, at least once a day, and observe whether it works freely. Attach a stop to the lever, so that the ball cannot possibly be moved out beyond the proper position; and never hang any additional weight on the

Among the steam gages examined by the company, 649 were found to be dangerously defective, having errors ranging from -45 to +70 with inoperative safely valves. What splendid chances for "mysterious explosions" were

A number of boilers were found without gages, and 19 of these were considered dangerous, because a high pressure

Several boilers were examined, in which there were no hand holes for removing the sediment, and in many boilers the bracing was very insufficient. When such boilers ex plode, there ought to be little difficulty in finding the cause The experience of the company, with boilers in which some of the sheets were made of Bessemer steel, seems to show tortion or fraction of steel plates being traced to overheating or sediment

During the time covered by the last report, 139 boiler explosions were reported in the United States, by which 191 persons were killed, and 267 injured. An investigation of a number of these by the company has served to clear up all mystery in reference to their causes.

In the above brief synopsis of this interesting report, we have endeavored to give prominence to such matters as will tural oil. The other staple productions are methyl, ethyl, yellow, indigo carmine, aniline blue, green, and violet, be of especial interest to those in charge of steam machin-

ery. We think the operations of this company show clearly that safety from boiler explosions can be obtained by careful inspection at frequent intervals, and careful management at all times, neither plan by itself constituting a sure preventive. Not the least among the results of the company's work is the clear demonstration of the fact that the hydraulic test alone will not reveal all the defects of a boiler; and, as we have frequently pointed out, when it is chemists, and dye and color manufactories, to one hundred made with cold water it sometimes produces defects which and twenty-four. In hair dressers the mortality is more did not formerly exist.

OCCUPATION AND THE DEATH RATE IN ENGLAND.

A comparative study of the death rate in seventy-three of the principal employments in England and Wales has lately been made in the British Registrar-General's office, based on the mortality returns of three years. The results show, among other matters of interest, the mortality among all the males aged fifteen years and upwards, in each of the specified employments, and also the relative mortality in the English clergy. each, the mean death rate of the whole being taken as one

For example, in the three years under examination, the deaths among grocers amounted to three thousand one hundred and sixty. Had their death rate been equal to the mean death rate for all the employments during those years, as many as four thousand one hundred and seventy-three gro cers would have died. The relative death rate of that class, therefore, in comparison with the whole, was only seventy

But the grocers were surpassed in healthfulness by the members of two learned professions, the lawyers and the clergymen. The barristers head the list, with a death rate of only sixty-three; the clergy of the Established Church follow, with a death rate of seventy-one, while the independent Protestant denominations stand at seventy-five.

It is scarcely probable that the immunity of the barristers is a together due to the lightness or wholesomeness of their work. That counts for much, but we must not forget to allow for the fact that in England a large number of independent gentlemen adopt that calling, not to make a living out of it by hard work, indeed not to work at all in it; but simply for the nominal professional rank it gives. If the working barristers only were counted, it is doubtful whether the class would stand so high in the sanitary list. Perhaps the refuge which the Established Church affords for many men of culture and leisurely regular life may similarly help to account for its lower death rate as compared with that of other Protestant clergy.

Next after the barristers and the Protestant clergy come the grocers, already mentioned, followed by men of the combined occupation of grocer and shopkeeper, with a death rate of seventy-seven. After these we find gamekeepers, with a death rate of eighty; farmers, one of eighty-five; civil engineers, eighty-six; booksellers and publishers, eighty-seven; wheelwrights, eighty-eight; silk manufacturers, eightynine; carpenters and joiners, and common laborers, stand together in the list, at ninety-one; bankers at ninety-two; domestic servants, ninety-three; sawyers at ninety-five; musical instrument makers, paper manufacturers, and brass workers, at ninety-six; blacksmiths and gunsmiths at ninety-seven; tanners and curriers, shoemakers, and workers in iron and steel, ninety-eight; and bakers at ninety-nine, completing the group of occupations in which the death rate is below the mean.

Machinists and woolen workers die at the mean rate for all, one hundred. Then follow half a hundred employments, more and more destructive to life. Manufacturers in iron, copper, tin, and lead, with bakers and confectioners-probably what would be classed as fancy bakers here-exceed the mean mortality by one. The schoolmaster's calling, and the solicitor's, rank next in unhealthiness, their death rate being one hundred and two. Millers and Roman Catholic priests stand next, with a death rate three above the mean, and thirty-two above that of the clergy of the church of England: a notable circumstance, to say the least.

Why should the mortality among the Roman Catholic priesthood exceed so largely-nearly fifty per cent-that of the English clergy? Are celibacy and asceticism the unsanitary conditions? Or shall we attribute their higher death rate to a more arduous and exposed life among the sick and squalid poor?

After the priests come watchmakers, one hundred and four; tobacconists, one hundred and five; physicians and shipbuilders, one hundred and six; messengers and porters, coach makers and rope makers, one hundred and seven drapers, one hundred and eight; tailors, one hundred and riosity which he had noticed to be especially developed and nine; and workers in cotton, flax and silk, the si Chemists, druggists, and commercial travelers exceed the country. mean death rate by ten; clerks, insurance men, and butch ers, by eleven; carvers and gilders, by twelve; farriers, by thirteen; miners, printers, and manufacturers of cotton and flax, by fifteen. It will be noticed that weavers and workers in silk are much the most healthy of all who have to do with textile fabrics, their death rate being eleven below the mean. Those that handle wool exhibit an average vitality, compared with all grades of working men. With the addition of cotton and flax to the fiber used the death rate rises to one hundred and nine; while those who handle flax and cotton without silk or wool die at the rate of one hundred and fifteen. Which is the more destructive to life in its working, cotton or flax, the statistics do not show.

Bookbinding is a degree more unhealthy than printing, the death rate of this class of workers being one hundred and sixteen. In glass manufacturers and fishmongers it rises to one hundred and nineteen; and in printers and

callings show a death rate of one hundred and twenty one; of your most distinguished men of letters, equally loved and namely, railway employees, dock laborers, tool makers, file admired in England and America, expressed an opinion makers, and saw makers. For the diverse causes of high which touched English feeling somewhat keenly-that there mortality in their occupations, it is not needful to enquire. In hatters, coppersmiths, and needle makers, the rate rises to one hundred and twenty-three; and in manufacturing than double what it is in the legal profession, that is, one main difference as to the men being in the way of shaving. hundred and twenty-seven. Bargemen die at the rate of one hundred and twenty-nine, or twenty-nine above the did, yet, in respect to stature for fine portly women, I think standard death rate. The employments of carmen, dray men, horse-keepers, and grooms are still more fatal, the group, embracing potters, innkeepers, licensed victuallers, cabmen and coachmen (not domestic), the death rate rises to its highest, one hundred and forty-three, or twice that of plates and spoons. Another feature has impressed itself up-

These figures show with practical accuracy the comparative mortality of the men engaged in these various employments. To considerable extent also, they represent the comparative healthfulness of the several callings; but the reader affect the death rate in each. An easy and healthful calling may show a high death rate, simply because it is easy and comparatively favorable to life, and consequently attracts to itself the feeble and disabled. For example, the statistics of the Medical Department of the Provost Marshal General's Bureau, during our late war, shows that proportionally more watchmen were rejected for physical unfitness than men of any other employment. Yet the watchman's work is easy and not specially unhealthful: so easy, in fact, that the worn-out and crippled and diseased natural-

be expected. Their working hours are long and irregular; and they are exposed to all weathers under unfavorable conditions. It is not so apparent why the unexposed innkeepers and victuallers should die almost as rapidly. The clever author of "Diseases of Modern Life" charges their high death rate to drink. No doubt excessive indulgence does cut short the lives of very many. But we are inclined to think that the selective action of the business has much to answer for. A large proportion of the English innkeepers are men whose working days are past: men who have earned a little money as butlers, stable keepers, small traders, and the like, and find the inn, or "saloon," as we

Again, the mortality of hair dressers is relatively high, thirty per cent higher than that of blacksmiths. It can hardly be that their business is in itself so much more killing, notwithstanding the hot and ill ventilated rooms they usually occupy. It is another case, we think, of natural say, affectionate reception." selection. Out of a hundred boys fated to be blacksmiths and barbers, there is little doubt that the majority of the sturdy ones will gravitate to the blacksmith shop, the majority of the undersized and feeble ones to the barber's.

In another article we propose to examine the relative healthfulness of the different employments of men in thiscountry. The results are in many respects curiously unlike those derived from the English statistics.

-The Meeting of the American Association for the Advancement of Science.

The annual meeting of this association convened at Buffalo, N, Y., on August 23. There is a remarkably large attendance, not only of American scientists, but of scientific men from Europe, who are on a visit over here to the Centennial. The proceedings were formally opened in the Common Council Chamber of the City Hall by a speech by the retiring president, Professor G. S. Hilgard. This was followed by a brief address by the new president, Professor William B. Rogers, after which a formal welcome was extended to the Association by the Mayor of Buffalo and influential citizens. These proceedings, together with the work of electing a standing committee and the reading of a few papers, which will be referred to in the abstracts which we shall publish next week, occupied the attention of the scientists for the first day. On the ensuing morning Professor Huxley arrived, and after receiving an enthusiastic welcome, addressed the assembly substantially as follows. gracefully returning thanks for the reception accorded him, he stated that he had no scientific matter to communicate. and in that respect was unprepared, but that, to satisfy a cu-

PROFESSOR HUXLEY'S ADDRESS.

"Since my arrival," he continued, "I have learned a great many things, more, I think, than ever before in an equal space of time in my life. In England, we have always taken a lively interest in America; but I think no English man who has not had the good fortune to visit America has any real conception of the activity of the population, the enormous distances which separate the great centers; and least of all do Englishmen understand how identical is the great basis of character on both sides of the Atlantic. An Englishman with whom I have been talking since my arrival says: "I cannot find that I am abroad." The great features of your country are all such as I am familiar with in parts of England and Scotland. Your beautiful Hudson reminds me of a Scotch lake. The marks of glaciation in your hills remind me of those in Scottish highlands.

"I had heard of the degeneration of your stock from the the other way, they will be adjusted inward.

plumbers to one hundred and twenty. Quite a number of English type. I have not perceived it. Some years ago one was a difference between your women and ours after reaching a certain age. He said our English women were "beefy." That is his word, not mine. Well, I have studied the aspect of the people that I have met here in steamboats and railway carriages, and I meet with just the same faces, the Though I should be sorry to use the word which Hawthorne the average here fully as great as on the other side. Some people talk of the injurious influence of climate. I have death rate being one hundred and thirty-one. In the next seen no trace of the "North American type." You have among you the virtue which is most notable among savages, the mortality is thirty eight above the standard; while in that of hospitality. You take us to a bountiful dinner and are not quite satisfied unless we take away with us the on me. I have visited some of your great universities and meet men as well known in the old world as in the new, I find certain differences here. The English universities are the product of Government, yours of private, munificence. That among us is almost unknown. The general notion of will readily see that many outside conditions conspire to an Englishman when he gets rich is to found an estate and lenefit his family. The general notion of an American when fortunate is to do something for the good of the people and from which benefits shall continue to flow. The latter is the nobler ambition.

"It is popularly said abroad that you have no antiquities in America. If you talk about the trumpery of three or four thousand years of history, it is true. But, in the large sense, as referring to times before man made his momentary appearance, America is the place to study the antiquities of the globe. The reality of the enormous amount of material here has far surpassed my anticipation. I have That cabmen should show excessive mortality is rather to studied the collection gathered by Professor Marsh, at New Haven. There is none like it in Europe, not only in extent of time covered, but by reason of its bearing on the problem of evolution; whereas before this collection was made, evolution was a matter of speculative reasoning, it is now a matter of fact and history, as much as the monuments of Egypt. In that collection are the facts of succession of forms and the history of their evolution. All that remains to be asked is how, and that is a subordinate question. With such matters as this before my mind, you will excuse me if I cannot find thoughts appropriate to this occasion. I would that I might have offered something more worthy; but I lope that your association may do what the British Association is would call it, a sort of hospital for the physical incapacity. doing-may sow the seeds of scientific inquiry in your cities and villages, whence shall arise a process of natural selection by which those minds best fitted for the task may be led to help on the work in which we are interested. Again I thank you for your excessive courtesy and, I may almost

The Traveler Ropes of the Brooklyn Bridge.

The joining of the two ends of the first traveler rope, whereby the material for constructing the East River Bridge is to be transported over the river, was recently accomplished. The endless chain is now complete, passing over grooved pulleys on the towers. It is operated by the engine formerly used to elevate stone during the process of erection of the piers. At the time we write, the first section of the second traveling rope is about to be carried over the river. This is made fast to the rope now in position and run over by it. It is lashed to the first rope at regular distances of 50 or 60 feet, as it leaves the Brooklyn anchor pier; and when it is across, these fastenings will have to be cut. This is done by a man sent over in a 'buggy," which is a small platform hung upon the traveler rope by deeply grooved wheels. It is surrounded by a railing, inside of which the workman will stand, cutting the lash ings as he rides across. The ride down to the center of the traveler repe will be controlled with a hempen rope, and the 'buggy" will be hauled up the opposite incline with another. There will be nothing perilous in the process if the workman can keep from dizziness, nor more danger than in a great many other stages of the work.

In order to inspire confidence in the men who are to per form the undertaking, Mr. E. F. Farrington, master mecha nic of the bridge, recently crossed from the Brooklyn an chorage to the New York pier, seated on a boatswain's chair, or swing, attached to the moving rope. The trip was rapidly and safely accomplished in the presence of a large and enthusiastic crowd. Mr. Farrington, now the first man who has crossed the bridge, was also the first who traversed the spans at Cincinnati and Niagara.

Becent American and Loreign Latents.

NEW MECHANICAL AND ENGINEERING INVENTIONS.

IMPROVEMENT IN FEEDING PULVERIZED FUEL TO FURNACES Allin Cockrell, Lamar, Mo.-This consists of a fan blower co bined with a furnace in such manner as to feed it with a constant and regular supply of fuel, and having a conveyer for supplying the fuel to it from a mill in which it is ground, or from a feeding hopper to be supplied with previously pulverized culm, tan bark

IMPROVED EXPANDING METAL DRILL

Patrick Duffy, New Bedford, Mass., assignor to himself and James F. Powers, same place—Two cutters, fixed in the stock to slide forward and backward transversely, are slotted obliquely and reversely to each other. The fastening bult by which they are secured to the stock is fitted in said slots, and also fitted in a vertical slot in the stock, so that, by shifting the bolt along the slots in one direction, the cutters will be adjusted onward; by shifting the bolt APPARATUS FOR CUTTING AND ORNAMENTING SHOE UPPERS

APPARATUS FOR CUTTING AND ORNAMENTING SHOE UPPERS.

Edwin B. Stimpson, Brooklyn, N. Y.—This consists essentially of a series of small punches, one or more large punches, a bed die, and a stripper, contrived in the ordinary way of punching machines, for making ornamental figures in the uppers of shoes. The steel die plate is riveted to an iron plate, the object of which is to combine with the die plate a sufficient body of metal, that will not crack in cooling. The stripper is suspended from the head of the press by springs to raise it out of the way of handling the goods after the goods are cut. The marking plate has small points for marking imitation stitches, and there are broad punches for cutting out long strips made concave on the cutting end.

IMPROVED LUBRICATOR

Simon Smith and Isaac S. Collins, Mauch Chunk, Pa.—This is a horizontally feeding oil cup for parts of steam engines, which can be regulated to feed a greater or less quantity of oil when the engine is in motion, but which discontinues the oil supply when the engine is stopped. It consists of a horizontal cup of cylindrical shape, with tightly scated glass head. The feeding mechanism consists of a horizontal reciprocating pin, guided in suitable manner, and having recesses that take up the oil from supply perforations and convey it to the feed tube at each oscillation of the part of the engine to which the lubricator is attached. of the engine to which the lubricator is attached.

IMPROVED GRINDING MILL.

Enoch Moore and David Moore, Mooreville, Iowa.-These invent ors propose to provide a supporting plate, with a recess, on which they locate the rocking plate resting on the pivots in the bottom of the recess. The stone on the under side of it rests on other pivots. By this arrangement, sufficient space is secured between the beams without cutting or weakening them

IMPROVED COMBINATION LOCK

Isaac D. Sibley, Huntsville, Ala.—This consists of two systems of bars and springs, arranged one on each side of the guard boit to slide toward and from it, and so contrived that the bars of one side being adjusted against the block lock it, and in that position are unlocked by sliding up the bars of the other side.

IMPROVED LARD PRESS.

Pusey Pemberton, Newark, Del.-Devices are provided whereby the follower may be held level, and may thus be kept from binding, even should there be more scrap or cracklings in one side than in the other, and the mechanical construction is new and well calculated to render the machine efficient.

IMPROVED LEATHER-TAPERING MACHINE.

John Settle, Lebanon, Oregon, and George W. Settle, Oakland, Oregon.—This invention relates to certain improvements upon the patent granted the same inventors, January 19, 1875, for a machine for tapering leather, in which a pivoted frame carrying a knife moves over a hinged adjustable curved block to taper the end of a strap, belt, or other piece of leather, preparatory to attaching the same to another piece, and it consists in the construction and ar-rangement of a device for clamping and holding the piece of leather in a convenient and effective manner.

IMPROVED TWEER.

Mark Lester, Bellaire, Ohio.-The object of this invention is to Mark Lester, Bellaire, Ohio.—The object of this invention is to prevent the accumulation of sediment in the annular water space of a tweer for blast furnaces, and to prolong the life and utility of the latter. To this end the invention consists in providing the overflow pipe of the tweer with an outlet cock, located near the bottom of the water space, through which the mud and sediment may be washed out, and extending the supply pipe to the nose or hottest part of the tweer, whereby the cold water is first brought in contact with the part of the tweer which most needs the cooling effect, and whereby also the accumulated mud and sediment may be readily washed out by the natural passage of the water. may be readily washed out by the natural passage of the water.

NEW CHEMICAL AND MISCELLANEOUS INVENTIONS.

IMPROVEMENT IN ORNAMENTING BUTTONS.

Samuel S. Moyer, Berlin, Ontario, Canada.—This process consists, first, in printing the figures upon the face surface of the button by means of type coated with an impermeable composition, then applying the coloring matter, after which the composition is removed by polishing or otherwise.

IMPROVED DIFFUSION APPARATUS.

IMPROVED DIFFUSION APPARATUS.

Charles Neames, New Orleans, La.—The object of this invention is to improve the Julius Roberts diffusion apparatus, in such a way as to secure a more perfect extraction of the saccharine matter from the material used, and at the same time simplify the apparatus. It consists in a diffusion vessel of a diffusion apparatus, gradually increasing in size from its top or inlet, opening to its bottom or outlet opening; in the wood packing interposed between the rim of the doors and the door frames of a diffusion vessel; in a division plate extending from the top to the bottom of the vessel to form the heating chamber, and having its lower part perforated to form the heating chamber, and having its lower part perforated with numerous small holes to serve as a strainer. Finally, heating pipes are placed within the diffusion vessels of the apparatus; and there is likewise a combination of the circulating wheel and its pipe with the diffusion vessel.

IMPROVED CUFF AND COLLAR BOX.

Ernest Scheel, New York city.—This consists of a box divided by a lateral partition into two sections or compartments, of which one is intended for the cuff, and provided with a central tubular post with sliding top. The other is divided by horizontal supports into two parts for inserting a receptacle and storing the collars, neck-

IMPROVED HOMINY KNIFE.

John Outcalt, Spotswood, N. J.—This consists in improved knives of hullers for hominy mills, made with their blades curved their rear ends. They are also made wider toward their rear ends inclined upon their upper sides, flat or inclined upon their lower sides, and provided with rasp teeth above, and file or rasp teeth

IMPROVED HARNESS SADDLE

Robert Spencer, Brooklyn, N. Y.—The object here is to afford a of wood is made broader than the tree plate, and the flap an jockey are attached to the margins of the face or outer side of the pads. The tree plate is made of sheet metal, with a transverse ridge and corresponding groove or depression.

IMPROVED PACKAGE FOR PAINTS, ETC.

George Sidey, Brooklyn, N. Y.—This invention consists in causing the upper edge of the can body to bear in a groove and against the center of a strip, and providing a flat headed screw working in a nut on the bottom of the can, in order to form a close joint. The article placed in the can is thus hermetically scaled.

IMPROVED PAPER BAG PASTENINGS.

Henry S. Giliette, New Preston, Conn.—A string of suitable length and strength is attached to the bag by means of a piece of paper which is pasted to the bag over the string. This little clip of paper secures the string permanently, so that the clerk need waste no time in seeking for a string to tie the bag.

IMPROVED TOY MARBLE RAKE.

*Alfred Gurny, Robert H. Piper, and Henry E. Waite, Bridgepori, Conn.—This is a rake or notched bar employed in marble playing for determining the gains by the numbered notches through which the marbles pass. There is a spring tablet to each notch, with the number of the notch upon it, and contrived to be set in the way of the marble passing through the notch, so as to be tripped by the striking of the marble against it. On being raised, it exposes the number of the notch to view, thus showing the count toward game, the number being concealed while the tablet is set.

IMPROVED AWNING.

Anthony Hesselis, New York city.—This consists of a swinging stretching frame and outer curtain, that is wound up by a roller and cord. The roller is supported on a second swinging frame, to be lowered and adjusted to any position for regulating the hight. When the awning is lowered entirely, it serves to close the window like a curtain, forming a protection against heavy rain, hail

IMPROVED CIGAR BOX.

Simon Hood, New York city.-This cigar box admits the conve nient arranging of the cigars in bundles, the exhibiting of the same, and the ready taking out for selling them. The body is made of diagonally tapering shape, with steps and guard strips, and is closed by hinged side and front parts and lid.

IMPROVED SHEARS AND SCISSORS

George H. Taylor, New York city.—This invention consists in constructing shear or selssor blades with a curved shoulder at the rear end of the cutting edge of the blades, to adapt them for use

IMPROVED HARNESS BUCKLE.

Benjamin F. Frazier, Grand Rapids, Wis.-By suitable construc tion, when a strain comes upon the strap, the tendency is to draw a frame back, and clamp the said strap between cross bars. The strap is thus held securely without holes being punched in it.

IMPROVED CAMP STOOL

Charles M. Lungren, Toledo, Ohio.-This invention consists of a double ferrule and hook attachment for the top of the legs, com-prising in one casting the hook and the ferrule for connecting the nook to the leg, and also a socket for the attachment of the back support. This forms a stool which may be folded into small com-pass, and which, nevertheless, when extended, gives a comfortable seat. At the Centennial Exposition, where chairs or seats of any kind are few and far between, portable devices of this type are found very useful.

IMPROVED BEER PUMP

Philip Krumscheid, Boston, Mass., assignor to himself, J. Krum ramp kromsened, beston, sass, assay, assign to the misser, 3. Krumscheid, and John R. Foley, same place.—This invention consists of a beer pump in which a float shuts off, when raised to a certain hight, the water supply, and draws off a certain quantity of water, sufficient to lower the float and re-establish the water supply. The air is forced through and retained in the barrel by a check valve, and drawn into the pump through an air pipe with mother check raive, on the falling of the water level. with another check valve, on the falling of the water level.

NEW WOODWORKING AND HOUSE AND CARRIAGE BUILDING INVENTIONS.

IMPROVED GIN SAW FILER.

Frank Charter, Little Rock, Ark.—This is a machine for filing gin saws without removing the saw shaft from its frame, and in such a way as not to leave angular or wiry edges upon the surface of the saw teeth, to cut, chop, or nap the cotton fiber, and thus in-jure it. The novelties lie in the mechanical construction.

IMPROVED PILE SAW.

David Bean, Le Sueur, Minn, -- This consists of a standard for sup-David Bean, Le Sueur, Minn.—This consists of a standard for sup-porting the saw frame, with a clamping device for attaching it to the upper end of the pile to be sawed off under water. There is al-so a vertically adjustable arm, on which the frame swings, and on which arm the frame is adjustable to feed the saw up to the pile as the work progresses, and to measure its depth in the water.

IMPROVED BILLIARD TABLE LEVELER.

Samuel May, Toronto, Ontario, Canada.—This consists of a long nut, with an enlarged bead at the lower end, screwing on a rod projecting from the bottom of a socket in the end of the leg, in which the nut works so as to conceal the screw rod. Said rod is either a short one, screwing into the leg at the bottom of the socket, or it is formed on the rod used to screw the leg to the table. In both cases it has a collar screwing against the bottom of the sock-et, and is secured by wood screws screwing into the wood through notches in the edges of the collar.

IMPROVED WHIFFLETREE CONNECTION.

George W. Ingersoll and Harvey L. Fisher, Toledo, Iowa.-This consists in an inclined whiffletree coupling, composed of two un-equal bars connected by an eye bar. The inclination of the coup-ling causes either end of the whiffletree that may swing back to pass above or below the double tree, according as the longer arm is placed above or below the shorter arm, so that there can be no ubbing and wear between said double tree and whiffletree.

NEW HOUSEHOLD INVENTIONS.

IMPROVED MEAL BIN

John Hunter, Ashland, Pa.-This consists of a kneeding trough needing board, and a flour sieve, contrived in connection with a flour chest, so as to be more convenient and easier to use than as commonly arranged.

IMPROVED BED SPRING.

John Reardon, New York city, assignor to Orville D. Lovell and Frank H. Lovell, of same place.—This is a bed bottom spring formed of a rabbeted U-frame, a flanged crosshead, a guide pin, and a spiral spring, constructed and arranged so that the bedstead can be put up, taken down, and carried from place to place with as much case as if the slats rested upon cleats, and the various parts of the spring are so arranged that they cannot cut or injure

IMPROVED CARPET STRETCHER

Lewis W. Rivers, Salt Lake City, Utah Ter., assignor to himself and Hanson J. Rivers, of same place.—In using the device, the car pet is placed between jaws, and a lever is arranged with its sharp lower end resting upon the floor, and its upper part inclining for-ward over a bar. The upper end of the lever is then forced back or from the carpet, which draws the said carpet to its place. When the carpet has been strained sufficiently a pawl, holds the lever in place until the stay tacks can be driven.

IMPROVED SNOW SHOVEL

Eugene Campbell, South Westerlo, N. Y.—This shovel is provided with a face plate extended beyond the edge of the shovel plate. It also has, on the under side of its front end, and in one piece therewith, the runners arranged to keep the edge of the plate from coming in context with the shovel is below. coming in contact with the surface upon which the shovel is being

IMPROVED WEATHER STRIP.

William Watkins, West Joplin, Mo.—This weather strip is formed of a metallic plate, having its edges bent over upon themselves to form grooves to receive a strip of flexible metal, said flexible strip is made wider than the said metallic plate, to give its middle part

IMPROVED WASH BOARD.

John S. Washburn, Yonkers, N. Y.—This invention consists in an improved washboard formed of grooved side bars, over which a rubber plate is passed, so that a rubber surface and a wooden surface may alternate with each other to form the rubbing surface of the board.

NEW TEXTILE MACHINERY.

IMPROVED TENSION DEVICE FOR TWISTING MACHINES.

Paul A. Chadbourne, Williamstown, Mass.—This is a contrivance of guide eyes and a roller with the spool stand, from which the threads are supplied to the twister, whereby the tension of all the threads is more uniform than in the common arrangement.

IMPROVED FEEDER FOR CARDING MACHINES.

William C. Bramwell, Terre Haute, Ind., assignor to himself and Edwin Ellis, of same place.—The invention consists of a tilting scale for weighing the wool deposited upon it by a toothed travel-ing apron, the two (scales and apron) being so connected by a clutch mechanism that the apron is stopped intermittingly, thus shutting off further supply until the scale has deposited or dis-charged the wool which it already contains. The wool having been thus deposited on the feed table, and the scale returned to its orsupply to the scale, a loosely pivoted rotating scraper is at work removing the pile of wool just dropped by the scale, and pressing it up to the edge of that which has already been fed on and is about to enter the feed rolls of the carding engine. By this operation to enter the feed rolls of the carding engine. By this operation the wool is removed out of the way, and a clear place given to the next lot, so that it may not, by piling up, obstruct the proper action of the tilting pan of the scale, and that all the wool may be dropped each time. The tilting and emptying out of the wool from the scale is entirely independent of the time it may take the scale to turn its balance, as this time is constantly varying. It is by this means that the apparatus is caused to run itself out of wool when desired, and yet keep the work even to the last.

NEW AGRICULTURAL INVENTIONS.

IMPROVED PLOW STOCK.

Lemuel H. Davis and Irvin Aycock, Morgan, Ga.-This consists in a plow stock formed of three iron bars, constructed and com-bined with each other, and with the handles, so as to form a strong

IMPROVED COMBINED LISTING PLOW AND SEED DRILL.

Alonzo M. Coston, Maryville, Mo.-This is an improved machine for preparing the soil and planting the seed at one passing over the ground, which is left in a deep furrow and ridge alternately. The subsoiler runs in the rear of the main plow, thereby loosening the soil in the bed of the furrow, forming a suitable place to deposit the seed, and dropping the seed and covering it.

IMPROVED CORN PLANTER.

Nathan H. Meeks, Salado, Tex.—This consists of a circularly vibrating dropper slide contrived to be attached to a plow beam or other object to be drawn by a single horse, and be worked by the whiffletree, which has the requisite vibratory motion from the

IMPROVED HOG TROUGH.

Newton A. Clark, Harveyville, Kan.—The object here is to keep the hogs away from the trough when putting in food, to prevent the hogs from putting their feet into the trough when feeding. The mode of operation is as follows: A lever being raised into a perpendicular position, boards are thrown against the back of a frame, so as to allow the hogs to have access to the trough by passing between ribs. On the other hand, when the lever is brought to a horizontal position, or nearly so, the boards are thrown out in front of the trough, so as to exclude the hogs therefrom.

IMPROVED FERTILIZER DISTRIBUTOR.

David C. Brown, Log Town, La.—This is a device for attachment to the rear end of a wagon body for distributing cotton seed as a fertilizer. It may be used for distributing other fertilizers, and which will enable the material to be placed wherever desired. In using the device, a man is placed in the wagon to keep the hopper filled with the fertilizer. The amount of fertilizer distributed may be regulated by increasing or diminishing the number of pins which feed out the material, and by varying the relative size of the driving pulleys.

IMPROVED ANIMAL TRAP.

Homer S. Davis, Camp Brown, Wyoming Ter.—This improves the well known spring trap used for catching animals of large size, such as beavers, foxes, otters, etc., so as to prevent the throwing out of the leg or foot, or the breaking of the same by the action of the spring, in consequence of which the animals frequently escape. IMPROVED CORN-PLANTING ATTACHMENT FOR SOD PLOWS. Sanford M. Scott, Stockbridge, Wis.—This is an attachment for breaking-up or sod plows, so constructed as to plant the corn as the sod is turned, and close to the outer edge of the furrow. The corn will thus come up between the sods of two furrows. The device is not in the way of turning the plow over to file or sharpen the

IMPROVED POTATO PLOW

Tubal C. Baxter, Monticello, Kan.—This consists of a forked cam, with a landside and cutter to each branch of the fork, be tween which is a shovel plow fixed on an easy incline, for the po-tatoes and the earth to be forced along over the rear end. From said end extend a number of rods, suitably arranged to let the earth sift through, and to carry the potatoes back and discharge them in a row on the top of the earth.

IMPROVED PLOW

Alva A. Preston, New Troy, Mich.—This is an improved iron beam plow, light, and at the same time strong, which may be easi-ly adjusted to take or leave land, and to run deep or shallow, as

IMPROVED MILK PAIL

Newton McKusick, Stillwater, Minn.—This is a pail with a cover having an opening closed by a strainer, and a detachable funne with a second strainer, through which the milk passes into the pan. The double strainers prevent any foreign substances, however small, from passing into the milk.

IMPROVED HARROW

William C. Moore, Cairo, Pa.—This is formed in three sections hinged to each other by bolts and straps. The middle section is made rectangular, and the side sections oblique, having their for-ward corners beveled off. Shoes are attached to the forward sides of the freed exceeds.

Business and Lersonal.

The Charge for Insertion under this head is One Dollar a Line for each insertion. If the Notice ex-

Pat.Att'ys & Experts wanted everywhere, to Coll't Millions, Good pay, Add, Am. Pat. Coll'n Co., Phila., Pa.

Agricultural Implements and Industrial Machin-ry for Exportand Domestic Use. R.H. Allen & Co., N.Y.

Solid Emery Vulcanite Wheels-The Solid Origmal Emery Wheel-other kinds imitations and inferior. Caution.—Our name is stamped in full on all our best Standard Belting, Packing, and Hose. Buy that only. The best is the cheapest. New York Belting and Pack-ing Company, 37 and 38 Park Row, New York.

The Target Air Pistol kills cats, rabbits, squir-rels, pheasants, pigeons, and other small game. Mailed, post paid, for \$3.78. Send stamp for circular and testi-monials. E. H. Hawley, 130 George St., New Haven, Ct.

Glass Blown Cylinders. T. Degnan, 129 Milk St., Boston, Mass.

Wind Turbine Wheel for raising water, etc. Late patent. On royalty or sale. P. O. Box 75, Santa Fé, New

Planing Machines—For the best and cheapest traveling-bed or "Farrar" Planers—24, 27, and 30 in.— also 15, 18, and 24 in. stationary-bed machines, address _ane M't'g Company, Montpelier, Vermont.

Machinist wanted in every town, as Agent; term iberal. Address Knight & Knight, Washington, D.C.

For Sale—Machinists' Tools, nearly new: One Planer, one Lathe, and one Drill Press. \$300, Cash. W. Crabb, Nassau Works, Newark, N. J.

A Responsible Patent Right Manager Wanted-Carriages and R.R. Cars can be run without oiling. Address or call on Geo. Beck. Charlotte, Monroe, Co., N. Y

Models for Inventors. H. B. Morris, Ithaca, N.Y.

Steel Name Stamps, post paid, for 18c. per letter. Marks on Wood, Iron, and Steel. Agents wanted. Steel Stamp Works, 213 Chapel St., New Haven, Conn.

Handbook of Useful Information for Lumber-men, Millwrights, and Engineers (152 pages) sent free by Lane M'f's Company, Montpeller, Vermont.

Horse Nail Machines—Wanted Machines for fin-ishing and pointing Horse Nails. J. W. Britton, 18th Ward, Cleveland, O.

Jethro Wood.—If any of our readers can send or refer us to any publication containing a portrait of Jethro Wood, the plow inventor, we should be obliged.

For the cheapest and best Small Portable Engine manufactured, address Peter Walrath, Chittenango, N. Y.

Walrus Leather, Walrus Wheels, and Polishing Material. Greene, Tweed & Co., 18 Park Place, N. Y.

Biake's Belt Studs, Belting, Packing, Hose and Manufacturers' Supplies generally. Greene, Tweed & Co., 18 Park Place, New York.

For 2d Hand Portable and Stationary Boilers and Engines, address Junius Harris, Titusville, Pa.

Yacht and Stationary Engines, sizes 2, 4, 6 and 8. P. Best for price. N. W. Twiss, New Haven, Conn. Circular Saw Mills of the celebrated and popular "Lane" pattern, made under direct support under, direct supervis Ventor by the Lane M'f'g Company, Montpeller, Vt.

Hotchkiss Air Spring Forge Hammer, best in the tarket. Prices low. D. Frisbie & Co., New Haven, Ct. Patent Scroll and Band Saws, best and cheapest use. Cordesman, Egan & Co., Cincinnati, Ohio.

M. Shaw, Manufacturer of Insulated Wire for galvanic and telegraph purposes, &c., 259 W. 27th St., N.Y.

F. C. Beach & Co., makers of the Tom Thumb Telegraph and other electrical machines, have removed to 530 Water Street, New York.

Pat'd Graining Stencils-J. J. Callow, Clevel'd, O

Lathe Dogs, Expanding Mandrels, Steel Clamps c., for Machinists. Manufactured by C. W. LeCount, p. Norwalk, Ct. Send for reduced Price List.

"Abbe" Boit Forging Machines and Palmer Power Hammers a specialty. Send for reduced price lats. S. C. Forsaith & Co., Manchester, N. H.

400 new & 2d hand Machines, at low prices, fully described in printed lists. Send stamp, stating just wha you want. S.C. Forsaith & Co., Manchester, N. H.

Lane's "Monitor" Turbine Water-Whe of perpetual motion machines, but they combi and greater advantages than any other water motors of fered the public. Address Lane Mfg Co., Montpeller, V

Driving Belts made to order, to accomplish work required. Send full particulars for prices to U. W. Arny, 148 North Third St., Philadelphia, Pa.

Scientific American—The early Volumes for Sale—very cheap—either bound or in numbers. Address A. F. B., Box 773, New York City.

Hydrant Hose, Pipes, and Couplings. Send for rices to Balley, Farrell & Co., Pittsburgh, Pa.

"Dead Stroke" Power Hammers—recently greatly improved, increasing cost over 10 per cent. Prices reduced over 20 per cent. Hull & Beiden Co., Danbury, Ct

Power & Foot Presses & all Fruit-can Tools. Fer-cute Wks., Bridgeton, N.J. & C. 27, Mchy. Hall, Cent'l

Shingles and Heading Sawing Machine. See advertisement of Trevor & Co., Lockport, N. Y.

Steel Castings, from one lb. to five thousand ibs. invaluable for strength and durability. Circulars free. fittsburgh Steel Casting Co., Pittsburgh, Pa.

For best Presses, Dies, and Fruit Can Tools, Bliss Williams, cor. of Plymouth and Jay, Brooklyn, N. Y. For Solid Wrought-iron Beams, etc., see adver-sement. Address Union Iron Mills Pittsburgh, Pa. for lithograph, &c.

Hotchkies & Ball, Meriden, Conn., Foundrymen and workers of sheet metal. Fine Gray Iron Castings to order. Job work solicited.

For Solid Emery Wheels and Machinery, send to the Union Stone Co., Boston, Mass., for circular.

Clapboard Machinery-Sawing, dressing, and trimming-a specialty of the Lane M'f'g Company.

Hydraulic Presses and Jacks, new and second and. Lathes and Machinery for Polishing and Buffing metals. E. Lyon, 470 Grand Street, New York.

Diamond Tools-J. Dickinson, 64 Nassau St., N. Y. Temples and Oilcans. Draper, Hopedale, Mass. boss to connection with engines is only 4 feet. metal? A. Try melted paraffin.



W. H. H. will find directions for preventing rust on iron on p. 169, vol. 33.—C. W., Jr., wil find directions for calculating the proportions o compound gears on p. 107, vol. 34.—A. K. will find that good glue is the best material for fixing sand on belts.—W. A. G. can make and use leather pulp by following the directions on p. 105, vol. 25 R. S. will find a description of a cold tinning process on p. 154, vol. 34.—J. R. C. should consult the makers of his fan.—E G. A. is informed that the sand blast (see p. 195, vol. 27) has been used for cutting iron; but whether it is now in practical use for that purpose, we do not know.—C. W. L. will find directions for making artificial meerschaum (not ivory) from carrots, etc., on p. 307, vol. 34.—H. H. L. can make a good indelible ink for stamping by following the directions on p. 129, vol. 28.—H. S. can polish Britannia ware by e method described on p. 57, vol, 34.-N. S. the method described on p. 57, vol, 34.—N. S. W. will find answers to his queries as to the Scientific American Supplement on p. 124, vol. 35.—H. W. C. will find a recipe for a hair stimulant on p. 138, vol. 33.—J. P. G. will find directions for tempering springs on p. 11, vol. 34.—E. H. B.'s query as to eggs is a schoolboy's problem, of no practical value.—C. E. C. can clean rust from tin by following the directions on p. 57, vol. 34.—E. W. H will find a recipe for artificial coral on p. 307, vol. 34.—C. B. R. will find a description of phosphor bronze on p. 315, vol. 30.—C. A. will find directions for etching on glass on p. 203, vol. 33.—H. L. will find directions for gilding on glass on p. 313, vol. 34.—B. will find a recipe for a depila-tory on p. 186, vol. 34.— J. M. will find full direc-tions for stuffing birds on p. 159, vol. 32.—H. T. will find directions for making fulminating pow-der on p. 250, vol. 31.—J. D., Jr., will find directions for japanning tin ware on p. 132, vol. 24.-D. M. L. can cement glass to brass with the pre-paration described on p. 117, vol. 32.—R. I. G. is informed that there can be no such instrument at a needle that will point to buried gold.—F. W. S. will find a description of the underground telegraph wires in London and elsewhere on p. 294, vol. 30.—G. K., of Highgate, London, England, will find directions for nickel plating on p. 235, vol. 33.—A. F. will find directions for getting rid of fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid of fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid of fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid of fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions for getting rid fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. & S. will find directions fleas on p. 217, vol. 27.—C. ions for making pickles on p. 155, vol. 31 .- J. H. K. can prevent mildew on sails by the process de-scribed on p. 90, vol. 31.—A. D. L. will find a formula for calculating the centrifugal force of a body on p. 378, vol. 30.—J. O. S. can render his windows opaque by the process described on p. 264, vol. 30. —H. W. G. will find an article on chlorophyll on p. 247, vol. 29. —W. A. D. will find directions for making artificial stone on p. 124, vol. 22.—H. J. can silver brass and copper, without a battery, by using the preparation described on p. 299, vol. 31. using the preparation described on p. 200, vol. 31.

—D. D. W.'s letter has been placed in the hands of several chemists, who may take action in the matter.—A. H., E. W. M., F. C. L., W. J. B., C. F., W. M., N. J. O., C. J. C., H. M. L., W. B. W., B. H., R. B., C. R., J. W. F., W. B. E. P., W. H. B., and others who ask us to recommend books on industrial and scientific subjects, should address the booksellers who advertise in our columns, all of whom are trustworthy firms, for catalogues.

(1) F. R. Jr. asks: How can I find the diameter of one of four equal circles inscribed in a large circle, of given diameter? A. Multiply the given diameter by 0.414213.

(2) W. H. S. says: I enclose a specimen of deposit taken from my heater reservoir, which I am unable to get rid of and which is very trou blesome. The heater is 14 feet long and 22 inche n diameter, and in it are three pans 12 feet long by 14 inches wide, with partitions in middle. The cold water runs into the top pan on one side at end, and along the length of pan; it returns and fails through holes into next, and so on through, lastly falling on bottom of heater, and is then conveyed to a reservoir 6 feet deep and 22 inche in diameter. The exhaust comes up into my heat er at the end at which the cold water comes in and goes out at the opposite end, so that the wa-ter gets boiling hot before it leaves the heater. use water from the top of the reservoir, and the deposit seems to float on top, and will not mix with the water after it is precipitated. Can you suggest any means of getting rid of it? A. By the use of a surface blow, you could probably discharge the most of it. It would be still better to filter the water after leaving the reservoir Probably a box filled with sponges would answer every purpose; and the sponges could be removed and washed, from time to time, as they become stopped up.

(3) A. O. says: I have an engine of the folter, stroke 6 inches. The boiler is 5 feet long by 34 feet in diameter, made of 14 inch boiler iron single riveted. It is to run, if possible, at about 200 revolutions per minute. Is it big enough to 230 revolutions per minute. run a cylinder journal printing press, generally run by hand power, and a printing press run by foot power? Is the boiler big enough to general steam enough to run the engine and heat a building of 30 x 60 feet? A. We think the machinery will answer, and that you can heat the building with the exhaust steam. It must be evident to you, however, that an opinion, based on the data you have sent, cannot be of any great value. It only amounts to saying that if th hinery is properly designed, constructed, and set, it will give satisfaction.

(4) J. H. B. asks: What should be the di amoter of a propeller shaft, to transmit with safety an actual thrust of 10 tuns, the strain to be the case? Length of shaft after leaving propelled

Propeller is supposed to revolve in water con stantly, never to be thrown out of it and thus subjected to the undue strains of racing on its return. Material is to be steel. A. A shaft 2 nches in diameter will answer for the conditions

Suppose cold water to be kept in constant circulation on the exterior of a cylinder with shell 11/2 inches thick. What is about the highest temperature to which the interior may be exposed as long of that of the interior elreumference of shell does not exceed 700° Fab.? A. There is no limit to the temperature, if, as we understand you, it is assumed that the temperature of the iron can be kept at or below 700°

(5) P. R. asks; Please give me a simple rule for calculating how much weight a horizontal spruce beam will bear. A. If the beam is rectangular, and supported at both ends, the breaking weight, applied at the middle, will be:

(Depth in inches)2×(breadth in inches)×400.

Length between supports in feet. If the load is uniformly distributed over the beam, it can be twice as great as the above.

(6) C. C. asks: How can I make a dark col ored chalk, suitable for lining purposes on light colored wood, having the same cohesion as the common white chalk used for that purpose? A. Grind the pigment into an impalpable powder, thoroughly moisten with a little dilute solution of dextrin in hot water, knead the mixture well, and dry thoroughly at a gentle heat.

(7) T. M. H. asks: Can any use be made of dross from tin and lead? A. If there is any considerable quantity of the material it would probably pay to treat it for the recovery of the metals in the following manner: Mix thoroughly with allowed as company weight of arthurst are considered. with almost an equal weight of anthracite coal spread evenly on the bed of a small reverberatory furnace, and smelt, with a gradually incre ing temperature, until the reduction of the metal has begun. Then throw in a little lime, increas the temperature for a short time, draw off the reduced metal into a large iron vessel, and stir with a piece of wet wood to raise the impurities to the surface; remove these by skimming and pour the metal into a stone or iron mold to cool.

(8) C. G. L. asks: Is there any way of get ting a press copy from thin writing ink, or from writing too old to copy from moisture only? A.
Try the following: In a half pint of water dissolve about a tablespoonful of white sugar, and to the solution add a sufficient quantity of the ferrocyanide of potassium to distinctly color it, also about half a gill of pure muriatic acid (free from iron). Moisten white tissue paper with this, partially dry it with a blotter, place the wri-ting to be copied in contact with it, and keep un-der pressure for about five minutes. With most inks this recipe will give very good results.

(9) H. A. P. L. says: Would an electrical machine with one glass cylinder and two round silk cushions, electricity being conducted to a Leyden jar or a prime conductor, be powerful enough for experiments? A. As far as we may judge from your description, the machine is properly constructed; but to obtain good results, it will be necessary to rub on the cushions an amalgam, which may be prepared as follows: Melt together in a crucible 2 ozs. zinc and 1 oz. tin; when fused, pour the alloy into a cold crucible containing 4 drachms dry mercury; when cold the amalgam is ready for use. Before applying the above amalgam, the cushion should be rubbed over with a mixture of tallow and beeswax. In pouring the fused metals into the cold mercury, do not inhale the mercurial vapors that may be formed, as they are very poisonous.

(10) C. A. R. asks: Is there a cement or fluid which will fasten together two straps of sole leather a yard long, which will not be affected by moisture? A. Melt together equal parts of pitch and gutta percha. Apply hot.

What will remove stains from a shirt bosom A. Try touching the spots with a little benzole and afterwards pressing for several hours with warm pipe clay.

(11) A. B. says: Some plumbers use muri-atic acid with no zinc in it. I would like to know what effect this acid has on iron and brass. Dilute muriatic acid will answer, but a strong acid solution of chloride of zinc is much better, as it not only cleans the metallic surfaces but protects them, by the formation of a coating of the fused chloride, which excludes the air.

(12) J. S. M. asks: How large a pipe will it take to give sufficient blast to a cupola 22 inches in diameter, distant 80 feet from a common fan? A. About 2 or 234 inches in diameter.

(13) A. F. J. asks: Can water be raised by suction? If so, how far? A. If, as we under-stand it, reference is made to the hight to which hours without refilling the pot? Can the gas be water can be raised by atmospheric pressure, 33 led to the purifier and from that right to the feet is about the practical limit, and one which is burners? A.This is not practicable, as, when the seldom reached by ordinary pumps.

(14) J. F. asks; What is the rule fo ascertaining the proper amount and form of space up derneath and at the back end of the boiler? There is no definite rule for this proportion,

(15) C. & T. ask: If you found that the piston of your engine was striking the bottom or top of the cylinder, what would you do to stop the pounding? A. If the pound were serious, we would put linings in one of the connecting rod boxes. In case it was not possible to stop, we would work the engine slowly, and cushion the steam, if any means for so doing were available.

(16) R. asks: How can I coat, easily and cheaply, the inside of an iron pipe so that the water passing through may not be affected by the

(17) P. V. T. and others.-There is no spe cific for catarrh. Temperament, habits, etc., must be taken into account, for which reason a course of treatment suitable to one person would be entirely unsuited to another. We cannot ad-vise anything but continuance under the care of a regular practitioner.

(18) J. G. Q. asks: In what non-freezing liquid can phosphorus be kept from combustion? A. In naphtha.

(19) S, W. T. says: How can I make a first class waterproof blacking, that does not require brushing? A. Vinegar I quart, ivory black and molasses, each 6 ozs., oil of vitriol and spermaceti, each 1½ ozs. Mix the acid and spermaceti first, and then add the other ingredients.

What is the best way to clean a copper boller? It is used in a kitchen; the boller is 18 inches diameter and 5 feet high, the burnish on the out-side gets dull and of a mauve color. A. Clean with a little dilute oxalic acid solution, wash, dry, and polish with a little tripoli.

How can I make soap bubbles so that they will

last long, or at least not break so soon as those made with soap and a pipe in the ordinary way? A. Use a fatty soap, preferably one made with fish oil, and to the solution add a little glycerin.

How can I find a number which, multiplied by itshalf, will make 20? A. Let x=the number; then $(\frac{1}{2}x)x = \frac{x^2}{2} \cdot \frac{x^3}{2} = 20$, $x^2 = 40$, x = 0.32455, $\frac{1}{2}x = 0.32455$

3·16228, $x \times \frac{1}{3}x = 19 \cdot 90009719$. If you carry out the square root of 40 until you obtain the root of mplete, and multiply this number by one half itself, then the result will be 20 instead of the re-

How can I darken my hair, which is a light red, without using a dye? A. You cannot. What is a good substitute for gum arabic for sticking on labels? A. Use a boiled solution of lextrin in water.

Is there anything that will keep the snow from lying on the ground in winter? It is a patch 40 yards square that is required to be kept clear. A.

(20) H. A. G. says; I have a coat which was originally of a dark blue color; but owing to exposure to the sun's rays, it has faded to a reddish hue. How can I restore the original dark blue color? A. Try treating the fabric with strong ammonia water for a few minutes, and then wash thoroughly with clean water. If this does not suffice, it will be necessary to have the

(21) W. C. W. says: You published a recipe for making black varnish by mixing oil of tur-pentine and sulphuric acid. I tried the experiment, which cost me a loss of some clothes,n ly the loss of an eye, and about two weeks' labor, brought about by an explesion which burnt my face severely. I purchased what a druggist said was oil of turpentine (spirits of turpentine). I mixed the ingredients in various ways, with no results as predicted; and then, having a phial partially full of each, I poured one into the other, and then shook the mixture, when an explosion took place. What was the matter? A. The re-cipe, as given, is perfectly correct; and if you had closely and carefully followed its directions, all would have been well. Instead of dropping the sulphuric acid into the turpentine, it would, per-haps, be better to slowly drop the turpentine into the strong acid. The only precautions necessary are to mix the reagents slowly, so as to avoid a too rapid rise in the temperature of the mixture, and to keep the mixture cool by surrounding the vessel with cold water during the operation. The viscous and dark red body obtained consists principally of a mixture of terebene and colophene. The proper proportions are about 1 part of strong

(22) I. N. R. R. says: I have charge of some coal mines, in which there is a great deal of gas. In one part of the pit the gas shows a bine thame on the safety lamp gauze; and in another part there is a fault in the coal, and the gas shows the blue flame, and on the top of the blue flame a white flame. Please explain this. A. It may be due to some peculiarity in the oil, an unusual quantity of carbonaceous matter in the atmo-sphere, or to the fire damp itself becoming intermixed with some higher carburet of hydrogen. You do not furnish sufficient data to enable us to answer the question more positively. In case the latter suggestion should prove the correct one, and, inadvertently, the mixture should become ignited, the explosion that would follow would be very severe, much more so than that of ordinar-

(23) A. K. says: We have a small stage (13) A. F. J. asks: Can water be raised by an ordinary suction pump below a level of 33 feet by the aid of check valves placed below the temperature reaches a certain point, the gas comes over quite rapidly and not at all uniformly. It will be necessary to pass the purified gas to a reservoir (a large gas bag will answer your pur-pose) that will adapt itself to the volume of the gas and maintain a steady pressure. In order to avoid reducing the luminosity of the gas, it is re-

> (24) R. F. asks. What is the best, cheapest, and most effectual means of removing salt water rust from boiler plate iron? A. Steep it in a weak pickle of oil of vitriol in water, and dry immediately with sawdust. It is better before placing it in pickle to go carefully over the sur

(25) S. D. asks; What will clarify a solution of 5 lbs. of Irish moss, boiled in 20 gallons of water, long enough to extract the gelatin? I want to get rid of the small particles, which give it a cloudy appearance. A. Mix with clean paper pulp, place in a fine linen bag, and strain. The paper and gelatin should be mixed and well stirred together while the gelatin is hot and as liquid as possible.

possible.

(26) H. S. S. C. asks: Will a house 30 feet by 3), covered with tin and having a water conductor at each corner connected with the ground by a copper wire, be sufficiently protected against lightning without a lightning rod? A. The water conductors, not being in the form of a compact body of metal, would hardly be so good as a rod; but, if provided with a pointed rod at top in connection with each, extending about three feet high above the roof, and a like rod extending some distance into the ground at the bottom, they might be considered safe.

(27) O. A. W. asks: Is there a chemical

might be considered safe.

(27) O. A. W. asks: Is there a chemical that, when rubbed on the hand, enables one to handle red hot iron or melted lead with impunity? A. No; but if the hand be damp with perspiration, or slightly moistened, it may for an instant be dipped in melted lead or white hot melted iron without burning or discomfort. The moisture is thrown into the spheroidal condition, and presents an effectual barrier against the inand presents an effectual barrier against the in-

(28) W. M. M. asks: How is a bichromate battery made? A. It consists usually of a large glass jar having within it a cup of porous unglazed porcelain. The intermediate space, between the sides of the vessels, is filled with dilute sulphuric acid (1 to 20), and contains a sheet of zinc shaped so as to conform to the curve of the inner cup, which it completely surrounds. A stick of gas carbon is placed in the porous cup, and surrounded with a fluid made by adding strong sulphuric acid to a saturated aqueous solution of bichromate of potassa until the chromic acid begins to separate in flakes, it is afterwards diluted a very little in order to redissolve the precipitate. The proportion of the several ingredients in this mixture should be about as follows: to about 10 ozs. of bichromate of potassa in 1 gallon of water, add 1 pint of strong oil of vit-(28) W. M. M. asks; How is a bichromate battery made ⁹ A. It consists usually of a large gallon of water, add 1 pint of strong oil of vit-

(29) S. asks: Is the common arsenic of the drug stores the kind that can be fused with block tin? A. No, use metallic arsenic.

MINERALS, ETC.—Specimens have been received from the following correspondents, and examined, with the results stated:

examined, with the results stated:

W.Z.J.—No. I is blue clay. No. 3 is a piece of slate. No. 4 is a variety of steatite. No. 5 is basalt. No. 6 is a piece of bituminous shale. No. 7 is chalcopyrite (sulphide of copper). A smaller specimen numbered 6 is an agate. No. 2 did not arrive.—P. & B.—It is nodular iron pyrites.—B. M. R.—No. I is a limestone fossil, but has been so badly damaged that we cannot classify it. No. 2 is a piece of shale.—S. S.—It is a broken quartz crystal.—S. L.—It is partially reduced oxide of copper.—W. E.—The color on the window blind does not contain arsenic. It is an organic pigment.—C. C.—They are garnets, of considerable value when large and perfect.—J. A. C.—It is a bituminous shale, and might be used for heating purposes.—S. J.—The sand might, if properly screened, find a limited employment for scouring, grinding, and p-lishing purposes, as well as in the manufacture of glass and glazes.

8. G. C. asks: Is there anything which will restore drawing paper, which has become soft from age and use so that Ink runs on it, sufficlearly to ink on a few lines at a time when necessary?—O. S. says: Can you inform me what is the yield of oil to the bushel of peanuts, and what are the means of extracting the oil?—J. L. R. Jr asks: Please tell me where the character \$ came

COMMUNICATIONS RECEIVED.

The Editor of the SCIENTIFIC AMERICAN acknowledges, with much pleasure, the receipt of original papers and contributions upon the follow-

On Weight on and in the Earth. By E. B. W. On the Polarity of the Compass Needle. By D.

On a Rope Swing. By J. S. P. On the Monjolo. By C. J. W.

Also inquiries and answers fro a the following A. S.—J. R.—J. A. P.—J. H. E.—C. C.—G. T. D.— J. M.—T. J. B.—J. McC.—W. B. P.—C. H. P.—H. H. —T. I. H.

HINTS TO CORRESPONDENTS

should repeat them. If not then published, they may conclude that, for good reasons, the Editor declines them. The address of the writer should always be given.

bility of inventions, assignments, etc., will not be published here. All such questions, when initial only are given, are thrown into the waste basket as it would fill half of our paper to print them all but we generally take pleasure in answering briefly by mail, if the writer's address is given.

by mail, if the writer's address is given.

Hundreds of inquiries analogous to the following are sent: "Who makes machines for pressing stove blacking? Who sells electric telegraph apparatus? Who sells propeller wheels? Who makes east steel bells? Who makes labeling machines?" All such personal inquiries are printed, as will be observed, in the column of "Business and Personal," which is specially set apart for that purpose, subject to the charge mentioned at the bead of that column. Almost any desired information can in this way be street. mentioned at the head of that column. Almost
any desired information can in this way be expeditiously obtained.

Grain grits, making, F. Schumacher...

[OFFICIAL]

INDEX OF INVENTIONS

Letters Patent of the United States were Granted in the Week Ending

August 8, 1876,

AND EACH BEARING THAT DATE.

[Those marked (r) are relasued patents.]

A complete copy of any patent in the annexed list

	farnished from this office for one dollar. In order please state the number and date of the patent de-	sired.
ľ	and remit to Munn &Co., 37 Park Row, New York	city.
	Aerometer, C. Godfrey 1	90,901 90,760
	Animal-weaning bit, Ingersoll & Fisher 1	80,958 90,885
		90,534
		80,930 80,836
	Bale tie, W. S. Davis (r)	7,252
	Bale tie lock, D. Ohrsted 1	80,910 80,788
	Ball and socket support, H. Howson 1	80,881 80,843
	Barrels, making, T. M. Healey 1	80,815
	Bedstead, extension, R. Righ 1	80,909
	Bedstead, sofa, J. A. Bigger	80,935 80,935
	Beveling machine, plate, Pedder & Abel	80,915
		80,871
		80,850
		190,883
	Boller, flue and tubular, A. J. Stevens	190,95g 190,968
	Boiler, feed water heater, M. W. Hazelton	180,876 180,714
	Boot upper, J. Mohan	180, 779
	Boots, forming stiffeners for, W. C. Wise	180,978
	Bottle washer, W. Scherenberg	180,976 180,937
	Brick and mop handles, S. J. Mather 180,723,	180,941
	Building block, F. Schaffer	180,926 180,794
	Burner, lamp, H. A. Chapin	180,753 180,980
	Car brake, S. G. Smith	180,502 180,728
	Car door, grain, R. Brydon	150,699
	Car starter, E. Salomon	180,792
	Car wheel, W. McConway	180,844
	Cartridge, H. C. Bull	190, 906 180,840
	Casting, mold and core for, H, and F. Tank	180,746 180,807
	Chain, drive, E. M. Morgan	180,903 180,907
	Chain swivel clamp, V. Draper	150,555 150,961
	Cheese cutter, H. S. Jones. Churn dasher, M. L. Traver	190,888 180,983
	Churn power, S. Weaver. Clay retorts, carriage for, W. D. Cliff	190,797 190,845
		180,899
	Clothes stick, D. B. Pond	180,919 180,799
		180, 943 180, 879
	Corn drill, D. R. Groves	180,879 180,870 180,875
	Cornet spring, T. M. Hass	150, 761
	Cotton duck, etc., preserving, W. Lewis Cotton gin saw, C. F. Scattergood	190,722
	Cracker machine, G. W. Baker	190,697 190,851
	Cradle, rocker and track etc., D. Rupp	180,983
	Cutlery, handle for table, A. Gottschalk	190,711
	Door, water fender, E. L. Valentine	180,967
	Drill chuck, rock, Roc & Tallman Duster, wool. E. C. Patterson.	180,730
	Ear ring, L. P. Jeaune	190,917
	Eaves trough hanger, Abbott et al	190,817
	Egg box, A. H. Bryant (r)	180,909
	Engine stuffing box, C. T. Sleeper	190,949
	Envelope, Magruder & Walsh	180,70
	Faucet, S. Kranshaar	180,968
	Feed cutter and grinder, H. G. Fritz	190,890
	Fifth wheel, E. J. Lucey	180,777
	Fire arm, breech-loading, A. Spellerberg	189,781
	Fireproof building, M. A. Burnham	180,750 180,940
j	Furnaces, steam, D. N. Melvin (r.)	180,696
1	Furnace, laundry, G. W. Robertson	7,250
	Furnaces, etc., lining puddling, M. E. P. Andonia	180,850
8	Gas generating, I. N. Stanley. Gas generator, carbonic seld, O. Zwietnsch	180,953
,	Gas lighting, electric, A. L. Borner, 199 and	180,800
r	Gas trap, sewer, J. M. Falk	150, 500
ť	Gate, farm, W. W. Gift.	150, 666
t	Glassware, making, L. Wagner	150.92
t	Couls with making W Schomanker	The same of the same of

rvester, H. L. Strock	
athinding, Starr & Whiting	190,805 180,954
v loader, J. L. Mathews	190,900
	180,813 180,811
ogs, moving and cooling, P. L. Groot	180,712
of parer, O. Rogers	190,731
	180,825 180,828
reshor (2 Smith	180,950
as coupling, W. A. Caswell (r)	7,251
	180,790
drant, C. H. Moore	190,790
dwarf fire I Hisbinhine	180,830
WEST, MILICIES OF MING WHILE OF COMPANY	180,785
dder W Small Jr	180,783
dder freman's J A Grosbon	190,761
dle, etc., C. P. Housum	7 256
teh cate C S Corrie	180,751
tch, mortise, A. H. Leach,	190,894
th machine, E. H. Hancock	190,872 190,947
	180,903
ck, combination, N. Friedman	150.738
CHE STORY S NOT THE WAR IN MINISTER STORY	180,874 180,965
comotive draft pipe, T. Diffenbaugh	150,853
om harness, J. G. Weeks	180,808
bricator J. W. Reed	180,925
	180,898 180,707
at, wood, S. Lewis,	180,771
olding flask, J. J. Lebeau	150,721
esquito bar, M. J. Waldron	180,972 180,782
otor, E. Pepple	180,786
ower, lawn, R. Hughes	180,768
usic stands, J. E. Schonacker180,795,	180,796 180,928
dl plate feeder, W. H. Rittenhouset lock, A. J. Potter	180,928
eaginous seeds, crushing, A. B. Lawther	180, 770
dlock, M. C. Hawkins	180,857 180,918
per-folding machine, R. M. Hoe	180,918
per pulp, making palls from, E. Hubbard	180,882
g float, J. & E. Popham	180,921
en and pencil case, J. Holland	180,715
otographic apparatus, J. B. David	180,704
otographic lens, H. E. Mead	180,776
notographic lens, A. & E. Ste nhell	180,957
notographic stand, M. Striegel	180,865
ck eyes, forming, Kiein et al	180,889
llow, spring, J. Beamer	180, 227
pe connection, A. O'Neill	180,911
ston, J. C. Wood, Jr	180,979
ane bench, J. Gorham	180,867
anter, corn, L. J. Corbin	180,702 180,846
anter, check row, J. B. Conn	190,742
low, H. Gale (r)	7,258
ow, reversible, J. Hartmann	180,713
ocketbook fastening, E. Schnopp	190,938
otato masher. A. Huffer	150,767
otato masher. A. Huffer	180,996
otato masher, A. Huffer ress, cotton, L. Lewis	180,996 180,961
otato masher, A. Huffer	180,996
otato masher, A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell	180,896 180,861 180,857 180,966 180,778
otato masher. A. Huffer ress, cotton, L. Lewis. rinting, autographic, T. A. Edison. rinting press cutting cylinder, S. D. Tucker. ropellers, raising and lowering, B. Mitchell. ump, W. S. & E. Buunt, Jr.	180,896 180,861 180,857 180,966 180,778 1F0,831
otato masher, A. Huffer	180,896 180,861 180,857 180,966 180,778
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, star Cope et al.	180,896 180,861 180,867 180,966 180,778 180,774 180,774 180,707 183,701
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar	180,896 180,881 180,887 180,966 180,778 1F0,831 180,774 180,757 183,701 180,924
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Bunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, Curtis & Thompson.	180,896 180,861 180,867 180,966 180,778 180,774 180,774 180,707 183,701
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uilting frame, F. McKenna addator, Curtis & Thompson. addator, steam, J. K. Abbott	180, 996 180, 851 180, 857 180, 966 180, 776 180, 776 180, 767 180, 767 180, 984 180, 986 180, 750 180, 750
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Bunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar. uliting frame, F. McKenna adjator, Cuttls & Thompson adjator, steam, J. K. Abbott adjator, steam, J. K. Abbott	180,996 180,861 180,857 180,966 180,778 1F0,831 180,751 180,751 180,702 180,924 180,905 180,753 180,753
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar, uliting frame, F. McKenna adiator, cuttis & Thompson, adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, Crane & Abbott adiatory axil joint, Waddell & Finger, aliway switch, J. C. Middleton	180, 996 180, 851 180, 857 180, 966 180, 776 180, 776 180, 767 180, 767 180, 984 180, 986 180, 750 180, 750
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographie, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uilting frame, F. McKenna adiator, Curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, Grane & Abbott adiator, steam, Crane & Abbott	180, 896 180, 861 180, 861 180, 861 180, 961 180, 778 180, 774 180, 787 180, 787 180, 763 180, 763
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, Crane & Abbott aliway rail joint, Waddell & Finger aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway switch, F. C. Weir aliway tack broom, M. C. Isaacs	180, 896 180, 861 180, 861 180, 768 180, 768 180, 778 180, 757 180, 757 180, 753 180, 753 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uitting frame. F. McKenna adiator, Curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiavay rail joint, Waddell & Finger. aliway switch, J. C. Middleton aliway switch, F. C. Weir. aliway track broom, M. C. Isaacs livets, M. Bray. 180,747, oiling sucker rod joints, L. Rogers.	180, 896 180, 861 180, 861 180, 861 180, 861 180, 778 170, 831 180, 774 180, 774 180, 763 180, 763 180, 763 180, 763 180, 777 180, 777
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, Crane &	180, 896 180, 851 180, 857 180, 857 180, 956 180, 778 180, 778 180, 701 180, 700 180, 703 180, 703 180, 703 180, 703 180, 954 180, 974 180, 717 180, 717 180, 718 180, 718
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway track broom, M. C. Isaacs. livets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. McIutyre. all, making solar, T. R. Timby	180, 896 180, 561 180, 567 180, 577 180, 778 180, 787 180, 787 180, 787 180, 906 180, 763 180, 763 180, 763 180, 763 180, 777 180, 774 180, 748 180, 748 180, 748 180, 748 180, 748 180, 969
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, sutographic, T. A. Edison. rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uilting frame, F. McKenna adiator, Curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, Crane & Abbott aliway witch, J. C. Middleton. aliway switch, J. C. Middleton. aliway switch, F. C. Weir aliway track broom, M. C. Isaacs ivets, M. Bray olling sucker rod joints, L. Rogers afe, provision, G. McIutyre. alt, making solar, T. B. Timby assh fastener, J. S. Hescock ash fastener, F. J. Hoyt	180, 996 180, 561 180, 567 180, 577 180, 578 180, 778 180, 778 180, 787 180, 783 180, 763 180, 763 180, 763 180, 763 180, 777 180, 974 180, 777 180, 974 180, 777 180, 974 180, 783 180, 783 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, J. C. Middleton aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, J. C. Weir aliway tack broom, M. C. Isaacs livets, M. Bray oling sucker rod joints, L. Rogers afe, provision, G. Melntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, F. J. Hoyt ash fastener, T. Thorn	180, 896 180, 561 180, 557 180, 577 180, 778 180, 778 180, 787 180, 787 180, 763 180, 763 180, 763 180, 763 180, 763 180, 777 180, 774 180, 774 180, 748 180, 748 180, 748 180, 748 180, 969 180, 777 180, 748 180, 969 180, 777 180, 748 180, 969 180, 777 180, 969
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uilting frame. F. McKenna adiator, Curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adilator, steam, J. K. Abbott adilator, steam, J. C. Middleton allway rail joint, Waddell & Finger, allway switch, J. C. Middleton allway switch, F. C. Welr. allway track broom, M. C. Isaacs, ivets, M. Bray oliting sucker rod joints, L. Bogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn as west, C. Heinen.	180, 896 180, 851 180, 857 180, 557 180, 778 170, 831 180, 757 180, 763 180, 763 180
otato masher. A. Huffer ress, cotton, L. Lewis rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, Mayer & Wirtz ump, steam, Cope et al. umching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, Crane & Abbott adiator, steam, Crane & Abbott adiator, steam, M. C. Middleton aliway rack broom, M. C. Isaacs lives, M. Bray oliling sucker rod joints, L. Rogers afe, provision, G. Melntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, F. J. Hoyt ash fastener, T. Thorn aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp	180, 896 180, 581 180, 587 180, 596 180, 778 1F0, 831 1F0, 831 180, 757 180, 767 180, 767 180, 750 180, 750 180, 750 180, 777 180, 748 180, 748 180, 748 180, 748 180, 962 180, 592 180, 576 180, 588 180, 578 180, 578 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway switch, F. C. Weir aliway switch, J. C. Middleton aliway switch, J. C. Middleton aliway track broom, M. C. Isaacs. Ivets, M. Bray oiling sucker rod joints, L. Bogers, afe, provision, G. McIntyre, alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen, awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith	180, 896 180, 561 180, 567 180, 567 180, 566 180, 778 180, 787 180, 787 180, 787 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 869 180, 873 180, 869 180, 873 180, 869 180, 873
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell cump, W. S. & E. Buunt, Jr. cump, Mayer & Wirtz cump, ship's, Eels & Loud cump, team, Cope et al. cump, machine, feed, L. Prahar culting frame. F. McKenna adiator, Curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott aliway rail joint, Waddell & Finger. aliway switch, J. C. Middleton aliway switch, F. C. Weir. aliway strack broom, M. C. Isaacs livets, M. Bray oiling sucker rod joints, L. Rogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Heines. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Babse & Haendel	180, 896 180, 551 180, 557 180, 557 180, 557 180, 758 160, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 716 180, 718 180, 718 180, 718 180, 952 180, 952
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uitting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway switch, F. C. Weir aliway sway track broom, M. C. Isaacs. Ivets, M. Bray oiling sucker rod joints, L. Bogers, afe, provision, G. McIntyre, alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen, awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith chool furniture, Bahse & Haendel. crow-threading device, Green & Thomson, eed drill fertilizer distributer, L. W. Shepard	180, 896 180, 551 180, 557 180, 966 180, 778 170, 831 180, 771 180, 771 180, 752 180, 966 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 974 180, 978 180, 9
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uitting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway switch, F. C. Weir aliway sway track broom, M. C. Isaacs. Ivets, M. Bray oiling sucker rod joints, L. Bogers, afe, provision, G. McIntyre, alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen, awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith chool furniture, Bahse & Haendel. crow-threading device, Green & Thomson, eed drill fertilizer distributer, L. W. Shepard	180, 896 180, 551 180, 557 180, 966 180, 778 170, 831 180, 771 180, 771 180, 752 180, 966 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 753 180, 974 180, 978 180, 9
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uitting frame. F. McKenna adiator, Curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott aliway witch, J. C. Middleton aliway switch, J. C. Middleton aliway track broom, M. C. Isaacs livets, M. Bray oiling sucker rod joints, L. Rogers afe, provision, G. McIntyre. alt, making solar, T. B. Timby ash fastener, J. S. Heacock ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Babse & Haendel. crew-threading device, Green & Thomson. eed drill fertilizer distributer, L. W. Shepard eparator, grain, J. M. Williams.	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 871 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 860
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uitting frame. F. McKenna adiator, Cuttis & Thompson. adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, J. K. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, F. C. Welr. allway track broom, M. C. Isaacs, tivets, M. Bray oliling sucker rod joints, L. Rogers, afe, provision, G. McIntyre, alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen, awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel, crow-threading device, Green & Thomson eed drill fertilized distributer, L. W. Shepard eparator, cranberry, E. Buzby cparator, grain, J. M. Williams ewer excavator, D. Keating, ewer gas trap, J. M. Falk,	180, 896 180, 561 180, 577 180, 966 180, 778 170, 831 180, 767 180, 767 180, 767 180, 768 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell tump, W. S. & E. Buunt, Jr. tump, Mayer & Wirtz tump, Mayer & Wirtz tump, ship's, Eels & Loud tump, team, Cope et al. tump,	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 831 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 850 180, 850 180, 850 180, 851 180, 850 180, 851 180, 853 180, 755 180, 850 180, 850 180, 851 180, 853 180, 755 180, 850 180, 850 180, 853 180, 755 180, 755 180, 756
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway track broom, M. C. Isaacs livets, M. Bray olling sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. B. Timby ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Babse & Haendel crow-threading device, Green & Thomson ced drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buzby eparator, grain, J. M. Williams ewer gas trap, J. M. Falk ewing books, H. R. Heyl ewing books, H. R. Heyl ewing machine, button-hole, E. S. Spaulding,	180, 896 180, 561 180, 577 180, 596 180, 778 1F0, 831 1F0, 831 180, 757 180, 757 180, 757 180, 757 180, 756 180, 969 180, 756 180, 969 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 748 180, 890 180, 901 180, 800 180, 801 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803 180, 803
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell tump, W. S. & E. Buunt, Jr. tump, Mayer & Wirtz tump, ship's, Eelis & Loud tump, steam, Cope et al. tump, team, J. K. Abbott adiator, curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir. allway track broom, M. C. Isaacs tivets, M. Bray tolling sucker rod joints, L. Bogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen. aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Babse & Haendel crow-threading device, Green & Thomson, ced drill fertillizer distributer, L. W. Shepard eparator, grain, J. M. Williams, ewer gas trap, J. M. Falk ewing books, H. B. Heyl, ewing machine, button-hole, E. S. Spaulding, heet metal elbow, A. Syverson hip's rigging leader, J. Sampson	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 817 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 860
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway switch, J. C. Middleton aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway track broom, M. C. Isaacs livets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. Melntyre ait, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Heinen awing machine, A. McCreight corf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel corew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Busby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. R. Heyl ewing machine, button-hole, E. S. Spaulding, heet metal clow, A. Syverson, hip's rigging leader, J. Sampson hoe, J. E. Beasley	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 831 180, 757 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 969 180, 716 180, 969 180, 748 180, 716 180, 890 180, 891 180, 793 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell tump, W. S. & E. Buunt, Jr. tump, Mayer & Wirtz tump, ship's, Eelis & Loud tump, steam, Cope et al. tump, ship's, Eelis & Loud tump, steam, Cope et al. tump, steam, J. K. Abbott adiator, curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir. allway track broom, M. C. Isaacs tivets, M. Bray. tolling sucker rod joints, L. Rogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thora aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Babse & Haendel crow-threading device, Green & Thomson, ced drill fertillizer distributer, L. W. Shepard eparator, cranberty, E. Buzby eparator, grain, J. M. Williams, ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. B. Heyl, ewing machine, button-hole, E. S. Spanlding, heet metal elbow, A. Syverson, hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, iliver ore, treating, F. Dibleen.	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 837 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 850
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, Crane & Abbott adiator, steam, J. C. Middleton aliway rack broom, M. C. Isaacs livets, M. Bray	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 831 180, 757 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 969 180, 716 180, 969 180, 716 180, 969 180, 716 180, 969 180, 716 180, 969 180, 716 180, 890 180, 818 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umching machine, feed, L. Prahar uitting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway rail joint, Waddell & Finger allway switch, J. C. Middleton allway switch, F. C. Weir allway switch, F. C. Weir allway track broom, M. C. Isaacs. livets, M. Bray oiling sucker rod joints, L. Bogers. afe, provision, G. McIntyre. alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, T. Thora aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel. crow-threading device, Green & Thomson. eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buzby eparator, cranberry, E. Suzby eparator, cranberry, E. Suzby eparator, cranberry, E. Suzby eparator, cranberry, E. Sapauding, heet metal elbow, A. Syverson, hip's rigging leader, J. Sampson, hoc, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, diver ore, treating, F. Dibben, kirt protector, G. Schwab, oldering fron heater, J. H. Whitting	180, 896 180, 561 180, 577 180, 966 180, 778 180, 967 180, 771 180, 771 180, 771 180, 772 180, 966 180, 783 180, 866 180, 783 180, 874 180, 962 180, 962 180, 963 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763 180, 763
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell tump, W. S. & E. Buunt, Jr. tump, Mayer & Wirtz tump, ship's, Eelis & Loud tump, steam, Cope et al. tump, team, Cope et al. tump, team, Cope et al. tump, team, Cope et al. tump, steam, Cope et al. tump, team, J. K. Abbott adiator, curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir. allway track broom, M. C. Isaacs tivets, M. Bray tolling sucker rod joints, L. Bogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen. aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crow-threading device, Green & Thomson, ced drill fertillizer distributer, L. W. Shepard eparator, grain, J. M. Williams, ewer gas trap, J. M. Falk ewing books, H. B. Heyl, ewing machine, button-hole, E. S. Spaulding, heet metal cibow, A. Syverson hip's rigging leader, J. Sampson, hoc, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, diver ore, treading, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whitling, oldering iron heater, J. H. Whitling, oldering iron heater, J. H. Whitling, oldering of the contraction of the contraction of the part	180, 896 180, 561 180, 577 180, 566 180, 778 180, 757 180, 757 180, 757 180, 757 180, 756 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar uniting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway rail joint, Waddell & Finger aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway sway track broom, M. C. Isaacs. Ivets, M. Bray oiling sucker rod joints, L. Bogers. afe, provision, G. McIntyre. alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, T. Thora aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith chool furniture, Bahse & Haendel. crow-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buzby eparator, cranberry, E. Buzby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing machine, button-hole, E. S. Spaulding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, diver ore, treating, F. Dibben, kirt protector, G. Schwab, oidering iron heater, J. H. Whitling pirometer, W. H. Burt, tean, condensing, W. Walker titch machine, imitation, E. Brown	180, 896 180, 561 180, 577 180, 966 180, 778 170, 837 180, 767 180, 767 180, 767 180, 768 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering. B. Mitchell tump, W. S. & E. Buunt, Jr. tump, Mayer & Wirtz tump, ship's, Eelis & Loud tump, steam, Cope et al. tump, team, J. K. Abbott adiator, curtis & Thompson. adiator, curtis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, J. C. Middleton allway strack broom, M. C. Isaacs tivets, M. Uray tolling sucker rod joints, L. Bogers afe, provision, G. McIntyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, T. Thora aw set, C. Heinen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson. eed drill fertillizer distributer, L. W. Shepard eparator, cranberry, E. Busby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. R. Heyl. ewing machine, button-bole, E. S. Spaulding, heet metal cibow, A. Syverson. hip's rigging leader, J. Sampson, hoo, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, ilker ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whitling phrometer, W. H. Bart team, condensing, W. Walker titch machine, imitation, E. Brown titch machine, imitation, E. Brown topped and the protector. Schwab, One-sawing machine, J. Penjer	180, 896 180, 561 180, 577 180, 566 180, 778 180, 767 180, 767 180, 767 180, 767 180, 767 180, 766 180, 766 180, 766 180, 766 180, 766 180, 766 180, 766 180, 766 180, 766 180, 766 180, 860 180, 765 180, 766 180
otato masher. A. Huffer ress, cotton, L. Lewis rinting autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, Mayer & Loud ump, Mayer & Wirtz ump, Mayer & Wirtz ump, Mayer & Wirtz ump, Mayer & Wirtz ump, Mayer & Mokena adiator, steam, Cope et al. umching frame, F. McKenna adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway ratch broom, M. C. Isaacs livay as witch, J. C. Middleton aliway switch, J. C. Wirt aliway ratch broom, M. C. Isaacs livats, M. Bray olithing sucker rod joints, L. Rogers afe, provision, G. Melityre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, J. J. H. Williams ever fpin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel, crew-threading device, Green & Thomson, eed drill fertillizer distributer, L. W. Shepard eparator, cranberry, E. Busby eparator, grain, J. M. Williams ever excavator, D. Keating, ever gas trap, J. M. Falk eving books, H. B. Heyl eving machine, button-hole, E. S. Spaulding, heet metal elbow, A. Syverson, hip's rigging leader, J. Sampson, hoo, J. E. Beasley liks, etc., boiling and dyeing, L. Leigh, inver ore, treating, F. Dibben kirt protector, G. Schwab, oldering iron heater, J. H. Whiting pitrometer, W. H. Burt toon, condensing, W. Walker stitch machine, imitation, B. Brown tone-aswing machine, J. Tepier, toton, coal oil, N. H	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 871 180, 757 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 969 180, 716 180, 969 180, 716 180, 969 180, 716 180, 969 180, 878 180, 718 180, 718 180, 718 180, 718 180, 718 180, 718 180, 890 180, 818
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umphing machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway rall joint, Waddell & Finger allway switch, F. C. Weir allway frack broom, M. C. Isaacs. Ivets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buxby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. B. Heyl ewing machine, button-hole, E. S. Spaniding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, liver ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whilling, phrometer, W. H. Burt towe pipe thimble and register, C. Pertit tove, poal oil, N. H. Sherburne, tove, coal oil, N. H. Sherburne, tove, poal oil, N. H. Sherburne, tove, coal oil, N. H. Sherburne, towe pipe thimble and register, C. Pertit	180, 896 180, 561 180, 577 180, 966 180, 778 180, 767 180, 771 180, 771 180, 772 180, 566 180, 753 180, 566 180, 753 180, 566 180, 753 180, 574 180, 567 180, 568
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. unching machine, feed, L. Prahar untiting frame, F. McKenna adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, F. C. Welr. allway track broom, M. C. Isaacs. Ivets, M. Bray oilling sucker rod joints, L. Rogers. afe, provision, G. McIntyre. alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thorn aw eet, C. Heinen. awing machine, A. McCreight carf pin, A. Komp. cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel. crow-threading device, Green & Thomson, eed drill fertilizer distributer, L. W. Shepard eparafor, cranberry, E. Busby eparafor, grain, J. M. Williams ewer excavator, D. Keating, ewer gas trap, J. M. Falk ewing books, H. B. Heyl ewing machine, button-bole, E. S. Spaulding, heet metal elbow, A. Syverson, hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, iliver ore, treating, F. Dibben, kirt protector, G. Schwab, oidering iron heater, J. H. Whiting, pirometer, W. H. Burt, tecan, condensing, W. Walker titch machine, imitation, E. Brown tone-swing machine, J. Pepier, tove, coal oil, N. H. Sherburne, tove pipe thimble and register, C. Pettil uspenders, F. C. Wright uspenders, P. C. Wright uspenders, P. C. Wright uspenders, P. C. Wright uspenders, P. C. Wright	180, 896 180, 561 180, 577 180, 966 180, 778 180, 767 180, 771 180, 772 180, 767 180, 763 180, 866 180, 733 180, 816 180, 816 180, 871 180, 717 180, 717 180, 717 180, 717 180, 717 180, 717 180, 717 180, 717 180, 717 180, 718 180, 801 180, 862 180, 862 180, 863 180, 863 180, 863 180, 863 180, 863 180, 863 180, 863 180, 763
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. ump, team, Cope et al. unching machine, feed, L. Prahar uliting frame. F. McKenna adiator, cuttis & Thompson. adiator, cuttis & Thompson. adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Middleton allway rail joint, Waddell & Finger. allway switch, J. C. Middleton allway switch, F. C. Welr. allway track broom, M. C. Isaacs, tivets, M. Bray oliling sucker rod joints, L. Rogers, afe, provision, G. McIntyre, alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, T. Thora aw set, C. Heinen, awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel, crow-threading device, Green & Thomson eed drill fertilized distributer, L. W. Shopard eparator, cranberry, E. Buzby cparator, grain, J. M. Williams ewer excavator, D. Keating, ewer gas trap, J. M. Falk, ewing books, H. B. Heyl ewing machine, button-hole, E. B. Spaulding, heet metal elbow, A. Syverson, hip's rigging leader, J. Sampson hoo, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, liver ore, treating, F. Dibben kirt protector, G. Schwab, holdering iron beater, J. H. Wbitling prometer, W. H. Burt tecan, condensing, W. Walker stitch machine, imitation, E. Brown hone-swing machine, J. Pepier tove, coal oil, N. H. Sherburne tove pipe thimble and register, C. Pettil uspenders, P. C. Wright auspenders, P. C. Wright	180, 896 180, 561 180, 577 180, 966 180, 778 180, 767 180, 771 180, 772 180, 767 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton, and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. umching machine, feed, L. Prahar uliting frame, F. McKenna adiator, curtis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway ratck broom, M. C. Isaacs livets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. B. Timby ash fastener, J. S. Hescock ash fastener, F. J. Hoyt ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel cerew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Busby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. B. Heyl ewing machine, button-hole, E. S. Spaulding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson hoe, J. E. Beasley liks, etc., boiling and dyeing, L. Leigh, inver ore, treating, F. Dibben kirt protector, G. Schwab, oldering iron heater, J. H. Whiting pirometer, W. H. Burt toon-sawing machine, J. Pepier tove, coal oil, N. H. Sherburne tove pipe thimble and register, C. Pettil uspenders, F. C. Wright uspenders, button strap for, J. B. Sharp, Table, chair, and walking stool, W. C. McGilli, able, leveluge, N. N. elson hable legt support, J. D. Alward	180, 896 180, 561 180, 567 180, 567 180, 566 180, 778 180, 757 180, 757 180, 757 180, 757 180, 756 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umphing machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway switch, F. C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buxby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing machine, button-hole, E. S. Spaniding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson, hoe, J. E. Beasley Wiks, etc., boiling and dyeing, L. Leigh, liver ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whilling, prometer, W. H. Burt towe pipe thimble and register, C. Pettit uspenders, button strap for, J. B. Sharp achie, chair, and walking stool, W. C. Megfill, rable, chair, and walking stool, W. C. Megfill, rable, chair, and walking stool, W. C. Megfill	180, 896 180, 561 180, 577 180, 576 180, 778 180, 757 180, 757 180, 757 180, 757 180, 756 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Bunt, Jr. ump, Mayer & Wirtz ump, ship's, Eelis & Loud ump, steam, Cope et al. umching machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway ratck broom, M. C. Isaacs livets, M. Bray olling sucker rod joints, L. Rogers afe, provision, G. Melutyre. alt, making solar, T. B. Timby ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Hetnen. awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Balase & Haendel crow-threading device, Green & Thomson ced drill ferillizer distributer, L. W. Shepard eparator, cranberry, E. Buby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, I. M. Falk ewing books, H. R. Heyl ewing books, H. R. Heyl ewing machine, button-hole, E. S. Spaulding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson hoe, J. E. Beasley like, etc., boiling and dyeing, L. Leigh, lillyer ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron beater, J. H. Wbitting phrometer, W. H. Burt, tecano, condensing, W. Waiker titch machine, imitation, E. Brown tore, coal old, N. H. Sherburne, tove, coal old, N.	180, 896 180, 561 180, 577 180, 566 180, 778 1F0, 817 180, 757 180, 757 180, 757 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 756 180, 869 180, 716 180, 869 180, 878 180, 718 180, 878 180, 718 180, 878 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umphing machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway switch, F. C. Weir allway track broom, M. C. Isaacs. livets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buxby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. B. Heyl ewing machine, button-hole, E. S. Spaniding, heet metal cibow, A. Syverson hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, liver ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whitling prometer, W. H. Burt towe pipe thimble and register, C. Pettit uspenders, button strap for, J. B. Sharp, athle, chair, and walking stool, W. C. MeGill, rable, chair, and walking stool,	180, 896 180, 561 180, 577 180, 966 180, 778 180, 966 180, 770 180, 770 180, 701 180, 701 180, 703 180, 966 180, 733 180, 816 180, 974 180, 974 180, 962 180, 962 180, 963 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay, Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Bunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umching machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton aliway switch, J. C. Middleton aliway switch, F. C. Weir aliway switch, F. C. Weir aliway ratck broom, M. C. Isaacs livets, M. Bray olling sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. B. Timby ash fastener, F. J. Hoyt ash fastener, T. Thora aw set, C. Hetnen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson ced drill ferillizer distributer, L. W. Shepard eparator, cranberry, E. Buby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. R. Heyl ewing books, H. R. Heyl ewing machine, button-hole, E. S. Spaulding, heet metal cibow, A. Syverson, hip's rigging leader, J. Sampson hoe, J. E. Beasley like, etc., boiling and dyeing, L. Leigh, lillyer ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron beater, J. H. Wbitting phrometer, W. H. Burt tector, condensing, W. Walker titch machine, imitation, E. Brown towe, coal old, N. H. Sherburne, towe opipe thimble and register, C. Petili uspenders, P. C. Wright uspenders, button strap for, J. B. Sharp able leaf sengenders, button strap for, J. B. Sharp able, chair, and walking stool, W. C. McGill, able, Irondup, N. Nelson able, Irondup, J. A. Edison elegraph key, J. O. Byrns elegraph key, J. O. Byrns elegraph contenting, J. P. Quesada obacco, testmind and cutting, J. P. Smothers c	180, 896 180, 561 180, 567 180, 567 180, 567 180, 767 180, 757 180, 757 180, 757 180, 756 180
otato masher. A. Huffer ress, cotton, L. Lewis ress, cotton and hay. Z. S. Freeman rinting, autographic, T. A. Edison rinting press cutting cylinder, S. D. Tucker ropellers, raising and lowering, B. Mitchell ump, W. S. & E. Buunt, Jr. ump, Mayer & Wirtz ump, ship's, Eells & Loud ump, steam, Cope et al. umphing machine, feed, L. Prahar uliting frame, F. McKenna adiator, cuttis & Thompson adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. K. Abbott adiator, steam, J. C. Middleton allway switch, J. C. Middleton allway switch, F. C. Weir allway switch, F. C. Weir allway track broom, M. C. Isaacs. livets, M. Bray oliting sucker rod joints, L. Rogers afe, provision, G. Melutyre alt, making solar, T. R. Timby ash fastener, J. S. Hescock ash fastener, J. S. Hescock ash fastener, T. Thorn aw set, C. Heinen awing machine, A. McCreight carf pin, A. Komp cholar's companion, J. S. Smith, chool furniture, Bahse & Haendel crew-threading device, Green & Thomson eed drill fertilizer distributer, L. W. Shepard eparator, cranberry, E. Buxby eparator, grain, J. M. Williams ewer excavator, D. Keating ewer gas trap, J. M. Falk ewing books, H. B. Heyl ewing machine, button-hole, E. S. Spaniding, heet metal cibow, A. Syverson hip's rigging leader, J. Sampson, hoe, J. E. Beasley ilks, etc., boiling and dyeing, L. Leigh, liver ore, treating, F. Dibben, kirt protector, G. Schwab, oldering iron heater, J. H. Whitling prometer, W. H. Burt towe pipe thimble and register, C. Pettit uspenders, button strap for, J. B. Sharp, athle, chair, and walking stool, W. C. MeGill, rable, chair, and walking stool,	180, 896 180, 561 180, 567 180, 567 180, 567 180, 767 180, 757 180, 757 180, 757 180, 756 180

Turnstile, electric register, R. J. Sheehy 180,94
Umbrella, G. B. Kirkham
Umbrella runner, H. S. Frost
Umbrella support, A. H. Adams
Umbrellas, ferrule for, H. S. Frost.
Universal Joiner, E., E. C., & E. W. Strange 100 mg
Valve, safety, C. H. Thompson.
Vehicle running gear, M. T. Jackson.
Vehicle spring, C. B. Koon
Vehicles, brake for light, Appel & Rothenberger up me
Ventilating buildings, M. A. Burnham.
Ventilating buildings, F. Gresves 180 no.
Wagon for delivering coal, A. Iske 180 500
Wagon spring attachment, R. & J. Doty 150 use
Wash bench, H. C. & F. L. Paine 180 701
Wash bench, P. E. Rudel 180 000
Wash bench and ironing table, W. J. Lake 100,899
Wash stand, W. H. Zinn tan and
Washing and wringing machine, T. H. Patee 180 at
Washing machine, G. Brooks 180,756
Washing machine, J. M. Curtice 180 559
Washing machine, A. D. & A. N. Ferris 180,500
Washing machine, boiler, G. A. Starkweather 100 Tur
Watches, etc., stem winding, H. Abbott 180.730
Wells, packing and steaming oil, M. Harold 180,873
Wheel tire, G. Cornwall 180.847
Whip socket, J. J. Schalrer 180,50g
Windmill, H. W. Bolender 180,744
Wire-bending machine, E. I. Braddock 180,745
Wringer, R. C. Browning 180,837
Yoke, neck, C. F. Whipple 180,812
TOPSTONS DATENTED

434.—BRACKLETS.—I. Rice, New York city. 435.—Ash Boxes.—A. Schmitt, Williamsburg, N. Y. 436.—FINGER RING.—A. V. Moore, Hackensack, N. J

(A copy of any one of the above patents may be had by emitting one dollar to MUNN & Co., 37 Park How, New

	SCHEDULE OF PATENT FEED,	
On e	each Caveat \$10	ı
One	each Trade mark\$25	
Ont	lling each application for a Patent (17 years) \$15	
On I	ssuing each original Patent826	ı
On	appeal to Examiners-in-Chief	ı
On i	appeal to Commissioner of Patents826	ı
On	application for Reissue830	ı
Ont	filing a Disclaimer	ı
	an application for Design 3% years)	
00.1	application for Design (7 years)	ı
On	application for Design (14 years)	ä
	the second secon	

THE VALIDITY OF PATENTS.

THE VALIDITY OF PATENTS.

We recommend to every person who is about to purchase a patent, or about to commence the manufacture of any article under a license, to have the patent carefully examined by a competent party, and to have a research made in the Patent Office to see what the condition of the art was when the patent was issued. He should also see that the claims are so worded as to cover all the inventor was entitled to when his patent was issued: and it is still more essenis patent was issued; and it is still more essenhis patent was issued; and it is still more essential that he be informed whether it is an infringement on some other existing patent. Parties desiring to have such searches made can have them done through the Scientific American Patent Agency, by giving the date of the patent and stating the nature of the information desired. For further information, address MUNN & CO., 37 PARK ROW, New York.

Advertisements.

Inside Page, each insertion - - - 75 cents a line. Back Page, each insertion - - - \$1.00 a line. Ingravings may head advertisements at the same rate per line, by measurement, as the letter press. Adver-

\$200 a month. Outfit worth \$1 free to agent

JOHN WILEY & SONS, 15 Autor Place, NEW YORK Publish Prof. S. E. Warren's Series of Prepara-tory, College, and Polytechnic School Text Books.

Free-hand Geometrical Drawing and Lettering.

Free-hand Geometrical Drawing and Letterus. Elementary Plane Problems.
Drafting Instrum'ts, Materials, and Operations. Elementary Projection or Plan and Elevation Drawing, with Shadows & Isometric Drawing. Elementary Perspective of Forms and Shadows. Descriptive Geometry. Complete Solutions, Large Figures, Examples for Practice.
Shades and Shadows. Concludy comprehensive.

Shades and Sundows. Concacy Conjugate Hinear Perspective. General and Practical Problems. Machine Construction and Drawing. Gentlag. Ac. Stereotomy: Problems in Stone Cutting.

For full Descriptive Catalogue and Circulars, Terms. Ac., address as above. Also for sale by all leading Book.

WILEY & SONS' new complete Descriptive ue of Scientific Text Books and Practical Works

FRICTION CLUTCHES CO. PROV.R.I.

EDSON'S RECORDING GAUGE FOR STEAM OR WATER.

Todd & Rafferty Machine Co.

MANUPACTURERS OF
The celebrated Greene Variable Cut-Off Engine, Lowe's
Patent Tubutar and Five Bollers, Plain Side Valves,
The celebrated Greene Variable Cut-Off Engine, Lowe's
Patent Tubutar and Five Bollers, Plain Side Valves,
Town Condens, Baggring, Hope, Plax, and Hemp Machherry,
Agents for the New Haven Manufacturing Co. * Machle
Int. Tools, for Judgon's Governors and Stop Valves,
Startevant Blowers, and Differential Puller-Ribetts
WORKS, PATERSON, NEW JERSEY.

OSE'S COMPLETE PRACTICAL MACHIN

S COMP By 120 pages, 12100, bessured 120 pages, 12100, bessured 120 pages, 12100 pages, 12100 pages, 1200 pages, 1

MERY WHEELS.-For Sale, Cheap about 400 Emery Wheels. Part 1 in. face, part 1)



FOR GRINDING BONES.

DISINTEGRATING MILL.

MACHINERY OF EVERY DESCRIPTION, BULLED SHAFTING, HANGERS, PULLEYS, LINGS, BELLTING, TANITE EMERY WHEELS GRINDERS, IN STOCK.

GEORGE PLACE,
121 Chambers & 103 Reade Sts., New York City.

HOW TO BUILD CHEAP BOATS. By Pad

ROSE'S COMPLETE PRACTICAL MACHIN-7S COMPLETONS, 576 pages, 12mo, beautifully Price \$2,50 by mail, free of postage. HENRY CAREY BAIRD & CO., Industrial Publishers, 810 Walnut St., Philadelphia



THREE THINGS IN ONE

VENTILATION of a Fire Place; CIRCULATION of a Furnace

Pure Air and an Even Temperature throughout a Room. 'THE CENTENNIAL," Annex Main Building.

THE OPEN STOVE VENTILA-TING COMPANY, 107 Fulton St., YORK, T. 107 Fulton St.,

Cotton Seed Huller.

OR SALE-Patent right of expanding Drill Supplies a want long felt in every machine shop dress P. DUFFY, 238 Nor. 3d St., New Bedford, Mass

Steel Castings,

ANTED—Circulars and Catalogues, Price Lists of Articles suitable for the Swedish Market. ss W. B. NIELSEN, Engineer, Malmo, Sweden.

VINEGAR. 10 HOURS from

UNITED STATES PATENT ASSOCIATION.

ntors, Owners of Patents, Manufacturers of Pat-Articles, and all who are interested in the subject, vited to be present and to co-operate in this move-

ient.
Visitors from abroad are specially invited to take part
of the proceedings. JOHN S. PERRY, President.
CHARLES F. STANSBURY, Secretary.

TOW TO MAKE SPIRAL SPRINGS. Joshus Rose. With three engravings of the tools, which are easily made, and complete practical directions for working, including Hardening and Temperale. Frice Oceats. Contained to SCIENTIFIC AMERICAN SUPPLEMENT NO. 20. To be had at this office and at all News Stores throughout the country.

WHIPPLE'S Patent Door Knob.

warded a Bronze Medal at the American Institute Fair or 1874. The Judges say: "We consider this method or astening DOOR KNOBS a great improvement over any-hing yet invented for the purpose, as it obviates the use if side screws and washers, and can be regulated to suit my thickness of Doors." Send for Circular. THE PARKER & WHIPPLE COMPANY, West Meriden, Conn., or yi Chambers St., N. Y.

N. F. BURNHAM'S 1874 TURBINE

Water Wheel Has DISPLACED hundreds of other Turbines, but HAS NEVER BEEN IT SELF DISPLACED. Pamphlet Free. N. F. Burnham, York, Pa.

R OSE'S COMPLETE PRACTICAL MACHIN
187, 120 illustrations, 376 pages, 12mo, beautifully
printed. Price \$2.50 by mail, free of postage.
HENRY CAREY BAIRD & CO.,
Industrial Publishers, 510 Walnut St.,
Philadelphia.

WOODWORTH SURFACE PLANERS \$125. Planers and Matchers, \$250. S. C. HILLS, \$1 Courtland street, New York.





STEAM PUMPS.

FIRST PRIZES, VIENNA, PARIS, NEW YORK,
BALTIMORE, BOSTON.

Send for circular of recent patented improvements.

THE NORWALK IRON WORKS.

South Norwalk. Conn.

Lathes, Planers, Shapers, Drills, Gear & Bolt Cutters, &c. E. GOULD, Newark, N. J.

MANUFACTURER OF FIRST CLASS TAPS AND DIES, Pawtucket, R. I.

ROSE'S COMPLETE PRACTICAL MACHINprinted. Price \$2.50 by mail, free of postage.
HENRY CAREY BAIRD & CO.,
Industrial Publishers, 810 Walnut 81.,
PHILAPRIPIA.

WATER SUPPLY FOR TOWNS AND VIL

SPARE THE CROTON & SAVE THE COST Driven or Tube Wells



NEW YORK.

outer. Please say where you saw this. PHOTO-ENGRAVING CO., 67 Park Place, New York.

\$50. SCREW-CUTTING FOOT LATHES-Foot Drill Presses. Send for Circular to H. L. SHEPARD, Cincinnati, O.

I RON CLANING MACHINES A SPECIALTY.
C WHITCOMB & CO., M'f'rs, Worcester, Mass.

BIG PAY to sed our RUBBRE PRINTING STAMPS.

R OSE'S COMPLETE PRACTICAL MACHIN1ST, 130 illustrations, 376 pages, 12mo, beautifully
printed. Price \$2.50 by mail, free of postage.
HENRY CAREY BAIRD & CO.,
Industrial Publishers, 310 Walnut St.,
PRILADELPHIA.

GUITERMAN, Export and Commission Mer-chant. 2 Fountain Court, Aldermanbury, London. New York Office, Guiterman Bros., 454 Broadway. Best of attention to introduce Merchandise. Patents, etc., in any part of Europe.

ENGINE LATHES, PLANERS, DRILLS, &c.

MACHINERY OF IMPROVED STYLES FOR making SHINGLES, HEADING, and STAVES; also GUAGE LATHES for TURNING HANDLES. Sole makers of Laws Pat. Shingle and Heading Sawing Ma-chine. Address TREVOR & CO., Lockport, N. Y.

LOSSOM ROCK, HARBOR OF SAN FRANCISCO.
Full Account of its Removal, Method and Cost. By
Col. R. S. Williamson. With 23 lilustrations, diagrams,
&c. Presenting valuable information for engineers.
Price locents. Contained in SCIENTIFIC AMERICAN
SUPPLEMENT, No. 24. To be had at this Office and of



ENGINEERS and Engine Owners should all understand the ALLEN GOVERNOR. Illustrated circular sent free. S. S. ALLEN, Boston

Planing & Matching.

Moulding, Re-sawing, and Tenoning Machines. Scroll

Saws and General Wood-Working Machinery

JOHNB. SCHENCK'S SONS | Matteawan, M. Y.

Bend for Catalogue. (118 Liberty St., N.Y. city.

\$12 a day at home. Agents wanted. Outfit and terms free. TRUE & Co., Augusta, Maine.

Wood-Working Machinery,

Such as Woodworth Planing, Tongueing, and Grooving Machines. Danier's Planers, Richardson's Patent Im-groved Tenon Machines, Mortising, Moulding, and Re-saw Machines, and Wood-Working Machinery gene-

BEAMS & GIRDERS

THE UNION IRON MILLS, Pittsburgh, Pa.
The attention of Engineers and Architects is called our improved Wrought-Iron Beams and Girders (pamted), in which the compound welds between the ste and flanges, which have proved so objectionable in the onode of manufacturing, are entirely avoided. We are presented to furnish all sizes ht terms as favorable as can obtained classwhere. For descriptive lithograph, address the province of t

al Exposition, should have the SCIENTIFIC AMERI-AN SUPPLEMENT.

S world, J.M. BEUGLER, M.T. Williamsport, Pa

\$5 to \$20 per day at home. Samples worth \$1 free. Stinson & Co., Portland, Me.

PATENT OLD ROLLED

REVERSIBLE

HOISTING ENGINE
FOR ALL PURPOSES.
Cheap, simple, durable, and effective. All
LIDGERWOOD M.F.G.CO., 165 Pearl St., N.Y.

Northfield, Vt. Address Prof. CHARLES DOLE.

TIS, Machinery.

No. 348 BROADWAY, NEW YORK. & CO.





BRADFORD MILL CO.

THON BRIDGE BUILDING-A complete de



R OSE'S COMPLETE PRACTICAL MACHIN-OSE'S CONPLETE TO THE ACTION OF THE ACTION O

NEW DEPARTURE

STEAM ENGINES FOR SALE

Address J. C. TODD. 10 Barclay St., New York, or Paterson, N. J. CENTENNIAL MILLS.

Harrison's Standard Flouring

and Grinding Mills

Harities. Call on or address
EDWARD HARRISON,
Post 50. Sec. E. No. 8, Machinery Hall, Philadelphia, Pa

THE HOADLEY
PORTABLE STEAM ENGINE.
WITH AUTOMATICAL CUT-OFF REGULATOR
AND BALANCED VALVE.
THE BEST MOST ECONOMICAL ENGINE MADE
SEND FOR CIRCULAR.
The J.C. HOADLEY CO. LAWRENCE, MASS.
STATE WHERE YOU SAW THIS.

R OSE'S COMPLETE PRACTICAL MACKIN-18T, 130 illustrations, 376 pages, 12mo, beautifully printed. Price \$2.50 by mail, free of postage. HENRY CAREY BAIRD & CO., Industrial Publishers, 810 Walnut St., PHILADELPHIA.

HARVARD UNIVERSITY DENTAL
SCHOOL. The next year of this school begins
under the new plan, Sept. 28, 1878, and ends June 27,
1877, with a recess of one week at Christmas and another
in February. The teaching is consecutive thesewher address THOMAS H. CHANDLER, Dean, 222 Tre-Street, Boston, Mass



Stubs' Files, Tools & Steel

SHAFTSPULLEYSHANGERS COUPLINGS ETC.

In Stock, and for Sale by
WILLIAM SELLERS & CO.,
Philadelphia, and 79 Liberty St., New York.
Price lists and pamphlets on application.



Stone and Ore Breaker

Advertisements.

Back Page - - - - - - - \$1.00 a line.

THE ALLEN GOVERNOR

LARGEST NAIL FACTORY IN PENN-

CHARLES L. BALLES
ALEXANDER MORESON, Foreman
Fleur Mills require regular, exact motion. The
wernor enables them to make more and better flour.
Relling Mills and Machine Shops save the value
the governor every month by the steady motion which
alone can give. Lumber Mills run with increaves
distender speed, and everywhere praise our governor.
The Engineer's Friend.—No invention within the
start of the start

OR SALE—A Valuable Patent, in whole or part, for renovating black Crape Laces, &c., which ces them superior to new. Address A. J. SHRIVER, 157 West Fayette St., Baltimore, Md

STONE DIAMOND DRESSING MA

CREW PROPELLERS, THEIR SHAFTS AND



[ESTABLISHED 1846.]

Munn & Co.'s Patent Offices.

The Oldest Agency for Soliciting Patents in the United States.

THIRTY YEARS EXPERIENCE.

MORE PATENTS have been secured through this ency, at home and abroad, than through any other in the world.

the world.

They employ as their assistants a corps of the most experienced men as examiners, specification writers, and draftamen that can be found, many of whom have been selected from the ranks of the Patent Office.

SIXTY THOUSAND inventors have availed themselves of Munn & Co.'s services in examining their inventions and procuring their patents.

MUNN & CO., in connection with the publication of the SCIENTIFIC AMERICAN, continue to examine inventions, confer with inventors, prepare drawings, specifications, and assignments, attend to filing applications in the Patent Office, paying the government fees, and watch each case step by step while pending before the examiner. This is done through their branch office, corner F and 7th streets, Washington. They also prepare and file caveats, procure design patents, trademarks, and reissues, attend to rejected cases (prepared by the inventor or other attorneys), procure copyrights, attend to interferences, give written opinions on matters of infringement, furnish copies of patents, and, in fact, attend to every branch of patent business both in this and in foreign countries.

A special notice is made in the SCIENTIFIC AMERICAN of all inventiors are accounted to the state of the scientific and the services are accounted to the scientific and the scientific an

A special notice is made in the SCIENTIFIC AMERI-CAN of all inventions patented through this agency, with the name and residence of the patentee. Patents are of-ten sold, in part or whole, to persons attracted to the in-vention by such notice.

vention by such notice.

Patents obtained in Canada, England, France, Beigium, Germany, Rossia, Prussia, Spain, Portugal, the British Colonies, and all other countries where patents are granted, at prices greatly reduced from former rates. Send for pamphlet pertaining specially to foreign patents, which states the cost, time granted, and the requirements of such country.

Persons desiring any patent issued from 1856 to November 26, 1857, can be supplied with official copies at reasonable cost, the price depending upon the extent of drawings and length of specifications.

Any patent issued since November 27, 1867, at which time the Patent Office commenced printing the drawings and specifications, may be had by remitting to this of-

A copy of the claims of any patent issued since 1836 will be furnished for \$1.

When ordering copies, please to remit for the same as above, and state name of patentee, title of invention, and date of patent.

A pamphlet containing the laws and full directions for obtaining United States patents sent free. A handsomely bound Reference Book, gilt edges, contains 10 pages and many engravings and tables important to every patentee and mechanic, and is a useful handbook of reference for everybody. Price 25 cents, mailed free.

Address MUNN & CO.,

Publishers SCIENTIFIC AMERICAN.

37 Park Row, N. Y.

BRANCH OFFICE-Corner F and 7th Streets. Wash-

ROCK-DRILLING MACHINES AIR COMPRESSORS

Manufactured by
BURLEIGH ROCK DRILL CO.,
Send for Pamphlet. Fitchburg, Mass

R. HOE & CO.,
Grand, Broome, Sheriff, Columbia, and Gold
Streets, New York.

CAST STEEL SAWS
OF EVERY DESCRIPTION.
Send for Reduced Price Lists and Description of their
NEW PATENT

Chisel Tooth Circular Saws, which cut faster, more easily and economically than any other saw in the world. R. HOE & Co., 504 Grand St., cor, Sheriff St., N.Y.

VELOCIPEDE CARRIAGES, OF LIGHT CONstruction, fast speed. Worked by hand cranks,
also by foot treanles. Hustrafed in SCIENTIFIC AME
RICAN SUPPLEMENT So. S. To be nad at this office
and of all news agents. Price 10 cents.

EHIGH UNIVERSITY.—TUITION FREE.—

Civil. Mechanical and Mining Engineering; Chemisand Metaliurgy; A Classical Course; French and Gern; English Literature; International and Constitunal Law; Psychology and Christian Evidences. Address
eREV.JOHN M. LEAVITT, D. D. Pres. Bethlenem, Pa


PRICES-684, \$1,25; \$x1, \$2.25; 12x14, \$5.50; 16x2, \$12.5 \$x2, \$16.00; 20x2, \$19.50; \$1x3, \$42. All other sizes at pro-ortionate prices. Fast cutting, free from glazing, the re the best Solid Emery Wheels. Give diam, of holin your order for wheels. Emery Grinders unequalled any in the world. Address AMERICAN TWIST DIGILL CO., Woonsocket, R. I.

W. C. DUYCKINCK, IMPORTER, MANUFACTURER, AND DEALER IN

Railway, Machinists', and Engineers' Supplies.
50 and 52 JOHN STREET.
P. O. Box 400. NEW YORK.

COMPRESSED AIR MOTIVE POWER.—For particulars of the most recent practice, send 20 cents for SUIENTIFIC AMERICAN SUPPLEMENT, Nos. 1 and 2, containing 5 engravings of the "Compressed Air" Locomotives now in use in St. Gothard Tunné Works, with dimensions, etc.

Stone Channeling OR Quarrying Machine,



WARDWELL PATENT,

FOR CUTTING STONE INTO VARIOUS SIZES AND DIMENSIONS IN ALL KINDS OF

QUARRIES.
STEAM STONE CUTTER CO., RUTLAND, VT.
SOLE PROPRIETORS AND MANUFACTURERS.
Three Machines at Philadelphia Exhibition,
Annexe No. 2, Machinery Hall.

INVALIDITY OF STATE LAWS
CONCERNING THE SALE OF PATENTS
All laws of State legislatures that in any manner interfere with the free sale of Patent rights, such as the re-

GEO. W. READ & CO.

STEAM BAND SAW
AND VENEER CUTTING MILL,
186 to 200 LEWIS ST., foot 5th and 6th Sts., E. R., N. Y
Always on hand, FULL STOCK of SEASONED

Hard-Wood Lumber

AND CHOICE FIGURED VENEERS.
The LARGEST STOCK! The GREATEST
VARIETY! The Lowest Prices!

Enclose Stamp for Catalogue and Price-List.
Orders by mail promptly and faithfully executed.

P. BLAISDELL & CO.,

Worcester, Mass.,
Manufacturers of the Blaisdell Patent Upright Drill and
other first-class Machinist's Tools.

NEWSPAPER FILE.

The Koch Patent File, for preserving newspapers assazines, and pamphiets, has been recently improved a price reduced. Subscribers to the SCHENTIFIC AM SIGNAY and SCHENTIFIC AMMERICAN SUPPLIMENT Can be upplied for the low price of \$1, 50 by mail, or \$1, 50 at the most of this paper. Heavy board addes, lascriptic SCHENTIFIC AMERICAN," in gill. Necessary to very one who wishes to preserve the paper.

MUNN & CO., Publishers SCIENTIFIC AMERICAN

The Scientific American

A Bound Book of 144 Pages, for 25c.

On receipt of 25 cents, we send by mall, post paid, a opp of a handsome little bound volume entitled the SCI-NTIFIC AMERICAN REFERENCE BOOK, containing 14 ages illustrated with engravings, and forming one of the cheapest and most valuable books of condensed recreace ever printed. Among its contents are:

ng over 10,000 inhabitants-Com-

United States Trade Mark Registration, show-

United States Copyright Law for Labels, in

The Principal Mechanical Movements. De-cribed and illustrated by 150 small diagrams, of great alue to Inventors and Designers of Mechanism. Geometry, as Applied to Practical Purposes. With

The Modern Steam Engine.—With engraving, showing all the parts, names, etc., and a brief history of the invention and Progress of Steam Power.

Horse Power. Simple and plain rules for Calcu-lating the Horse Power of Steam Engines and Streams

of Prainage explained; Amount of Power at present Yielded from Coal by best Engines; Sound—its velocity and action; Liquid Glues, Becipes; Value of Brains Properties of Charcoal; Hight of Waves; Speed of Electric Spark, etc.; Valuable Recipes.

The SCIENTIFIC AMERICAN REFERENCE BOOK rice only 25 cents, may be had of News Agents in alirits of the country, and of the undersigned. Sent by all on receipt of the price.

MUNN & CO., Publishers,

Scientific American Office, 37 Park Row, New York.

TO INVENTORS AND MANUFACTURERS

WITH "AIR SPACE" IMPROVEMENT, haves 10 to 20 per cent. CHALMERS SPENCE CO., Foot E. 9th St., N. Y.; 1202 N. 2nd St., St. Louis, Mo.

SCHLENKER'S Stationary-Die and Revolving-Die

THE BEST AND CHEAPEST MADE. HOWARD IRON WORKS,

Wheels and Rope for conveying power long distances. Send for Circular.

ROGERS' TANNATE OF SODA BOILER SCALE PREVENTIVE.

JOS. G. ROGERS & CO., Madison, Ind.

For Send for book on Boiler Increstation.

BOILERS-If you wish to save fuel, get Bollers. We have seven different styles. J. HEATHCOTE & CO., Boiler Makers, Williamsport, Pa.

Portland and Keene's Cement. From the best London Manufacturers. For sale by JAMES BRAND, 85 Beckman St., New York A Practical Treatise on Cement furnished for 25 cents.

UNCHING For the Best and Cheapent, address THE STILES
DROP PRESSES. MIDDLETOWN, CORN. PUNCHING



Niagara Steam Pump Works

CHARLES B. HARDICK. BROOKLYN, N. Y.

The Tanite Co.,

STROUDSBURG, PA. EMERY WHEELS & GRINDERS

Machinists' Tools.

Send for ney illustrated catalogue.

Lathes, Planers, Drills, &c.

NEW HAVEN MANUFACTURING CO.

New Haven, Coun.

M. SELIG JUNIOR, & CO., orters of American Machinery, Tools, Agricultura ements, Wholesale and Export Hardware and Macry Merchants. Est. 41866.
LONDON, ENGLAND, and BEHLIN, GERMANY.

PREPARATORY SCIENTIFIC SCHOOL,
Warren Academy, Woburn, Mass. For circulars, address. L. S. BURBANK, PRINCIPAL.

O'GARDOS FALENT UNIVERSAL ECCEN.

TRIC MILLS-For grinding Rones, Ores, Sand, Glo
Crucibles, Fire Clay, Guanos, Oll Cake, Feed, Corn.
Corn and Cob, Tobacco, Snuff, Sugar, Salts, Roots,
Spices, Coffee, Cocoanut, Flaxseed, Asbestos, Mica,
etc., and whatever cannot be ground by other mills.
Also for Paints, Frinters Inks, Paste Riacking, etc.
JOHN W. THOMSON, successor to JAMES ROGARDUS corner of White and Elm Sts., New York

DAMPER REGULATORS BEST GAGE COCKS.
MURRILL & KEIZER, 44 Holliday St., Balt,

HARTFORD

STEAM BOILER

Inspection & Insurance COMPANY.

W. B. FRANKLIN, V. Pres't. J. M. ALLEN, Pres't. J. B. PIERCE, Sec'y.

Mill Furnishing Works



SCIENTIFIC AMERICAN,

FOR 1576. THE MOST POPULAR SCIENTIFIC PAPER IN THE WORLD.

THIRTY-FIRST YEAR.

VOLUME XXXV.-NEW SERIES.

The publishers of the SCIENTIFIC AMERICAN beg to announce that on the first day of July, 1876, a new volume commenced. It will continue to be the aim of the publishers to render the contents of the new volume more attractive and use ful than any of its predecessors.

To the Mechanic and Manufacturer.

No person engaged in any of the mechanical pur-suits should think of doing without the SCIES-TIFIC AMERICAN. Every number contains from six to ten engravings of new machines and inven-tions which cannot be found in any other publica-

The SCIENTIFIC AMERICAN is devoted to the The SCIENTIFIC AMERICAN is devoted to the interests of Popular Science, the Mechanic Aris, Manufactures, Inventions, Agriculture, Commerce and the industrial pursuits generally; and it is valuable and instructive not only in the Workshop and Manufactory, but also in the Household, the Library, and the Reading Room. Each volume contains hundreds of Notes, Receipts, and Suggestions and Advice, by Practical Writers, for Workshop and Employers, in all the various arts.

ing Men and Employers, in all the various arts. TERMS OF SUBSCRIPTION - POSTAGE

PAID BY U One copy Scientific American, one year ...\$3 20 One copy Scientific American, six months. 1.60 One copy Scientific American, three months 1.00

One copy Scientific American and one copy Scientific American Supplement, both for one year, post-paid...... 7,00

The Scientific American Supplement. A weekly paper, uniform in size with the SCIEN TIFIC AMERICAN, but a distinct publication. It contains working drawings of engineering works, and elaborate treatises on every branch of Science and Mechanics, by eminent writers, at home and abroad. An illustrated cover protects the handomely printed sheets. Price, \$5.00 per annum

Remit by postal order, draft, or express.

Address all letters and make all Post Office orders and drafts payable to

MUNN & CO

37 PARK ROW, NEW YORK. The "Scientific American" is printed with CHAS, ENEU JOHNSON & CO. SINK Tenth and Lombard-ets., Philadelphia, and SP Gold st. New-York